Foodies database

9 tables, 57 columns, 10 relationships. PostgreSQL schema of the Foodies API. Same tables as db/schema.sql and db/foodies.dbml.

regions

2 columns

Lebanese regions the restaurants are in

PK	**id**	serial	
UQ	name	varchar(50)	Beirut, Byblos, Zahle...

The 9 tables

- **regions**
- **categories**
- **restaurants**
- **restaurant_dishes**
- **dishes**
- **chat_logs**
- **reviews**
- **users**
- **favorites**

categories

2 columns

Dish families: mezze, grills, desserts...

PK	**id**	serial	
UQ	name	varchar(50)	Mezze, Grills, Bakery...

How to read it

PK	Primary key: identifies the row
FK	Foreign key: the arrow points to the row it references (many to one)
UQ	Unique: no two rows share the value

Catalog **People** **Chatbot**

restaurants

9 columns

The places that serve the dishes

PK	**id**	serial	
	name	varchar(100)	
FK	region_id	integer	to regions
	address	varchar(200)	optional
	phone	varchar(30)	optional
	lat	double	-90 to 90
	lng	double	-180 to 180
	price_level	smallint	1 to 4
	style	varchar(10)	heritage, authentic, fusion, modern

restaurant_dishes

4 columns

The menu: who serves what, at what price

PK FK	**restaurant_id**	integer	to restaurants
PK FK	**dish_id**	integer	to dishes
	price_usd	numeric(8,2)	0 or more
	available	boolean	default true

dishes

16 columns

Traditional Lebanese dishes

PK	**id**	serial	
	name_en	varchar(100)	
	name_ar	varchar(100)	Arabic name
	description	text	
FK	category_id	integer	to categories
	is_vegetarian	boolean	default false
	weather	varchar(10)	hot, cold or any
UQ	slug	varchar(40)	photo: img/photos/dishes/<slug>.jpg
	ingredients	text[]	list of ingredients
	is_vegan	boolean	siyami; vegan means vegetarian too
	is_gluten_free	boolean	as usually served
	allergens	text[]	gluten, dairy, nuts, sesame, fish, eggs
	meat	varchar(10)	none, lamb, beef, chicken, fish
	served_raw	boolean	raw meat or fish
	good_to_know	text	tip for first-timers
	first_timer	boolean	shown in "New to Lebanese food?"

chat_logs

6 columns

Questions asked to the chatbot

PK	**id**	serial	
FK	user_id	integer	null for visitors
	question	varchar(500)	
	answer	text	
FK	matched_dish_id	integer	null if no dish matched
	created_at	timestamptz	default now

reviews

8 columns

One review per user per restaurant

PK	**id**	serial	
FK UQ	user_id	integer	to users, unique with restaurant_id
FK UQ	restaurant_id	integer	to restaurants
	rating	smallint	1 to 5
	tradition_rating	smallint	1 modern to 5 traditional
	comment	varchar(1000)	optional
	created_at	timestamptz	default now
	updated_at	timestamptz	null until edited

users

7 columns

Accounts: password or Google sign-in

PK	**id**	serial	
	name	varchar(100)	
UQ	email	varchar(255)	saved in lowercase
	password_hash	varchar(255)	bcrypt, null for Google-only
UQ	google_id	varchar(255)	null unless Google
	role	varchar(10)	user or admin
	created_at	timestamptz	default now

favorites

3 columns

The dishes a user saved

PK FK	**user_id**	integer	to users
PK FK	**dish_id**	integer	to dishes
	created_at	timestamptz	newest first