

PRÉREQUIS TECHNIQUES

Dimensionnement d'infrastructure Zextras Carbonio

Client	Université d'Amboise
Prestataire	Zextras Services
Commercial charge en	William SANTALIESTRA (Directeur d'agence)
Document généré par	Julien NICOLAS (Ingénieur avant-vente)
Version du document	1.0
Date	24/08/2026
Classification	Public/Client

Historique des révisions

Version	Date	Auteur	Nature de la modification
1.0	24/08/2026	Julien NICOLAS	Première version

Prestataire

Zextras Services

1 allée Ferdinand de Lesseps, 37200 Tours, France

<https://www.zextras-services.fr>

1 Prérequis techniques

Le tableau ci-dessous détaille les machines virtuelles nécessaires au déploiement, réparties entre la zone publique (DMZ) et la zone privée (LAN).

Nœud	Zone	Composants	vCPU	RAM	Disque OS	Disque Appli	Disque Store
proxy01	DMZ	Proxy	4	8 Go	30 Go	60 Go	—
proxy02	DMZ	Proxy	4	8 Go	30 Go	60 Go	—
mta_auth01	DMZ	MTA AUTH	4	8 Go	30 Go	90 Go	—
mta_auth02	DMZ	MTA AUTH	4	8 Go	30 Go	90 Go	—
mta_in01	DMZ	MTA IN	4	8 Go	30 Go	90 Go	—
mta_in02	DMZ	MTA IN	4	8 Go	30 Go	90 Go	—
mta_out01	DMZ	MTA OUT	4	8 Go	30 Go	90 Go	—
mta_out02	DMZ	MTA OUT	4	8 Go	30 Go	90 Go	—
services01	LAN	Mesh, LDAP Master	4	16 Go	30 Go	160 Go	—
services02	LAN	Mesh, LDAP Replica	4	16 Go	30 Go	160 Go	—
services03	LAN	Mesh, Database	4	16 Go	30 Go	160 Go	—
mailstore01	LAN	Mailstore	4	16 Go	30 Go	500 Go	5000 Go
mailstore02	LAN	Mailstore	4	16 Go	30 Go	500 Go	5000 Go
mailstore03	LAN	Mailstore	4	16 Go	30 Go	500 Go	5000 Go
mailstore04	LAN	Mailstore	4	16 Go	30 Go	500 Go	5000 Go
mailstore05	LAN	Mailstore	4	16 Go	30 Go	500 Go	5000 Go
application01	LAN	Chat, Tasks	4	4 Go	30 Go	20 Go	—
application02	LAN	Files, Docs	4	4 Go	30 Go	20 Go	—
visio	DMZ	Visioconférence	4	4 Go	30 Go	100 Go	—
migration_factory	LAN	Usine de migration	4	8 Go	30 Go	500 Go	—
Total nœuds (20 nœuds)			80	212 Go	600 Go	4280 Go	25000 Go

2 Schéma d'architecture

Répartition des machines virtuelles entre la zone publique (DMZ) et la zone privée (LAN).

