

Generative Modelling Challenge

4th Tutorial Session: Generative Adversarial Networks

Michaël Allouche


2022, November 15th



BNP PARIBAS




Generative model




Noise

Generator




Probability density function

Generative model



Noise

Generator




Probability density function

If X denotes the r.v. taking values in some space $\mathcal{X} \subseteq \mathbb{R}^d$ from which we have observations (X_1, \dots, X_n) , the problem is to find a function $G : \mathbb{R}^{d'} \rightarrow \mathcal{X}$ and a **latent probability distribution** π on $\mathbb{R}^{d'}$ such that


$$X \stackrel{d}{=} G(Z) \text{ and } Z \sim \pi$$

Generative model



Noise

Generator



Probability density function

If X denotes the r.v. taking values in some space $\mathcal{X} \subseteq \mathbb{R}^d$ from which we have observations (X_1, \dots, X_n) , the problem is to find a function $G: \mathbb{R}^{d'} \rightarrow \mathcal{X}$ and a **latent probability distribution** π on $\mathbb{R}^{d'}$ such that

$$X \stackrel{d}{=} G(Z) \text{ and } Z \sim \pi$$

Existence: see the Kuratowski's Theorem [Bertsekas and Shreve, 1978, Proposition 7.15]

Questions: which π ? which d' ? how to learn G ? $\text{dist.}(\text{law}(X), \text{law}(G(Z)))$?

Learning G : **Generative Adversarial Networks (GANs)** [Goodfellow et al., 2014]

Generative Adversarial Networks (GANs)

Data: X_1, \dots, X_n , i.i.d. according to some unknown density p_X on $\mathcal{X} \subseteq \mathbb{R}^d$

Generative Adversarial Networks (GANs)

Data: X_1, \dots, X_n , i.i.d. according to some unknown density p_X on $\mathcal{X} \subseteq \mathbb{R}^d$

Generator: parametric family of functions $\mathcal{G} = \left\{ G_\theta : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d \right\}_{\theta \in \Theta}$

- *Goal:* learn optimal parameters θ^* s.t. $\tilde{X} := G_{\theta^*}(Z) \stackrel{d}{=} X$

Generative Adversarial Networks (GANs)

Data: X_1, \dots, X_n , i.i.d. according to some unknown density p_X on $\mathcal{X} \subseteq \mathbb{R}^d$

Generator: parametric family of functions $\mathcal{G} = \left\{ G_\theta : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d \right\}_{\theta \in \Theta}$

- *Goal:* learn optimal parameters θ^* s.t. $\tilde{X} := G_{\theta^*}(Z) \stackrel{d}{=} X$

Discriminator: parametric family of functions $\mathcal{D} = \left\{ D_\phi : \mathbb{R}^d \rightarrow [0, 1] \right\}_{\phi \in \Phi}$

- *Goal:* give the probability that an observation x is drawn from p_X

Generative Adversarial Networks (GANs)


Data: X_1, \dots, X_n , i.i.d. according to some unknown density p_X on $\mathcal{X} \subseteq \mathbb{R}^d$

Generator: parametric family of functions $\mathcal{G} = \left\{ G_\theta : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d \right\}_{\theta \in \Theta}$

- *Goal:* learn optimal parameters θ^* s.t. $\tilde{X} := G_{\theta^*}(Z) \stackrel{d}{=} X$

Discriminator: parametric family of functions $\mathcal{D} = \left\{ D_\phi : \mathbb{R}^d \rightarrow [0, 1] \right\}_{\phi \in \Phi}$

- *Goal:* give the probability that an observation x is drawn from p_X



GAN model with $d' = 3$ and $d = 2$

Generative Adversarial Networks (GANs)


Data: X_1, \dots, X_n , i.i.d. according to some unknown density p_X on $\mathcal{X} \subseteq \mathbb{R}^d$

Generator: parametric family of functions $\mathcal{G} = \{G_\theta : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d\}_{\theta \in \Theta}$

- *Goal:* learn optimal parameters θ^* s.t. $\tilde{X} := G_{\theta^*}(Z) \stackrel{d}{=} X$

Discriminator: parametric family of functions $\mathcal{D} = \{D_\phi : \mathbb{R}^d \rightarrow [0, 1]\}_{\phi \in \Phi}$

- *Goal:* give the probability that an observation x is drawn from p_X



GAN model with $d' = 3$ and $d = 2$

Results

Proposition ([Goodfellow et al., 2014, Proposition 1])

For any generator G_θ , the optimal discriminator is

$$D_{\phi_\theta^*}(x) = \frac{p_X(x)}{p_X(x) + p_\theta(x)}.$$

Results

Proposition ([Goodfellow et al., 2014, Proposition 1])

For any generator G_θ , the optimal discriminator is

$$D_{\phi_\theta^*}(x) = \frac{p_X(x)}{p_X(x) + p_\theta(x)}.$$

Theorem ([Goodfellow et al., 2014, Theorem 1])

For a given optimal discriminator, the optimal generator is achieved for $p_X = p_\theta$, so it entails from Proposition 1

$$D_{\phi_\theta^*}(x) = \frac{1}{2}.$$

Results

Proposition ([Goodfellow et al., 2014, Proposition 1])

For any generator G_θ , the optimal discriminator is

$$D_{\phi_\theta^*}(x) = \frac{p_X(x)}{p_X(x) + p_\theta(x)}.$$

Theorem ([Goodfellow et al., 2014, Theorem 1])

For a given optimal discriminator, the optimal generator is achieved for $p_X = p_\theta$, so it entails from Proposition 1

$$D_{\phi_\theta^*}(x) = \frac{1}{2}.$$

\Rightarrow See [Biau et al., 2020] for more theoretical results

Optimization

Theoretical Loss:

$$\min_{\theta \in \Theta} \max_{\phi \in \Phi} [\mathbb{E}_{p_X} (\log D_{\phi}(X)) + \mathbb{E}_{p_Z} (\log (1 - D_{\phi}(G_{\theta}(Z)))]$$

Optimization

Theoretical Loss:

$$\min_{\theta \in \Theta} \max_{\phi \in \Phi} [\mathbb{E}_{p_X} (\log D_{\phi}(X)) + \mathbb{E}_{p_Z} (\log (1 - D_{\phi}(G_{\theta}(Z)))]$$

Alternative optimization program with SGD:

❶ Discriminator update

$$\phi^{t+1} = \phi^t + \eta_D^t \frac{1}{M} \sum_{m=1}^M \nabla_{\phi} \left[\log D_{\phi^t}(x^{(m)}) + \log \left(1 - D_{\phi^t}(G_{\theta^t}(Z^{(m)})) \right) \right]$$

Optimization

Theoretical Loss:

$$\min_{\theta \in \Theta} \max_{\phi \in \Phi} [\mathbb{E}_{p_X} (\log D_{\phi}(X)) + \mathbb{E}_{p_Z} (\log (1 - D_{\phi}(G_{\theta}(Z))))]$$

Alternative optimization program with SGD:

① Discriminator update

$$\phi^{t+1} = \phi^t + \eta_D^t \frac{1}{M} \sum_{m=1}^M \nabla_{\phi} \left[\log D_{\phi^t}(x^{(m)}) + \log \left(1 - D_{\phi^t}(G_{\theta^t}(Z^{(m)})) \right) \right]$$

② Generator update

$$\theta^{t+1} = \theta^t - \eta_G^t \frac{1}{M} \sum_{m=1}^M \nabla_{\theta} \log \left(1 - D_{\phi^{t+1}}(G_{\theta^t}(Z^{(m)})) \right)$$

Optimization

Theoretical Loss:

$$\min_{\theta \in \Theta} \max_{\phi \in \Phi} [\mathbb{E}_{p_X} (\log D_{\phi}(X)) + \mathbb{E}_{p_Z} (\log (1 - D_{\phi}(G_{\theta}(Z)))]$$

Alternative optimization program with SGD:

1 Discriminator update

$$\phi^{t+1} = \phi^t + \eta_D^t \frac{1}{M} \sum_{m=1}^M \nabla_{\phi} \left[\log D_{\phi^t}(x^{(m)}) + \log \left(1 - D_{\phi^t}(G_{\theta^t}(Z^{(m)})) \right) \right]$$

2 Generator update

$$\theta^{t+1} = \theta^t - \eta_G^t \frac{1}{M} \sum_{m=1}^M \nabla_{\theta} \underbrace{\log \left(1 - D_{\phi^{t+1}}(G_{\theta^t}(Z^{(m)})) \right)}_{\rightarrow 0 (\triangle \text{ Vanishing Gradient } \triangle)}$$

Optimization

Theoretical Loss:

$$\min_{\theta \in \Theta} \max_{\phi \in \Phi} [\mathbb{E}_{p_X} (\log D_{\phi}(X)) + \mathbb{E}_{p_Z} (\log (1 - D_{\phi}(G_{\theta}(Z))))]$$

Alternative optimization program with SGD:

① Discriminator update

$$\phi^{t+1} = \phi^t + \eta_D^t \frac{1}{M} \sum_{m=1}^M \nabla_{\phi} \left[\log D_{\phi^t}(x^{(m)}) + \log (1 - D_{\phi^t}(G_{\theta^t}(Z^{(m)}))) \right]$$

② Generator update

$$\theta^{t+1} = \theta^t - \eta_G^t \frac{1}{M} \sum_{m=1}^M \underbrace{\nabla_{\theta} \log (1 - D_{\phi^{t+1}}(G_{\theta^t}(Z^{(m)})))}_{\rightarrow 0 (\triangle \text{ Vanishing Gradient } \triangle)}$$

Numerical Loss:

$$\max_{\theta \in \Theta} \max_{\phi \in \Phi} [\mathbb{E}_{p_X} (\log D_{\phi}(X)) + \mathbb{E}_{p_Z} (\log (D_{\phi}(G_{\theta}(Z))))]$$

Numerical issues

Challenges:

- **Oscillating Loss.** Non-convergence with large oscillations during the iterations.
- **Hyperparameter sensitive.** GANs require large number of hyperparameters to tune (batch-size, latent space, learning rate, ...) and they are very sensitive to small changes.
- **Mode collapse.** The Generator is overfitted and collapses to a single mode, *i.e.* it simulates the same objects (no diversification).

Attempt to remedy:

- Consider other loss functions (WGAN, EBGAN, ...)
- Consider penalization terms (Spectral normalization, Gradient penalty, ...)

References I

 Bertsekas, D. P. and Shreve, S. E. (1978).

Stochastic optimal control, volume 139 of *Mathematics in Science and Engineering*.

Academic Press, Inc., New York-London.

 Biau, G., Cadre, B., Sangnier, M., Tanielian, U., et al. (2020).

Some theoretical properties of gans.

Annals of Statistics, 48(3):1539–1566.

 Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., and Bengio, Y. (2014).

Generative adversarial nets.

In *Advances in neural information processing systems*, pages 2672–2680.