



WEB CHECKOUT SDK

+ Payment Transaction Status API

Version 2.0.5.5 • 2 January 2025

FOO OFFSHORE SAL – www.foo.mobi

Copyright © FOO OFFSHORE SAL, 2019. All rights reserved.

The copyright in this document is owned by FOO OFFSHORE SAL, ["FOO"]. This document may not be reproduced, in whole or in part, in any form without the express consent of FOO in

writing.

Information contained in this document is proprietary and confidential to FOO. That information, irrespective of form, must not be used other than for the purposes for which it is disclosed to the recipient and must not under any circumstances be disclosed to any third party without the express consent in writing of FOO.

Although FOO uses all reasonable efforts to ensure the accuracy and completeness of this document, no warranty or representation whatever is given by FOO in respect of it and any use of or reliance on any of the information contained herein is entirely at the risk of the person so acting. FOO shall have no liability whatsoever in respect of any use of or reliance on any of such information.

FOO2

1. Web SDK.....4

1.1. Implementation4

1.2. Utilization5

2. Payment Transaction Status.....6

2.2. API Reference Documentation8

1. Table of Contents

Document History

Revision History

This document has been revised by:

Revision Number	Revision Date	Summary of Changes
V 1.0	30-11-2018	Initial version
V 2.0.2	22-05-2019	Added paymentType and showResult params
V 2.0.3	01-08-2019	Added encoding for hashing
V 2.0.4	01-11-2019	Added iOS 13 support
V 2.0.5.1	25-01-2021	Added the ability to hide QR code on mobile
V 2.0.5.2	30-4-2024	Added error codes for check status api
V 2.0.5.3	21-5-2024	Fixes response of check status api

SDK Compatibility

Environment	Application	Version
Production	Android BenefitPay	v.1.0.23 and above
	iOS BenefitPay	v.10.0.11 (2) and above
Sandbox	Android TBenefitPay	v.1.0.74 and above
	iOS TBenefitPay	v.1.0.1 (10.2) and above

1. Web SDK

This guide discusses how the Checkout Web SDK works, along with all related functions that can be used.

1.1. Implementation

You have to include InApp.min.js file downloaded from the portal.

1.2. Utilization

Once the file is included you have to create button with “inapp-btn” class, by default the button will have the following dimensions: width: 201px and height: 48px, you can override them depending on your needs.

1.2.1. Open Method

Method	Purpose
InApp.open	Open popup payment

1.2.2. Parameters

Name	Type	Description	Required
first parameter	Object	the first parameter should be an object with the following properties : 1) merchantId 2) transactionAmount 3) transactionCurrency 4) hashedString 5) appId 6) referenceNumber 7) secure_hash: this parameter is for security reason, the Hashing should be done by concatenating grouping the request parameters except “lang” and “hashedString” parameter as key value pairs, sorting them ascending by key and value, combining key and value with an =, then concatenating all the key-value pairs separated by a comma and finally performing a SHA-256 hash using the secret token with base64 encoding	Yes
		8) showResult: value should be 1 to show result in the user app or 0 to show “Check merchant website for result” message without result in the user app. 9) hideMobileQR: value should be 1 to hide QR code on mobile or 0 to show it. 10) qr_timeout: (in milliseconds) When this timeout is reached, the popup displaying the QR code should automatically close, and the payment process will no longer be considered valid or allowed to proceed qr_timeout = 150000 = 2.5 minutes	

second parameter	Function name	the second parameter should be a success callback function that will be called when the operation is successful	Yes
third parameter	Function name	the third parameter should be an error callback function that will be called when the operation is unsuccessful	Yes
fourth parameter	Function name	the fourth parameter should be a close callback function that will be called when the user click on the close popup button	No

If the operation was processed, an object containing the following fields will return to the success callback function (second parameter) that was previously provided:

- cardNumber
- errorCode
- errorDescription
- merchantId
- referenceNumber

If it wasn't same object will return to the error callback function (third parameter) that was previously provided.

If the operation was processed, in order to get the transaction status, IT IS REQUIRED to use Payment Transaction Status API from section 2 to check if the payment is successful or not.

Note: Successful operation does not indicate successful payment.

1.2.3. Close Method

Method	Purpose
InApp.close	Close the payment and didn't take any parameter.

2. Payment Transaction Status

This guide discusses how to integrate with the check payment transaction API.

2.1.1. Conventions

We use the following conventions in this document:

- Responses are listed under 'Responses' for each method.

- Responses are in JSON format.
- Request parameters are mandatory unless explicitly marked as Optional.
- The type of values accepted for a request parameter are shown the **values** column.
- The | symbol means OR.

2.1.2. HTTP Requests

API requests must be written as HTTP requests, and include the following components:

- **HTTP Method:** Describes the type of HTTP action (POST, GET, PUT or DELETE)
- **URL:** Describes the resource you are creating or accessing, along with any optional arguments
- **HTTP Headers:** Specifies attributes of the request, including authentication, encoding and request format
- **Request Body:** Describes resources or specifies a call-control script

2.1.3. Hashing and Encryption

Hashing of the requests should be done by concatenating grouping the request parameters as key value pairs, sorting them ascending by key and value, combining key and value with an =, then concatenating all the key-value pairs separated by a comma and finally performing a SHA-256 hash using the secret token with base64 encoding. This hashing method should be specified in the request header as X-FOO-Signature-Type = KEYVAL.

Example request string to hash (request): key1="value1",key2="value2",key3="value3"

Hashing algorithm: base64encode(hash_hmac_sha256(request))

Real example:

request string : appId="1884561591",merchantId="66600003"

hashing value: SmEvGzapGwyccyKFtilgJBIO6EJEiX2p2F/h7ri6gFI=

2.1.4. URL Format

The API URL uses the following format:

```
<protocol>://<host>:<port>/payment-  
platform/ext/v1/payment/<MethodName>
```

2.2. API Reference Documentation

2.2.1. Headers

The following headers should be sent with the request:

Name	Type	Description	Required
X-FOO-Signature	alphanumeric	Hashing of request as described above	Yes
X-CLIENT-ID	alphanumeric	The ID of the client making the request. This is a unique ID provided by FOO.	Yes
X-FOO-Signature-Type	Key-value pairs	Hashing of the requests by concatenating grouping the request parameters as key value pairs and performing a SHA-256 hash using the secret token with base64 encoding, check examples in 2.1.3	Yes

2.2.2. Check Transaction Status

Checks the status of the sent payment transaction.

2.2.2.1. Resource Information

Method	Purpose
Response formats	JSON
Requires Hashing	Yes

2.2.2.2. Request

Method	URL
POST	https://<baseurl>/web/v1/merchant/transaction/check-status

2.2.2.3. Parameters

Name	Type	Description	Required
------	------	-------------	----------

merchant_id	String	The unique merchant ID provided by FOO	Yes
reference_id	String		Yes

2.2.2.4. Response

Name	Type	Description
amount	String	Transaction amount
currency	String	Transaction currency
reference_number	Alphanumeric	Transaction reference number
status	String	Transaction status: success or failed
authorization_code	Alphanumeric	Transaction authorization code
date	Object	Object containing the following three fields: date, timezone_type and timezone
card_number	string	Card number
transaction_receipt	String	Transaction receipt
issuer_bank_name	string	Bank name
rrn	String	RRN
receipt_number	String	Receipt number
card_brand	String	Card brand
wallet_key	String	Wallet key

gateway	string	Gateway name
error_code	String	Error code in case the transaction was failed, otherwise it is not returned in the response
error_description	String	Error description in case the transaction was failed, otherwise it is not returned in the response

If successful, HTTP Code 200, this method returns a response body with the following structure

```
{
  "meta": {
    "status": "OK"
  },
  "response": {
    "amount": string,
    "currency": string,
    "reference_number": alphanumerical,
    "status": "success",
    "authorization_code": string,
    "card_number": string,
    "transaction_receipt": string,
    "issuer_bank_name": string,
    "rrn": string,
    "receipt_no": string,
    "card_brand": string,
    "wallet_key": string,
    "gateway": string,
    "date": {
      "date": string
      "timezone_type": numerical,
      "timezone": string
    }
  }
}
```

If failed, HTTP Code 200, this method returns a response body with the following structure

©2009–2019 FOO. Proprietary and Confidential. All rights reserved.

Web Checkout + Transaction Status API

```
{
  "meta": {
    "status": "OK"
  },
  "response": {
    "amount": string,
    "currency": string,
    "reference_number": alphanumerical,
    "status": "failed",
    "authorization_code": string,
    "card_number": string,
    "transaction_receipt": string,
    "issuer_bank_name": string,
    "rrn": string,
    "receipt_no": string,
    "card_brand": string,
    "wallet_key": string,
    "gateway": string,
    "date": {
      "date": string
      "timezone_type": numerical,
      "timezone": string
    },
    "error_code": string,
    "error_description": string
  }
}
```

If transaction doesn't exists HTTP Code 200, this method returns a response body with the following structure:

```
{
  "meta": {
    "status": "FAILED"
  },
  "response": {
    "message": "transaction does
    not exists",
    "status": "FAILED"
  }
}
```

2.2.1. Status Code

The APIs uses the following Status Codes:

Code	Error Message
FOO_001	Terminal has been blocked
FOO_002	Reference number is already used
FOO_003	Merchant does not support payment
FOO_004	Invalid merchant
FOO_005	App not available
FOO_006	Outdated App
FOO_007	Merchant not configured for masterpass
FOO_008	Payment gateway not configured for this type of payment
FOO_009	Invalid QR String
FOO_010	Invalid Hash String
FOO_011	Merchant is inactive

FOO_012	Invalid Code!
FOO_013	Invoice not available
FOO_300	Unauthorized
FOO_301	Invalid App

2.2.2. HTTP Response Codes

The API uses the following HTTP status codes. 200 – Success; 4XX - Error in client; 5XX - Error in server.

Status Code	Description
200	OK
400	Bad Request
401	Authentication failure
403	Forbidden
404	Resource not found
412	Precondition Failed
500	Internal Server Error
503	Service Unavailable

2.2.3. Error code (Benefit Gateway)

Code	Description
BEN-00	Generic Error
BEN-04	Pick-up card
BEN-05	Please contact issuer bank
BEN-12	Invalid Transaction
BEN-14	Invalid card, Please delete and re-add your card
BEN-33	Expired card, Please delete and re-add your card
BEN-36	Restricted card, Please delete and readd your card
BEN-38	Allowable PIN tries exceeded

BEN-51	Insufficient funds
BEN-54	Expired card, Please delete and re-add your card

BEN-55	Incorrect PIN
BEN-61	Daily Transaction Limit exceeded
BEN-62	Restricted Card
BEN-65	Exceeds withdrawal frequency limit
BEN-67	Restricted Card
BEN-75	Allowable number PIN tries exceeded
BEN-76	Ineligible card, Please delete and readd your card
BEN-78	Please delete and re-add your card, or contact your bank for more information
BEN-88	BENEFIT PGW System Error
BEN-91	Issuer is inoperative
BEN-95	Payment needs otp verification
IPAY0100400	Invalid OTP
OTP EXPIRED	Expired OTP

2.2.4. Error code (MPGS Gateway)

Code	Description
------	-------------

PAY-400	Bad request
FOO-200	Success
FOO-217	Acquirer system error occurred processing the transaction
FOO-277	Transaction declined by issuer
FOO-218	Transaction Approved - pending batch settlement
FOO-204	Expired card
FOO-205	Insufficient funds
FOO-232	Cancelled
FOO-264	Deferred transaction received and awaiting processing
FOO-241	The transaction has successfully been created in the gateway. It is either awaiting submission to the acquirer or has been submitted to the acquirer but the gateway has not yet received a response about the success or otherwise of the payment
FOO-231	PIN entry tries exceeded
FOO-265	Transaction declined due to address verification
FOO-254	CVV Verification failed
FOO-267	Transaction declined due to address verification and card security code
FOO-215	Card is not authenticated
FOO-269	Transaction blocked due to Risk or 3D Secure blocking rules

FOO-270	Transaction declined - do not contact issuer
FOO-263	Pin verification failed
FOO-271	Transaction declined due to payment plan
FOO-272	Transaction declined due to duplicate batch
FOO-273	Order locked - another transaction is in progress for this order
FOO-219	Card not enrolled in 3DSecure
FOO-248	Operation not permitted
FOO-274	Transaction is pending
FOO-275	The transaction has been submitted to the acquirer but the gateway was not able to find out about the success or otherwise of the payment. If the gateway subsequently finds out about the success of the payment it will update the response code
FOO-235	Gateway system fault
FOO-236	Timed out