

Programming Test Results (With Test Cases)

Result Summary

Field	Value
Test ID	40150
Student ID	29195
Programs (with test cases)	3
Total Test Cases	9
Test Cases Passed	9
Fully Passed Programs	3
Partially Passed Programs	0
Failed Programs	0
Overall % (with test cases)	100.00%
Grade	Outstanding

Programs With Test Cases

#	Program Name	Total TC	Passed	Success Rate	Score /10	Submitted At	Attempts
1	Customer and Orders Management	3	3	100.0%	10	19/11/2025, 13:33:17	0
2	Car Has An Engine	3	3	100.0%	10	19/11/2025, 12:28:28	0
3	Modeling Employee and Address Details	3	3	100.0%	10	19/11/2025, 12:03:58	0

Program Details (With Test Cases)

Program 1: Customer and Orders Management

Languages: Java

Score (010): 10 / 10

Test Case Summary: Total: 3 Passed: 3
Failed: 0 Success: 100.0%

Attempts: 0

Submitted At: 19/11/2025, 13:33:17

Description: Task Description :-

Create a program that manages customers and their orders using Aggregation.

Create a BLC class Order.

A class to represent an order with details like order ID, product name, and price.

Field Declarations :-

```
private String orderId;    -> Stores the order ID
private String itemName;   -> Stores the name of the product ordered
private double price;      -> Stores the price of the product
```

Constructor Declaration :-

```
-> public Order(String orderId, String itemName, double price) A constructor to initialize
the order ID, item name, and price.
```

getter() Methods Declaration :-

```
-> public String getOrderId();
-> public String getProductName();
-> public double getPrice();
```

toString() Method Declaration :-

```
@Override
public String toString();
A method to return a string representation of the order.
```

Create a class called Customer.

A class to represent a customer with details

Field Declarations :-

-> private String name; // Stores the customer's name
-> private String email; // Stores the customer's email
-> private String address; //Stores the customer's address
-> private long mobileNo; //Stroes the customer's mobile number
-> private Order order; // Stores the order object

Constructor Declaration :-

->Take a parameterized constructor to initialize all the fields.

toString Method Declaration :-

@Override

public String toString();

A method to return a string representation of the customer, including order details.

Create an ELC class Zomoto class with the following tasks:

-> Create a main method.
-> Create an Order object.
-> Create a Customer object that includes the Order.
-> Display the customer information.

Constraints:

-

Sample Input:

O101 Pizza 499.50 Rahul Sharma rahul@gmail.com Delhi 9876543210

Sample Output:

Customer Details: Name: Rahul Sharma Email: rahul@gmail.com Address: Delhi Mobile: 9876543210 Order Details: Order ID: O101 Product Name: Pizza Price: 499.5

Explanation:

-

Solution Code

```
import java.util.*;

public class Zomato{

    public static void main(String [] args){

        Scanner sc = new Scanner(System.in);

        String id = sc.nextLine();
```

```

String itemName = sc.nextLine();
double price = Double.parseDouble(sc.nextLine());

Order d = new Order(id,itemName,price);

String name = sc.nextLine();
String email = sc.nextLine();
String address = sc.nextLine();
long mobNo = Long.parseLong(sc.nextLine());
Customer c = new Customer(name,email,address,mobNo,d);
System.out.println(c.toString());

    }

}

class Order{
    private String orderId;
    private String itemName;
    private double productPrice;

    Order(String orderId,String itemName,double productPrice){
        this.orderId = orderId;
        this.itemName = itemName;
        this.productPrice = productPrice;

    }
    public String getOrderId(){
        return this.orderId;
    }

    public String getItemName(){
        return this.itemName;
    }
    public double getPrice(){
        return this.productPrice;
    }
    public String toString(){
        return "Order Details: "+"\\n"+"Order ID: "+this.orderId+"\\n"+"Product Name:
"+this.itemName+"\\n"+"Price: "+this.productPrice;
    }
}

```

```

class Customer{
    private String name;
    private String email;
    private String address;
    private long mobileNo;
    private Order order;

    Customer(String name,String email,String address,long mobileNo,Order order){
        this.name = name;
        this.email=email;
        this.address=address;
        this.mobileNo = mobileNo;
        this.order = order;
    }
    public String toString(){
        return "Customer Details:"+ "\n" + "Name: " +this.name+ "\n" + "Email: "
        +this.email+ "\nAddress: " +this.address+ "\nMobile: "
        +this.mobileNo+ "\n\n" +order.toString();
    }
}

```

Program 2: Car Has An Engine

Languages: Java

Score (010): 10 / 10

Test Case Summary: Total: 3 Passed: 3
Failed: 0 Success: 100.0%

Attempts: 0

Submitted At: 19/11/2025, 12:28:28

Description: Create a Car class that contains an Engine object as a composition. The Engine class should store details about the engine, while the Car class should include details about the car along with validation checks for numeric values.

Create a BLC class Engine.

A class to represent an engine with a model and capacity attributes.

Field Declarations :-

private String model; > Stores the model of the engine.
private int engineCapacity; > Stores the capacity of the engine (must be positive).

Constructor Declaration :-

public Engine(String model, int engineCapacity) -> Initializes the engine model and capacity.

Note:-

If engineCapacity <= 0, print "Error Invalid Input" and terminate object creation.

Getter Methods :-

-> public String getModel()

-> public int getEngineCapacity()

Returns model and capacity.

toString() method :-

@Override

public String toString() -> Returns a string representation of the engine in the format :-

Engine Model: [model], Engine Capacity: [capacity]cc

Create another BLC class called Car.

A class to represent a car that contains an engine.

variable Declarations :-

private String make; > Stores the car's make.

private String model; > Stores the car's model.

private int year; > Stores the car's manufacturing year (must be positive).

private final Engine engine; > Stores the engine object.

Constructor Declaration :-

public Car(String make, String model, int year) -> Initializes make, model, and year.

Use composition logic to create Engine object.

Note :-

If year <= 0, print "Error Invalid Input" and terminate object creation.

toString() method :-

@Override

public String toString() -> Returns a string representation of the car in the format :-

Create an ELC class CompositionDemo with main method to test this application.

Constraints: -

Sample Input: TurboDiesel 2200 Mahindra XUV700 2022

Sample Output: Engine Model: TurboDiesel, Engine Capacity: 2200cc Car Make: Mahindra, Car Model: XUV700, Year: 2022 Engine Details -> Engine Model: TurboDiesel, Engine Capacity: 2200cc

Explanation: -

Solution Code

```
import java.util.*;

public class CompositionDemo{
    public static void main(String [] args){
        Scanner sc = new Scanner (System.in);
        String engModel = sc.nextLine();
        int engCap =Integer.parseInt(sc.nextLine());

        String carMke = sc.nextLine();
        String carmod = sc.nextLine();
        int year = Integer.parseInt(sc.nextLine());
        Car c = new Car(engModel,engCap,carMke,carmod,year);
        System.out.println(c.toString());
    }
}

class Engine{
    private String model;
    private int ingineCapacity;
    Engine(String model,int ingineCapacity){
        this.model= model;
        this.ingineCapacity = ingineCapacity;
        if(ingineCapacity<=0){
            System.out.println("Error Invalid Input");
            System.exit(0);
        }
    }
}
```

```

    }

    public String getModel(){
        return this.model;
    }

    public int getIEngineCapacity(){
        return this.ingineCapacity;
    }

    public String toString(){
        return "Engine Details -> Engine Model: "+this.getModel()+", Engine Capacity:
"+this.getIEngineCapacity()+"cc";
    }

}

class Car {
    private String carMake;
    private String carModel;
    private int year;
    private Engine engine;
    Car(String model ,int capacity,String carMake,String carModel,int year){
        this.carMake = carMake;
        this.carModel = carModel;
        this.year = year;
        if(year<=0){
            System.out.println("Error Invalid Input");
            System.exit(0);
        }
        this.engine = new Engine(model,capacity);
    }
    public String toString(){
        return "Car Make: "+this.carMake+", Car Model: "+this.carModel+", Year:
"+this.year+"\n"+engine.toString();
    }

}

```

Program 3: Modeling Employee and Address Details

Languages: Java

Score (010): 10 / 10

Test Case Summary: Total: 3 Passed: 3
Failed: 0 Success: 100.0%

Attempts: 0

Submitted At: 19/11/2025, 12:03:58

Description: Create a BLC class Address

Fields :-

Implement a class with private fields for street and city.

Constructor :-

Provide a constructor to initialize these fields.

getter() & toString() method :-

Implement getter methods and a toString() method to display the address.

Create another BLC class Person.

Fields :-

Implement a class with private fields for name and an Address object.

Constructor :-

Provide a constructor to initialize name and address.

method getPersonDetails()

Implement a method to display the person's name and address.

Create an ELC class called Test

Implement a main method :-

-> Instantiate an Address object with sample data.

-> Instantiate a Person object using the Address object created earlier.

-> Print the person's details using the method in the Person class.

Constraints: -

Sample Input: MG Road Bengaluru Rahul Sharma

Sample Output: Person Name: Rahul Sharma Address: Street - MG Road, City - Bengaluru

Explanation: -

Solution Code

```
import java.util.*;

public class Test{

public static void main(String [] args){
    Scanner sc = new Scanner(System.in);

    String street = sc.nextLine();
    String city = sc.nextLine();
    String name = sc.nextLine();

    Address ad = new Address(street,city);

    Person p = new Person(name,ad);
    System.out.println(p.getPerson());
}
}

class Address{
    private String street;
    private String city;
    Address(String street,String city){
        this.street = street;
        this.city= city;
    }
    public void setStreet(String street){
        this.street=street;
    }
    public String getStreet(){
        return this.street;
    }
    public void setCity(String city){
        this.city=city;
    }
    public String getCity(){
        return this.city;
    }
    public String toString(){
        return "Address: Street - "+this.street+", City - "+this.city;
```

```
    }  
}  
  
class Person{  
    private String name;  
    private Address address;  
  
    Person(String name,Address address){  
        this.name=name;  
        this.address= address;  
    }  
    public String getPerson(){  
        return "Person Name: "+this.name+"\n"+" "+address.toString();  
    }  
}
```