



Programming Test Results (With Test Cases)

Result Summary

Field	Value
Test ID	39182
Student ID	29195
Programs (with test cases)	3
Total Test Cases	9
Test Cases Passed	9
Fully Passed Programs	3
Partially Passed Programs	0
Failed Programs	0
Overall % (with test cases)	100.00%
Grade	Outstanding

Programs With Test Cases

#	Program Name	Total TC	Passed	Success Rate	Score	Submitted At	Attempts
1	StudentTracker	4	4	100.0%	10	15/11/2025, 13:14:21	0
2	EmployeeSalaryDemo	2	2	100.0%	10	15/11/2025, 12:26:34	0
3	RectangleELC	3	3	100.0%	10	15/11/2025, 11:51:46	0

Program Details (With Test Cases)

Program 1: StudentTracker

Field	Value
Program No.	1
Program Name	StudentTracker
Description	Person (Base Class) Represents a generic person with basic information. Instance Variables:

Field	Value
	<p>name (String)</p> <p>id (int)</p> <p>Constructor:</p> <p>Initializes name and id.</p> <p>Ø=Ý9 Student (Inherits from Person) Represents a student with academic effort tracking.</p> <p>Instance Variables:</p> <p>hardWorkScore (int) !' (0–100)</p> <p>taskCompleted (int) !' (number of assignments out of 10)</p> <p>Constructor:</p> <p>Calls super() and initializes additional fields.</p> <p>Ø=Ý9 PlacementCandidate (Inherits from Student) Represents a final-year student evaluated for placement.</p> <p>Instance Variables:</p> <p>classAttendance (double) !' percentage (0–100)</p> <p>labAttendance (double) !' percentage (0–100)</p> <p>Constructor:</p> <p>Uses constructor chaining to initialize all fields.</p> <p>Method:</p> <p>void evaluateCandidate(int choice):</p> <p>menu using switch-case or if else :</p> <ol style="list-style-type: none"> 1.Show all scores 2.Calculate placement probability 3.Show eligibility status (based on thresholds) 4.Exit <p>Placement Probability Logic:</p> $\text{probability} = (\text{hardWorkScore} * 0.3 + \text{taskCompleted} * 5 + \text{classAttendance} * 0.2 + \text{labAttendance} * 0.2)$ <p>[Note :----</p> <p>Eligibility Rules:</p> <p>Hard work score "e 70</p> <p>Task completed "e 7</p> <p>Class & Lab attendance "e 75 %</p> <p>]</p> <p>Take an ELC class StudentTracker and instantiate the PlacementCandidate and invoke the evaluateCandidate method .</p>

Field	Value
	<p>Sample Input :</p> <p>-----</p> <p>Name: virat ID: 101 HardWorkScore: 85 TaskCompleted: 9 ClassAttendance: 80.0 LabAttendance: 85.0</p> <p>Sample Output :</p> <p>-----</p> <p>Candidate: VIRAT (ID: 101)</p> <p>=== Placement Evaluation Menu ===</p> <p>1. View All Scores 2. Check Placement Probability 3. Check Placement Eligibility 4. Exit</p> <p>-----</p> <p>Enter your choice: 1</p> <p>Hard Work Score: 85 Tasks Completed: 9/10 Class Attendance: 80.0% Lab Attendance: 85.0%</p> <p>-----</p> <p>Enter your choice: 2</p> <p>Estimated Placement Probability: 92.5%</p> <p>-----</p> <p>Enter your choice: 3</p> <p>You are ELIGIBLE for placement!</p> <p>-----</p> <p>Enter your choice: 4 Exiting...</p>
Constraints	
Sample Input	virat 101 85 9 80.0 85.0 1
Sample Output	Hard Work Score: 85 Tasks Completed: 9/10 Class Attendance: 80.0% Lab Attendance: 85.0%
Explanation	-
Language(s)	java
Total Test Cases	4

Field	Value
Test Cases Passed	4
Test Cases Failed	0
Success Rate	100.0%
Score (0–10)	10
Attempts	0
Submitted At	15/11/2025, 13:14:21

Code

```

import java.util.*;
public class StudentTracker{
    public static void main(String [] args){
        Scanner sc = new Scanner(System.in);
        String name = sc.nextLine();
        int id =Integer.parseInt(sc.nextLine());
        int hardWorkScore = Integer.parseInt(sc.nextLine());
        int taskCompleted = Integer.parseInt(sc.nextLine());
        double clas = Double.parseDouble(sc.nextLine());
        double lab = Double.parseDouble(sc.nextLine());
        PlacementCandidate p = new
PlacementCandidate(name,id,hardWorkScore,taskCompleted,clas,lab);
        int c = Integer.parseInt(sc.nextLine());
        p.evalutate(c);
    }
}
class Person{
    String name;
    int id;
    Person(String name, int id){
        this.name= name;
        this.id= id;
    }
}
class Student extends Person{
    int hardWorkScore;
    int taskCompleted;
    Student(String name,int id,int hardWorkScore,int taskCompleted){
        super(name,id);
        this.hardWorkScore = hardWorkScore;
        this.taskCompleted=taskCompleted;
    }
}
class PlacementCandidate extends Student{
    double Percentage;
    double labAttendance;
    PlacementCandidate(String name,int id,int hardWorkScore,int taskCompleted,double
Percentage,double labAttendance){
        super(name, id,hardWorkScore,taskCompleted);
        this.Percentage=Percentage;
        this.labAttendance = labAttendance;
    }
    public void evalutate(int choice){
        if(choice ==1){
System.out.println("Hard Work Score: "+hardWorkScore);
System.out.println("Tasks Completed: "+taskCompleted+"/10");
System.out.println("Class Attendance: "+Percentage+"%");
System.out.println("Lab Attendance: "+labAttendance+"%");
        }
        else if(choice==2){
            double per=(hardWorkScore*0.3+taskCompleted*5+Percentage*0.2+labAttendance*0.2);
            System.out.printf("Estimated Placement Probability: %.2f%%",per);
        }
        else{
            System.out.println("You are NOT eligible for placement.");
        }
    }
}
}

```

Program 2: EmployeeSalaryDemo

Field	Value
Program No.	2
Program Name	EmployeeSalaryDemo
Description	<p>Create a class Employee (Business Logic Class)</p> <p>Non static Fields :</p> <p>employeeNumber : private-int employeeName : private-String employeeSalary:private -double</p> <p>Create a parameterized constructor to initialilize all the fields.</p> <p>Create a pair of setter and getter methods for all the Non static fields.</p> <p>Methods : ----- 1) Method Name : getEmployeeDesignation() Parameter : double salary [Here method should receive updated salary] Return Type : String Access modifier : public</p> <p>In this method, Take the updated salary in the parameter variable and return the employee designation based on the following criteria :</p> <p>a) If updatedSalary is greater than 120000, return Employee is a HR Manager. b) If updatedSalary is greater than 90000, return Employee is a Developer. c) If updatedSalary is greater than 60000, return Employee is a Designer. d) In the else part, return Employee is a Tester.</p> <p>Take toString() method to print Employee Object properties.</p> <p>Create an ELC class EmployeeDemo which contains main method, with the help of Scanner class take the input from the user to initialize the non static field through parameterized constructor.</p> <p>Print the employee details using toString() method.</p> <p>Take the salary increment amount from the user using Scanner class, update the employee salary using setter and getter.</p> <p>Print the employee data with updated salary.</p> <p>Pass this updated salary to getEmployeeDesignation() method to get and print the Employee Designation as per below output.</p>
Constraints	
Sample Input	101 Ravi 80000 10000
Sample Output	Updated Salary = 90000.0 !' Employee is a Developer
Explanation	-
Language(s)	java

Field	Value
Total Test Cases	2
Test Cases Passed	2
Test Cases Failed	0
Success Rate	100.0%
Score (0–10)	10
Attempts	0
Submitted At	15/11/2025, 12:26:34

Code

```

import java.util.*;
public class EmployeeDemo{
    public static void main(String [] args){
        Scanner sc = new Scanner(System.in);
        int eNO =Integer.parseInt(sc.nextLine());
        String name = sc.nextLine();
        double Salary = Double.parseDouble(sc.nextLine());
        double update = Double.parseDouble(sc.nextLine());
        Employee e = new Employee(eNO,name,Salary);
        System.out.println(e.getEmployeeDesigntion());
        e.setSalary(update);
        // System.out.println();
        System.out.println(e.toString());
    }
}
class Employee{
    private int emNo;
    private String emName;
    private double emSalary;

    Employee(int emNo,String emName,double emSalary){
        this.emNo=emNo;
        this.emName=emName;
        this.emSalary=emSalary;
    }
    public String getEmployeeDesigntion(){
        return "Employee Details:"+ "\n"+"Employee Number: "+this.emNo+"\n"+"Employee Name: "+this.emName+"\n"+"Employee Salary: "+this.emSalary;
    }
    public void setSalary(double Salary){
        this.emSalary+=Salary;
    }
    public String toString(){
String Posi="0";
        if(this.emSalary>=120000){
            Posi="Employee is a HR Manager.";
        }
        else if(this.emSalary>=90000){
            Posi = "Employee is a Developer.";
        }
        else if(this.emSalary>=60000){
            Posi ="Employee is a Designer.";
        }
        return "Employee Details:"+ "\n"+"Employee Number: "+this.emNo+"\n"+"Employee Name: "+this.emName+"\n"+"Employee Salary: "+this.emSalary+"\n"+" \n"+Posi;
    }
}

```

Program 3: RectangleELC

Field	Value
Program No.	3
Program Name	RectangleELC
Description	Create a BLC class Rectangle

Field	Value								
	<p>Attributes :</p> <table> <tr> <td>names</td><td>datatypes</td></tr> <tr> <td>-----</td><td>-----</td></tr> <tr> <td>width</td><td>double-privatre</td></tr> <tr> <td>height</td><td>double-private</td></tr> </table> <p>Implement a parameterized constructor to initialize the non static Field width and height.</p> <p>Methods :</p> <p>-----</p> <p>1) Method Name : getArea() Parameter : No Parameters Return Type : double Access modifier : public</p> <p>In this method returns the area of the rectangle.</p> <p>2) Method Name : getPerimeter() Parameter : No Parameters Return Type : double Access modifier : public</p> <p>In this method returns the perimeter of the rectangle.</p> <p>Note : Don't use toString() method</p> <p>Take one Main class ELC class which is having main method, Create a Rectangle object with width 5 and height 10 and call the getArea() and getPerimeter() methods on it.</p>	names	datatypes	-----	-----	width	double-privatre	height	double-private
names	datatypes								
-----	-----								
width	double-privatre								
height	double-private								
Constraints									
Sample Input	5 10								
Sample Output	Area = 50.0 Perimeter = 30.0								
Explanation	-								
Language(s)	Java								
Total Test Cases	3								
Test Cases Passed	3								
Test Cases Failed	0								
Success Rate	100.0%								
Score (0–10)	10								
Attempts	0								
Submitted At	15/11/2025, 11:51:46								

Code

```

import java.util.*;
public class Main {
    public static void main(String [] args){
        Scanner sc = new Scanner(System.in);
        double width =Double.parseDouble(sc.next());
        double height = Double.parseDouble(sc.next());
        if(width<=0||height<=0){
            System.out.println("Invalid input! Width and height must be positive numbers.");
            System.exit(0);
        }
        Rectangle r = new Rectangle(width,height);
        System.out.println("Area of Rectangle: "+r.getArea());
        System.out.println("Perimeter of Rectangle: "+r.getPerimeter());
    }
}
class Rectangle{
    private double width;
    private double height;
    Rectangle(double width,double height){
        this.width = width;
        this.height=height;
    }
    public double getArea(){
        return this.width*this.height;
    }
    public double getPerimeter(){
        return (width+height)*2;
    }
}

```