

Product name: See3CAM_24CUG_CHL_TC

Model number: See3CAM_24CUG_CHL_TC

The products mentioned above have been tested in accordance with the tests listed below and were found to comply during the development phase of the product.

1. Reliability Test

BS EN 50130-5:2011 Alarm systems Part 5: Environmental test methods	Specific Test description Class III weather protected Outdoor, fixed equipment	Comments	Status PASS/FAIL
Dry heat Operational IEC 60068-2-2:2007	Temp. +70°C, duration 16 hrs.	Tested in operating condition	PASS
Cold Operational IEC 60068-2-1:2007	Temp. -30°C, duration 16 hrs.	Tested in operating condition	PASS
Damp Heat Cyclic (operational) IEC 60068-2-30:2005	Temp. 30°C at 95% of RH with non-condensing, 55°C at 93% of RH with non-condensing (2 cycle, 12 hours dwell per cycle).	Tested in operating condition	PASS
Vibration sinusoidal operational IEC 60068-2-6:2008	Freq. Range 10-150Hz, 5m/s ² , 3 axes, sweep rate 1 octave/min 1 sweep/axis. Covered by Vibration endurance test	Tested in operating condition	PASS
Vibration sinusoidal endurance IEC 60068-2-6:2008	Freq. Range 10-150Hz, 10m/s ² , 3 axes, sweep rate 1 octave/min, 20 sweep/axis.	Tested in operating condition	PASS

2. Additional tests by e-con

Test specification	Specific Test description	Comments	Status PASS/FAIL
HALT (Highly Accelerated Life Test)	Overstress test to Fail. Determination of fail limits for • Low ambient temperature, Step raise +20°C to -40°C • High ambient temperature, Step raise + 20°C to +120°C • Rapid thermal Cycling -40°C to +120°C (5 cycles, 40 minutes dwell per cycle)	Tested in operating condition	PASS
HASS (Highly Accelerated Stress Screening)	Stress test performed within its operating temperature range. • -30°C to +70°C (5 cycles, 60 minutes dwell per cycle)	Tested in operating condition	PASS
Humidity Storage Temperature Test	Temp. 30°C at 95% of RH with Non-condensing, 55°C at 93% of RH with Non-condensing (2 cycle, 12 hours dwell per cycle).	Tested under Non-Operating condition	PASS

Product Tests Report

Endurance test	Continuous streaming test for 21 days at room temperature	Tested in operating condition	PASS
	Continuous streaming test for 21 days at +70°C	Tested in operating condition	PASS
Thermal cycling/power cycling test	Power on/off switching test in combination with thermal cycling. Thermal cycling range: -30°C to +70°C. Duration: 500 cycles continuously (on/off for every 1 minute)	Tested in operating condition	PASS
Low Storage Temperature Test	Stress test with 16hrs at specified temperature. • Low temperature -40°C	Tested under Non-Operating condition	PASS
High Storage Temperature Test	Stress test with 16hrs at specified temperature. • High temperature 90 °C	Tested under Non-Operating condition	PASS

Test Conducted by:	J.Suresh	STATUS: Pass/Fail	PASS
Test approved by:	S. Karthikeyan		