

1
point

1.

For which of the following problems would anomaly detection be a suitable algorithm?

- ☐ From a large set of hospital patient records, predict which patients have a particular disease (say, the flu).
- ☐ Given data from credit card transactions, classify each transaction according to type of purchase (for example: food, transportation, clothing).
- ☐ From a large set of primary care patient records, identify individuals who might have unusual health conditions.
- ☐ In a computer chip fabrication plant, identify microchips that might be defective.

1
point

2.

Suppose you have trained an anomaly detection system that flags anomalies when $p(x)$ is less than ϵ , and you find on the cross-validation set that it has too many false negatives (failing to flag a lot of anomalies). What should you do?

- ☒ Increase ϵ
- ☐ Decrease ϵ

1
point

3.

Suppose you are developing an anomaly detection system to catch manufacturing defects in airplane engines. Your model uses

$$p(x) = \prod_{j=1}^n p(x_j; \mu_j, \sigma_j^2).$$

You have two features x_1 = vibration intensity, and x_2 = heat generated. Both x_1 and x_2 take on values between 0 and 1 (and are strictly greater than 0), and for most "normal" engines you expect that $x_1 \approx x_2$. One of the suspected anomalies is that a flawed engine may vibrate very intensely even without generating much heat (large x_1 , small x_2), even though the particular values of x_1 and x_2 may not fall outside their typical ranges of values. What additional feature x_3 should you create to capture these types of anomalies:

☒ $x_3 = \frac{x_1}{x_2}$

☐ $x_3 = \frac{1}{x_2}$

☐ $x_3 = x_1 + x_2$

☐ $x_3 = \frac{1}{x_1}$

Anomaly Detection

Quiz, 5 questions

1
point

4.

Which of the following are true? Check all that apply.

☐ In a typical anomaly detection setting, we have a large number of anomalous examples, and a relatively small number of normal/non-anomalous examples.

☒ When developing an anomaly detection system, it is often useful to select an appropriate numerical performance metric to evaluate the effectiveness of the learning algorithm.


☐ When evaluating an anomaly detection algorithm on the cross validation set (containing some positive and some negative examples), classification accuracy is usually a good evaluation metric to use.

☒ In anomaly detection, we fit a model $p(x)$ to a set of negative ($y = 0$) examples, without using any positive examples we may have collected of previously observed anomalies.

1
point

5.

You have a 1-D dataset $\{x^{(1)}, \dots, x^{(m)}\}$ and you want to detect outliers in the dataset. You first plot the dataset and it looks like this:



Anomaly Detection

Quiz, 5 questions

Suppose you fit the gaussian distribution parameters μ_1 and σ_1^2 to this dataset. Which of the following values for μ_1 and σ_1^2 might you get?

☒ $\mu_1 = -3, \sigma_1^2 = 4$

☐ $\mu_1 = -6, \sigma_1^2 = 4$

☐ $\mu_1 = -3, \sigma_1^2 = 2$

☐ $\mu_1 = -6, \sigma_1^2 = 2$



I, **Jun-Chieh Wang**, understand that submitting work that isn't my own may result in permanent failure of this course or deactivation of my Coursera account. Learn more about Coursera's Honor Code

Submit Quiz

