

ORAC

INTERNATIONAL

ELECTRIC RECOVERY WINCH

Heavy-Duty 4x4 • Off-Road • Industrial Recovery

P R O D U C T S P E C I F I C A T I O N S H E E T

Product Information			
Product Name	Electric Recovery Winch	Voltage	DC 12V or 24V
Brand	NeuXatrix LED	Rope Compatibility	Steel / Synthetic / Dyneema
Product Type	Heavy-Duty Electric Winch	Motor	High-Torque Series Wound
Origin	China	Gear System	Planetary

Technical Specifications — Model Range							
Model	Pulling Capacity	Lifting Capacity	Rope Length	Rope Dia.	Voltage	Drum Size	Weight
2000 LB	2000 lb (900 kg)	200 kg	6 m	4 mm	12V / 24V	1.25"	6.5 kg
3000 LB	3000 lb (1300 kg)	300 kg	6 m	5 mm	12V / 24V	1.25"	7 kg
3500 LB	3500 lb (1500 kg)	350 kg	10 m	5 mm	12V / 24V	1.45"	9 kg
4000 LB	4000 lb (1800 kg)	400 kg	10 m	5 mm	12V / 24V	1.45"	10 kg
4500 LB	4500 lb (2000 kg)	450 kg	10 m	5 mm	12V / 24V	1.45"	12 kg
6000 LB	6000 lb (2700 kg)	500 kg	14 m	7 mm	12V / 24V	2.52"	28 kg
9500 LB	9500 lb (4300 kg)	600 kg	24 m	9 mm	12V / 24V	2.52"	37 kg
12000 LB	12000 lb (5400 kg)	750 kg	24 m	9 mm	12V / 24V	2.52"	38 kg
13500 LB	13500 lb (6000 kg)	800 kg	24 m	9 mm	12V / 24V	2.52"	38 kg
16800 LB	16800 lb (7600 kg)	950 kg	24 m	11 mm	12V / 24V	2.52"	56 kg
20000 LB	20000 lb (9000 kg)	1000 kg	24 m	11 mm	12V / 24V	2.52"	56 kg

Rope Options

STEEL WIRE - Galvanised high-tensile construction - Excellent abrasion resistance - Cost-effective & highly durable - Ideal for industrial recovery	SYNTHETIC - Ultra-lightweight construction - Safer than steel under recoil - Floats on water • easy handling - UV & moisture resistant	DYNEEMA® - Premium UHMWPE fibre - Very high tensile strength - Minimal stretch • low weight - Chemical & corrosion resistant
--	---	---

General Specifications

Braking	Automatic Load-Hold
Clutch	Sliding Ring Gear
IP Rating	Weather Resistant
Operating Temp.	-20°C to +60°C
Mounting	Universal Pattern
Finish	Powder-Coated / Corrosion Resistant

ORAC

INTERNATIONAL



AMBIENT STRIP LIGHTS

Transform Every Drive • Light Up Every Moment

P R O D U C T S P E C I F I C A T I O N S H E E T

PRODUCT INFORMATION			
PRODUCT NAME	Ambient Strip Lights	APPLICATION	Cars / SUVs / Trucks / Vans
BRAND	NeuXatrix LED	INSTALLATION	Adhesive Backing (Plug & Play)
PRODUCT TYPE	Automotive Interior RGB Lighting	CONTROL	Bluetooth App
ORIGIN	China	WARRANTY	12 Months

TECHNICAL SPECIFICATIONS			
OPERATING VOLTAGE	DC 12V (Car Adapter)	WATERPROOF RATING	IP65 (Strip Light)
LED TYPE	5050 RGB LED	OPERATING TEMPERATURE	-20°C ~ +60°C
COLOUR SYSTEM	16 Million+ Colours	LIFESPAN	> 50,000 Hours
POWER CONSUMPTION	Low Power	LIGHTING MODES	Static / Breathing / Music Sync / Gradient

AVAILABLE MODELS					
MODEL	LENGTH	LEDS	STRIP TYPE	CONTROL	APPLICATION
ASL-4IN1	4 × 60 cm	48 LEDs / Strip	4-in-1 Set	Bluetooth App	Dashboard + Doors
ASL-6IN1	6 × 60 cm	48 LEDs / Strip	6-in-1 Set	Bluetooth App	Dashboard + Doors
ASL-9IN1	9 × 60 cm	48 LEDs / Strip	9-in-1 Set	Bluetooth App	Full Interior
ASL-11IN1	11 × 60 cm	48 LEDs / Strip	11-in-1 Set	Bluetooth App	Full Interior Premium
ASL-CUSTOM	Custom Length	Custom	Custom Set	Bluetooth App	Custom Fit Solutions

ORAC

INTERNATIONAL

CAMPING & OFF-ROAD KITS

Built for Adventure • Ready for Any Terrain

P R O D U C T S P E C I F I C A T I O N S H E E T

Product Information			
PRODUCT NAME	Camping & Off-Road Kits	APPLICATION	4x4 / SUV / Truck / Overlanding
BRAND	NeuXatrix	STORAGE	Compact & Portable
PRODUCT TYPE	All-in-One Outdoor & Overlanding Kit	CONFIGURATIONS	Basic / Adventure / Expedition
ORIGIN	China	WARRANTY	12 Months

Common Specifications			
MATERIAL	Aluminium / Steel / ABS / Oxford Fabric	OPERATING TEMPERATURE	-20°C to +60°C
POWER SUPPLY	12V DC (Most Accessories)	WATERPROOF RATING	IP65 & above (Selected Items)
COLOUR	Black / Grey / Khaki	BUILD QUALITY	Heavy-Duty & Weather Resistant

Kit Components (Typical)			
ROOF TOP TENT Waterproof, UV resistant, easy setup	PORTABLE FRIDGE 12V / 24V / 240V, large capacity	LED LIGHTS Spot, flood & combo, high brightness	PORTABLE STOVE Dual burner, windproof, fuel efficient
LED LANTERN Rechargeable, multi-mode lighting	FOLDING CHAIR Heavy-duty, comfortable & compact	FOLDING TABLE Aluminium, lightweight & sturdy	RECOVERY TRACKS High strength, anti-slip, sand/mud use
RECOVERY KIT Tow rope, shackles, snatch strap	MULTI-FUNCTION SHOVEL Foldable, durable & portable	AIR COMPRESSOR 12V, high pressure, fast inflation	CARRY BAG Heavy-duty, organised & easy storage

Available Kit Options		
BASIC KIT <i>Essential gear for short trips & camping</i> - LED Lantern - Folding Chair - Folding Table - Portable Stove - Carry Bag	ADVENTURE KIT <i>Enhanced gear for off-road & adventure</i> - Roof Top Tent - Portable Fridge - LED Light Bar - Recovery Kit - Air Compressor - Folding Table & Chair - Carry Bag	EXPEDITION KIT <i>Complete premium kit for extreme expeditions</i> - Roof Top Tent - Portable Fridge - LED Light Bar (Set) - Recovery Tracks - Recovery Kit - Air Compressor - Multi-Function Shovel - Portable Stove - Folding Table & Chairs - LED Lantern - Carry Bag / Storage Box

SOUND INSULATION & DAMPING SHEETS

Automotive • Building • Equipment • Industrial

P R O D U C T S P E C I F I C A T I O N S H E E T

PRODUCT INFORMATION			
PRODUCT NAME	Sound Insulation & Damping Sheets	APPLICATION	Automotive / Building / Industrial
BRAND	NeuXatrix	INSTALLATION	Self-Adhesive, Easy Fit
PRODUCT TYPE	Vibration Damping & Sound Deadening	CERTIFICATION	5 Patents / VOC Compliant
ORIGIN	China	CUSTOM SIZES	Available (As Per Order)

COMMON SPECIFICATIONS			
HIGH TEMPERATURE	Up to +180°C	MATERIAL TYPES	Butyl Film / Insulation Cotton / Polyester Fibre
LOW TEMPERATURE	Down to -50°C	KEY FUNCTION	Sound & Heat Insulation, Vibration Damping
GREEN RATING	Superior to VOC Standards	BUILD	Durable, Easy Install & Eco-Friendly

PRODUCT DIRECTORY					
NO.	PRODUCT	SIZE (MM)	MATERIAL	TEMP. RANGE	PACKING
1	Antela Shock-proof Plate	2 × 460 × 800	Aluminium foil composite butyl film	-50°C ~ +180°C	25 pcs/box
2	Antela Shock-proof Plate	2.3 × 460 × 800	Aluminium foil composite butyl film	-50°C ~ +180°C	20 pcs/box
3	INPHIC Shock-proof Plate (OEM)	2 × 460 × 800	Aluminium foil composite butyl film	-50°C ~ +180°C	25 pcs/box
4	INPHIC Shock-proof Plate (Custom)	As per order	Aluminium foil composite butyl film	-50°C ~ +180°C	As per order
5	Big Mac Vibration Stop Plate	As per order	Aluminium foil composite butyl film	-50°C ~ +180°C	As per order
6	Accident Car Soundproof Blanket	2.3 × 500 × 1000	Non-woven composite butyl film	-50°C ~ +100°C	20 pcs/box
7	Low Frequency Sound Insulation King	8 × 460 × 800	Sound-absorbing cotton + vibration plate	-50°C ~ +180°C	18 pcs/box
8	Three-in-One Sound Insulation Board	10 × 460 × 800	Insulation cotton + aluminium foil vibration plate	-50°C ~ +180°C	30 pcs/box
9	Engine Room Insulation Cotton	5 × 100 × 1400	Aluminium foil composite insulation cotton	-50°C ~ +180°C	10 pcs/box
10	Sound Absorbing & Insulating Cotton	10 × 1500 (Roll)	Polyester fibre sound-absorbing cotton	-50°C ~ +100°C	As per order



INTERNATIONAL

ON-BOARD AIR COMPRESSOR

Power On Demand • Air Where You Need It

P R O D U C T S P E C I F I C A T I O N S H E E T

PRODUCT INFORMATION			
PRODUCT NAME	On-Board Air Compressor	APPLICATION	4x4 / SUV / Truck / Overlanding / Air Tools
BRAND	NeuXatrix	RANGE	7 Models — Bare Units & Kits
PRODUCT TYPE	12V Vehicle Air Compressor & Kits	INSTALLATION	Compact & Easy Mount
ORIGIN	China	PROTECTION	Overheat / Thermal Cut-Off

COMMON SPECIFICATIONS			
VOLTAGE	12 V DC	EXTENDABLE HOSE	6 m
PRESSURE SWITCH	120 PSI On / 150 PSI Off	POWER CORD	2.2 – 2.5 m
TANK (KITS)	1.0 Gallon	INLINE FUSE (KITS)	2 × 40 A

PERFORMANCE SPECIFICATIONS						
MODEL	TYPE	AIR FLOW	DUTY CYCLE	MAX AMP DRAW	MAX PRESSURE	NET WEIGHT
YF6475R	Metal Air Compressor	3.0 CFM	33%	28 A	150 PSI	4.5 kg
YF6276R-1	Compact Air Compressor	0.98 CFM	35%	10 A	150 PSI	2.4 kg
YF6475R-4	Twin-Cylinder Compressor	130 LPM	100%	55 A	300 PSI	9.73 kg
YF6475R-5	Twin-Cylinder Compressor	5.9 CFM	100%	58 A	150 PSI	7.67 kg
YF6477R	Air Compressor Kit (Tank)	5.9 CFM	100%	62 A	150 PSI	16 kg
YF6478R	Air Compressor Kit (Tank)	130 LPM	100%	61 A	300 PSI	16 kg
YF6277R	Portable Compressor Kit	3.0 CFM	33%	28 A	120 PSI	7.4 kg

PACKING & LOADABILITY					
MODEL	CARTON QTY	G.W / N.W (KG)	CARTON SIZE (CM)	20FT (PCS)	40HQ (PCS)
YF6475R	1	4.5 / 3.8	23 × 13 × 19	4577	11266
YF6276R-1	4	8.13 / 7.2	30 × 20 × 51	3400	8620
YF6475R-4	1	12 / 11.5	35.5 × 19.5 × 24.7	1520	3860
YF6475R-5	1	8.6 / 7.5	37.5 × 27 × 19.5	1317	3343
YF6477R	1	18 / 17	51.5 × 40 × 19.5	647	1503
YF6478R	1	17 / 16	51.5 × 40 × 19.5	397	1693
YF6277R	1	7.53 / 7.03	36 × 30.5 × 17	1500	3643

ORAC

INTERNATIONAL

PAINT PROTECTION FILM (PPF)

Invisible Shield • Lasting Shine

P R O D U C T S P E C I F I C A T I O N S H E E T

Product Information			
Product Name	Paint Protection Film (PPF)	Material	TPU (Thermoplastic Polyurethane)
Brand	NeuXatrix	Application	Automotive Exterior Paint Protection
Product Type	TPU Self-Healing Protective Film	Adhesive Type	Pressure Sensitive Acrylic
Origin	China	Warranty	5 – 10 Years (Series Dependent)

Technical Specifications			
Thickness Options	6.5 / 7.5 / 8.5 mil (165–215μ)	Peel Strength	> 1.5 N/mm
Film Transparency	> 90%	Temperature Resistance	–40°C to +110°C
Gloss Level	High Gloss	UV Resistance	Excellent
Hydrophobic Angle	> 100°	Yellowing Resistance	Excellent
Tensile Strength	> 28 MPa	Self-Healing	Heat Activated (Minor Scratches)
Elongation at Break	> 300%	Finish Options	High Gloss / Ultra Gloss / Matte

Product Series						
Series	Thickness	Key Features	Self-Healing	Hydrophobic	Warranty	Best For
Standard	6.5 mil (165μ)	Good protection, high clarity, cost-effective	★★★★☆	★★★★☆	5 Years	Daily use • Sedan / Hatchback
Premium	7.5 mil (190μ)	Enhanced durability, self-healing, high gloss	★★★★☆	★★★★☆	7 Years	SUV / Luxury • Highway driving
Pro	8.5 mil (215μ)	Maximum protection, impact resistant, self-healing	★★★★★	★★★★★	10 Years	Performance • Off-road / Extreme

Available Sizes & Finish			
Standard Roll Widths	0.61 / 0.76 / 1.22 / 1.52 / 1.83 m	Standard Roll Length	15 m (All Widths)
Width (Inches)	24" / 30" / 48" / 60" / 72"	Custom Cuts	Available on Request