



COCO FIBER BALE

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
PRODUCT NAME	Coco Fiber Bale	RAW MATERIAL	Coconut Husk
BOTANICAL SOURCE	Cocos nucifera	HARVEST SEASON	Throughout the Year
PRODUCT TYPE	Natural Coco-Fiber Bale	PROCESSING	Retting, Washing, Drying, Combing and Baling
HS CODE	53050090 (Coco Fiber)	ORIGIN	India

PHYSICAL & CHEMICAL SPECIFICATIONS	
PARAMETER	RANGE / LIMIT
Fiber Length	5 – 30 cm
Fiber Diameter	0.1 – 0.5 mm
Tensile Strength	100 – 200 MPa
Elongation at Break	15 – 40%
Lignin Content	40 – 45%
Cellulose Content	35 – 40%
Ash Content	8% Maximum
Oil & Grease	1% Maximum
Impurities (Dust, Sand, Husk)	5% Maximum
Shrinkage	5 – 10%
Foreign Matter	5% Maximum

BALE SPECIFICATION (STANDARD)	
PARAMETER	VALUE
Bale Size (L x W x H)	90 × 45 × 30 cm (Approx.)
Bale Weight	100 – 120 kg (Approx.)
Compression	High Compression
Strapping	PP Strapping (2 – 3 Nos.)
Bales per 40ft Container	100 – 110 Bales (Approx.)

PACKAGING OPTIONS	
PACKAGING TYPE	DETAILS
Standard Bale	Compressed bale packed with PP wrap
Customized Bale	Size and weight as per buyer requirement
Bulk in Container	Loose fiber in 20ft / 40ft container as per buyer requirement
Custom Labeling	Available as per buyer requirement

ORIGIN

India

QUALITY ASSURED

Specifications are typical values and may vary slightly depending on raw material and processing conditions.

PACKING

As Per Buyer Requirement

ORAC INTERNATIONAL

Instagram [orac_international](#) | LinkedIn [Orac International](#) | +91 8870615820 | info@oracholdings.com | www.oracholdings.com

COCO PEAT BLOCKS

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
PRODUCT NAME	Coco Peat Blocks	RAW MATERIAL	Coconut Husk
BOTANICAL SOURCE	Cocos nucifera	PH (1:5 SOLUTION)	5.5 – 6.8
PRODUCT TYPE	Compressed Coco Peat Block	ELECTRICAL CONDUCTIVITY (EC)	< 1.0 mS/cm
HARVEST SEASON	Throughout the Year	ORGANIC MATTER	> 90%
PROCESSING	Washed, Screened, Dehydrated and Compressed	SALMONELLA	Absent / 25g
HS CODE	14049090 (Coco Peat)	WEED SEEDS	Absent

PHYSICAL & CHEMICAL SPECIFICATIONS	
PARAMETER	RANGE / LIMIT
Particle Size	90% Passes Through 6 mm Sieve
Moisture Content	15% Maximum
Water Holding Capacity	650 – 750% (Dry Basis)
Air Filled Porosity	10 – 30%
Ash Content	8% Maximum
Compression Ratio	5:1
Bulk Density (Uncompressed)	80 – 100 kg/m ³
Bulk Density (Compressed Block)	500 – 550 kg/m ³
Color	Brown
Odor	Odorless
Impurities (Plastic, Stones, etc.)	Absent

MOISTURE & EXPANSION	
PARAMETER	VALUE / RANGE
Moisture Content	15% Maximum
Expansion Ratio	5:1 (Minimum)
Volume After Expansion	70 – 75 Liters (Per 5 kg Block)
Water Absorption	650 – 750%
Time to Expand	15 – 20 Minutes

BLOCK SIZE & WEIGHT (STANDARD)	
PARAMETER	VALUE
Block Size (Compressed)	30 × 30 × 10 cm (± 1 cm)
Block Weight (Compressed)	5 kg (± 250 g)
Blocks per Pallet	60 – 72 Blocks
Pallet Size	100 × 120 × 150 cm (Approx.)
Pallet Weight	300 – 400 kg (Approx.)

PACKAGING OPTIONS	
PACKAGING TYPE	DETAILS
Shrink Wrapped Blocks	Individually shrink wrapped
Stacked on Pallet	Stacked and stretch wrapped on pallet
Bulk in Container	Loose blocks in bulk as per buyer request
Custom Labeling	Available as per buyer requirement

ORIGIN
India

QUALITY ASSURED
Specifications are typical values and may vary slightly depending on raw material and processing conditions.

PACKING
As Per Buyer Requirement



COTTON YARN

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
PRODUCT NAME	Cotton Yarn	FIBER	100% Cotton
YARN TYPE	Combed / Carded	GRADE	Premium
CONSTRUCTION	Single / Ply	STRENGTH	High Tenacity
TWIST	Standard Twist	EVENNESS	Good
SPINNING SYSTEM	Ring Spun	ELONGATION	Low to Medium
GAUGE	7G to 32G	QUANTITY PER CONE	1.0 kg to 5.0 kg
USAGE	Weaving / Knitting / Dyeing	PACKAGING TYPE	Hanks / Cones / Cheese
HS CODE	52051200	ORIGIN	India

YARN PARAMETERS	
PARAMETER	VALUE / RANGE
Count (Ne)	6s – 60s
Strength (RKM)	Min 14 – Max 28
Evenness (U%)	10% – 14%
CVm%	12% – 16%
Hairiness Index	3.0 – 5.0
Twist (TPI)	As per Count
Moisture Regain	6.5% – 8.5%
Shrinkage	2% – 4%
Wax Content	0.4% – 0.6%
Rag Content	Max 16
Neps (per 1000 m)	Max 200
Count Strength Product (CSP)	1800 – 2400

YARN COUNT & STRUCTURE	
YARN COUNT (NE)	PLY
Ne 6s – Ne 16s	Single Ply
Ne 16s – Ne 30s	Single Ply
Ne 30s – Ne 40s	Single Ply
Ne 40s – Ne 60s	Single Ply

PACKAGING DETAILS		
PACKAGE TYPE	NET WEIGHT	PACKING METHOD
Hanks	840 gms / Hank	Poly Bag + Carton
Cones	1.0 – 5.0 kg / Cone	Shrink Wrap + Carton
Cheese	1.0 – 3.6 kg / Cheese	Shrink Wrap + Carton
Carton Size	As per Buyer Requirement	5 Ply / Standard Export Carton

ORIGIN

India

QUALITY ASSURED

Specifications are typical values and may vary slightly depending on raw material and processing conditions.

PACKING

Hanks / Cones / Cheese — As Per Buyer Requirement

ORAC INTERNATIONAL

Instagram [orac_international](#) | LinkedIn [Orac International](#) | +91 8870615820 | info@oracholdings.com | www.oracholdings.com

JUTE BAGS / SACKS

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
PRODUCT NAME	Jute Bags / Sacks	SIZE (W X L)	As per Requirement
MATERIAL	100% Natural Jute	STITCHING	Machine Stitching
FABRIC TYPE	Hessian / Plain Weave	LOAD CAPACITY	5 kg to 100 kg
GSM (FABRIC WEIGHT)	200 – 400 GSM	MOISTURE REGAIN	12% Maximum
WEAVE	Plain Weave	BIODEGRADABLE	Yes
COLOR	Natural Golden / Beige	HS CODE	53063200

FABRIC SPECIFICATIONS	
PARAMETER	VALUE / RANGE
GSM (Fabric Weight)	200 – 400 GSM
Mesh (Warp x Weft)	7 × 7 to 10 × 10
Breaking Strength (Warp)	> 400 N/5 cm
Breaking Strength (Weft)	> 250 N/5 cm
Elongation (Warp)	< 7%
Elongation (Weft)	< 7%
Tear Strength	> 30 N
Water Absorbency	High
Flammability	Low
UV Resistance	Moderate

SACK / BAG SPECIFICATIONS	
FEATURE	DETAILS
Bag Type	Open Mouth / Hemmed
Bottom Type	Single Fold / Double Fold
Top Type	Open / Hemmed
Liner	With / Without (HDPE / LDPE)
Printing	As per Requirement
Minimum Order Quantity	As per Buyer Requirement
Customization	Size, GSM, Stitching, Printing as per Requirement

PACKAGING & SHIPPING	
PARAMETER	DETAILS
Packing	Bundle Packing
Bundle Weight	50 – 100 Bags per Bundle
Loading Capacity	As per Container Size
Container Capacity (40ft)	Approx. 22,000 – 28,000 Bags Depending on Size & GSM

ORIGIN	QUALITY ASSURED	PACKING
India	Specifications are typical values and may vary slightly depending on raw material and processing conditions.	Bundle Packing — As Per Buyer Requirement

QUARTZ LUMPS

PRODUCT SPECIFICATION SHEET

SIZE RANGE & TYPICAL SPECIFICATIONS

SIZE RANGE	NOMINAL SIZE	TYPICAL USAGE	SiO ₂ (MIN.)	Fe ₂ O ₃ (MAX.)	Al ₂ O ₃ (MAX.)	PACKING
2 mm to 5 mm	~3.5 mm	Glass, Paint, Filtration	99.0%	0.10%	0.20%	50 kg / HDPE Bag
5 mm to 10 mm	~7.5 mm	Glass, Foundry, Ceramics	99.0%	0.10%	0.20%	50 kg / HDPE Bag
10 mm to 20 mm	~15 mm	Foundry, Construction	98.5%	0.15%	0.30%	50 kg / HDPE Bag
20 mm to 40 mm	~30 mm	Construction, Concrete	98.0%	0.15%	0.30%	50 kg / HDPE Bag
40 mm to 80 mm	~60 mm	Road Metal, Drainage	97.5%	0.20%	0.40%	50 kg / HDPE Bag
80 mm to 150 mm	~115 mm	Construction, Landscaping	97.0%	0.20%	0.40%	Bulk / Jumbo Bag

Sizes can be customized as per buyer requirements.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE
Appearance	White to Off White
Form	Lumps (Angular)
Hardness (Mohs)	7
Specific Gravity	2.65
Bulk Density	1.40 – 1.60 g/cc
Water Absorption	< 0.5%
Solubility in Water	Insoluble
Lustre	Vitreous

CHEMICAL COMPOSITION
(TYPICAL %)

COMPONENT	TYPICAL VALUE
Silicon Dioxide (SiO ₂)	97.0% – 99.5%
Aluminum Oxide (Al ₂ O ₃)	0.10% – 0.50%
Iron Oxide (Fe ₂ O ₃)	0.05% – 0.20%
Calcium Oxide (CaO)	0.10% – 0.30%
Magnesium Oxide (MgO)	0.05% – 0.20%
Sodium Oxide (Na ₂ O)	0.05% – 0.20%
Potassium Oxide (K ₂ O)	0.05% – 0.20%
Loss on Ignition (LOI)	< 0.5%

PACKAGING & SHIPPING

PARAMETER	DETAILS
Packing Type	50 kg HDPE Bags · Jumbo Bags (1 MT)
Net Weight	50 kg per Bag (±1 kg tolerance)
Jumbo Bag Weight	1000 kg per Jumbo Bag (±10 kg)
Container Load (20 ft)	~25 MT
Container Load (40 ft)	~25 – 27 MT
Loading Port	India (West / East Coast)

APPLICATIONS

◆ Glass Industry

◆ Foundry Industry

◆ Ceramics & Refractories

◆ Construction Industry

◆ Paints & Coatings

◆ Rubber & Plastics

◆ Filtration Media

ORIGIN

India (West / East Coast Loading Ports)

QUALITY ASSURED

Specifications are typical values and may vary slightly depending on raw material and processing conditions.

PACKING

50 kg HDPE Bags / Jumbo Bags



SILK FIBER

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
PRODUCT NAME	Silk Fiber	NET WEIGHT	1.0 kg / 5.0 kg
SOURCE	Bombyx mori (Mulberry Silk)	TEXTURE	Soft & Smooth
FIBER TYPE	Natural Continuous Filament	PURITY	High
GRADE	Premium	FOREIGN MATTER	Minimal
FILTRATION	Double Refined	LUSTER	Excellent
DEGUMMING	Complete / Partially Degummed	HEAT STABILITY	Good
APPEARANCE	Shiny, Soft & Lustrous	STORAGE	Cool & Dry Place
PACKAGING	HDPE Bag / Vacuum Packed	HS CODE	50021000

PHYSICAL SPECIFICATIONS	
PARAMETER	VALUE / RANGE
Fiber Denier	1.2 – 1.6 d
Fineness	Fine
Tensile Strength	3.5 – 5.0 g/denier
Elongation	18% – 25%
Raw Silk Color	Off White to Cream
Feel	Soft & Silky
Length	Continuous
Reelability	Excellent
Uniformity	Good
Strength Evenness	Good

CHEMICAL COMPOSITION	
COMPONENT	PERCENTAGE (APPROX.)
Fibroin	70% – 75%
Sericin	20% – 25%
Waxes & Fats	1% – 2%
Mineral Matter	0.2% – 0.5%
Others	0.5% – 1.0%

PACKAGING DETAILS	
PACKAGING TYPE	NET WEIGHT
HDPE Bag	1.0 kg / Bag
Vacuum Packed	5.0 kg / Bag
Customized Packing	As per Buyer Requirement

ORIGIN

India

QUALITY ASSURED

Specifications are typical values and may vary slightly depending on raw material and processing conditions.

PACKING

HDPE Bag / Vacuum Packed

ORAC INTERNATIONAL

Instagram orac_international | LinkedIn Orac International | +91 8870615820 | info@oracholdings.com | www.oracholdings.com



WASTE COTTON

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION			
PRODUCT NAME	Waste Cotton	IMPURITIES	2% Maximum
MATERIAL	100% Cotton	TRASH CONTENT	Low to Medium
TYPE	Comber / Carding / Yarn Waste	GRADE	A / B / C Grade
ORIGIN	India	PACKING TYPE	Bale
COLOR	White / Off White / Mixed	NET WEIGHT	120 to 180 kgs per bale
MOISTURE	8% Maximum	HS CODE	52063000
FIBER LENGTH	10 mm to 50 mm	FIBER STRENGTH	Medium
STAPLE	Medium to Good	YARN COUNT	Ne 0.5s to Ne 40s
USAGE	Spinning, Nonwoven, Re-spinning, Stuffing	STORAGE	Cool & Dry Place

PHYSICAL PROPERTIES	
PARAMETER	TYPICAL VALUE
Staple Length	10 mm to 50 mm
Micronaire Value	3.0 to 4.5
Uniformity Index	Medium
Trash Content	Low to Medium
Moisture Regain	8% Maximum
Color	White / Off White / Mixed
Oil & Grease	1% Maximum
Recyclability	High
Suitability	Suitable for Spinning & Nonwoven

PACKAGING DETAILS	
DETAILS	SPECIFICATION
Packing Type	Bale
Net Weight	120 to 180 kgs per bale
Compression	Hydraulic Pressed
Wrapping	PP Strapping
Container Load	22 – 24 MT (20 ft FCL)
Loading Port	India (as per requirement)

ORIGIN	QUALITY ASSURED	PACKING
India	Specifications are typical values and may vary slightly depending on raw material and processing conditions.	Bale — Hydraulic Pressed, PP Strapping
ORAC INTERNATIONAL		
Instagram orac_international LinkedIn Orac International +91 8870615820 info@oracholdings.com www.oracholdings.com		