



Chapter 4: Intermediate SQL

Database System Concepts, 6th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Chapter 4: Intermediate SQL

- Join Expressions
- Views
- Transactions
- Integrity Constraints
- SQL Data Types and Schemas
- Authorization



Joined Relations

- **Join operations** take two relations and return as a result another relation.
- A join operation is a Cartesian product which requires that tuples in the two relations match (under some condition). It also specifies the attributes that are present in the result of the join
- The join operations are typically used as subquery expressions in the **from** clause



Joined Relations

- Example:

```
SELECT temp.customer_name, temp.balance
FROM (
    SELECT c.customer_name, a.balance
    FROM customer c INNER JOIN account a
    ON c.customer_id = a.customer_id) AS temp
    WHERE temp.balance > 1000;
```



Join operations – Example

- Relation *course*

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>
BIO-301	Genetics	Biology	4
CS-190	Game Design	Comp. Sci.	4
CS-315	Robotics	Comp. Sci.	3

- Relation *prereq*

<i>course_id</i>	<i>prereq_id</i>
BIO-301	BIO-101
CS-190	CS-101
CS-347	CS-101

- Observe that

prereq information is missing for CS-315 and
course information is missing for CS-437



Outer Join

- An extension of the join operation that avoids loss of information.
- Computes the join and then adds tuples from one relation that does not match tuples in the other relation to the result of the join.
- Uses *null* values.




Left Outer Join

- *course* **natural** left outer join *prereq*

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>
BIO-301	Genetics	Biology	4
CS-190	Game Design	Comp. Sci.	4
CS-315	Robotics	Comp. Sci.	3

<i>course_id</i>	<i>prereq_id</i>
BIO-301	BIO-101
CS-190	CS-101
CS-347	CS-101

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<i>prere_id</i>
BIO-301	Genetics	Biology	4	BIO-101
CS-190	Game Design	Comp. Sci.	4	CS-101
CS-315	Robotics	Comp. Sci.	3	<i>null</i>






Right Outer Join

- *course* **natural right outer join** *prereq*

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<i>prereq_id</i>
BIO-301	Genetics	Biology	4	BIO-101
CS-190	Game Design	Comp. Sci.	4	CS-101
CS-347	<i>null</i>	<i>null</i>	<i>null</i>	CS-101

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>
BIO-301	Genetics	Biology	4
CS-190	Game Design	Comp. Sci.	4
CS-315	Robotics	Comp. Sci.	3

<i>course_id</i>	<i>prereq_id</i>
BIO-301	BIO-101
CS-190	CS-101
CS-347	CS-101





Joined Relations

- **Join operations** take two relations and return as a result another relation.
- These additional operations are typically used as subquery expressions in the **from** clause
- **Join condition** – defines which tuples in the two relations match, and what attributes are present in the result of the join.
- **Join type** – defines how tuples in each relation that do not match any tuple in the other relation (based on the join condition) are treated.

<i>Join types</i>	<i>Join Conditions</i>
inner join left outer join right outer join full outer join	natural on <predicate> using $(A_1, A_1, \dots, A_n)$




Full Outer Join

- *course* **natural full outer join** *prereq*

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<i>prereq_id</i>
BIO-301	Genetics	Biology	4	BIO-101
CS-190	Game Design	Comp. Sci.	4	CS-101
CS-315	Robotics	Comp. Sci.	3	<i>null</i>
CS-347	<i>null</i>	<i>null</i>	<i>null</i>	CS-101

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>
BIO-301	Genetics	Biology	4
CS-190	Game Design	Comp. Sci.	4
CS-315	Robotics	Comp. Sci.	3


<i>course_id</i>	<i>prereq_id</i>
BIO-301	BIO-101
CS-190	CS-101
CS-347	CS-101






Joined Relations – Examples

- *course* **inner join** *prereq* on
course.course_id = prereq.course_id



<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<i>prereq_id</i>	<i>course_id</i>
BIO-301	Genetics	Biology	4	BIO-101	BIO-301
CS-190	Game Design	Comp. Sci.	4	CS-101	CS-190

- What is the **difference** between the above, and a natural join?
- *course* **left outer join** *prereq* on
course.course_id = prereq.course_id



<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<i>prereq_id</i>	<i>course_id</i>
BIO-301	Genetics	Biology	4	BIO-101	BIO-301
CS-190	Game Design	Comp. Sci.	4	CS-101	CS-190
CS-315	Robotics	Comp. Sci.	3	<i>null</i>	<i>null</i>



Joined Relations – Examples

- What is the difference between the inner join, and a natural join?


Join condition	Determined automatically based on matching column names
Output columns	Removes duplicate join columns
Preferred use	Shorter but riskier if tables share multiple column names



Joined Relations – Examples


- *course* **natural right outer join** *prereq*

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<u><i>prereq_id</i></u>
BIO-301	Genetics	Biology	4	BIO-101
CS-190	Game Design	Comp. Sci.	4	CS-101
CS-347	<i>null</i>	<i>null</i>	<i>null</i>	CS-101



- *course* **full outer join** *prereq* **using** (*course_id*)

<i>course_id</i>	<i>title</i>	<i>dept_name</i>	<i>credits</i>	<u><i>prereq_id</i></u>
BIO-301	Genetics	Biology	4	BIO-101
CS-190	Game Design	Comp. Sci.	4	CS-101
CS-315	Robotics	Comp. Sci.	3	<i>null</i>
CS-347	<i>null</i>	<i>null</i>	<i>null</i>	CS-101





Views

- In some cases, it is not desirable for all users to see the entire logical model (that is, all the actual relations stored in the database.)
- Consider a person who needs to know an instructors name and department, but not the salary. This person should see a relation described, in SQL, by

```
select ID, name, dept_name  
from instructor
```

- A **view** provides a mechanism to hide certain data from the view of certain users.
- Any relation that is not of the conceptual model/physically stored but is made visible to a user as a “virtual relation” is called a **view**.



View Definition

- A view is defined using the **create view** statement which has the form

create view *view_name* **as** <query expression>

where <query expression> is any legal SQL select expression. The view name is represented by ***view_name***.

- Once a view is defined, the view name can be used to refer to the virtual relation that the view generates.
- View definition is not the same as creating a new relation by evaluating the query expression
 - Rather, a view definition **causes the saving of an expression**; the **expression is substituted** into queries using the view.
- Example:
 - View creation: **create view v as select** *ID, name, dept_name* **from** *instructor*
 - Use: **select** *ID, name* **from** *v*
 - How does it work?
 - **select** *ID, name* **from** (**select** *ID, name, dept_name* **from** *instructor*)



Example Views

- A view of instructors without their salary

create view *faculty* **as**

select *ID, name, dept_name*
from *instructor*

- Find all instructors in the Biology department

select *name*

from *faculty*

where *dept_name* = 'Biology'

- Create a view of department salary totals

create view *departments_total_salary*(*dept_name, total_salary*) **as**

select *dept_name, sum* (*salary*)

from *instructor*

group by *dept_name*;



Views Defined Using Other Views

- **create view** *physics_fall_2009* **as**
 select *course.course_id, sec_id, building, room_number*
 from *course, section*
 where *course.course_id = section.course_id*
 and *course.dept_name = 'Physics'*
 and *section.semester = 'Fall'*
 and *section.year = '2009'*;
- **create view** *physics_fall_2009_watson* **as**
 select *course_id, room_number*
 from *physics_fall_2009*
 where *building = 'Watson'*;



View Expansion

- Expand use of a view or substitute the expression in a query/another view

```
create view physics_fall_2009_watson as  
(select course_id, room_number  
from (select course.course_id, building, room_number  
        from course, section  
        where course.course_id = section.course_id  
            and course.dept_name = 'Physics'  
            and section.semester = 'Fall'  
            and section.year = '2009')  
where building = 'Watson';
```



Update of a View

- Add a new tuple to *faculty* view which we defined earlier
insert into *faculty* values ('30765', 'Green', 'Music');

This insertion must be represented by the insertion of the tuple
(*'30765', 'Green', 'Music', null*)
into the *instructor* relation



Materialized Views

- **Materializing a view**: create a physical table containing all the tuples in the result of the query defining the view
- If relations used in the query are updated, the materialized view result becomes out of date
 - Need to **maintain** the view, by updating the view whenever the underlying relations are updated.
- **create materialized view** *departments_total_salary*(*dept_name*, *total_salary*) **as**
 select *dept_name*, **sum** (*salary*)
 from *instructor*
 group by *dept_name*;
- **select** * **from** *departments_total_salary*;



Integrity Constraints

- Integrity constraints guard against accidental damage to the database, by ensuring that authorized changes to the database do not result in a loss of data consistency.
 - A checking account must have a balance greater than \$10,000.00
 - A salary of a bank employee must be at least \$4.00 an hour
 - A customer must have a (non-null) phone number
 - **salary** must be higher or equal to 1000 and **name**-length must be longer than 2
- INSERT INTO `instructor\_test` VALUES ('10101','Sr','sri@gmail.com','Comp. Sci.', 500); => Failed



Integrity Constraints on a Single Relation

- **not null**
- **primary key**
- **unique**
- **check (P)**, where P is a predicate



Not Null and Unique Constraints

- **not null**
 - Declare *name* and *budget* to be **not null**
name **varchar(20) not null unique**
budget **numeric(12,2) not null**
- **unique** ($A_1, A_2, \dots, A_m$)
 - The unique specification states that the attributes $A_1, A_2, \dots, A_m$ form a candidate key.
 - Candidate keys are permitted to be null (in contrast to primary keys).



The check clause

- **check (P)**

where P is a predicate

Example: ensure that semester is one of fall, winter, spring or summer:

```
create table section (  
    course_id varchar (8),  
    sec_id varchar (8),  
    semester varchar (6),  
    year numeric (4,0),  
    building varchar (15),  
    room_number varchar (7),  
    time slot id varchar (4),  
    primary key (course_id, sec_id, semester, year),  
    check (semester in ('Fall', 'Spring', 'Summer'))  
);
```

- INSERT INTO `section` VALUES ('BIO-101','1','Winter',2009,'Painter','514','B'); => **Failed**



Referential Integrity

- Ensures that a value that appears in one relation for a given set of attributes also appears for a certain set of attributes in another relation.
 - Example: If “Biology” is a department name appearing in one of the tuples in the *instructor* relation, then there exists a tuple in the *department* relation for “Biology”.
- Let A be a set of attributes. Let R and S be two relations that contain attributes A and where A is the primary key of S. A is said to be a **foreign key** of R if for any values of A appearing in R these values also appear in S.
- $\text{course} \Rightarrow \text{dpt_name}$
- $\text{department} \Rightarrow \text{department_name}$
- **foreign key** (*dpt_name*) **references** *department*(department_name)



Cascading Actions in Referential Integrity

- **create table** *course* (
 course_id **char**(5) **primary key**,
 title **varchar**(20),
 dept_name **varchar**(20) **references** *department*
)
- **create table** *course* (
 ...
 dept_name **varchar**(20),
 foreign key (*dept_name*) **references** *department*
 on delete cascade
 on update cascade,
 ...
)
- alternative actions to cascade: **set null**



Built-in Data Types in SQL

- **date**: Dates, containing a (4 digit) year, month and date
 - Example: **date** '2005-7-27'
- **time**: Time of day, in hours, minutes and seconds.
 - Example: **time** '09:00:30' **time** '09:00:30.75'
- **timestamp**: date plus time of day
 - Example: **timestamp** '2005-7-27 09:00:30.75'
- **interval**: period of time
 - Example: **interval** '1' day
 - Subtracting a date/time/timestamp value from another gives an interval value
 - Interval values can be added to date/time/timestamp values



Default Value in SQL

create table *student*

**(*ID* varchar (5),
 name varchar (20) not null,
 dept_name varchar (20),
 tot_cred numeric (3,0) default 0,
 primary key (*ID*));**

**insert into *student*(*ID*, *name*, *dept_name*)
 values ('12789', 'Newman', 'Comp. Sci.');**

- 12789, Newman, comp. sci, 0




Index Creation

- **create table** *student*
(*ID* **varchar** (5),
name **varchar** (20) **not null**,
dept_name **varchar** (20),
tot_cred **numeric** (3,0) **default** 0,
primary key (*ID*))
- **create index** *studentID_index* **on** *student*(*ID*)
- Indices are data structures used to speed up access to records with specified values for index attributes
 - e.g. **select** *
 from *student*
 where *ID* = '145'

can be executed by using the index to find the required record,
without looking at all records of *student*

More on indices in Chapter 11





Large-Object Types

- Large objects (photos, videos, CAD files, etc.) are stored as a *large object*:
 - **blob**: binary large object -- object is a large collection of uninterpreted binary data (whose interpretation is left to an application outside of the database system)
 - **clob**: character large object -- object is a large collection of character data
 - When a query returns a large object, a pointer is returned rather than the large object itself.



End of Chapter 4

Database System Concepts, 6th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Figure 4.01

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>tot_cred</i>
00128	Zhang	Comp. Sci.	102
12345	Shankar	Comp. Sci.	32
19991	Brandt	History	80
23121	Chavez	Finance	110
44553	Peltier	Physics	56
45678	Levy	Physics	46
54321	Williams	Comp. Sci.	54
55739	Sanchez	Music	38
70557	Snow	Physics	0
76543	Brown	Comp. Sci.	58
76653	Aoi	Elec. Eng.	60
98765	Bourikas	Elec. Eng.	98
98988	Tanaka	Biology	120



Figure 4.02

<i>ID</i>	<i>course_id</i>	<i>sec_id</i>	<i>semester</i>	<i>year</i>	<i>grade</i>
00128	CS-101	1	Fall	2009	A
00128	CS-347	1	Fall	2009	A-
12345	CS-101	1	Fall	2009	C
12345	CS-190	2	Spring	2009	A
12345	CS-315	1	Spring	2010	A
12345	CS-347	1	Fall	2009	A
19991	HIS-351	1	Spring	2010	B
23121	FIN-201	1	Spring	2010	C+
44553	PHY-101	1	Fall	2009	B-
45678	CS-101	1	Fall	2009	F
45678	CS-101	1	Spring	2010	B+
45678	CS-319	1	Spring	2010	B
54321	CS-101	1	Fall	2009	A-
54321	CS-190	2	Spring	2009	B+
55739	MU-199	1	Spring	2010	A-
76543	CS-101	1	Fall	2009	A
76543	CS-319	2	Spring	2010	A
76653	EE-181	1	Spring	2009	C
98765	CS-101	1	Fall	2009	C-
98765	CS-315	1	Spring	2010	B
98988	BIO-101	1	Summer	2009	A
98988	BIO-301	1	Summer	2010	<i>null</i>



Figure 4.03

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>tot_cred</i>	<i>course_id</i>	<i>sec_id</i>	<i>semester</i>	<i>year</i>	<i>grade</i>
00128	Zhang	Comp. Sci.	102	CS-101	1	Fall	2009	A
00128	Zhang	Comp. Sci.	102	CS-347	1	Fall	2009	A-
12345	Shankar	Comp. Sci.	32	CS-101	1	Fall	2009	C
12345	Shankar	Comp. Sci.	32	CS-190	2	Spring	2009	A
12345	Shankar	History	32	CS-315	1	Spring	2010	A
12345	Shankar	Finance	32	CS-347	1	Fall	2009	A
19991	Brandt	Music	80	HIS-351	1	Spring	2010	B
23121	Chavez	Physics	110	FIN-201	1	Spring	2010	C+
44553	Peltier	Physics	56	PHY-101	1	Fall	2009	B-
45678	Levy	Physics	46	CS-101	1	Fall	2009	F
45678	Levy	Physics	46	CS-101	1	Spring	2010	B+
45678	Levy	Physics	46	CS-319	1	Spring	2010	B
54321	Williams	Comp. Sci.	54	CS-101	1	Fall	2009	A-
54321	Williams	Comp. Sci.	54	CS-190	2	Spring	2009	B+
55739	Sanchez	Music	38	MU-199	1	Spring	2010	A-
76543	Brown	Comp. Sci.	58	CS-101	1	Fall	2009	A
76543	Brown	Comp. Sci.	58	CS-319	2	Spring	2010	A
76653	Aoi	Elec. Eng.	60	EE-181	1	Spring	2009	C
98765	Bourikas	Elec. Eng.	98	CS-101	1	Fall	2009	C-
98765	Bourikas	Elec. Eng.	98	CS-315	1	Spring	2010	B
98988	Tanaka	Biology	120	BIO-101	1	Summer	2009	A
98988	Tanaka	Biology	120	BIO-301	1	Summer	2010	<i>null</i>



Figure 4.04

ID	name	dept_name	tot_cred	course_id	sec_id	semester	year	grade
00128	Zhang	Comp. Sci.	102	CS-101	1	Fall	2009	A
00128	Zhang	Comp. Sci.	102	CS-347	1	Fall	2009	A-
12345	Shankar	Comp. Sci.	32	CS-101	1	Fall	2009	C
12345	Shankar	Comp. Sci.	32	CS-190	2	Spring	2009	A
12345	Shankar	History	32	CS-315	1	Spring	2010	A
12345	Shankar	Finance	32	CS-347	1	Fall	2009	A
19991	Brandt	Music	80	HIS-351	1	Spring	2010	B
23121	Chavez	Physics	110	FIN-201	1	Spring	2010	C+
44553	Peltier	Physics	56	PHY-101	1	Fall	2009	B-
45678	Levy	Physics	46	CS-101	1	Fall	2009	F
45678	Levy	Physics	46	CS-101	1	Spring	2010	B+
45678	Levy	Physics	46	CS-319	1	Spring	2010	B
54321	Williams	Comp. Sci.	54	CS-101	1	Fall	2009	A-
54321	Williams	Comp. Sci.	54	CS-190	2	Spring	2009	B+
55739	Sanchez	Music	38	MU-199	1	Spring	2010	A-
70557	Snow	Physics	0	<i>null</i>	<i>null</i>	<i>null</i>	<i>null</i>	<i>null</i>
76543	Brown	Comp. Sci.	58	CS-101	1	Fall	2009	A
76543	Brown	Comp. Sci.	58	CS-319	2	Spring	2010	A
76653	Aoi	Elec. Eng.	60	EE-181	1	Spring	2009	C
98765	Bourikas	Elec. Eng.	98	CS-101	1	Fall	2009	C-
98765	Bourikas	Elec. Eng.	98	CS-315	1	Spring	2010	B
98988	Tanaka	Biology	120	BIO-101	1	Summer	2009	A
98988	Tanaka	Biology	120	BIO-301	1	Summer	2010	<i>null</i>



Figure 4.05

ID	course_id	sec_id	semester	year	grade	name	dept_name	tot_cred
00128	CS-101	1	Fall	2009	A	Zhang	Comp. Sci.	102
00128	CS-347	1	Fall	2009	A-	Zhang	Comp. Sci.	102
12345	CS-101	1	Fall	2009	C	Shankar	Comp. Sci.	32
12345	CS-190	2	Spring	2009	A	Shankar	Comp. Sci.	32
12345	CS-315	1	Spring	2010	A	Shankar	History	32
12345	CS-347	1	Fall	2009	A	Shankar	Finance	32
19991	HIS-351	1	Spring	2010	B	Brandt	Music	80
23121	FIN-201	1	Spring	2010	C+	Chavez	Physics	110
44553	PHY-101	1	Fall	2009	B-	Peltier	Physics	56
45678	CS-101	1	Fall	2009	F	Levy	Physics	46
45678	CS-101	1	Spring	2010	B+	Levy	Physics	46
45678	CS-319	1	Spring	2010	B	Levy	Physics	46
54321	CS-101	1	Fall	2009	A-	Williams	Comp. Sci.	54
54321	CS-190	2	Spring	2009	B+	Williams	Comp. Sci.	54
55739	MU-199	1	Spring	2010	A-	Sanchez	Music	38
70557	<i>null</i>	<i>null</i>	<i>null</i>	<i>null</i>	<i>null</i>	Snow	Physics	0
76543	CS-101	1	Fall	2009	A	Brown	Comp. Sci.	58
76543	CS-319	2	Spring	2010	A	Brown	Comp. Sci.	58
76653	EE-181	1	Spring	2009	C	Aoi	Elec. Eng.	60
98765	CS-101	1	Fall	2009	C-	Bourikas	Elec. Eng.	98
98765	CS-315	1	Spring	2010	B	Bourikas	Elec. Eng.	98
98988	BIO-101	1	Summer	2009	A	Tanaka	Biology	120
98988	BIO-301	1	Summer	2010	<i>null</i>	Tanaka	Biology	120



Figure 4.07

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000
69987	White	<i>null</i>	<i>null</i>

instructor

<i>dept_name</i>	<i>building</i>	<i>budget</i>
Biology	Watson	90000
Comp. Sci.	Taylor	100000
Elec. Eng.	Taylor	85000
Finance	Painter	120000
History	Painter	50000
Music	Packard	80000
Physics	Watson	70000
<i>null</i>	Taylor	<i>null</i>

department



Figure 4.06

<i>Join types</i>
inner join
left outer join
right outer join
full outer join

<i>Join conditions</i>
natural
on <predicate>
using ($A_1, A_2, \dots, A_n$)