


IT – Entrepreneurship Activity Lifecycle




Activity Lifecycles

- Application comprises of one or more activities.
- An activity is governed by a set of states called the lifecycle.
- Unlike programming paradigms in which apps are launched with a `main()` method, the Android system initiates code in an Activity instance by invoking specific callback methods that correspond to specific stages of its lifecycle.




The concept of activities

- The Activity class serves as the entry point for an app's interaction with the user, providing the window in which the app draws its UI.
- You implement an activity as a subclass of the Activity class.
- Most apps contain multiple screens, which means they comprise multiple activities.



The concept of activities

- Typically, one activity in an app is specified as the main activity, which is the first screen to appear when the user launches the app.
- Each activity can then start another activity in order to perform different actions.



Configuring the manifest

- To declare your activity, open your manifest file and add an `<activity>` element as a child of the `<application>` element.
- The manifest file provides essential information about your app to the Android system, which the system must have before it can run any of the app's code.

```
<manifest ... >
  <application ... >
    <activity android:name=".ExampleActivity" />
    ...
  </application ... >
  ...
</manifest >
```



Intents and Intent Filters

- Intent filters are declared in the manifest file.
- Intent filter describes a capability of the component (like activities)
- An Intent is a messaging object you can use to request an action from another app component.




Intents and Intent Filters

- There are two types of intents; Explicit and Implicit.
- An explicit request might tell the system to “Start the Send Email activity in the Gmail app”
- An implicit request tells the system to “Start a Send Email screen in any activity that can do the job.”
- When the system UI asks a user which app to use in performing a task, that’s an intent filter at work.





Managing the activity lifecycle

- `onCreate()`, fires when the system creates your activity.
- When `onCreate()` finishes, the next callback is always `onStart()`.
- `onStart()`, the activity enters the Started state, and the activity becomes visible to the user.
- `onResume()`, system invokes this callback just before the activity starts interacting with the user.




Activity Lifecycle




Managing the activity lifecycle

- The system calls `onPause()` when the activity loses focus and enters a Paused state.
- The system calls `onStop()` when the activity is no longer visible to the user.
- The system invokes this callback when an activity in the Stopped state is about to restart.
- The system invokes this callback before an activity is destroyed.




Importing our project

- The problem is that this project is created with some other 'SDK' version than the one we have installed.
- To solve this, we can either install the missing SDK by clicking the 'Install missing ...'




Importing our project

- Or we can solve it by changing it to the one we have installed.
- For that, we first need to know what we have installed.
- Open the 'SDK Manager'
- It is the second last icon, next to the Question mark.




Importing our project



Importing our project

- After identifying our SDK version and build-tools version.
- We open our app gradle file
- App → build.gradle
- At the starting, we have the sdk and buildtools used by our project. It should look something like this.


```
android {  
    compileSdkVersion 21  
    buildToolsVersion "21.1.2"  
}
```





Importing our project

- After changing the sdk and buildTools version to appropriate values, press 'Try Again' or 'Sync'.
- Now, the gradle should look something like this.

```
android {  
    compileSdkVersion 25  
    buildToolsVersion "25.0.2"
```



Identify the activity transitions



References

- Android Developers
- cs.dartmouth.edu

