



Samueli
Computer Science



Universal Representation Learning of Knowledge Bases by Jointly Embedding Instances and Ontological Concepts

Junheng Hao, Muhao Chen, Wenchao Yu, Yizhou Sun, Wei Wang
University of California, Los Angeles

Outline

- **Background: Knowledge Graphs and Embeddings** ←
- Formulation: Two-view Knowledge Graphs
- JOIE Modeling: Cross-view & Intra-view
- Experimental Results
- Conclusion & Future Work

Knowledge graphs (KGs) Are Everywhere

General-purpose KGs



Product Graphs & E-commerce



Bio & Medical KGs



Common-sense KGs & NLP



Knowledge Graphs Are Foundational


- Foundational to knowledge-driven AI systems
- Enable many downstream applications (NLP tasks, QA systems, etc)



Natural Language Processing




Recommendation Systems



Knowledge Graphs



QA & Dialogue systems



Computational Biology


KG Example From YAGO

Triple

UCLA


Located In

Los Angeles




KG Embedding From Triples

- Knowledge graph embeddings represent entities and relations as latent vectors or matrices and support effective relation learning and inference.
- Input:** Relation facts (triples)
- Output:** Embedding representations of objects and relations



Learning KG Embeddings

- Key of existing KG embedding methods: Triple score function




- Previous research employ various arithmetic methods to capture observed relations of entities in a single KG (for example, translational distance or similarity)

Model	Score Function	Embeddings
TransE (Bordes et al., 2013)	$- \mathbf{h} + \mathbf{r} - \mathbf{t} $	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{R}^k$
TransX	$- g_{r,1}(\mathbf{h}) + \mathbf{r} - g_{r,2}(\mathbf{t}) $	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{R}^k$
DistMult (Yang et al., 2014)	$(\mathbf{h} \circ \mathbf{t}) \cdot \mathbf{r}$	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{R}^k$
HolE (Nickel et al., 2016)	$(\mathbf{h} \star \mathbf{t}) \cdot \mathbf{r}$	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{R}^k$
ComplEx (Trouillon et al., 2016)	$\text{Re}\langle \mathbf{r}, \mathbf{h}, \bar{\mathbf{t}} \rangle$	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{C}^k$
ConvE (Dettmers et al., 2017)	$\langle \sigma(\text{vec}(\sigma([\mathbf{r}, \mathbf{h}] * \Omega)) \mathbf{W}), \mathbf{t} \rangle$	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{R}^k$
RotateE (Sun et al., 2017)	$- \mathbf{h} \circ \mathbf{r} - \mathbf{t} ^2$	$\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{C}^k, r_i = 1$

Drawbacks & Limitation


- Most existing approaches embed instance-level knowledge.
- KGs have both specific instances and general ontological concepts.




Outline

- Background: Knowledge Graphs and Embeddings
- **Formulation: Two-view Knowledge Graphs** ←
- JOIE Modeling: Cross-view & Intra-view
- Experimental Results
- Conclusion & Future Work

Two-view KG: More than a instance view





Two-view KG: More than just a set of triples



Problem Formulation

- **Input:** Instance-view KG triples, ontology-view KG triples, cross-view type links
- **Output:** Embeddings of entities, concepts, relations and meta-relations



Why Two-view KG Embeddings?




- Many existing KGs, such as YAGO and DBpedia, have constructed two views.
- Two views represent different levels of abstraction for relational knowledge, and can be used to enhance each other.
- Embeddings of a two-view KG provide more natural and clearer knowledge organization and curation, and are in line with human cognition.


Outline

- Background: Knowledge Graphs and Embeddings
- Formulation: Two-view Knowledge Graphs
- **JOIE Modeling: Cross-view & Intra-view** 
- Experimental Results & Case Study
- Conclusion & Future Work

- Cross-view Association model
- Intra-view model



JOIE: Cross-view Association Model



JOIE: Cross-view Model



- **Goal:** capture associations between the entities e and corresponding concepts c
- **Cross-view Grouping (CG)**

$$J_{\text{Cross}}^{\text{CG}} = \frac{1}{|\mathcal{S}|} \sum_{(e,c) \in \mathcal{S}} [||\mathbf{c} - \mathbf{e}||_2 - \gamma^{\text{CG}}]_+$$


- **Cross-view Transformation (CT)**

$$f_{\text{CT}}(\mathbf{e}) = \sigma(\mathbf{W}_{\text{ct}} \cdot \mathbf{e} + \mathbf{b}_{\text{ct}})$$

$$J_{\text{Cross}}^{\text{CT}} = \frac{1}{|\mathcal{S}|} \sum_{\substack{(e,c) \in \mathcal{S} \\ \wedge (e,c') \notin \mathcal{S}}} [\gamma^{\text{CT}} + ||\mathbf{c} - f_{\text{CT}}(\mathbf{e})||_2 - ||\mathbf{c}' - f_{\text{CT}}(\mathbf{e})||_2]_+$$



JOIE: Intra-view Model



JOIE: Intra-view Model for Instance View

- Goal: To embed the relational structures in the instance view of the KB
- Apply any KG embedding techniques on instance view
 - Three representatives: TransE, DistMult, and HolE


$$f_{\text{TransE}}(\mathbf{h}, \mathbf{r}, \mathbf{t}) = -\|\mathbf{h} + \mathbf{r} - \mathbf{t}\|_2$$

$$f_{\text{Mult}}(\mathbf{h}, \mathbf{r}, \mathbf{t}) = (\mathbf{h} \circ \mathbf{t}) \cdot \mathbf{r}$$

$$f_{\text{HolE}}(\mathbf{h}, \mathbf{r}, \mathbf{t}) = (\mathbf{h} \star \mathbf{t}) \cdot \mathbf{r}$$

- Training on marginal ranking loss

$$J_{\text{Intra}}^{\mathcal{G}} = \frac{1}{|\mathcal{G}|} \sum_{\substack{(h, r, t) \in \mathcal{G} \\ \wedge (h', r, t') \notin \mathcal{G}}} [\gamma^{\mathcal{G}} + f(\mathbf{h}', \mathbf{r}, \mathbf{t}') - f(\mathbf{h}, \mathbf{r}, \mathbf{t})]_+$$




JOIE: Intra-view Model for Ontology View

- We can still follow the same techniques as the instance view. $J_{\text{Intra}} = J_{\text{Intra}}^{\mathcal{G}_I} + \alpha_1 \cdot J_{\text{Intra}}^{\mathcal{G}_O}$
- However, the hierarchical structure of the ontology-view represents critical semantics, with special meta relations such as “*is_a*” and “*subclass*”.

c_l : Scientist c_h :Person

$$g_{\text{HA}}(\mathbf{c}_h) = \sigma(\mathbf{W}_{\text{HA}} \cdot \mathbf{c}_l + \mathbf{b}_{\text{HA}})$$



- Similar to CT model, we model such hierarchical structures in,

$$J_{\text{Intra}}^{\text{HA}} = \frac{1}{|\mathcal{T}|} \sum_{\substack{(c_l, c_h) \in \mathcal{T} \\ \wedge (c_l, c'_h) \notin \mathcal{T}}} [\gamma^{\text{HA}} + \|\mathbf{c}_h - g(\mathbf{c}_l)\|_2 - \|\mathbf{c}_h' - g(\mathbf{c}_l)\|_2]_+$$

- Two model components: Cross-view model and intra-view model
- Cross-view association model $\Rightarrow J_{\text{Cross}}$
 - Categorical grouping (CG)
 - Categorical transformation (CT)
- Intra-view model $\Rightarrow J_{\text{Intra}}$
 - Can apply any KG embedding on each view
 - Hierarchical-aware modeling on ontological view specifically for taxonomy meta relations
- Joint training on cross-view loss and intra-view loss

$$J = J_{\text{Intra}} + \omega \cdot J_{\text{Cross}}$$

Outline

- Background: Knowledge Graphs and Embeddings
- Formulation: Two-view Knowledge Graphs
- JOIE Modeling: Cross-view & Intra-view
- **Experimental Results & Case Study** ←
- Conclusion & Future Work

Experiment Setup



- Datasets: YAGO26K-906 (from YAGO) and DB111K-184 (from DBpedia)
- Tasks: **Triple completion** and **entity typing**
- Evaluation metrics
 - Triple completion: MRR, Hit@ K score ($K=1,3,10$)
 - Entity typing: Accuracy (Hit@1), Hit@3 Score
- Baselines: TransE, DistMult, HolE, TransC, MTransE

Dataset	Instance Graph \mathcal{G}_I			Ontology Graph \mathcal{G}_O			Type Links \mathcal{S}
	#Entities	#Relations	#Triples	#Concepts	#Meta-relations	#Triples	
YAGO26K-906	26,078	34	390,738	906	30	8,962	9,962
DB111K-174	111,762	305	863,643	174	20	763	99,748





Task 1: Triple Completion

- Given the head and predicate of a triple, what is the most likely tail (answer)?




Task 2: Entity Typing

- Given an entity without a known type, what is the most likely type (concept) that it associates with?



Type inference on 30%
of all entities on YAGO.

Task 2+: Long-tail Entity Typing



Example of long-tail entity typing


Entity	Model	Top 3 Concept Prediction
Laurence Fishburne	DistMult MTransE JOIE	football team, club, team writer, person , artist person , artist, philosopher
Warangal City	DistMult MTransE JOIE	country, village,city administrative region, city , settlement city , town, country
Royal Victorian Order	DistMult MTransE JOIE	person, writer, administrative region election, award, order award, order , election

Entity typing accuracy on long-tail entities

Metrics	YAGO26K-906		
	MRR	Acc.	Hit@3
DistMult	0.156	10.89	25.33
MTransE	0.526	46.45	67.25
JOIE-TransE-CG	0.708	59.97	79.80
JOIE-TransE-CT	0.737	62.05	82.60
JOIE-HATransE-CT	0.802	69.66	87.75

Task 3: Ontology Population

→ JOIE can help enhance the quality of ontology view and make it more complete and informative by populating the instance-level knowledge.



Examples of ontology population


Query	Top 3 Populated Triples with distances
(scientist, ?r, university)	scientist, <i>graduated_from</i> , university (0.499) scientist, <i>isLeaderOf</i> , university (1.082) scientist, <i>isKnownFor</i> , university (1.098)
(boxer, ?r, club)	boxer, <i>playsFor</i> , club (1.467) boxer, <i>isAffiliatedTo</i> , club (1.474) boxer, <i>worksAt</i> , club (1.479)
(scientist, ?r, scientist)	scientist, <i>doctoralAdvisor</i> , scientist (0.204) scientist, <i>doctoralStudent</i> , scientist (0.221) scientist, <i>relative</i> , scientist (0.228)

Outline

- Background: Knowledge Graphs and Embeddings
- Formulation: Two-view Knowledge Graphs
- JOIE Modeling: Cross-view & Intra-view
- Experimental Results & Case Study
- **Conclusion & Future Work** 

Conclusion & Future Work

- Joint learning on the instance and ontology views improves the KG embeddings.
- Incorporating ontologies in KGs is beneficial.
- Two-view KG modeling can be applied in a wide selection of interdisciplinary applications.
 - Disease-symptom with multiple medical KGs for automated patient case report analysis.



Join us in **Bio-KARE** community!

Sign up with your email:



Scan this QR Code or visit:
Bio-KARE.org/KDD2019



National Center for Biomedical
Knowledge Architecture
& Relationship Enrichment

Dr. Wei Wang (University of California, Los Angeles)
Dr. Peipei Ping (University of California, Los Angeles)
Dr. Cathy Wu (University of Delaware)
Dr. Jiawei Han (University of Illinois, Urbana-Champaign)

Do you have biomedicine's next TOP model?
Validate your model with Bio-KARE

Join the Bio-KARE community
of researchers, developers, and clinicians today

Opportunity to revolutionize model development and empower your research.

Sign up with your email:



Scan this QR Code or visit: Bio-KARE.org/KDD2019



Samueli
Computer Science



Thank you!

Q & A

*Join us in Bio-KARE
community!*

Sign up with your email:



Scan this QR Code or visit:
Bio-KARE.org/KDD2019