

S3 BUCKET FOR AWS CODEPIPELINE ARTIFACTS

Create bucket

Buckets are containers for data stored in S3. [Learn more](#)

General configuration

Bucket name

awsgcode-artifacts

Bucket name must be unique and must not contain spaces or uppercase letters. [See rules for bucket naming](#)

Region

US East (N. Virginia) us-east-1

Copy settings from existing bucket - optional

Only the bucket settings in the following configuration are copied.

Choose bucket

Amazon S3

>

awsgcode-artifacts

>

Edit bucket policy

Edit bucket policy

Bucket policy

The bucket policy, written in JSON, provides access to the objects stored in the bucket. Bucket policies don't apply to objects owned by other accounts. [Learn more](#)

Policy examples

Policy generator

Bucket ARN

arn:aws:s3:::awsgcode-artifacts

Policy

```
1 {
2   "Statement": [
3     {
4       "Sid": "WhitelistedGet",
5       "Effect": "Allow",
6       "Principal": {
7         "AWS": [
8           "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodeBuildServiceRole",
9           "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodePipelineServiceRole"
10        ]
11      },
12      "Action": [
```

artifacts-bucket-policy.json

iac > IaC-Mythical-Misfits > artifacts-bucket-policy.json > ...

```
1 {
2   "Statement": [
3     {
4       "Sid": "WhitelistedGet",
5       "Effect": "Allow",
6       "Principal": {
7         "AWS": [
8           "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodeBuildServiceRole",
9           "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodePipelineServiceRole"
10        ]
11      },
12      "Action": [
13        "s3:GetObject",
14        "s3:GetObjectVersion",
15        "s3:GetBucketVersioning"
16      ],
17      "Resource": [
18        "arn:aws:s3:::awsgcode-artifacts/*",
19        "arn:aws:s3:::awsgcode-artifacts"
20      ]
21    },
22    {
23      "Sid": "WhitelistedPut",
24      "Effect": "Allow",
25      "Principal": {
26        "AWS": [
27          "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodeBuildServiceRole",
28          "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodePipelineServiceRole"
29        ]
30      },
31      "Action": "s3:PutObject",
32      "Resource": [
33        "arn:aws:s3:::awsgcode-artifacts/*",
34        "arn:aws:s3:::awsgcode-artifacts"
35      ]
36    }
37  ]
38 }
```

CODEBUILD PROJECT SETUP

Project configuration

Project name

MythicalMysfitsServiceCodeBuildProject

A project name must be 2 to 255 characters. It can include the letters A-Z and a-z, the numbers 0-9, and the special characters - and _.

Source

Add source

Source 1 - Primary

Source provider

GitHub

Repository

Public repository

Repository in my GitHub account

GitHub repository

https://github.com/nkdchck/Backend-Mythical-Mysfits.git

https://github.com/<user-name>/<repository-name>

Connection status

You are connected to GitHub using a personal access token.

Disconnect from GitHub

Source version - optional

Info

Enter a pull request, branch, commit ID, tag, or reference and a commit ID.

master

Additional configuration

Git clone depth, Git submodules, Build status config

Environment variables

Name	Value	Type	
AWS_ACCOUNT_ID	959910143348	Plaintext	Remove
AWS_DEFAULT_REGION	us-east-1	Plaintext	Remove

Add environment variable

Developer Tools > CodeBuild > Build projects > MythicalMysfitsServiceCodeBuildProject

MythicalMysfitsServiceCodeBuildProject

Notify

Share

Edit

Delete build project

Start build

Configuration

Source provider	Primary repository	Artifacts upload location	Build badge
GitHub	nkdchck/Backend-Mythical-Mysfits	-	Disabled

code-build-project.json

```
1 {
2   "name": "MythicalMysfitsServiceCodeBuildProject",
3   "artifacts": {
4     "type": "no_artifacts"
5   },
6   "environment": {
7     "computeType": "BUILD_GENERAL1_SMALL",
8     "image": "aws/codebuild/python:3.5.2",
9     "privilegedMode": true,
10    "environmentVariables": [
11      {
12        "name": "AWS_ACCOUNT_ID",
13        "value": "959910143348"
14      },
15      {
16        "name": "AWS_DEFAULT_REGION",
17        "value": "us-east-1"
18      }
19    ],
20    "type": "LINUX_CONTAINER"
21  },
22  "serviceRole": "arn:aws:iam::959910143348:role/MythicalMysfitsServiceCodeBuildServiceRole",
23  "source": {
24    "type": "GITHUB",
25    "location": "https://github.com/nkdchck/Backend-Mythical-Mysfits"
26  }
27 }
```

1: bash

MacBook-Air-nikita:IaC-Mythical-Misfits nkdchck\$ aws codebuild create-project --cli-input-json file:///./code-build-project.json

project:
 arn: arn:aws:codebuild:us-east-1:959910143348:project/MythicalMysfitsServiceCodeBuildProject
 artifacts:
 encryptionDisabled: false
 name: MythicalMysfitsServiceCodeBuildProject
 packaging: NONE
 type: NO_ARTIFACTS
 badge:
 badgeEnabled: false
 cache:
 type: NO_CACHE
 created: '2020-11-17T18:25:01.455000+03:00'
 encryptionKey: arn:aws:kms:us-east-1:959910143348:alias/aws/s3
 MacBook-Air-nikita:IaC-Mythical-Misfits nkdchck\$