Data & Memory

Part 1

1

Binary Numbers

Bit of This and a Bit of That

2

What is a Number?

- *Hindu-Arabic Number System*
  - positional grouping system
  - each position represents an increasing power of 10
  - used throughout the World
- Binary numbers
  - based on the same system
  - use powers of **2** rather than 10

3

Evolution of a Genius System



4

Base 10 Number

The number 1783 is ...

10^4	10^3	10^2	10^1	10^0
10000	1000	100	10	1
0	**1**	**7**	**8**	**3**

1000 + 700 + 80 + 3 = 1783

5

Binary Number Example

The number 0100 1010 is ...

2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
128	64	32	16	8	4	2	1
0	**1**	**0**	**0**	**1**	**0**	**1**	**0**

64 + 8 + 2 = 74

6

Binary Number Example

The number 1101 1011 is ...

2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
128	64	32	16	8	4	2	1
1	**1**	**0**	**1**	**1**	**0**	**1**	**1**

128 + 64 + 16 + 8 + 2 + 1 = 219

7

Hexadecimal Numbers

- Writing out long binary numbers is cumbersome and error prone
- As a result, computer scientists often write computer numbers in hexadecimal
- Hexadecimal is base-16
  - we only have 0 ... 9 to represent digits
  - So, hex uses **A ... F** to represent **10 ... 15**

8

Hexadecimal Numbers

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111

Hex	Decimal	Binary
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

9

Hex Example

The number 7AC is ...

16^4	16^3	16^2	16^1	16^0
65536	4096	256	16	1
0	**0**	**7**	**A**	**C**

(7×256) + (10×16) + (12×1) = 1964

10

Converting Binary to Hex = Easy

- Since $16^1 = 2^4$, a single hex character can represent a total of 4 bits
- Convert every 4-bits to a single hexadecimal digit

5				**C**			
0	1	0	1	1	1	0	0

11

Bits and Bytes

- Everything in a *modern* computer is stored using combination of ones and zeros
- *Bit* is one binary digit
  - either 1 or 0
  - shorthand for a bit is b
- *Byte* is a group of 8 bits
  - e.g. **1101 0100**
  - shorthand for a byte is B

12

The Byte



13



Text in Programming Languages

Press Any Key to Continue

14

How Text Is Stored

- Computer often store and transmit textual data
- Examples:
  - punctuation
  - numerals 0 – 9
  - letter
- Each of these symbols is called a *character*



15

Characters

- Processors rarely know what a "character" is, and instead store each as an integer
- In this case, each character is given a unique value
- For instance
  - "A", could have the value of 1
  - "B" is 2
  - "C" is 3, etc…



16

Characters

- Characters and their matching values are a *character set*
- There have been many characters sets developed over time



17

Character Sets

- ASCII
  - 7 bits – 128 characters
  - uses a full byte, one bit is not used
  - created in the 1967
- EBCDIC
  - Alternative system used by old IBM systems
  - Not used much anymore

18

ASCII Chart

Control characters

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	NUL	SOH	STX	ETX	EOT	ENQ	ACK	BEL	BS	HT	LF	VT	FF	CR	SO	SI
1	DLE	DC1	DC2	DC3	DC4	NAK	SYN	ETB	CAN	EM	SUB	ESC	FS	GS	RS	US
2	sp	!	"	#	$	%	&	'	(	)	*	+	,	-	.	/
3	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
4	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
5	P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
6	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
7	p	q	r	s	t	u	v	w	x	y	z	{	|	}	~	DEL

19

ASCII Codes

- Each character has a unique value
- The following is how "OMG" is stored in ASCII

	Binary	Hex	Decimal
O	0100 1111	4F	79
M	0100 1101	4D	77
G	0100 0111	47	71

20

ASCII Codes

- ASCII is laid out very logically
- Alphabetic characters (uppercase and lowercase) are 32 "code points" apart

	Decimal	Hex	Binary
A	65	41	01000001
a	97	61	01100001

21

ASCII Codes

- $32^1 = 2^5$
- 1-bit difference between upper and lowercase letters
- Printers can easily convert between the two

	Decimal	Hex	Binary
A	65	41	01000001
a	97	61	01100001

22

ASCII: Number Characters

- ASCII code for 0 is 30h
- Notice that the actual value of a number character is stored in the lower nibble
- So, the characters 0 to 9 can be easily converted to their binary values

0	0011 0000
1	0011 0001
2	0011 0010
3	0011 0011
4	0011 0100
5	0011 0101
6	0011 0110
7	0011 0111
8	0011 1000
9	0011 1001

23

ASCII: Number Characters

- Character → Binary
  - clear the upper nibble
  - Bitwise And: 0000 1111
- Binary → Character
  - set the upper nibble to 0011
  - Bitwise Or: 0011 0000

0	0011 0000
1	0011 0001
2	0011 0010
3	0011 0011
4	0011 0100
5	0011 0101
6	0011 0110
7	0011 0111
8	0011 1000
9	0011 1001

24



Evolution of ASCII

From ASCII to Unicode

25

Evolution of ASCII

- The ASCII Character Set has gone through a few minor revisions this it was first created
- But, the 1967 standard is still used today



26

Evolution of ASCII

- The initial 1963 version didn't include lowercase letters
- As shocking as it sounds, there was a time where lowercase letters were considered obsolete
- All-caps was called "modern"



27

Evolution of ASCII

- Back in the 1960's – there were no computer monitors
- Nor did you enter programs using a keyboard
- Instead…
  - programs were inputted using punched cards or tape
  - all output was printed



28

Original 1963 ASCII Proposal

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	NUL	SOM	EOA	EOM	EOT	WRU	RU	BEL	FE0	HT	LF	VT	FF	CR	SO	SI
1	DC0	DC1	DC2	DC3	DC4	ERR	SYN	LEM	S0	S1	S2	S3	S4	S5	S6	S7
2	sp	!	"	#	$	%	&	'	(	)	*	+	,	−	.	/
3	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
4	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
5	P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	↑	←
6																
7													ACK		ESC	DEL

29

1967 Revision Added Lowercase

Changed

New

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	NUL	SOH	STX	ETX	EOT	ENQ	ACK	BEL	BS	HT	LF	VT	FF	CR	SO	SI
1	DLE	DC1	DC2	DC3	DC4	NAK	SYN	ETB	CAN	EM	SUB	ESC	FS	GS	RS	US
2	sp	!	"	#	$	%	&	'	(	)	*	+	,	−	.	/
3	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
4	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
5	P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
6	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
7	p	q	r	s	t	u	v	w	x	y	z	{	|	}	~	DEL

30

Control Characters

- Many of the control characters were designed for transferring data (SOH, STX, FS, GS, etc…)
- Other control characters we designed for printing

31

Backspace Control Character

- Printers, at the time, were basically classic typewriters
- The backspace character (BS) was used to print 2+ symbols on top of each other
- This would essentially create a new character on the paper

32

IBM Ball-Printers



33

Power of the Backspace



34

Recreating the Removed Arrows



35

DEL Control Character

- You might have noticed an odd control character located at 7F
- This is the "Deleted" control character and was used with punched cards and tape

36

ASCII Chart

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	NUL	SOH	STX	ETX	EOT	ENQ	ACK	BEL	BS	HT	LF	VT	FF	CR	SO	SI
1	DLE	DC1	DC2	DC3	DC4	NAK	SYN	ETB	CAN	EM	SUB	ESC	FS	GS	RS	US
2	sp	!	"	#	$	%	&	'	(	)	*	+	,	-	.	/
3	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
4	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
5	P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
6	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
7	p	q	r	s	t	u	v	w	x	y	z	{	|	}	~	DEL

37

Punched Tape



38

Bill Gates – Original Altair BASIC

Intel 8080 machine code

39

Example Punched Tape: `int x;`



```
i
n
t

x
>
```

Student punched the wrong hole! They meant `;`

Do they have to punch an entire new tape?

40

Example Punched Tape: `int x;`



```
i
n
t

x
DEL
;
```

Just punch all remaining holes. It becomes DEL and is ignored

41

Times have changed

A New Character Set Enters the Scene

42

Times have changed…

- Computers have changed quite a bit since the 1960's
- As a result, most of these clever control characters are no longer needed
- Backspace, DEL, and numerous others are obsolete



43

Only Control Characters Still Used

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	NUL	SOH	STX	ETX	EOT	ENQ	ACK	BEL	BS	HT	LF	VT	FF	CR	SO	SI
1	DLE	DC1	DC2	DC3	DC4	NAK	SYN	ETB	CAN	EM	SUB	ESC	FS	GS	RS	US
2	sp	!	"	#	$	%	&	'	(	)	*	+	,	-	.	/
3	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
4	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
5	P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
6	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
7	p	q	r	s	t	u	v	w	x	y	z	{	|	}	~	DEL

44

Unicode Character Set

- ASCII is only good for the United States
  - Other languages need additional characters
  - Multiple competing character sets were created
- Unicode was created to support every spoken language
- Developed in Mountain View, California

45

Unicode Character Set

- Originally used 16 bits
  - that's over 65,000 characters!
  - includes every character used in the World
- Expanded to 21 bits
  - 2 million characters!
  - now supports every character ever created
  - … and emojis
- Unicode can be stored in different formats

46



Computer Memory

Its… um…. I forgot….

47

Computer Memory

- Programs access and manipulate memory far more than you realize
- So, understanding it…
  - is vital to becoming a great assembly programmer
  - and understanding computer architecture



48

What is Memory?

- Memory is essentially an enormous array
- It is also, sometimes, referred to as *storage*
- It stores both running programs and their related data



49

Memory Addresses

- Memory is divided into a storage locations that can hold 1 byte (8 bits)
- Each an be accessed using an *address*
  - unique value that refers to that specific byte
  - used to locate the exact byte the processor wants

Memory	
0	01000100
1	01000011
2	01101111
3	01101111
4	01101011

50

What is Memory?

- Each address is conceptually the same as an "index" in arrays
- … and you will write access memory as would an array

Memory	
0	01000100
1	01000011
2	01101111
3	01101111
4	01101011

51

Memory is a Hardware Array



52

Memory Contains Data & Programs



- Data and programs are just binary numbers (stored in a series of bytes)
- …and are stored together
- Appreciating this is vital to understanding computer architecture

53

Memory Contains Data & Programs



54



Processors

What are they? Besides awesome!

55

Computer Processors

- The *Central Processing Unit (CPU)* is the most complex part of a computer
- In fact, it is the computer!
- It works far different from a high-level language
- *Thousands* of processors have been developed

56

Some Famous Computer Processors

- RCA 1802
- Intel 8086
- Zilog Z80
- MOS 6502
- Motorola 68000
- ARM



57

Computer Processors

- Each processor functions differently
- Each is designed for a specific purpose – *form follows function*



58

Computer Processors

- But all share some basic properties and building blocks…
- Computer hardware is divided into two "units"
  1. Control Logic Unit
  2. Execution Unit



59

Control Logic Unit (CLU)

- *Control Logic Unit (CLU)* controls the processor
- Determines when instructions can be executed
- Controls internal operations
  - fetch & decode instructions
  - invisible to running programs

60

Execution Unit

- *Execution Unit (EU)* contains the hardware that *executes* tasks (your programs)
- Different in many processors
- Modern processors often use multiple execution units to execute instructions in parallel to improve performance

61

Execution Unit – The ALU

- *Arithmetic Logic Unit* is part of the Execution Unit and performs all calculations and comparisons
- Processor often contains special hardware for integer and floating point

62

Registers

Where the work is done

63

Registers

- In high level languages, you put active data into variables
- However, it works quite different on processors
- All computations are performed using *registers*

64

What – exactly – is a register?

- A *register* is a location, on the processor itself, that is used to store temporary data
- Think of it as a special global "variable"
- Some are accessible and usable by a programs, but many are hidden

65

What are registers used for?

- Registers are used to store anything the processor needs to keep to track of
- Designed to be *fast!*
- Examples:
  - the result of calculations
  - status information
  - memory location of the running program
  - and much more…

66

General Purpose Registers

- *General Purpose Registers (GPR)* don't have a specific purpose
- They are designed to be used by programs – however they are needed
- Often, you must use registers to perform calculations

67

Special Registers

- There are a number of registers that are used by the Control Logic Unit and cannot be accessed by your program
- This includes registers that control how memory works, your program execution thread, and much more.

68

Special Registers

- *Instruction Pointer (IP)*
  - also called *the program counter*
  - keeps track of the address of your running program
  - think it as the "line number" in your Java program – the one is being executed
  - it can be changed, but only indirectly *(using control logic – which we will cover later)*

69

Special Registers

- *Status Register*
  - contains Boolean information about the processors current state
  - we will use this later, indirectly
- *Instruction Register (IR)*
  - stores the current instruction (being executed)
  - used internally and invisible to your program

70

Register Files



- All the related registers are grouped into a *register file*
- Different processors access and use their register files in very different ways
- Sometimes registers are implied or hardwired

71



Instructions

It's all just a bunch of bytes

72

Instructions

- You are used to writing programs in high level programming languages
- Examples:
  - C#
  - Java
  - Python
  - Visual Basic



73

High-Level Programming

- These are *third-generation languages*
- They are designed to isolate you from architecture of the machine
- This layer of abstraction makes programs "portable" between systems



74

Instructions

- Processors do not have the constructs you find in high-level languages
- Examples:
  - Blocks
  - If Statements
  - While Statements
  - … etc



75

Instructions

- Processors can only perform a series of simple tasks
- These are called *instructions*
- *Examples:*
  - add two values together
  - copy a value
  - jump to a memory location



76

Instructions

- These instructions are used to create all logic needed by a program
- We will cover how to do this during the semester



77

Processor Instruction Set



- A processor's *instruction set* defines all the available instructions
- The instructions and their respective formats are very different for each processor

78

Components of a Processor



79