



[Course](#) > [Ch8 Tree-Based Methods](#) > [Chapter 8 Quiz](#) > Chapter 8 Quiz

Chapter 8 Quiz

8.Q1

1/1 point (graded)

The tree building algorithm given on pg 13 is described as a Greedy Algorithm. Which of the following is also an example of a Greedy Algorithm?:

☐ The Lasso

☐ Support Vector Machines

☐ The Bootstrap

☒ Forward Stepwise Selection



Explanation

Forward Stepwise Selection is a Greedy Algorithm because at each step it selects the variable that improves the current model the most. There is no guarantee that the final result will be optimal.

Submit

Answers are displayed within the problem

8.Q2

1/1 point (graded)

Examine the plot on pg 23. Assume that we wanted to select a model using the one-standard-error rule on the Cross-Validated error. What tree size would end up being selected?:

☐ 1

☒ 2

☐ 3

☐ 10



Explanation

Cross-Validated error is minimized at tree size 3. The error for Tree size 2 is within one standard error of the minimum, but the error for tree size 1 is not. Thus, the one-standard-error rule selects tree size 2.

Submit

i Answers are displayed within the problem

8.Q3

1/1 point (graded)

Suppose I have two qualitative predictor variables, each with three levels, and a quantitative response. I am considering fitting either a tree or an additive model. For the additive model, I will use a piecewise-constant function for each variable, with a separate constant for each level. Which model is capable of fitting a richer class of functions:

☒ Tree

☐ Additive Model

☐ They are equivalent



Explanation

Although each split of the tree makes two partitions, it can fit interactions, while

the additive model cannot. With enough splits the tree can fit a full 3x3 regression surface.

Submit

i Answers are displayed within the problem

© All Rights Reserved