



DC – AI – Routing – Switching – Security – Wireless – Automation

BNG on MPC10

An HPE Juniper Networking Techpost

Ricardo Dominguez

2023-12-08

HPE



Contents

1	BNG on MPC10E	3
1.1	Introduction	3
1.2	Test Topology	3
1.3	Hardware Used	4
1.4	RADIUS Subscribers' Profiles	5
1.5	Configuration	6
1.5.1	Access Interface	7
1.5.2	DHCPv6 Local Server	7
1.5.3	Dynamic Profile	7
1.5.4	Service Profile	9
1.5.5	IPv4 and IPv6 Pools	11
1.5.6	DS CGNAT Subscribers Configuration	12
1.5.7	CGNAT Service Interface	12
1.5.8	CGNAT Dynamic Profile	12
1.5.9	CGNAT Routing Instance	14
1.5.10	Deterministic CGNAT Translation	15
1.6	Verification	17
1.6.1	DS Subscribers Verification	19
1.6.2	DS CGNAT Subscribers Verification	21
1.7	Conclusion	24
1.8	Useful links	24
1.9	Glossary	25
1.10	Acknowledgements	25

List of Figures

1	DS Subscriber on MPC10E	4
2	DS CGNAT Subscriber on MPC10E	4

1 BNG on MPC10E

Ricardo Dominguez - 12/08/2023

Starting in the 22.4R1 JUNOS release, MPC10E supports BNG subscriber access connections.

1.1 Introduction

Both MPC10E line card versions support subscriber management. MPC10E-10C has 2 Trio-5 PFEs, supporting 32K Dual Stack subscribers per PFE, for a total of 64K Dual Stack subscribers. MPC10E-15C has 3 Trio-5 PFEs supporting 32K Dual Stack subscribers per PFE, for a total of 96K subscribers.

MPC10E supports both PPPoE and IPoE access methods along PWHT for PPPoE or IPoE, scalability is the same for any of these access methods.

Enabling HQoS, ingress/egress FW Filtering, or ingress/egress policing for subscriber access connections in any of the MPC10E line cards, doesn't impact subscriber scalability.

This tech post will explore the following BNG capabilities on MPC10E:

- Test Topology
- Hardware Used
- RADIUS Subscribers' Profiles
- Configuration
 - DS Subscribers
 - DS CGNAT Subscribers
- Verification
 - DS Subscribers
 - DS CGNAT Subscribers

We will show both DS subscribers and DS CGNAT subscribers in the same BNG, in other words, for CGNAT subscribers, BNG will perform DS subscriber termination plus CGNAT functionalities.

PPPoE is the broadband access method used in this tech post, NDRA for IPv6 WAN addressing, and DHCPv6 Prefix Delegation for IPv6 LAN addressing. IPoE could be used as an alternative access method and DHCPv6 IA_NA also as an alternative for WAN Addressing.

BNG+CGNAT with MPC10+SPC3 is supported starting in 23.1R1 release.

The test is based on MPC10E-10C using JUNOS 23.2R1 release and having 10GigE access connections, although we connect 16K DS subscribers in a single PFE, this is not a scalability report, it's target to demonstrate typical Dual Stack BNG functionalities on MPC10E.

1.2 Test Topology

Our test topology consists of a Tester (Spirent Test Center) to emulate PPPoE Dual Stack subscribers, connected to xe-9/0/3:0 port on MPC10E, uplink interfaces, and RADIUS to provide AAA service for subscribers. The below figures show both a public IPv4 DS subscriber and DS CGNAT subscriber.




Figure 1: DS Subscriber on MPC10E




Figure 2: DS CGNAT Subscriber on MPC10E

1.3 Hardware Used

MX960 is acting as BNG, it includes 1 x MPC10E-10C for access and uplink connections, it also includes an SPC3 to perform CGNAT functions for BNG subscribers.

```

1 jnpr@MX960> show chassis hardware
2 Hardware inventory:
3 Item Version Part number Serial number Description
4 Chassis JN1122462BGB MX960
  
```

```

5 Midplane REV 03 710-013698 TS4563 MX960 Backplane
6 Fan Extender REV 02 710-018051 CABA5883 Extended Cable Manager
7 FPM Board REV 03 710-014974 XE1257 Front Panel Display
8 PDM Rev 03 740-013110 QCS124350BD Power Distribution Module
9 PEM 2 Rev 02 740-063048 QCS2410V0AF DC 4.1kW Power Entry Module
10 PEM 3 Rev 02 740-063048 QCS2410V0M2 DC 4.1kW Power Entry Module
11 Routing Engine 0 REV 05 750-072925 CAPD8855 RE-S-2X00x6
12 CB 0 REV 32 750-070866 CAPD7333 Enhanced MX SCB 3
13 CB 1 REV 32 750-070866 CAPC9612 Enhanced MX SCB 3
14 FPC 5 REV 31 750-073435 CANB4267 SPC3
15 CPU BUILTIN BUILTIN SPC3 vCPP Broadwell
16 PIC 0 BUILTIN BUILTIN SPC3-PIC
17 PIC 1 BUILTIN BUILTIN SPC3-PIC
18 FPC 9 REV 42 750-078633 CAPD7388 MPC10E 3D MRATE-10xQSFP
19 CPU REV 20 750-072571 CAPE1525 FMPC PMB
20 PIC 0 BUILTIN BUILTIN MRATE-5xQSFP
21 Xcvr 3 REV 01 740-054050 INFAK0601128 QSFP+-4X10G-LR
22 PIC 1 BUILTIN BUILTIN MRATE-5xQSFP
23 Fan Tray 0 REV 03 740-057995 DAAA3433 Enhanced Fan Tray
24 Fan Tray 1 REV 02 740-057995 DAAA2754 Enhanced Fan Tray
25
26 jnpr@MX960> show chassis hardware models
27 Hardware inventory:
28 Item Version Part number Serial number FRU model number
29 Midplane REV 03 710-013698 TS4563 CHAS-BP-MX960-S
30 Fan Extender REV 02 710-018051 CABA5883 ECM-MX960
31 FPM Board REV 03 710-014974 XE1257 CRAFT-MX960-S
32 PEM 2 Rev 02 740-063048 QCS2410V0AF PWR-MX960-4100-DC-S
33 PEM 3 Rev 02 740-063048 QCS2410V0M2 PWR-MX960-4100-DC-S
34 Routing Engine 0 REV 05 750-072925 CAPD8855 RE-S-X6-128G-S-S
35 CB 0 REV 32 750-070866 CAPD7333 SCBE3-MX-S
36 CB 1 REV 32 750-070866 CAPC9612 SCBE3-MX-S
37 FPC 5 REV 31 750-073435 CANB4267 JNP-SPC3
38 CPU BUILTIN BUILTIN
39 FPC 9 REV 42 750-078633 CAPD7388 MPC10E-10C-X
40 Fan Tray 0 REV 03 740-057995 DAAA3433 FFANTRAY-MX960-HC-S
41 Fan Tray 1 REV 02 740-057995 DAAA2754 FFANTRAY-MX960-HC-S

```

1.4 RADIUS Subscribers' Profiles

The following RADIUS Profile is used for Public IPv4 DS subscribers.

```

1 Inte-Subsc
2 Service-Type = Framed-User
3 Framed-Pool = POOL_IPv4_PUBLIC
4 Unisphere-Client-Profile-Name= "GIGE_DS_PROFILE"
5 Unisphere-Activate-Service="SERVICE_ACTIVATE_DS_IN(100000000,15000000):1"
6 Unisphere-Cos-Parameter-Type="T02 100000000"
7 Unisphere-Cos-Scheduler-Pmt-Type="DOWNSTREAM_VoIP T01 15000000"
8 Framed-IPv6-Pool="POOL_IPv6_NDRA"
9 Unisphere-IPv6-Delegated-Pool-Name= "POOL_IPv6_PD"

```

The Inte-Subsc is the username used for DS subscribers, RADIUS returns this profile to subscribers with the following RADIUS attributes:

- An IPv4 Pool configured on MX, this pool emulates public IPv4 addressing.
- The dynamic profile “GIGE_DS_POFILE” has parameters and variables for IPv4, IPv6, NDRA, and HQoS to be applied to the subscriber.
- A service activate “SERVICE_ACTIVATE_DS” dynamic profile to be applied to subscribers returns two values that correspond to two variables configured in this dynamic profile. In this way, the MX configuration is reduced, and the values are handled via AAA, which reduces time to market and human errors. This dynamic profile contains IPv4 and IPv6 ingress FWF with MF classifiers and policers.
- CoS parameter for egress shaping is applied to subscribers, same here, this reduces MX configuration, and downstream bandwidth per subscriber is handled from AAA reducing time to market and human errors.

- A scheduler transmit-rate value, reducing MX configuration, time to market, and human errors. This value is handled by AAA.
- IPv6 NDRA Pool configured on MX, this one is used for IPv6 WAN addressing.
- IPv6 PD Pool configured on MX and used for IPV6 LAN addressing.

The MX configuration for the above parameters is shown in the configuration section.

Below is displayed the RADIUS Profile for DS CGNAT subscribers.

```

1 CGNAT-Subsc
2 Service-Type = Framed-User
3 Framed-Pool = "POOL_IPv4_PRIVATE"
4 Unisphere-Client-Profile-Name = "CGNAT_DS_PROFILE"
5 Unisphere-Activate-Service="SERVICE_ACTIVATE_DS_IN(10000000,1500000):1"
6 Unisphere-Cos-Parameter-Type="T02 10000000"
7 Unisphere-Cos-Scheduler-Pmt-Type="DOWNSTREAM_VoIP T01 1500000"
8 Unisphere-Virtual-Router = "NAT-44"
9 Framed-IPv6-Pool="POOL_IPv6_NDRA_CGNAT"
10 Unisphere-IPv6-Delegated-Pool-Name= "POOL_IPv6_PD_CGNAT"

```

The CGNAT-Subsc is the username used for DS CGNAT subscribers, RADIUS returns this profile to subscribers with the following RADIUS attributes:

- An IPv4 Pool configured on MX, this pool emulates private IPv4 addressing.
- The dynamic profile “GGNAT_DS_POFILE” that has parameters and variables for IPv4, IPV6, NDRA, HQoS, and a Routing-Instance to be applied to the subscriber.
- A service activate “SERVICE_ACTIVATE_DS” dynamic profile to be applied to subscribers returns two values that correspond to two variables configured in this dynamic profile. In this way, the MX configuration is reduced, and the values are handled via AAA, which reduces time to market and human errors. This dynamic profile contains IPv4 and IPV6 ingress FWF with MF classifiers and policers.
- CoS parameter for egress shaping is applied to subscribers, same here, this reduces MX configuration and downstream bandwidth per subscriber is handled from AAA reducing time to market and human errors.
- A scheduler transmit-rate value, reducing MX configuration, time to market, and human errors. This value is handled by AAA.
- The Routing-Instance name which the subscriber interface will be assigned.
- IPv6 NDRA Pool configured on MX, this one is used for IPv6 WAN addressing.
- IPv6 PD Pool configured on MX and used for IPV6 LAN addressing.

Again, MX configuration for the above parameters is shown in the configuration section.

1.5 Configuration

In the following sections are shown the most relevant BNG configuration such as an access interface, IPv4 and IPv6 pools, and dynamics profiles. The DS CGNAT specific configuration is displayed in the DS CGNAT subscribers configuration.

Routing, MPLS, RADIUS, uplink interfaces, ALG, QoS along more generic configurations are omitted for brevity.

1.5.1 Access Interface

MPC10E access interfaces xe-9/0/3:0 for PPPoE subscribers in displayed below, it will negotiate PPPoE parameters received over VLAN 1585 statically configured (N:1 access) based on “GIGE_DS_PROFILE” and RADIUS returned attributes.

```

1 interfaces {
2   xe-9/0/3:0 {
3     description "SPIRENT_CONNECTION";
4     hierarchical-scheduler maximum-hierarchy-levels 2;
5     vlan-tagging;
6     mtu 2014;
7     unit 1585 {
8       encapsulation ppp-over-ether;
9       vlan-id 1585;
10      pppoe-underlying-options {
11        duplicate-protection;
12        dynamic-profile GIGE_DS_PROFILE;
13        max-sessions 16000;
14        short-cycle-protection {
15          lockout-time-min 60;
16          lockout-time-max 240;
17        }
18      }
19    }
20  }
21 }
```

1.5.2 DHCPv6 Local Server

For IPv6 LAN addressing, we use local DHCPv6 server in our testing scenario, the configuration is shown below, this includes de IPv6 PD pool along with accepting DHCPv6 over PPP interfaces. DHCPv6 Relay configuration is also supported.

IPv6 LAN addressing is negotiated via DHCPv6 PD. IPv6 WAN addressing is negotiated either via NDRA or DHCPv6 IA_NA.

```

1 system {
2   services {
3     dhcp-local-server {
4       dhcpv6 {
5         overrides {
6           interface-client-limit 1;
7           delegated-pool POOL_IPv6_PD;
8         }
9         group PPPoE {
10          interface pp0.0;
11        }
12      }
13    }
14  }
15 }
```

1.5.3 Dynamic Profile

PPPoE “GIGE_DS_PROFILE” configuration is displayed below, this profile allows PPP parameters, IPv4, IPv6 NDRA, and IPv6 LAN negotiation. It also includes egress HQoS parameters assignment to a subscriber such as a shaping rate (subscriber downstream bandwidth) and schedulers for a different kinds of traffic treatment as shown in this dynamic profile configuration.

Subscriber downstream bandwidth is returned by RADIUS in the Access-Accept message according to the subscriber bandwidth profile acquired. The transmit rate value for the “DOWNSTREAM_VoIP” scheduler is

also returned by RADIUS, based on the subscriber profile acquired.

Using JUNOS variables in dynamic profiles allows:

- Reduce MX configuration.
- A central place to modify values.
- Expedite go to market for any downstream or upstream bandwidth profile modification.
- Reduce human errors.
- It also allows to assign a default value to a variable If RADIUS is not configured correctly.

```

1  dynamic-profiles {
2      GIGE_DS_PROFILE {
3          predefined-variable-defaults {
4              cos-scheduler-tx rate 512k;
5              cos-shaping-rate 5120000;
6          }
7          interfaces {
8              pp0 {
9                  unit "$junos-interface-unit" {
10                     ppp-options {
11                         pap;
12                     }
13                     pppoe-options {
14                         underlying-interface "$junos-underlying-interface";
15                         server;
16                     }
17                     keepalives interval 30;
18                     family inet {
19                         rpf-check;
20                         unnumbered-address "$junos-loopback-interface";
21                     }
22                     family inet6 {
23                         rpf-check;
24                         unnumbered-address "$junos-loopback-interface";
25                     }
26                 }
27             }
28         }
29         protocols {
30             router-advertisement {
31                 interface "$junos-interface-name" {
32                     other-stateful-configuration;
33                     prefix $junos-ipv6-ndra-prefix;
34                 }
35             }
36         }
37         class-of-service {
38             traffic-control-profiles {
39                 PROFILE_DOWNSTREAM {
40                     scheduler-map DOWNSTREAM;
41                     shaping-rate "$junos-cos-shaping-rate";
42                 }
43             }
44             interfaces {
45                 pp0 {
46                     unit "$junos-interface-unit" {
47                         output-traffic-control-profile PROFILE_DOWNSTREAM;
48                     }
49                 }
50             }
51             scheduler-maps {
52                 DOWNSTREAM {
53                     forwarding-class AF2X scheduler DOWNSTREAM_AF2X;
54                     forwarding-class AF3X scheduler DOWNSTREAM_AF3X;
55                     forwarding-class VoIP scheduler DOWNSTREAM_VoIP;
56                     forwarding-class best-effort scheduler DOWNSTREAM_BEST_EFFORT;
57                     forwarding-class network-control scheduler NETWORK_CONTROL;
58                 }
59             }
60             schedulers {
61                 DOWNSTREAM_BEST_EFFORT {
62                     transmit-rate percent 20;
63                     priority low;
64                 }
65                 DOWNSTREAM_AF2X {
66                     transmit-rate percent 25;

```

```

67         priority medium-low;
68     }
69     DOWNSTREAM_AF3X {
70         transmit-rate percent 30;
71         priority high;
72     }
73     DOWNSTREAM_VoIP {
74         transmit-rate {
75             "$junos-cos-scheduler-tx";
76             rate-limit;
77         }
78         priority strict-high;
79     }
80     NETWORK_CONTROL {
81         transmit-rate percent 5;
82         priority high;
83     }
84 }
85 }
86 }
87 }

```

1.5.4 Service Profile

Service Activate “SERVICE_ACTIVATE_DS_IN” dynamic profile is used to assign upstream parameters to a subscriber such as upstream policer for upstream subscriber bandwidth, and MF classifier to assign a specific forwarding-class for traffic treatment accordingly.

Subscriber upstream bandwidth is returned by RADIUS in the Access-Accept message according to the subscriber bandwidth profile acquired. RADIUS service activate VSA allows a dynamic profile to be assigned to a subscriber for different use cases, in our example RADIUS instructs MX to activate the “SERVICE_ACTIVATE_DS_IN” dynamic profile, this one is used for upstream purposes.

Service Activate Profiles can be attached during session setup via a service activation in the access-accept and it can be attached via CoA. It is possible to dynamically add/remove one or more service profiles via CoA.

The variable used in this dynamic profile allows:

- Upstream subscriber bandwidth.
- VoIP upstream bandwidth.
- Upstream Policer Burst is calculated dynamically based on upstream subscriber bandwidth, reducing MX configuration and human errors.
- A logical interface hierarchical policer to limit Premium (VoIP) traffic and aggregate traffic.
- IPv4 MF classifier.
- IPV6 MF classifier.

```

1  dynamic-profiles {
2      SERVICE_ACTIVATE_DS_IN {
3          variables {
4              inBW;
5              voiceBW;
6              burstPolicer equals "$inBW * 0.125";
7              policer uid;
8              UPSTREAM_IN uid;
9              UPSTREAM_IN_v6 uid;
10         }
11         interfaces {
12             pp0 {
13                 unit "$junos-interface-unit" {
14                     family inet {
15                         filter {
16                             input "$UPSTREAM_IN";

```

```

17     }
18     }
19     family inet6 {
20         filter {
21             input "$UPSTREAM_IN_v6";
22         }
23     }
24 }
25 }
26 }
27 firewall {
28     family inet {
29         filter "$UPSTREAM_IN" {
30             interface-specific;
31             term 1 {
32                 from {
33                     dscp ef;
34                 }
35                 then {
36                     hierarchical-policer "$policer";
37                     count VoIP_ACCEPT;
38                     forwarding-class VoIP;
39                     accept;
40                 }
41             }
42             term 2 {
43                 from {
44                     dscp [ af33 af32 af31 ];
45                 }
46                 then {
47                     hierarchical-policer "$policer";
48                     forwarding-class AF3X;
49                     accept;
50                 }
51             }
52             term 3 {
53                 from {
54                     dscp [ af23 af22 af21 ];
55                 }
56                 then {
57                     hierarchical-policer "$policer";
58                     forwarding-class AF2X;
59                     accept;
60                 }
61             }
62             term 4 {
63                 then {
64                     hierarchical-policer "$policer";
65                     forwarding-class best-effort;
66                     accept;
67                 }
68             }
69         }
70     }
71     family inet6 {
72         filter "$UPSTREAM_IN_v6" {
73             interface-specific;
74             term 1 {
75                 from {
76                     traffic-class ef;
77                 }
78                 then {
79                     hierarchical-policer "$policer";
80                     count VoIP_IPV6_ACCEPT;
81                     forwarding-class VoIP;
82                     accept;
83                 }
84             }
85             term 2 {
86                 from {
87                     traffic-class [ af33 af32 af31 ];
88                 }
89                 then {
90                     hierarchical-policer "$policer";
91                     forwarding-class AF3X;
92                     accept;
93                 }
94             }
95             term 3 {
96                 from {
97                     traffic-class [ af23 af22 af21 ];

```

```

98         }
99         then {
100             hierarchical-policer "$policer";
101             forwarding-class AF2X;
102             accept;
103         }
104     }
105     term 4 {
106         then {
107             hierarchical-policer "$policer";
108             forwarding-class best-effort;
109             accept;
110         }
111     }
112 }
113 }
114 hierarchical-policer "$policer" {
115     logical-interface-policer;
116     aggregate {
117         if-exceeding {
118             bandwidth-limit "$inBW";
119             burst-size-limit "$burstPolicer";
120         }
121         then {
122             discard;
123         }
124     }
125     premium {
126         if-exceeding {
127             bandwidth-limit "$voiceBW";
128             burst-size-limit 9216;
129         }
130         then {
131             discard;
132         }
133     }
134 }
135 }
136 }
137 }

```

Having both “GIGE_DS_PROFILE” and “SERVICE_ACTIVATE_DS_IN” dynamic profiles allows MX to limit subscriber downstream and upstream traffic based on downstream and upstream values returned by RADIUS according to the subscriber profile acquired.

1.5.5 IPv4 and IPv6 Pools

IPv4, IPv6 PD (LAN addressing), and IPv6 NDRA (WAN addressing) pools for a DS subscriber are displayed below. These pools allow IPv4 addresses and IPv6 prefixes assignment to a subscriber. It also assigns IPv4 and IPv6 DNS to a subscriber.

```

1  access {
2      address-assignment {
3          high-utilization 85;
4          abated-utilization 75;
5          pool POOL_IPv4_PUBLIC {
6              family inet {
7                  network 172.20.1.0/16;
8                  range 1 {
9                      low 172.20.0.0;
10                     high 172.20.255.255;
11                 }
12                 xauth-attributes {
13                     primary-dns 8.8.8.8/32;
14                     secondary-dns 8.8.4.4/32;
15                 }
16             }
17         }
18         pool POOL_IPv6_PD {
19             family inet6 {
20                 prefix 2222::/48;
21                 range r1 prefix-length 64;
22                 dhcp-attributes {

```

```

23         maximum-lease-time 86400;
24         dns-server {
25             2001:4860:4860::8888;
26         }
27     }
28 }
29 }
30 pool POOL_IPv6_NDRA {
31     family inet6 {
32         prefix fdff:fffe::/48;
33         range r1 prefix-length 64;
34         dhcp-attributes {
35             maximum-lease-time 86400;
36         }
37     }
38 }
39 }
40 }

```

1.5.6 DS CGNAT Subscribers Configuration

This section describes specific CGNAT configurations for a DS subscriber.

1.5.7 CGNAT Service Interface

The multiservice interface allows traffic to be NATed in ingress and egress traffic direction. This interface has 2 legs, one to the private network (inside) and one to the public network (outside), the inside multiservice interface is in charge of sending traffic to the Juniper MX SPC3 service card, so traffic can be translated, this interface is assigned to a routing-instance. These interfaces are numbered according to the slot in which SPC3 is inserted, PIC0 represents SPC3 NPU0 and PIC1 represents SPC3 NPU1, the port number is always 0.

```

1  interfaces {
2      vms-5/0/0 {
3          unit 1 {
4              family inet;
5              service-domain inside;
6          }
7          unit 2 {
8              family inet;
9              service-domain outside;
10         }
11     }
12 }

```

1.5.8 CGNAT Dynamic Profile

PPPoE “GGNAT_DS_PROFILE” is assigned to the subscriber by RADIUS during the subscriber’s authentication. If the subscriber is a CGNAT subscriber, RADIUS will return another dynamic profile than the one assigned to the MPC10E access interface, because to CGNAT dynamic profile needs to assign the subscriber to a routing-instance which in our example is specified by RADIUS in the access-accept attributes returned to subscriber.

Routing redirect can be achieved in three ways: RADIUS returned Unisphere-Virtual-Router VSA, predefined-variable in the dynamic-profile and access domain-map target-routing-instance.

“CGNAT_DS_PROFILE” dynamic profile configuration is almost identical to the one described in the dynamic profile configuration section. The difference is that the “CGNAT_DS_PROFILE” dynamic profile includes a routing-instance to which the subscriber will be assigned.

```

1  dynamic-profiles {
2      CGNAT_DS_PROFILE {
3          predefined-variable-defaults {
4              cos-scheduler-tx rate 512k;
5              cos-shaping-rate 5120000;
6          }
7          routing-instances {
8              "$junos-routing-instance" {
9                  interface "$junos-interface-name";
10             }
11         }
12         interfaces {
13             pp0 {
14                 unit "$junos-interface-unit" {
15                     ppp-options {
16                         pap;
17                     }
18                     pppoe-options {
19                         underlying-interface "$junos-underlying-interface";
20                         server;
21                     }
22                     keepalives interval 30;
23                     family inet {
24                         rpf-check;
25                         unnumbered-address lo0.1;
26                     }
27                     family inet6 {
28                         rpf-check;
29                         address $junos-ipv6-address;
30                     }
31                 }
32             }
33         }
34         protocols {
35             router-advertisement {
36                 interface "$junos-interface-name" {
37                     other-stateful-configuration;
38                     prefix $junos-ipv6-ndra-prefix;
39                 }
40             }
41         }
42         class-of-service {
43             traffic-control-profiles {
44                 PROFILE_DOWNSTREAM {
45                     scheduler-map DOWNSTREAM;
46                     shaping-rate "$junos-cos-shaping-rate";
47                 }
48             }
49             interfaces {
50                 pp0 {
51                     unit "$junos-interface-unit" {
52                         output-traffic-control-profile PROFILE_DOWNSTREAM;
53                     }
54                 }
55             }
56             scheduler-maps {
57                 DOWNSTREAM {
58                     forwarding-class AF2X scheduler DOWNSTREAM_AF2X;
59                     forwarding-class AF3X scheduler DOWNSTREAM_AF3X;
60                     forwarding-class VoIP scheduler DOWNSTREAM_VoIP;
61                     forwarding-class best-effort scheduler DOWNSTREAM_BEST_EFFORT;
62                     forwarding-class network-control scheduler NETWORK_CONTROL;
63                 }
64             }
65             schedulers {
66                 DOWNSTREAM_BEST_EFFORT {
67                     transmit-rate percent 20;
68                     priority low;
69                 }
70                 DOWNSTREAM_AF2X {
71                     transmit-rate percent 25;
72                     priority medium-low;
73                 }
74                 DOWNSTREAM_AF3X {
75                     transmit-rate percent 30;
76                     priority high;
77                 }
78                 DOWNSTREAM_VoIP {
79                     transmit-rate {
80                         "$junos-cos-scheduler-tx";

```

```

81         rate-limit;
82     }
83     priority strict-high;
84 }
85 NETWORK_CONTROL {
86     transmit-rate percent 5;
87     priority high;
88 }
89 }
90 }
91 }
92 }

```

1.5.9 CGNAT Routing Instance

DS CGNAT subscriber is assigned to a CGNAT routing instance, we're using a VRF routing-instance in our example, a virtual-router routing-instance can also be used

The CGNAT routing-instance name is specified by RADIUS in the access-accept attributes returned to the subscriber.

This CGNAT routing-instance includes the DHCPv6 server configuration used for IPv6 PD assignment (LAN addressing) as described in the DHCPv6 Local Server configuration section. It also includes IPv4 private, IPv6 PD (LAN addressing), and IPv6 NDRA (WAN addressing) pools for a DS CGNAT subscriber. These pools allow IPv4 private address and IPv6 prefix assignment to a DS CGNAT subscriber. It also assigns IPv4 and IPv6 DNS to a DS CGNAT subscriber.

In our example, DS CGNAT subscriber's traffic is sent to virtual-router (PIC0) via a forwarding-options input filter. The inside multiservice interface is assigned to a virtual-router, this is used to send traffic to the corresponding multiservice interface in the next-hop CGNAT solution.

```

1  routing-instances {
2      NAT-44 {
3          instance-type vrf;
4          system {
5              services {
6                  dhcp-local-server {
7                      dhcpv6 {
8                          overrides {
9                              interface-client-limit 1;
10                             delegated-pool POOL_IPv6_PD_CGNAT;
11                         }
12                     }
13                     group PPPoE {
14                         interface pp0.0;
15                     }
16                 }
17             }
18         }
19         access {
20             address-assignment {
21                 high-utilization 85;
22                 abated-utilization 75;
23                 pool POOL_IPv4_PRIVATE {
24                     family inet {
25                         network 172.29.0.0/16;
26                         range 1 {
27                             low 172.29.0.0;
28                             high 172.29.247.255;
29                         }
30                     }
31                     xauth-attributes {
32                         primary-dns 8.8.8.8/32;
33                         secondary-dns 8.8.4.4/32;
34                     }
35                 }
36             }
37             pool POOL_IPv6_PD_CGNAT {
38                 family inet6 {

```

```

38         prefix 2223::/48;
39         range r1 prefix-length 64;
40         dhcp-attributes {
41             maximum-lease-time 86400;
42             dns-server {
43                 2001:4860:4860::8888;
44             }
45         }
46     }
47 }
48 pool POOL_IPv6_NDRA_CGNAT {
49     family inet6 {
50         prefix fdff:ffff::/48;
51         range r1 prefix-length 64;
52         dhcp-attributes {
53             maximum-lease-time 86400;
54         }
55     }
56 }
57 }
58 }
59 forwarding-options {
60     family inet {
61         filter {
62             input FILTER_TO_CGNAT;
63         }
64     }
65 }
66 route-distinguisher 192.168.0.1:13;
67 vrf-target import target:65500:13;
68 vrf-table-label;
69 }
70 PICO {
71     instance-type virtual-router;
72     routing-options {
73         static {
74             route 0.0.0.0/0 next-hop vms-5/0/0.1;
75             route 172.29.0.0/16 next-table NAT-44.inet.0;
76         }
77     }
78     interface vms-5/0/0.1;
79 }
80 }

```

Default route redirects traffic to inside multiservice interface, so traffic can be NATed. Static route 172.29/16 sends traffic to NAT-44 routing-instance which subscriber resides.

1.5.10 Deterministic CGNAT Translation

CGNAT specific configuration includes a service-set which is the main CGNAT building block, it groups the inside and outside multiservice interfaces along the NAT rule, this is where the translation takes place. The packets toward the inside multiservice interface are translated based on the NAT rule defined under this service-set.

Having a next-hop style service represents an inside multiservice interface (private network addressing) and an outside multiservice interface (public network addressing).

A firewall rule is needed for the service-set, this firewall rule can accept everything as displayed below or can do firewalling based on specific requirements.

The NAT rule identifies the source private addressing and based on the source addressing along the ALGs does the source NAT, it calls a pool in the source NAT action. A NAT rule is defined under a NAT rule-set, the NAT rule-set can have multiple NAT rules.

An address-book contains address ranges, and private source addressing is defined under these ranges.

Application Layer Gateways allows applications to work within NAT, Junos includes rich ALGs for NAT such as

FTP, DNS, H323, ICMP, SIP, PPTP, SNMP, TFTP, etc. Most applications have evolved to function in an IPv4 NAT, working in the application layer.

The NAT pool contains the public IPv4 address to which private addressing will be translated, and the ports range available per public IPv4 address, if PBA or Deterministic NAT is used, it then also includes the port block-size and the IPv4 private addressing.

```

1  services {
2      service-set SLOT5_PIC0 {
3          stateful-firewall-rules ALLOW-ALL;
4          nat-rule-sets CGNAT_PIC0_SET;
5          next-hop-service {
6              inside-service-interface vms-5/0/0.1;
7              outside-service-interface vms-5/0/0.2;
8          }
9      }
10     nat {
11         source {
12             pool CGNAT_PIC0_POOL {
13                 address {
14                     179.159.4.16/32 to 179.159.7.255/32;
15                     200.100.106.200/32 to 200.100.106.215/32;
16                 }
17                 port {
18                     range {
19                         2048;
20                         to {
21                             65535;
22                         }
23                     }
24                     deterministic {
25                         block-size 2048;
26                         host address-name RANGE_1;
27                         include-boundary-addresses;
28                     }
29                 }
30                 ei-mapping-timeout 120;
31                 mapping-timeout 120;
32             }
33             rule-set CGNAT_PIC0_SET {
34                 rule CGNAT_PIC0_RULE {
35                     match {
36                         source-address-name RANGE_1;
37                         application APPS;
38                     }
39                     then {
40                         source-nat {
41                             pool {
42                                 CGNAT_PIC0_POOL;
43                             }
44                         }
45                     }
46                 }
47                 match-direction input;
48             }
49         }
50     }
51     policies {
52         stateful-firewall-rule ALLOW-ALL {
53             match-direction input;
54             policy ACCEPT {
55                 match {
56                     source-address any;
57                     destination-address any;
58                     application any;
59                 }
60                 then {
61                     permit;
62                 }
63             }
64         }
65     }
66     address-book {
67         global {
68             address RANGE_1 {
69                 address-range 172.29.0.0/32 {
70                     to {

```

```

71      172.29.123.255/32;
72      }
73    }
74  }
75 }
76 }
77 }
```

1.6 Verification

MX BNG DS subscribers and DS CGNAT subscriber's connections on MPC10E are shown through the following commands,

Specific DS subscribers and DS CGNAT verification sections are displayed following the current section.

16K PPPoE sessions are connected on the MPC10E xe-9/0/3:0 port. Of these 16K subscribers, 8K are for DS subscribers and 8K for DS CGNAT subscribers.

As subscribers are DS, 16K DHCP, and 16K PPPoE sessions are established.

```

1 jnpr@MX960> show subscribers summary port
2
3 Interface Count
4 xe-9/0/3:0 16000
5
6 Total Subscribers: 16000
7
8
9 jnpr@MX960> show subscribers summary
10
11 Subscribers by State
12   Active: 32000
13   Total: 32000
14
15 Subscribers by Client Type
16   DHCP: 16000
17   PPPoE: 16000
18   Total: 32000
```

DS and DS CGNAT subscribers are shown below. DS subscribers are assigned to the default routing-instance, and DS CGNAT subscribers are assigned to the NAT-44 routing-instance.

Each subscriber has a unique dynamic PPPoE interface, an IPv4 address representing either a Public or Private IPv4, an Internet IPv6 PD (LAN addressing) prefix, and a private IPv6 prefix for WAN addressing.

The IPv4 172.20/16 prefix represents public addressing, while the IPv4 172.29/16 prefix represents private addressing.

IPv6 prefixes 2222::/64 and 2223::/64 represent Internet IPv6 prefixes.

IPv6 prefixes fdff:ffff::/64 and fdff:ffff::/64 represent private IPv6 prefixes.

Inte-Subsc username is used for 8K DS subscribers, and the CGNAT-Subsc username is used for 8K DS CGNAT subscribers.

```

1 jnpr@MX960> show subscribers
2 Interface IP Address/VLAN ID User Name LS:RI
3 pp0.3221225483 172.29.0.3 CGNAT-Subsc default:NAT-44
4 * 2223::/64
5 * fdff:ffff:0:3::/64
6 pp0.3221225485 172.29.0.4 CGNAT-Subsc default:NAT-44
7 * 2223:0:0:1::/64
8 * fdff:ffff:0:4::/64
9 pp0.3221225489 172.29.0.5 CGNAT-Subsc default:NAT-44
10 * 2223:0:0:2::/64
11 * fdff:ffff:0:5::/64
12 pp0.3221225494 172.20.0.1 Inte-Subsc default:default
```

```

13 * 2222:0:0:1::/64
14 * fdff:fffe:0:8::/64
15 pp0.3221225492 172.20.0.0 Inte-Subsc default:default
16 * 2222::/64
17 * fdff:fffe:0:7::/64
18 pp0.3221225493 172.29.0.6 CGNAT-Subsc default:NAT-44
19 * 2223:0:0:3::/64
20 * fdff:ffff:0:6::/64

```

16K PPPoE sessions have been established, and PPPoE messages have been exchanged.

```

1 jnpr@MX960> show pppoe statistics
2 Active PPPoE sessions: 16000
3   PacketType Sent Received
4   PADI 0 16000
5   PADO 16000 0
6   PADR 0 16000
7   PADS 16000 0
8   PADT 0 0
9   Service name error 0 0
10  AC system error 0 0
11  Generic error 0 0
12  Malformed packets 0 0
13  Unknown packets 0 0
14
15 jnpr@MX960> show pppoe sessions
16 Interface Underlying State Session Remote
17   interface ID MAC
18 pp0.3221225483 xe-9/0/3:0.1585 Session Up 1 DC:8D:B7:00:00:00
19
20 pp0.3221225485 xe-9/0/3:0.1585 Session Up 2 DC:8D:B7:00:00:01
21
22 pp0.3221225489 xe-9/0/3:0.1585 Session Up 3 DC:8D:B7:00:00:02
23
24 pp0.3221225493 xe-9/0/3:0.1585 Session Up 4 DC:8D:B7:00:00:03
25
26 pp0.3221225497 xe-9/0/3:0.1585 Session Up 5 DC:8D:B7:00:00:04
27
28 jnpr@MX960> show pppoe underlying-interfaces xe-9/0/3:0.1585 extensive
29 xe-9/0/3:0.1585 Index 539
30 State: Static, Dynamic Profile: GIGE_DS_PROFILE,
31 Max Sessions: 16000, Max Sessions VSA Ignore: Off,
32 Active Sessions: 16000,
33 Service Name Table: None,
34 Duplicate Protection: On, Short Cycle Protection: mac-address,
35 Direct Connect: Off,
36 AC Name: MX960,
37 PacketType Sent Received
38 PADI 0 16000
39 PADO 16000 0
40 PADR 0 16000
41 PADS 16000 0
42 PADT 0 0
43 Service name error 0 0
44 AC system error 0 0
45 Generic error 0 0
46 Malformed packets 0 0
47 Unknown packets 0 0
48 Lockout Time (sec): Min: 60, Max: 240
49 Total clients in lockout: 0
50 Total clients in lockout grace period: 0

```

NDRA packets per PPPoE interface are exchanged for both DS and DS GNAT subscribers, and NDRA is used for IPv6 WAN Addressing.

```

1 jnpr@MX960> show ipv6 router-advertisement
2 Interface: pp0.3221225483
3   Advertisements sent: 9, last sent 0:08:22 ago
4   Solicits received: 1, last received 1:02:28 ago
5   Advertisements received: 0
6 Interface: pp0.3221225484
7   Advertisements sent: 9, last sent 0:08:22 ago
8   Solicits received: 1, last received 1:02:28 ago
9   Advertisements received: 0
10 Interface: pp0.3221225485
11   Advertisements sent: 9, last sent 0:08:22 ago
12   Solicits received: 1, last received 1:02:28 ago
13   Advertisements received: 0

```

```

14 Interface: pp0.3221225486
15   Advertisements sent: 9, last sent 0:08:22 ago
16   Solicits received: 1, last received 1:02:28 ago
17   Advertisements received: 0

```

All subscribers have a shaping rate and a service activate assigned via RADIUS. Each subscriber also has an IPv4 and IPv6 input FWF.

```

1 jnpr@MX960> show subscribers extensive | match "junos-cos-shaping-rate:" | count
2
3 Count: 16000 lines
4
5 jnpr@MX960> show subscribers extensive | match SERVICE_ACTIVATE_DS_IN | count
6
7 Count: 16000 lines
8
9 jnpr@MX960> show subscribers extensive | match "IPv4 Input Filter Name: UPSTREAM_IN" | count
10
11 Count: 16000 lines
12
13 jnpr@MX960> show subscribers extensive | match "IPv6 Input Filter Name: UPSTREAM_IN_v6" | count
14
15 Count: 16000 lines
16
17 jnpr@MX960> show firewall templates-in-use
18   Dynamic Subscribers Reference Counts
19   Filter Template Reference Count
20   -----
21   UPSTREAM_IN_UID1008 16000
22   UPSTREAM_IN_v6_UID1009 16000

```

1.6.1 DS Subscribers Verification

8K DS subscribers are connected in the default routing-instance through the MPC10E xe-9/0/3:0 port.

As subscribers are DS, 8K DHCP and 8K PPPoE sessions are established.

```

1 jnpr@MX960> show subscribers summary routing-instance default
2
3 Subscribers by State
4   Active: 16000
5   Total: 16000
6
7 Subscribers by Client Type
8   DHCP: 8000
9   PPPoE: 8000
10  Total: 16000
11
12 Subscribers by LS:RI
13   default:default: 16000
14   Total: 16000

```

DHCPv6 PD (IPv6 LAN addressing) sessions are bound for each PPPoE subscriber.

```

1 jnpr@MX960> show dhcpv6 server binding routing-instance default
2 Prefix Session Id Expires State Interface Client DUID
3 2222::/64 74069 84036 BOUND pp0.3221225492 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:00
4 2222:0:0:4::/64 74073 84036 BOUND pp0.3221225495 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:01
5 2222:0:0:5::/64 74075 84036 BOUND pp0.3221225499 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:02
6 2222:0:0:7::/64 74077 84036 BOUND pp0.3221225502 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:03
7 2222:0:0:9::/64 74080 84036 BOUND pp0.3221225505 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:04
8 2222:0:0:b::/64 74084 84036 BOUND pp0.3221225508 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:05
9 2222:0:0:d::/64 74086 84036 BOUND pp0.3221225511 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:06
10 2222:0:0:f::/64 74091 84036 BOUND pp0.3221225514 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:07
11 2222:0:0:11::/64 74093 84036 BOUND pp0.3221225517 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:08
12 2222:0:0:12::/64 74096 84036 BOUND pp0.3221225520 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:09
13 2222:0:0:16::/64 74099 84038 BOUND pp0.3221225523 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:0a
14 2222:0:0:17::/64 74105 84038 BOUND pp0.3221225526 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:0b
15 2222:0:0:1e::/64 74106 84038 BOUND pp0.3221225528 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:0c
16 2222:0:0:20::/64 74109 84038 BOUND pp0.3221225531 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:0d
17 2222:0:0:21::/64 74111 84038 BOUND pp0.3221225532 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:0e
18 2222:0:0:22::/64 74114 84038 BOUND pp0.3221225538 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:0f
19 2222:0:0:24::/64 74117 84038 BOUND pp0.3221225549 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:10

```

```

20 2222:0:0:25::/64 74121 84039 BOUND pp0.3221225550 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:11
21 2222:0:0:26::/64 74124 84039 BOUND pp0.3221225551 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:12
22 2222:0:0:28::/64 74127 84039 BOUND pp0.3221225552 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:13
23 2222:0:0:2a::/64 74130 84039 BOUND pp0.3221225553 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:14
24 2222:0:0:2b::/64 74133 84039 BOUND pp0.3221225557 LL_TIME0x1-0x838aa9-ac:b6:87:00:00:15

```

8K IPv4 addresses and 8K IPv6 prefixes are consumed from their respective IP pools.

```

1 jnpr@MX960> show network-access aaa statistics address-assignment pool POOL_IPv4_PUBLIC
2 Address assignment statistics
3   Pool Name: POOL_IPv4_PUBLIC
4     Out of Memory: 0
5     Out of Addresses: 0
6     Address total: 65536
7     Addresses in use: 8000
8     Address Usage (percent): 13
9     Pool drain configured: no
10
11 jnpr@MX960> show network-access aaa statistics address-assignment pool POOL_IPv6_PD
12 Address assignment statistics
13   Pool Name: POOL_IPv6_PD
14     Out of Memory: 0
15     Out of Addresses: 0
16     Address total: 65536
17     Addresses in use: 8000
18     Address Usage (percent): 13
19     Pool drain configured: no

```

Each subscriber has been assigned an IPv4 address, DNS, an IPv6 PD prefix, and an IPv6 prefix for WAN addressing. IPv4 addresses and IPv6 prefixes are taken from the corresponding pools indicated by RADIUS.

A shaping rate to limit downstream subscriber bandwidth and a transmit rate for a scheduler are assigned to each subscriber via RADIUS. A service activate is also assigned to each subscriber by RADIUS with the corresponding IPv4 and IPv6 input FWF. The variables defined for such service-activate receive a value from RADIUS to limit upstream bandwidth for each subscriber.

In DS, a DHCP logical interface is tied to a PPPoE interface. The DHCP logical interface specifies the DHCPv6 pool used for DHCPv6 PD.

```

1 jnpr@MX960> show subscribers interface pp0.3221225492 extensive
2 Type: PPPoE
3 User Name: Inte-Subsc
4 IP Address: 172.20.0.0
5 IP Netmask: 255.255.255.255
6 Primary DNS Address: 8.8.8.8
7 Secondary DNS Address: 8.8.4.4
8 IPv6 Prefix: 2222::/64
9 IPv6 User Prefix: fdff:fffe:0:7::/64
10 Logical System: default
11 Routing Instance: default
12 Interface: pp0.3221225492
13 Interface type: Dynamic
14 Underlying Interface: xe-9/0/3:0.1585
15 Dynamic Profile Name: GIGE_DS_PROFILE
16 Dynamic Profile Version: 1
17 MAC Address: ac:b6:87:00:00:00
18 State: Active
19 Radius Accounting ID: 1619305
20 Session ID: 1619305
21 PFE Flow ID: 59750
22 VLAN Id: 1585
23 Login Time: 2023-08-28 17:20:32 CST
24 Service Sessions: 1
25 IP Address Pool: POOL_IPv4_PUBLIC
26 IPv6 Address Pool: POOL_IPv6_NDRA
27 IPv6 Delegated Address Pool: POOL_IPv6_PD
28 IPv6 Interface Address: fdff:fffe:0:7::1/64
29 IPv6 Framed Interface Id: 44f6:1f8b:9c2c:ec81
30 Accounting interval: 600
31 Dynamic configuration:
32   junos-cos-scheduler: DOWNSTREAM_VoIP
33   junos-cos-scheduler-tx: 15000000
34   junos-cos-shaping-rate: 100000000
35   junos-ipv6-ndra-prefix: fdff:fffe:0:7::/64

```

```

36
37 Service Session ID: 1619635
38 Service Session Name: SERVICE_ACTIVATE_DS_IN
39 Service Session Version: 1
40 State: Active
41 Family: inet, inet6
42 IPv4 Input Filter Name: UPSTREAM_IN_UID1008-pp0.3221225492-in
43 IPv6 Input Filter Name: UPSTREAM_IN_v6_UID1009-pp0.3221225492-in
44 Service Activation time: 2023-08-28 17:20:33 CST
45 Dynamic configuration:
46   UPSTREAM_IN: UPSTREAM_IN_UID1008
47   UPSTREAM_IN_v6: BROADBAND_185_IN_v6_UID1009
48   burstPolicer: 12500000
49   inBW: 100000000
50   policer: policer_UID1007
51   voiceBW: 15000000
52
53 Type: DHCP
54 IPv6 Prefix: 2222::/64
55 Logical System: default
56 Routing Instance: default
57 Interface: pp0.3221225492
58 Interface type: Static
59 Underlying Interface: pp0.3221225492
60 MAC Address: ac:b6:87:00:00:00
61 State: Active
62 Radius Accounting ID: 1619718
63 Session ID: 1619718
64 Underlying Session ID: 1619305
65 PFE Flow ID: 59750
66 Login Time: 2023-08-28 17:20:34 CST
67 IPv6 Address Pool: POOL_IPv6_NDRA
68 IPv6 Delegated Address Pool: POOL_IPv6_PD

```

1.6.2 DS CGNAT Subscribers Verification

8K DS CGNAT subscribers are connected in the NAT-44 routing-instance through the MPC10E xe-9/0/3:0 port.

As subscribers are DS, 8K DHCP and 8K PPPoE sessions are established.

```

1 jnpr@MX960> show subscribers summary routing-instance NAT-44
2
3 Subscribers by State
4   Active: 16000
5   Total: 16000
6
7 Subscribers by Client Type
8   DHCP: 8000
9   PPPoE: 8000
10  Total: 16000
11
12 Subscribers by LS:RI
13   default:NAT-44: 16000
14   Total: 16000
15
16 jnpr@MX960> show subscribers routing-instance NAT-44
17 Interface IP Address/VLAN ID User Name LS:RI
18 pp0.3221225483 172.29.0.3 CGNAT-Subsc default:NAT-44
19 * 2223::/64
20 * fdff:ffff:0:3::/64
21 pp0.3221225485 172.29.0.4 CGNAT-Subsc default:NAT-44
22 * 2223:0:0:1::/64
23 * fdff:ffff:0:4::/64
24 pp0.3221225489 172.29.0.5 CGNAT-Subsc default:NAT-44
25 * 2223:0:0:2::/64
26 * fdff:ffff:0:5::/64
27 pp0.3221225493 172.29.0.6 CGNAT-Subsc default:NAT-44
28 * 2223:0:0:3::/64
29 * fdff:ffff:0:6::/64
30 pp0.3221225497 172.29.0.7 CGNAT-Subsc default:NAT-44
31 * 2223:0:0:4::/64
32 * fdff:ffff:0:7::/64
33 pp0.3221225500 172.29.0.8 CGNAT-Subsc default:NAT-44
34 * 2223:0:0:5::/64
35 * fdff:ffff:0:8::/64
36 pp0.3221225503 172.29.0.9 CGNAT-Subsc default:NAT-44

```

```

37 * 2223:0:0:6::/64
38 * fdff:ffff:0:9::/64
39 pp0.3221225506 172.29.0.10 CGNAT-Subsc default:NAT-44
40 * 2223:0:0:7::/64
41 * fdff:ffff:0:a::/64
42 pp0.3221225509 172.29.0.11 CGNAT-Subsc default:NAT-44
43 * 2223:0:0:8::/64
44 * fdff:ffff:0:b::/64
45 pp0.3221225512 172.29.0.12 CGNAT-Subsc default:NAT-44
46 * 2223:0:0:9::/64
47 * fdff:ffff:0:c::/64
48 pp0.3221225515 172.29.0.13 CGNAT-Subsc default:NAT-44
49 * 2223:0:0:a::/64
50 * fdff:ffff:0:d::/64
51 pp0.3221225518 172.29.0.14 CGNAT-Subsc default:NAT-44
52 * 2223:0:0:b::/64
53 * fdff:ffff:0:e::/64
54 pp0.3221225521 172.29.0.15 CGNAT-Subsc default:NAT-44
55 * 2223:0:0:c::/64
56 * fdff:ffff:0:f::/64
57 pp0.3221225522 172.29.0.16 CGNAT-Subsc default:NAT-44
58 * 2223:0:0:d::/64
59 * fdff:ffff:0:10::/64

```

DHCPv6 PD (IPv6 LAN addressing) sessions are bound for each PPPoE subscriber in the NAT-44 routing-instance.

```

1 jnpr@MX960> show dhcpv6 server binding routing-instance NAT-44
2 Prefix Session Id Expires State Interface Client DUID
3 2223::/64 74059 84035 BOUND pp0.3221225483 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:00
4 2223:0:0:1::/64 74064 84035 BOUND pp0.3221225485 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:01
5 2223:0:0:2::/64 74067 84035 BOUND pp0.3221225489 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:02
6 2223:0:0:3::/64 74070 84036 BOUND pp0.3221225493 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:03
7 2223:0:0:4::/64 74072 84036 BOUND pp0.3221225497 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:04
8 2223:0:0:5::/64 74076 84036 BOUND pp0.3221225500 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:05
9 2223:0:0:6::/64 74078 84036 BOUND pp0.3221225503 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:06
10 2223:0:0:7::/64 74081 84036 BOUND pp0.3221225506 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:07
11 2223:0:0:8::/64 74083 84036 BOUND pp0.3221225509 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:08
12 2223:0:0:9::/64 74085 84036 BOUND pp0.3221225512 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:09
13 2223:0:0:a::/64 74090 84036 BOUND pp0.3221225515 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:0a
14 2223:0:0:b::/64 74094 84036 BOUND pp0.3221225518 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:0b
15 2223:0:0:c::/64 74097 84036 BOUND pp0.3221225521 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:0c
16 2223:0:0:d::/64 74100 84038 BOUND pp0.3221225522 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:0d
17 2223:0:0:e::/64 74102 84038 BOUND pp0.3221225527 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:0e
18 2223:0:0:f::/64 74104 84038 BOUND pp0.3221225529 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:0f
19 2223:0:0:10::/64 74108 84038 BOUND pp0.3221225530 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:10
20 2223:0:0:11::/64 74112 84038 BOUND pp0.3221225536 LL_TIME0x1-0x594d2c5e-dc:8d:b7:00:00:11

```

A 2,048 port block size from a public IPv4 address is assigned to each of the 8K private IPv4 addresses, in other words, 2,048 Deterministic NAT sessions are allowed per private IPv4 address.

```

1 jnpr@MX960> show services nat source deterministic
2
3 Pool name: CGNAT_PIC0_POOL
4 Port-overloading-factor: 1 Port block size: 2048
5 Used/total port blocks: 1/31775
6 Host_IP External_IP Port_Block Ports_Used/
7                                     Range Ports_Total
8 172.29.0.0 200.100.106.200 2048-4095 0/2048*1
9 172.29.0.1 200.100.106.200 4096-6143 0/2048*1
10 172.29.0.2 200.100.106.200 6144-8191 0/2048*1
11 172.29.0.3 200.100.106.200 8192-10239 0/2048*1
12 172.29.0.4 200.100.106.200 10240-12287 0/2048*1
13 172.29.0.5 200.100.106.200 12288-14335 0/2048*1
14 172.29.0.6 200.100.106.200 14336-16383 0/2048*1
15 172.29.0.7 200.100.106.200 16384-18431 0/2048*1
16 172.29.0.8 200.100.106.200 18432-20479 0/2048*1
17 172.29.0.9 200.100.106.200 20480-22527 0/2048*1
18 172.29.0.10 200.100.106.200 22528-24575 0/2048*1

```

Each of the subscribers has been assigned an IPv4 address, DNS, an IPv6 PD prefix, and an IPv6 prefix for WAN addressing. IPv4 addresses and IPv6 prefixes are taken from the corresponding NAT-44 routing-instance pools indicated by RADIUS.

For DS CGNAT subscribers, the client profile name is changed by RADIUS in order to assign subscriber to corresponding NAT-44 routing-instance.

A shaping rate to limit downstream subscriber bandwidth and a transmit rate for a scheduler are assigned to each subscriber via RADIUS. A service activate is also assigned to each subscriber by RADIUS with corresponding IPv4 and IPv6 input FWF. The variables defined for such service-activate receive a value from RADIUS to limit upstream bandwidth to each subscriber.

In DS, a DHCP logical interface is tied to a PPPoE interface, DHCP logical interface specifies the DHCPv6 pool used for DHCPv6 PD.

```

1 jnpr@MX960> show subscribers interface pp0.3221225483 extensive
2 Type: PPPoE
3 User Name: CGNAT-Subsc
4 IP Address: 172.29.0.3
5 IP Netmask: 255.255.255.255
6 Primary DNS Address: 8.8.8.8
7 Secondary DNS Address: 8.8.4.4
8 IPv6 Prefix: 2223::/64
9 IPv6 User Prefix: fdff:ffff:0:3::/64
10 Logical System: default
11 Routing Instance: NAT-44
12 Interface: pp0.3221225483
13 Interface type: Dynamic
14 Underlying Interface: xe-9/0/3:0.1585
15 Dynamic Profile Name: CGNAT_DS_PROFILE
16 Dynamic Profile Version: 1
17 MAC Address: dc:8d:b7:00:00:00
18 State: Active
19 Radius Accounting ID: 1409582
20 Session ID: 1409582
21 PFE Flow ID: 966921
22 VLAN Id: 1585
23 Login Time: 2023-08-28 17:27:43 CST
24 Service Sessions: 1
25 IP Address Pool: POOL_IPv4_PRIVATE
26 IPv6 Address Pool: POOL_IPv6_NDRA_CGNAT
27 IPv6 Delegated Address Pool: POOL_IPv6_PD_CGNAT
28 IPv6 Interface Address: fdff:ffff:0:3::1/64
29 IPv6 Framed Interface Id: 0:0:2e82:1500
30 Accounting interval: 600
31 Dynamic configuration:
32   junos-cos-scheduler: DOWNSTREAM_VoIP
33   junos-cos-scheduler-tx: 1500000
34   junos-cos-shaping-rate: 10000000
35   junos-ipv6-ndra-prefix: fdff:ffff:0:3::/64
36
37   Service Session ID: 1409681
38   Service Session Name: SERVICE_ACTIVATE_DS_IN
39   Service Session Version: 1
40   State: Active
41   Family: inet, inet6
42   IPv4 Input Filter Name: UPSTREAM_IN_UID1008-pp0.3221225483-in
43   IPv6 Input Filter Name: UPSTREAM_IN_v6_UID1009-pp0.3221225483-in
44   Service Activation time: 2023-08-28 17:27:44 CST
45   Dynamic configuration:
46     UPSTREAM_IN: UPSTREAM_IN_UID1008
47     UPSTREAM_IN_v6: UPSTREAM_IN_v6_UID1009
48     burstPolicer: 1250000
49     inBW: 10000000
50     policer: policer_UID1007
51     voiceBW: 1500000
52
53 Type: DHCP
54 IPv6 Prefix: 2223::/64
55 Logical System: default
56 Routing Instance: NAT-44
57 Interface: pp0.3221225483
58 Interface type: Static
59 Underlying Interface: pp0.3221225483
60 MAC Address: dc:8d:b7:00:00:00
61 State: Active
62 Radius Accounting ID: jnpr :1409657
63 Session ID: 1409657
64 Underlying Session ID: 1409582

```

```
65 PFE Flow ID: 966921
66 Login Time: 2023-08-28 17:27:45 CST
67 IPv6 Address Pool: POOL_IPv6_NDRA_CGNAT
68 IPv6 Delegated Address Pool: POOL_IPv6_PD_CGNAT
```

1.7 Conclusion

Juniper MX MPC10E-10C and MPC10E-15C line cards have subscriber management capabilities starting in the 22.4R1 release. These line cards support DS subscriber sessions, either IPoE or PPPoE access methods, NDRA or DHCPv6 IA_NA for WAN addressing, and DHCPv6 PD for LAN addressing. MX Trio-5 supports subscriber management as in previous MX Trio generations.

MPC10E-10C supports 32K Dual Stack subscribers per PFE, for a total of 64K Dual Stack subscribers. MPC10E-15C supports 32K Dual Stack subscribers per PFE, for a total of 96K subscribers.

MPC10E line cards subscriber scalability is not impacted when enabling HQoS, ingress/egress FW Filtering, or ingress/egress policing per subscriber access connection.

1.8 Useful links

- Centralized Deterministic CGNAT <https://juniper.github.io/techposts/centralized-deterministic-cgnat/article>
- MX Interface Module Reference <https://www.juniper.net/documentation/us/en/hardware/mx-module-reference/mx-module-reference.pdf>
- MPC10E Deep Dive <https://juniper.github.io/techposts/mpc10e-deepdive/article>
- Broadband Subscriber Sessions User Guide <https://www.juniper.net/documentation/us/en/software/junos/subscriber-mgmt-sessions/index.html>
- Broadband Subscriber Access Protocols User Guide <https://www.juniper.net/documentation/us/en/software/junos/subscriber-mgmt-access/index.html>
- Broadband Subscriber Management Wholesale User Guide <https://www.juniper.net/documentation/us/en/software/junos/subscriber-mgmt-wholesale/index.html>
- Broadband Subscriber Services User Guide <https://www.juniper.net/documentation/us/en/software/junos/subscriber-mgmt-services/index.html>
- Broadband Subscriber VLANs and Interfaces User Guide <https://www.juniper.net/documentation/us/en/software/junos/subscriber-mgmt-vlan/index.html>
- NDRA and DHCPv6 Prefix Delegation <https://www.juniper.net/documentation/us/en/software/nce/dual-stack-pppoe-ndra-dhcpv6-pd/index.html>
- DHCPv6 IA_NA and DHCPv6 Prefix Delegation <https://www.juniper.net/documentation/us/en/software/junos/subscriber-mgmt-sessions/topics/topic-map/dhcpv6-iana-prefix-delegation-addressing.html>
- Adaptive Services Interfaces User Guide for Routing Devices: <https://www.juniper.net/documentation/us/en/software/junos/interfaces-adaptive-services/interfaces-adaptive-services.pdf>
- Next Gen Services Interfaces User Guide for Routing Devices: <https://www.juniper.net/documentation/us/en/software/junos/interfaces-next-gen-services/interfaces-next-gen-services.pdf>

1.9 Glossary

- AAA: Authentication, Authorization and Accounting
- ALG: Application Layer Gateway
- BNG: Broadband Network Gateway
- CGNAT: Carrier Grade NAT
- CoA: Change of Authorization
- DHCPv6: Dynamic Host Configuration Protocol version 6
- DNS: Domain Name System
- DS: Dual Stack
- FTP: File Transfer Protocol
- FW: Firewall
- FWF: Firewall Filtering
- GigE: Gigabit Ethernet
- HQoS: Hierarchical Quality of Service
- IA_NA: Identity Association for Non-Temporary Addresses
- ICMP: Internet Control Message Protocol
- IPv4: Internet Protocol version 4
- IPv6: Internet Protocol version 6
- LAN: Local Area Network
- MF: Multi-field
- MPLS: Multiprotocol Label Switching
- NAPT: Network Address Port Translation
- NAT: Network Address Translation
- NAT44: Translates an IPv4 to another IPv4
- NDRA: Neighbor Discovery Router Advertisement
- PD: Prefix Delegation
- PFE: Packet Forwarding Engine
- PIC: Physical Interface Card
- PPPoE: Point-to-Point Protocol over Ethernet
- PPTP: Point-to-Point Tunneling Protocol
- RADIUS: Remote Authentication Dial-In User Service
- SIP: Session Initiation Protocol
- SNMP: Simple Network Management Protocol
- TFTP: Trivial File Transfer Protocol
- VR: Virtual Router
- VRF: Virtual Routing and Forwarding
- VSA: Vendor-specific attributes
- WAN: Wide-area Network

1.10 Acknowledgements

Thanks to Nicolas Fevrier for the opportunity and guidance to write this tech post. Thanks to Dirk van den Borne for encouraging me to create a tech post and also thanks to Aris Georgakas for the review and comments.



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

