



DC – AI – Routing – Switching – Security – Wireless – Automation

ACX7100/ACX7509 Validation: EVPN MAC-VRF

An HPE Juniper Networking Techpost

Suneesh Babu

2022-10-28

HPE



Contents

1	EVPN MAC-VRF Validation on ACX7000	2
1.1	Introduction	2
1.2	Metro EVPN Topology	3
1.2.1	Base Configuration	3
1.2.2	MAC-VRF Routing Instance Configuration	4
1.2.3	MAC-VRF CE Bound Interface Schema	5
1.2.4	MAC-VRF Verification	6
1.2.5	VLAN Based MAC VRF Verification	6
1.2.6	VLAN Bundle MAC-VRF Verification	8
1.3	Generating Scale Configuration	10
1.3.1	Jinja Configuration Template	10
1.3.2	Configuration Parameters	11

1 EVPN MAC-VRF Validation on ACX7000

Suneesh Babu - 10/29/2022

JUNOS unified way of bringing up EVPN E-LAN using mac-vrf instance type supporting 6,000 instances on ACX7000 with 642,000 MAC scale.

1.1 Introduction

This article is the first in a series on ACX7k Metro Validation. We are covering the following features and their scale.

Layer-2 VPN Technologies provide multipoint services over IP/MPLS networks. The latest addition to this is [Ethernet VPN \(EVPN\)](#) where MAC learning is done via control plane compared to its predecessor [Virtual Private LAN Service \(VPLS\)](#) where MAC got learned via data plane.

[RFC-7432](#) describes BGP MPLS Based Ethernet VPNs with three service types, namely VLAN-Based, VLAN-Bundle, and VLAN-Aware-Bundle. In VLAN-Based MAC-VRF, only one broadcast domain or VLAN is present. In VLAN-Bundle MAC-VRF multiple broadcast domains or VLANs are present, all of them bundled into a single bridge table. In VLAN-Aware Bundle MAC-VRF multiple broadcast domains are present, each having its own bridge table.

JUNOS supports EVPN with [MPLS](#) and [VxLAN](#) encapsulations. Its E-LAN configuration constructs differ across the platforms. The instance type “mac-vrf” is a unified way to configure EVPN E-LAN across entire Juniper platforms.

[ACX7100-32C](#) supports EVPN-MPLS E-LAN functionality with instance-type “mac-vrf”. In this test scenario, VLAN-Based and VLAN-Bundle service types of MAC VRF are covered for their scale with 22.2R1 Junos-EVO build. VLAN-Aware Bundle Support is on the roadmap.

6,000 EVPN MAC-VRF Instances were tested on ACX7100-32C with 3,000 VLAN-Based Service Types and 3,000 VLAN-Bundle Service Types. 642,000 MACs across 6,000 MAC-VRF Instances. The same scale is tested on [ACX7100-48L](#) as well as on [ACX7509](#).

But the [ACX7024](#) Scale is not covered in this article (same features but different scale are expected on this platform).

Please note that despite sharing the same ACX moniker, the ACX7000 products are different products than ACX500/710/1000/1100/2100/2200/4000/5000/5400/6000. They are powered by different Packet Forwarding Engines (PFE), and support different feature sets and scales.

The Key Performance Indicator (KPI) tested are:

EVPN MAC-VRF KPI	Scale
Number of MAC-VRF instances	6,000
Number of VLAN-Based Service Types	3,000
Number of VLAN-Bundle Service Types	3,000
Number of VLANs	9,000

EVPN MAC-VRF KPI	Scale
Number of Interfaces	9,000
Number of MACs	642,000


1.2 Metro EVPN Topology

Test topology consists of three routers:

- PE1: ACX7100-32C
- PE2: ACX7100-48L
- P1: [PTX10008](#).

CEs are simulated using a traffic generator and are connected to PEs using 5x 100G links. PEs are connected to the core using 8x 100G links, bundled in 2x LAGs of four links each.

The ACX7100-32C is the Device Under Test (DUT). The underlay transport used for testing is SR-MPLS with both OSPF and ISIS protocols individually. We also covered LDP as the underlay transport. The CE-bound interface configurations are of SP-Style (see glossary).



For this test, we configured 6,000 MAC-VRF instances:

- 3,000 with VLAN-Based and the remaining VLAN-Bundle.
- VLAN-Based instances have one VLAN and VLAN-Bundle have two VLANs.
- 43 Local and 43 Remote hosts are learned per VLAN-Based MAC-VRF Instances
- 64 Local and 64 Remote hosts are learned per VLAN-Bundle MAC-VRF Instances
- Total: 642,000 hosts.

Bidirectional traffic in iMIX mode at 99.9% offer-load flows for all the EVPN services. A total of ~1Tbps traffic transits through the DUT.

1.2.1 Base Configuration

The IGP and BGP configurations require to bring up EVPN:

```

1 regress@PE1> show configuration protocols |display inheritance no-comments
2 bgp {
3     group IBGP {
4         type internal;
5         local-address 12.1.1.1;
6         family inet {
7             unicast;
8         }
9         family evpn {
10            signaling;
11        }
12        neighbor 12.1.1.3 {
13            export nhself;
14        }
15    }
16 }
17 mpls {
18     interface ae0.0;
19     interface ae1.0;
20 }
21 ospf {
22     source-packet-routing {
23         node-segment ipv4-index 101;
24         srgb start-label 45000 index-range 2000;
25     }
26     area 0.0.0.0 {
27         interface lo0.0 {
28             passive;
29         }
30         interface ae0.0 {
31             interface-type p2p;
32         }
33         interface ae1.0 {
34             interface-type p2p;
35         }
36     }
37 }
38
39 regress@PE1>

```

1.2.2 MAC-VRF Routing Instance Configuration

MAC-VRF with VLAN-Based service type is as follows:

```

1 regress@PE1> show configuration
2 interfaces {
3     et-0/0/0 {
4         flexible-vlan-tagging;
5         encapsulation flexible-ethernet-services;
6         unit 1 {
7             encapsulation vlan-bridge;
8             vlan-id 1;
9         }
10    }
11 }
12 routing-instances {
13     METRO_MAC_VRF_1 {
14         instance-type mac-vrf;
15         protocols {
16             evpn {
17                 encapsulation mpls;
18                 normalization;
19                 no-control-word;
20             }
21         }
22         service-type vlan-based;
23         interface et-0/0/0.1;
24         route-distinguisher 12.1.1.1:1;
25         vrf-target target:65000:1;
26         vlans {
27             MVRF_VBASED_VLAN_1 {
28                 vlan-id 1;
29                 interface et-0/0/0.1;
30             }
31         }
32     }
33 }

```

```
33 }
```

MAC-VRF with VLAN-Bundle service type is as follows:

```
1 regress@PE1> show configuration
2 interfaces {
3   et-0/0/2 {
4     flexible-vlan-tagging;
5     encapsulation flexible-ethernet-services;
6     unit 1 {
7       encapsulation vlan-bridge;
8       vlan-id-list 1;
9     }
10  }
11  et-0/0/3 {
12    flexible-vlan-tagging;
13    encapsulation flexible-ethernet-services;
14    unit 1001 {
15      encapsulation vlan-bridge;
16      vlan-id-list 1001;
17    }
18  }
19 }
20 routing-instances {
21   METRO_MAC_VRF_3001 {
22     instance-type mac-vrf;
23     protocols {
24       evpn {
25         encapsulation mpls;
26         no-control-word;
27       }
28     }
29     service-type vlan-bundle;
30     interface et-0/0/2.1;
31     interface et-0/0/3.1001;
32     route-distinguisher 12.1.1.1:3001;
33     vrf-target target:65000:3001;
34     vlans {
35       MVRF_VBUNDLE_VLAN_3001 {
36         interface et-0/0/2.1;
37         interface et-0/0/3.1001;
38       }
39     }
40   }
41 }
```

1.2.3 MAC-VRF CE Bound Interface Schema

The five CE-bound 100G interfaces are logically split across the routing-instances as follows:

PE1	PE2	Port	Service Type	MAC-VRF	VLAN Association	Traffic Load
et-0/0/0	et-0/0/48:0	P1	VLAN-Based	1-1500	P1-1-1500	99.9%
et-0/0/1	et-0/0/48:1	P2	VLAN-Based	1501-3000	P2-1-1500	99.9%
et-0/0/2	et-0/0/48:2	P3	VLAN-Bundle	3001-4000	P3-1-1000,P4-1001-2000	99.9%
et-0/0/3	et-0/0/48:3	P4	VLAN-Bundle	4001-5000	P4-1-1000,P5-1001-2000	99.9%

PE1	PE2	Port	Service Type	MAC-VRF	VLAN Association	Traffic Load
et-0/0/4	et-0/0/49	P5	VLAN-Bundle	5001-6000	P5-1-1000,P3-1001-2000	99.9%

1.2.4 MAC-VRF Verification

The first step to verify the EVPN service is to make sure the PE devices are having BGP established with evpn-signalling. As shown below from PE1, BGP is in Established state for the Peer PE2(12.1.1.3) and bgp.evpn.0 table got populated with Type-2 MAC routes.

```

1 regress@PE1> show bgp summary |no-more
2 Threading mode: BGP I/O
3 Default eBGP mode: advertise - accept, receive - accept
4 Groups: 1 Peers: 1 Down peers: 0
5 Table Tot Paths Act Paths Suppressed History Damp State Pending
6 inet.0
7           10 1 0 0 0 0
8 inet6.0
9           0 0 0 0 0 0
10 bgp.evpn.0
11          327000 327000 0 0 0 0
12 inet6.3
13           0 0 0 0 0 0
14 Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn State|#Active/Received/Accepted/Damped...
15 12.1.1.3 65000 38691 158803 0 1 1d 0:24:43 Establ
16 inet.0: 1/10/10/0
17 bgp.evpn.0: 327000/327000/327000/0
18 METRO_MAC_VRF_1.evpn.0: 44/44/44/0
19 METRO_MAC_VRF_2.evpn.0: 44/44/44/0
20 METRO_MAC_VRF_3.evpn.0: 44/44/44/0
21 ...
22 METRO_MAC_VRF_2998.evpn.0: 44/44/44/0
23 METRO_MAC_VRF_2999.evpn.0: 44/44/44/0
24 METRO_MAC_VRF_3000.evpn.0: 44/44/44/0
25 METRO_MAC_VRF_3001.evpn.0: 65/65/65/0
26 METRO_MAC_VRF_3002.evpn.0: 65/65/65/0
27 METRO_MAC_VRF_3003.evpn.0: 65/65/65/0
28 ...
29 METRO_MAC_VRF_5998.evpn.0: 65/65/65/0
30 METRO_MAC_VRF_5999.evpn.0: 65/65/65/0
31 METRO_MAC_VRF_6000.evpn.0: 65/65/65/0
32 __default_evpn__.evpn.0: 0/0/0/0
33
34 regress@PE1>

```

The MAC-Table Summary shows the DUT learned the 642,000 host MAC addresses.

```

1 regress@PE1> show mac-vrf forwarding mac-table summary
2 Jun 29 05:14:19
3 Total dynamic and static MAC addresses learned globally : 642000
4 Configured static MAC addresses learned globally : 0

```

1.2.5 VLAN Based MAC VRF Verification

As shown below, the interface et-0/0/0.1 is bound to MAC-VRF Instance METRO_MAC_VRF_1 with a single vlan (vlan-id 1). The interface is in Forwarding state:

```

1 regress@PE1> show mac-vrf forwarding interface et-0/0/0.1
2 Routing Instance Name : METRO_MAC_VRF_1
3 Logical Interface flags (DL - disable learning, AD - packet action drop,
4                      LH - MAC limit hit, DN - interface down,

```

```

5          MMAS - Mac-move action shutdown, AS - Autostate-exclude enabled,
6          SCTL - shutdown by Storm-control, MI - MAC+IP limit hit)
7
8 Logical Vlan TAG MAC MAC+IP STP Logical Tagging
9 interface members limit limit state interface flags
10 et-0/0/0.1 0 0 tagged
11          MVRF_VBASED_VLAN_1 1 1000001 0 Forwarding tagged

```

The VLAN Association of the METRO_MAC_VRF_1 instance is shown below.

```

1 regress@PE1> show vlans MVRF_VBASED_VLAN_1
2
3 Routing instance VLAN name Tag Interfaces
4 METRO_MAC_VRF_1 MVRF_VBASED_VLAN_1 1
5                                     .local.202922*
6                                     et-0/0/0.1*

```

The extensive output of the METRO_MAC_VRF_1 instance captures the total number of MAC learned. The VLAN bound to instance can be found too.

```

1 regress@PE1> show evpn instance METRO_MAC_VRF_1 extensive
2 Instance: METRO_MAC_VRF_1
3 Route Distinguisher: 12.1.1.1:1
4 VLAN ID: 1
5 Per-instance MAC route label: 16
6 Duplicate MAC detection threshold: 5
7 Duplicate MAC detection window: 180
8 MAC database status Local Remote
9   MAC advertisements: 43 43
10  MAC+IP advertisements: 0 0
11  Default gateway MAC advertisements: 0 0
12  Number of local interfaces: 2 (2 up)
13   Interface name ESI Mode Status AC-Role
14   .local..51 00:00:00:00:00:00:00:00:00 single-homed Up Root
15   et-0/0/0.1 00:00:00:00:00:00:00:00:00 single-homed Up Root
16  Number of IRB interfaces: 0 (0 up)
17  Number of protect interfaces: 0
18  Number of bridge domains: 1
19   VLAN Domain-ID Intfs/up IRB-intf Mode MAC-sync v4-SG-sync v6-SG-sync
20   1 1 1 Extended Enabled Disabled Disabled
21  Number of neighbors: 1
22   Address MAC MAC+IP AD IM ES Leaf-label Remote-DCI-Peer
23   12.1.1.3 43 0 0 1 0
24  Number of ethernet segments: 0
25  SMET Forwarding: Disabled

```

The MAC-VRF Forwarding Table of METRO_MAC_VRF_1 instance captures both local and remote MAC addresses.

```

1 regress@PE1> show mac-vrf forwarding mac-table instance METRO_MAC_VRF_1
2
3 MAC flags (S - static MAC, D - dynamic MAC, L - locally learned, P - Persistent static, C -
4   Control MAC
5   SE - statistics enabled, NM - non configured MAC, R - remote PE MAC, O - ovsdb MAC)
6
7 Ethernet switching table : 86 entries, 86 learned
8 Routing instance : METRO_MAC_VRF_1
9   Vlan MAC MAC Age Logical NH RTR
10  name address flags interface Index ID
11  MVRF_VBASED_VLAN_1 00:11:01:00:00:01 D - et-0/0/0.1 0 0
12  MVRF_VBASED_VLAN_1 00:11:01:00:00:02 D - et-0/0/0.1 0 0
13  MVRF_VBASED_VLAN_1 00:11:01:00:00:03 D - et-0/0/0.1 0 0
14  ...
15  MVRF_VBASED_VLAN_1 00:13:01:00:00:01 DC - 202922 202922
16  MVRF_VBASED_VLAN_1 00:13:01:00:00:02 DC - 202922 202922
17  MVRF_VBASED_VLAN_1 00:13:01:00:00:03 DC - 202922 202922
18  ...
19
20 regress@PE1>

```

The labels associated with one of the remote MAC learned are displayed with:

```

1 regress@PE1> show route forwarding-table table METRO_MAC_VRF_1 | find 00:13:01:00:00:01/48
2 00:13:01:00:00:01/48 user 0 indr 228870 1

```



```

3          ulst 228867 1
4          sftw Push 17, Push 45103(top) 228865 1 ae0.0
5          15.1.1.2 ucst 17001 1 ae0.0
6          sftw Push 17, Push 45103(top) 228866 1 ae1.0
7          15.1.2.2 ucst 17000 1 ae1.0
8          ...
9 regress@PE1>
10 regress@PE1> show route table mpls.0 label 45103
11
12 mpls.0: 24013 destinations, 24013 routes (24013 active, 0 holddown, 0 hidden)
13 + = Active Route, - = Last Active, * = Both
14
15 45103 *[L-OSPF/10/5] 2d 22:01:11, metric 2
16     to 15.1.1.2 via ae0.0, Swap 45103
17     > to 15.1.2.2 via ae1.0, Swap 45103
18 regress@PE2> show route table mpls.0 label 17
19
20 mpls.0: 24013 destinations, 24013 routes (24013 active, 0 holddown, 0 hidden)
21 + = Active Route, - = Last Active, * = Both
22
23 17 *[EVPN/7] 23:52:42, routing-instance METRO_MAC_VRF_1, route-type Ingress-MAC, vlan-id 1
24     to table METRO_MAC_VRF_1.evpn-mac.0
25
26 regress@PE2>

```

1.2.6 VLAN Bundle MAC-VRF Verification

The interface and its vlan-association for a vlan-bundle service type mac-vrf instance METRO_MAC_VRF_3001 are as follows:

```

1 regress@PE1> show mac-vrf forwarding interface et-0/0/2.1
2 Routing Instance Name : METRO_MAC_VRF_3001
3 Logical Interface flags (DL - disable learning, AD - packet action drop,
4     LH - MAC limit hit, DN - interface down,
5     MMAS - Mac-move action shutdown, AS - Autostate-exclude enabled,
6     SCTL - shutdown by Storm-control, MI - MAC+IP limit hit)
7
8 Logical Vlan TAG MAC MAC+IP STP Logical Tagging
9 interface members limit limit state interface flags
10 et-0/0/2.1 0 0 tagged
11     MVRF_VBUNDLE_VLAN_3001 NA 1000001 0 Forwarding tagged
12
13 regress@PE1> show mac-vrf forwarding interface et-0/0/3.1001
14 Routing Instance Name : METRO_MAC_VRF_3001
15 Logical Interface flags (DL - disable learning, AD - packet action drop,
16     LH - MAC limit hit, DN - interface down,
17     MMAS - Mac-move action shutdown, AS - Autostate-exclude enabled,
18     SCTL - shutdown by Storm-control, MI - MAC+IP limit hit)
19
20 Logical Vlan TAG MAC MAC+IP STP Logical Tagging
21 interface members limit limit state interface flags
22 et-0/0/3.1001 0 0 tagged
23     MVRF_VBUNDLE_VLAN_3001 NA 1000001 0 Forwarding tagged

```

Vlan-1 and Vlan-1000 are associated with METRO_MAC_VRF_3001 mac-vrf instance and its interface association is shown below.

```

1 regress@PE1> show vlans MVRF_VBUNDLE_VLAN_3001
2
3 Routing instance VLAN name Tag Interfaces
4 METRO_MAC_VRF_3001 MVRF_VBUNDLE_VLAN_3001 NA
5     .local.202905*
6     et-0/0/2.1*
7     et-0/0/3.1001*

```

and also

```

1 regress@PE1> show evpn instance METRO_MAC_VRF_3001 extensive
2 Instance: METRO_MAC_VRF_3001
3 Route Distinguisher: 12.1.1.1:3001
4 Service interface type: VLAN-bundle service interface
5 Per-instance MAC route label: 6016
6 Duplicate MAC detection threshold: 5

```

```

7 Duplicate MAC detection window: 180
8 MAC database status Local Remote
9 MAC advertisements: 64 64
10 MAC+IP advertisements: 0 0
11 Default gateway MAC advertisements: 0 0
12 Number of local interfaces: 3 (3 up)
13 Interface name ESI Mode Status AC-Role
14 .local..2279 00:00:00:00:00:00:00:00:00:00 single-homed Up Root
15 et-0/0/2.1 00:00:00:00:00:00:00:00:00:00 single-homed Up Root
16 et-0/0/3.1001 00:00:00:00:00:00:00:00:00:00 single-homed Up Root
17 Number of IRB interfaces: 0 (0 up)
18 Number of protect interfaces: 0
19 Number of bridge domains: 1
20 VLAN Domain-ID Intfs/up IRB-intf Mode MAC-sync v4-SG-sync v6-SG-sync
21 None 2 2 Extended Enabled Disabled Disabled
22 Number of neighbors: 1
23 Address MAC MAC+IP AD IM ES Leaf-label Remote-DCI-Peer
24 12.1.1.3 64 0 0 1 0
25 Number of ethernet segments: 0
26 SMET Forwarding: Disabled
27
28 regress@PE1>

```

The DUT learns MAC addresses from both the vlans as well as from remote peer over the evpn-signalling.

```

1 regress@PE1> show mac-vrf forwarding mac-table instance METRO_MAC_VRF_3001
2
3 MAC flags (S - static MAC, D - dynamic MAC, L - locally learned, P - Persistent static, C -
4 Control MAC
5 SE - statistics enabled, NM - non configured MAC, R - remote PE MAC, O - ovsdb MAC)
6
7 Ethernet switching table : 128 entries, 128 learned
8 Routing instance : METRO_MAC_VRF_3001
9 Vlan MAC MAC Age Logical NH RTR
10 name address flags interface Index ID
11 MVRF_VBUNDLE_VLAN_3001 00:15:01:00:00:01 D - et-0/0/2.1 0 0
12 MVRF_VBUNDLE_VLAN_3001 00:15:01:00:00:02 D - et-0/0/2.1 0 0
13 MVRF_VBUNDLE_VLAN_3001 00:15:01:00:00:03 D - et-0/0/2.1 0 0
14 ...
15 MVRF_VBUNDLE_VLAN_3001 00:19:01:00:00:01 D - et-0/0/3.1001 0 0
16 MVRF_VBUNDLE_VLAN_3001 00:19:01:00:00:02 D - et-0/0/3.1001 0 0
17 MVRF_VBUNDLE_VLAN_3001 00:19:01:00:00:03 D - et-0/0/3.1001 0 0
18 ...
19 MVRF_VBUNDLE_VLAN_3001 00:1b:01:00:00:01 DC - 202905 202905
20 MVRF_VBUNDLE_VLAN_3001 00:1b:01:00:00:02 DC - 202905 202905
21 MVRF_VBUNDLE_VLAN_3001 00:1b:01:00:00:03 DC - 202905 202905
22 ...
23 MVRF_VBUNDLE_VLAN_3001 00:1f:01:00:00:01 DC - 202905 202905
24 MVRF_VBUNDLE_VLAN_3001 00:1f:01:00:00:02 DC - 202905 202905
25 MVRF_VBUNDLE_VLAN_3001 00:1f:01:00:00:03 DC - 202905 202905
26 ...
27 regress@PE1>

```

The following output captures the number of instances and total MAC learned in the DUT

```

1 regress@PE1> show bgp summary |match evpn.0 | count
2 Count: 6003 lines
3
4 regress@PE1> show ethernet-switching table summary
5 Total dynamic and static MAC addresses learned globally : 642000
6 Configured static MAC addresses learned globally : 0
7
8 regress@PE1> show mac-vrf forwarding mac-table summary
9 Total dynamic and static MAC addresses learned globally : 642000
10 Configured static MAC addresses learned globally : 0
11
12 regress@PE1>

```

Traffic flows are load-balanced across the LAG bundles and the LAG member interfaces as shown below

```

1 PE1 Seconds: 8 Time: 23:53:57
2
3 Interface Link Input packets (pps) Output packets (pps)
4
5 ae0 Up 430732227 (39467484) 426607625 (39090991)
6 ae1 Up 422504760 (38716208) 426628049 (39092631)
7 esi Up 0 (0) 0 (0)

```

```

 8 et-0/0/0 Up 170633946 (15628905) 170633785 (15628463)
 9 et-0/0/1 Up 170633695 (15629036) 170633820 (15629066)
10 et-0/0/2 Up 170656791 (15641087) 170656766 (15641091)
11 et-0/0/3 Up 170657143 (15641388) 170657268 (15641460)
12 et-0/0/4 Up 170656970 (15641588) 170657031 (15641683)
13 et-0/0/5 Down 0 (0) 0 (0)
14 et-0/0/6 Up 114219791 (10466300) 106662528 (9773701)
15 et-0/0/7 Up 108553610 (9946350) 106641383 (9771845)
16 et-0/0/8 Up 107267131 (9828675) 106646624 (9772262)
17 et-0/0/9 Up 100691695 (9226159) 106657090 (9773183)
18 et-0/0/10 Up 110934212 (10165928) 106662332 (9773648)
19 et-0/0/11 Up 104545101 (9579897) 106651718 (9772709)
20 et-0/0/12 Up 106957607 (9800959) 106662274 (9773644)
21 et-0/0/13 Up 100067840 (9169424) 106651725 (9772630)

```

1.3 Generating Scale Configuration

The Python Script is having three components:

- a Jinja File capturing the various configuration templates,
- a Params File capturing the various user variables
- the script uses both these input files and generates the required configurations and commit that in the router.

Note: The configs are generated as per the CE-bound interface schema.

1.3.1 Jinja Configuration Template

The template contains configurations for both interfaces which are part of the routing instances and routing instance configurations.

```

 1 # EVPN Mac-VRF Routing Instance Configuration
 2 # File Name: evpn_jinja.j2
 3 # Version: 1.0
 4 groups {{group_name}} {
 5     interfaces {
 6         {{ifd_name}} {
 7             flexible-vlan-tagging;
 8             encapsulation flexible-ethernet-services;
 9             {%- for unit_id, vlan_id in ifl_variables %}
10             unit {{unit_id}} {
11                 {%- if vlan_based_service %}
12                 vlan-id {{vlan_id}};
13                 {%- endif %}
14                 {%- if vlan_bundle_service %}
15                 vlan-id-list {{vlan_id}};
16                 {%- endif %}
17                 encapsulation vlan-bridge;
18             }
19             {%- endfor %}
20         }
21     }
22     routing-instances {
23         {%- for vrf_id, ifl_name, vlan_id in evpn_variables %}
24         METRO_MAC_VRF_{{vrf_id}} {
25             instance-type mac-vrf;
26             {%- if lo0_enabled %}
27             interface lo0.{{vrf_id}};
28             {%- endif %}
29             route-distinguisher {{router_id}}:{{vrf_id}};
30             vrf-target target:{{local_as_no}}:{{vrf_id}};
31             protocols {
32                 evpn {
33                     encapsulation mpls;
34                     no-control-word;
35                     {%- if vlan_based_service %}
36                     normalization;
37                     {%- endif %}

```

```
38     }
39     }
40     interface {{ifl_name}};
41     {%~ if vlan_based_service %}
42     service-type vlan-based;
43     vlans {
44         MVRF_VBASED_VLAN_{{vrf_id}} {
45             vlan-id {{vlan_id}};
46             interface {{ifl_name}};
47         }
48     }
49     {%~ endif %}
50     {%~ if vlan_bundle_service %}
51     service-type vlan-bundle;
52     vlans {
53         MVRF_VBUNDLE_VLAN_{{vrf_id}} {
54             interface {{ifl_name}};
55         }
56     }
57     {%~ endif %}
58 }
59 {%~ endfor %}
60 }
61 }
```

1.3.2 Configuration Parameters

““



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

HPE

