



DC – AI – Routing – Switching – Security – Wireless – Automation

ACX7100/ACX7509 Validation: EVPN-VPWS

An HPE Juniper Networking Techpost

Suneesh Babu

2022-11-05

HPE



Contents

1	EVPN VPWS Validation on ACX7000	2
1.1	Introduction	2
1.2	Metro EVPN-VPWS Topology	2
1.2.1	Base Configuration	3
1.2.2	EVPN-VPWS Routing-Instance Configuration	4
1.2.3	EVPN-VPWS CE Bound Interface Schema	5
1.3	EVPN-VPWS Verification	5
1.3.1	VLAN Unaware EVPN-VPWS Verification	6
1.3.2	VLAN-Aware EVPN-VPWS Verification	6
1.4	Generating Scale Configuration	7
1.4.1	Configuration Template	8
1.4.2	Configuration Parameters	9

1 EVPN VPWS Validation on ACX7000

Suneesh Babu - 11/05/2022

Junos EVPN-VPWS feature supports 8,000 instances with 4,000 VLAN-UnAware and 4,000 VLAN-Aware Service Types on ACX7000 Platforms.

1.1 Introduction

This is the second article in the ACX7k Metro Validation Series.

In this article, we validate the [EVPN-VPWS](#) feature and its scale on [ACX7100-32C](#) with 22.2R1 Junos-EVO image.

[RFC-8214](#) describes the VPWS support with [EVPN](#). EVPN-VPWS is a point-to-point ethernet service based on BGP MPLS connecting Customer Edge Devices (CEs) across a Provider Edge (PE) Network. The PEs of the network are connected over [MPLS](#) technology signalled via [LDP](#), [RSVP](#) or [SR-MPLS](#).

JUNOS supports EVPN-VPWS functionality with the “evpn-vpws” Instance Type.

In this test, we create 8,000 EVPN VPWS Instances on ACX7100-32C:

- 4,000 VLAN-Unaware Service Types
- 4,000 VLAN-Aware Service Types.

The same scale is tested on [ACX7100-48L](#) as well as on [ACX7509](#).

But the [ACX7024](#) Scale is not covered in this article (same features but different scale are expected on this platform).

Please note that despite sharing the same ACX moniker, the ACX7000 products are different products than ACX500/710/1000/1100/2100/2200/4000/5000/5400/6000. They are powered by different Packet Forwarding Engines (PFE), and support different feature sets and scales.

The Key Performance Indicators (KPI) tested are:

EVPN VPWS KPI	Scale
Number of VPWS instances	8,000
Number of VLAN-Unaware Service Types	4,000
Number of VLAN-Aware Service Types	4,000
Number of VLANs	12,000
Number of Interfaces	12,000

1.2 Metro EVPN-VPWS Topology


Test topology consists of three routers:

- an ACX7100-32C is PE1

- an ACX7100-48L is the PE2
- a [PTX10008](#) is P1

CEs are simulated using a traffic generator. PEs are connected to CEs using 4x 100G links and to the core using 8x 100G links, which are bundled in 2x LAGs each having four links.

The ACX7100-32C is the Device Under Test (DUT). The underlay transport used for testing is [SR-MPLS](#) with both [OSPF](#) and [ISIS](#) protocols individually. In this validation, we also covered LDP as the underlay transport. The CE-bound interface configurations are of SP-Style (see glossary).



1.2.1 Base Configuration

```

1 regress@PE1> show configuration protocols |display inheritance no-comments
2 bgp {
3   group IBGP {
4     type internal;
5     local-address 12.1.1.1;
6     family inet {
7       unicast;
8     }
9     family evpn {
10      signaling;
11    }
12    neighbor 12.1.1.3 {
13      export nhself;
14    }
15  }
16 }
17 mpls {
18   interface ae0.0;
19   interface ae1.0;
20 }
21 ospf {
22   source-packet-routing {
23     node-segment ipv4-index 101;
24     srgb start-label 45000 index-range 2000;
25   }
26   area 0.0.0.0 {
27     interface lo0.0 {
28       passive;
29     }
30     interface ae0.0 {
31       interface-type p2p;
32     }
33     interface ae1.0 {
34       interface-type p2p;
35     }
36   }
37 }
38
39 regress@PE1>

```

1.2.2 EVPN-VPWS Routing-Instance Configuration

VLAN-Unaware EVPN-VPWS routing-instance is configured as follows:

```

1  interfaces {
2      et-0/0/0 {
3          flexible-vlan-tagging;
4          encapsulation flexible-ethernet-services;
5          unit 1 {
6              encapsulation vlan-ccc;
7              vlan-id 1;
8              family ccc;
9          }
10     }
11 }
12 routing-instances {
13     METRO_EVPN_VPWS_1 {
14         instance-type evpn-vpws;
15         protocols {
16             evpn {
17                 interface et-0/0/0.1 {
18                     vpws-service-id {
19                         local 1001;
20                         remote 2001;
21                     }
22                 }
23                 flexible-cross-connect-vlan-unaware;
24                 group G1 {
25                     interface et-0/0/0.1;
26                     service-id {
27                         local 1001;
28                         remote 2001;
29                     }
30                 }
31             }
32         }
33         interface et-0/0/0.1;
34         route-distinguisher 12.1.1.1:1;
35         vrf-target target:65000:1;
36     }
37 }

```

VLAN-Aware EVPN-VPWS routing-instances with two VLANs are as follows:

```

1  interfaces {
2      et-0/0/2 {
3          flexible-vlan-tagging;
4          encapsulation flexible-ethernet-services;
5          unit 1 {
6              encapsulation vlan-ccc;
7              vlan-id 1;
8          }
9      }
10     et-0/0/0 {
11         flexible-vlan-tagging;
12         encapsulation flexible-ethernet-services;
13         unit 2001 {
14             encapsulation vlan-ccc;
15             vlan-id 2001;
16             family ccc;
17         }
18     }
19 }
20 routing-instances {
21     METRO_EVPN_VPWS_4001 {
22         instance-type evpn-vpws;
23         protocols {
24             evpn {
25                 interface et-0/0/2.1 {
26                     vpws-service-id {
27                         local 1001;
28                         remote 2001;
29                     }
30                 }
31                 interface et-0/0/0.2001 {
32                     vpws-service-id {
33                         local 1002;
34                         remote 2002;

```

```

35     }
36   }
37   flexible-cross-connect-vlan-aware;
38 }
39 }
40 interface et-0/0/2.1;
41 interface et-0/0/0.2001;
42 route-distinguisher 12.1.1.1:4001;
43 vrf-target target:65000:4001;
44 }
45 }

```

1.2.3 EVPN-VPWS CE Bound Interface Schema

The four CE-bound 100G interfaces are logically split across routing-instances as described in this chart:

PE1	PE2	Port	Service Type	VRF	VLAN Association	Traffic Load
et-0/0/0	et-0/0/48:0	P1	VLAN-Unaware	1-2000	1-2000	49.95%
et-0/0/1	et-0/0/48:1	P2	VLAN-Unaware	2001-4000	1-2000	49.95%
et-0/0/2	et-0/0/48:2	P3	VLAN-Aware	4001-6000	1-2000	99.9%
et-0/0/3	et-0/0/48:3	P4	VLAN-Aware	6001-8000	1-2000	99.9%
et-0/0/0	et-0/0/48:0	P1	VLAN-Aware	4001-6000	2001-4000	49.95%
et-0/0/1	et-0/0/48:1	P2	VLAN-Aware	6001-8000	2001-4000	49.95%

1.3 EVPN-VPWS Verification

The first step to verify the EVPN-VPWS service is to make sure that the PE devices are having BGP established with evpn-signalling. As shown below from PE1, BGP is in “established” state for the Peer PE2 (12.1.1.3) and bgp.evpn.0 table got populated with Type-1 Infra routes.

```

1 regress@PE1> show bgp summary
2 Threading mode: BGP I/O
3 Default eBGP mode: advertise - accept, receive - accept
4 Groups: 1 Peers: 1 Down peers: 0
5 Table Tot Paths Act Paths Suppressed History Damp State Pending
6 inet.0
7           35 1 0 0 0 0
8 inet6.0
9           0 0 0 0 0 0
10 bgp.evpn.0
11          12000 12000 0 0 0 0
12 inet6.3
13           0 0 0 0 0 0
14 Peer AS InPkt OutPkt OutQ Flaps Last Up/Dwn State|#Active/Received/Accepted/Damped...
15 12.1.1.3 65000 8011 8008 0 0 35 Establ
16   inet.0: 1/35/35/0
17   bgp.evpn.0: 12000/12000/12000/0
18   METRO_EVPN_VPWS_1.evpn.0: 1/1/1/0
19   METRO_EVPN_VPWS_2.evpn.0: 1/1/1/0
20   METRO_EVPN_VPWS_3.evpn.0: 1/1/1/0
21   ...
22   METRO_EVPN_VPWS_3998.evpn.0: 1/1/1/0
23   METRO_EVPN_VPWS_3999.evpn.0: 1/1/1/0
24   METRO_EVPN_VPWS_4000.evpn.0: 1/1/1/0
25   METRO_EVPN_VPWS_4001.evpn.0: 2/2/2/0

```

```

26 METRO_EVPN_VPWS_4002.evpn.0: 2/2/2/0
27 METRO_EVPN_VPWS_4003.evpn.0: 2/2/2/0
28 ...
29 METRO_EVPN_VPWS_7998.evpn.0: 2/2/2/0
30 METRO_EVPN_VPWS_7999.evpn.0: 2/2/2/0
31 METRO_EVPN_VPWS_8000.evpn.0: 2/2/2/0
32 __default_evpn__.evpn.0: 0/0/0/0
33
34 regress@PE1>

```

1.3.1 VLAN Unaware EVPN-VPWS Verification

As shown below, the interface et-0/0/0.1 is bound to EVPN-VPWS instance METRO_EVPN_VPWS_1 with a single VLAN with vlan-id 1.

```

1 regress@PE1> show evpn vpws-instance METRO_EVPN_VPWS_1
2 Instance: METRO_EVPN_VPWS_1, Instance type: EVPN VPWS FXC
3 Route Distinguisher: 12.1.1.1:1
4 Number of local interfaces: 1 (1 up)
5
6 Interface name ESI Mode Role Status Control-Word Flow-Label-Tx Flow-Label-Rx
7 et-0/0/0.1 00:00:00:00:00:00:00:00:00:00:00single-homed Primary Up No No No
8 Local SID: 1001 Advertised Label: 16
9 Remote SID: 2001
10 PE addr ESI Label Mode Role TS Status
11 12.1.1.3 00:00:00:00:00:00:00:00:00:00 16 single-homed Primary 2022-10-21 02:40:19.916
12 Resolved
13 Number of protect interfaces: 0
14 regress@PE1>

```

The routes of METRO_MAC_VRF_1 instance are shown below.

```

1 regress@PE1> show route table METRO_EVPN_VPWS_1.evpn.0
2
3 METRO_EVPN_VPWS_1.evpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
4 + = Active Route, - = Last Active, * = Both
5
6 1:12.1.1.1:1::0::1001/192 AD/EVI
7 * [EVPN/170] 2d 16:59:40
8 Indirect
9 1:12.1.1.3:1::0::2001/192 AD/EVI
10 * [BGP/170] 2d 16:55:47, localpref 100, from 12.1.1.3
11 AS path: I, validation-state: unverified
12 > to 15.1.1.2 via ae0.0, Push 45103
13 to 15.1.2.2 via ae1.0, Push 45103
14
15 regress@PE1>

```

1.3.2 VLAN-Aware EVPN-VPWS Verification

In VLAN-Aware EVPN-VPWS case, the entire VLAN information is bound to that instance.

```

1 regress@PE1> show evpn vpws-instance METRO_EVPN_VPWS_4001
2 Instance: METRO_EVPN_VPWS_4001, Instance type: EVPN VPWS FXC VLAN AWARE
3 Route Distinguisher: 12.1.1.1:4001
4 Number of local interfaces: 2 (2 up)
5
6 Interface name ESI Mode Role Status Control-Word Flow-Label-Tx Flow-Label-Rx
7 et-0/0/0.2001 00:00:00:00:00:00:00:00:00:00:00single-homed Primary Up No No No
8 Local SID: 1002 Advertised Label: 4016
9 Remote SID: 2002
10 PE addr ESI Label Mode Role TS Status
11 12.1.1.3 00:00:00:00:00:00:00:00:00:00 4016 single-homed Primary 2022-10-21
12 02:40:23.424 Resolved
13
14 Interface name ESI Mode Role Status Control-Word Flow-Label-Tx Flow-Label-Rx
15 et-0/0/2.1 00:00:00:00:00:00:00:00:00:00:00single-homed Primary Up No No No
16 Local SID: 1001 Advertised Label: 4016
17 Remote SID: 2001

```

```

17      PE addr ESI Label Mode Role TS Status
18      12.1.1.3 00:00:00:00:00:00:00:00:00 4016 single-homed Primary 2022-10-21
      02:40:23.424 Resolved
19      Number of protect interfaces: 0
20
21 regress@PE1>

```

The BGP route table of the instance includes routes belonging to VLANs of the aware instance.

```

1 regress@PE1> show route table METRO_EVPN_VPWS_4001.evpn.0
2
3 METRO_EVPN_VPWS_4001.evpn.0: 4 destinations, 4 routes (4 active, 0 holddown, 0 hidden)
4 + = Active Route, - = Last Active, * = Both
5
6 1:12.1.1.1:4001::0::1001/192 AD/EVI
7      *[EVPN/170] 2d 17:01:18
8      Indirect
9 1:12.1.1.1:4001::0::1002/192 AD/EVI
10     *[EVPN/170] 2d 17:01:25
11     Indirect
12 1:12.1.1.3:4001::0::2001/192 AD/EVI
13     *[BGP/170] 2d 16:57:30, localpref 100, from 12.1.1.3
14     AS path: I, validation-state: unverified
15     to 15.1.1.2 via ae0.0, Push 45103
16     > to 15.1.2.2 via ae1.0, Push 45103
17 1:12.1.1.3:4001::0::2002/192 AD/EVI
18     *[BGP/170] 2d 16:57:30, localpref 100, from 12.1.1.3
19     AS path: I, validation-state: unverified
20     to 15.1.1.2 via ae0.0, Push 45103
21     > to 15.1.2.2 via ae1.0, Push 45103
22
23 regress@PE1>

```

The following output captures the number of instances, vlan-unaware and vlan-aware in the DUT.

```

1 regress@PE1> show evpn vpws-instance |match "(1 up)" | count
2 Count: 4000 lines
3
4 regress@PE1> show evpn vpws-instance |match "(2 up)" | count
5 Count: 4000 lines
6
7 regress@PE1> show bgp summary |match "evpn.0" | count
8 Count: 8003 lines
9
10 regress@PE1>

```

Traffic flows are load-balanced across the LAG bundles and the LAG member interfaces as shown below

```

1 PE1 Seconds: 30 Time: 19:46:21
2
3 Interface Link Input packets (pps) Output packets (pps)
4
5 ae0 Up 6672538985109 (31797317) 6562622375572 (31273400)
6 ae1 Up 6452705368593 (30750384) 6562622460395 (31274253)
7 esi Up 0 (0) 0 (0)
8 et-0/0/0 Up 3281521334639 (15638860) 3281521039897 (15638591)
9 et-0/0/1 Up 3281521210490 (15638642) 3281521065394 (15638962)
10 et-0/0/2 Up 3281099910919 (15633867) 3281099930514 (15633920)
11 et-0/0/3 Up 3281099946314 (15633783) 3281099945857 (15633649)
12 et-0/0/4 Up 0 (0) 8460 (0)
13 et-0/0/5 Down 0 (0) 0 (0)
14 et-0/0/6 Up 1740727408250 (8295101) 1647217803561 (7849444)
15 et-0/0/7 Up 1659520685579 (7908298) 1634093396240 (7787043)
16 et-0/0/8 Up 1690694107451 (8056796) 1647217784947 (7849711)
17 et-0/0/9 Up 1581596783829 (7537122) 1634093390824 (7787202)
18 et-0/0/10 Up 1696433009095 (8084274) 1647217832273 (7849813)
19 et-0/0/11 Up 1617688474851 (7709175) 1634093403093 (7787259)
20 et-0/0/12 Up 1624252786691 (7740317) 1647217809682 (7849859)
21 et-0/0/13 Up 1514331097956 (7216618) 1634093415347 (7787322)

```

1.4 Generating Scale Configuration

The Python Script is having three components:

- a Jinja File capturing the various configuration templates,
- a Params File capturing the various user variables
- a script using the two input files above and generating the required configurations and committing them in the router.

Note: The configs are generated as per the CE-bound interface schema.

1.4.1 Configuration Template

The template contains configurations for both interfaces which are part of the routing instances and routing instance configurations.

```

1  # Routing Instance Configuration
2  # File Name: evpn_vpws_jinja.j2
3  # Version: 1.0
4  groups {{group_name}} {
5      interfaces {
6          {{ifd_name}} {
7              flexible-vlan-tagging;
8              encapsulation flexible-ethernet-services;
9              {%- for unit_id, vlan_id in ifl_variables %}
10             unit {{unit_id}} {
11                 {%- if vlan_unaware_service %}
12                 vlan-id {{vlan_id}};
13                 encapsulation vlan-ccc;
14                 family ccc;
15                 {%- endif %}
16                 {%- if vlan_aware_service %}
17                 encapsulation vlan-ccc;
18                 vlan-id {{vlan_id}};
19                 {%- endif %}
20             }
21             {%- endfor %}
22         }
23     }
24     routing-instances {
25         {%- for vrf_id, ifl_name, vlan_id in evpn_vpws_variables %}
26         METRO_EVPN_VPWS_{{vrf_id}} {
27             instance-type evpn-vpws;
28             interface {{ifl_name}};
29             route-distinguisher {{router_id}}:{{vrf_id}};
30             vrf-target target:{{local_as_no}}:{{vrf_id}};
31             protocols {
32                 evpn {
33                     interface {{ifl_name}} {
34                         vpws-service-id {
35                             local {{vpws_local_service_id}};
36                             remote {{vpws_remote_service_id}};
37                         }
38                     }
39                     {%- if vlan_unaware_service %}
40                     {%- if enable_fxc %}
41                     group G1 {
42                         interface {{ifl_name}};
43                         service-id {
44                             local {{vpws_local_service_id}};
45                             remote {{vpws_remote_service_id}};
46                         }
47                     }
48                     flexible-cross-connect-vlan-unaware;
49                     {%- endif %}
50                     {%- endif %}
51                     {%- if vlan_aware_service %}
52                     {%- if enable_fxc %}
53                     flexible-cross-connect-vlan-aware;
54                     {%- endif %}
55                     {%- endif %}
56                 }
57             }
58         }
59         {%- endfor %}
60     }
61 }
```

1.4.2 Configuration Parameters

““



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

HPE

