



DC – AI – Routing – Switching – Security – Wireless – Automation

IP/VPN provision and operation with Apstra Freeform

An HPE Juniper Networking Techpost

Elisabeth Rodrigues

2023-09-19

HPE



Contents

1	IP VPN Network Apstra Freeform	2
1.1	Introduction	2
1.2	Example description	2
1.3	Network design with the topology editor	2
1.4	Resource management	4
1.5	MPLS Network Config Templates	8
1.5.1	loopback.jinjaThis template configures the loopback IP as well as the router-id of all backbone devices :	9
1.5.2	MPLS-OSPF.jinja	9
1.5.3	ASN.jinja	11
1.5.4	Fullmesh-iBGP.jinja	11
1.5.5	Backbone_junos_configuration	12
1.6	IPVPN design and configuration	12
1.7	Operations and troubleshooting	14
1.8	Conclusion	15
1.9	Glossary	16
1.10	Acknowledgments	16

1 IP VPN Network Apstra Freeform

Elisabeth Rodrigues - 09/19/2023

Illustration of an IP/VPN MPLS network provisioned and operated with Apstra Freeform.

1.1 Introduction

Juniper Apstra is our specialized intent-based networking software. Juniper Apstra reference designs are DataCenter validated designs that provide comprehensive guidance from the initial setup (day 0) to ongoing operations (day 2). Our automation tool assists in the build, validation, deployment and monitoring of multivendor Datacenter fabrics.

In 2022, we introduced a new Apstra design called Freeform. With Apstra Freeform, network architects take charge of creating the topology and configuration templates. This design leverages notable features such as intent-based analytics, configuration validation, NOS management, and Time Voyager. Presently, Apstra Freeform is not compatible with multiple vendors but works seamlessly with Juniper devices supported by the Datacenter reference designs.

In this blog post, we will demonstrate the application of Apstra Freeform design using a real-world example outside the Datacenter domain: a small MPLS network with IPVPN service.

With this example, we'll observe how the utilization of Apstra's graph database along with resource management and templating can significantly enhance the standardization of configurations. This approach also proves beneficial for managing day 1 and day 2 operations across various networks and topologies.

Disclaimer: I am a network engineer, the templates provided in the document can be optimized.

1.2 Example description

This example utilizes Apstra release 4.1.2.

The automated network is a small MPLS backbone consisting of:


- PE devices completely managed by Apstra:
 - Device lifecycle
 - Complete configuration
 - Health and network monitoring
- CE devices not managed by Apstra
- Resources: IP addresses, ASN, RTs/RDs

Apstra is the Single Source of Truth. The MPLS backbone will use IPv4, OSPF, LDP and full mesh iBGP.

1.3 Network design with the topology editor

We will start the network with 4 PE devices and 3 CE devices.

For that, we create a Freeform Blueprint and then use the topology editor in Staged -> Physical -> Topology.






PE devices are Internal Systems and CE devices are External Systems.

In order to facilitate the config automation, we add tags to the devices and the links.

All PEs are tagged “backbone_device”

☐	Blue-CE-1	EXTERNAL	
☐	PE1	INTERNAL	backbone_device
☐	PE2	INTERNAL	backbone_device
☐	PE3	INTERNAL	backbone_device
☐	PE4	INTERNAL	backbone_device
☐	Red-CE-1	EXTERNAL	
☐	Red-CE-2	EXTERNAL	

All links are tagged “mpls_interface”

☐	Blue-CE-1<->PE3	external	
☐	P1<->PE4	internal	
☐	P2<->PE4	internal	
☐	PE3<->P1	internal	
☐	PE3<->P2	internal	
☐	Red-CE-1<->PE3	external	
☐	Red-CE-2<->PE4	external	

Several tags can be added to each device or link. This method is very useful to identify a group of objects and apply a specific configuration to it.

1.4 Resource management

The resources are the IP addresses, ASN and RT/RD.

In the Resources menu, we create the following pools:


- ASN pool from 65001 to 65099 that will be used to allocate ASN to CE devices.

ASN 65000 is used by the MPLS backbone, we don't need a pool for it - IP Pool for the loopbacks: 10.0.10.0/24 - IP pool for the links inside the MPLS backbone: 192.168.0.0/24 - IP pool for the links between the CE and PE devices: 172.16.0.0/24 - Integer pool that will be used to generate the RT/RDs for the VRFs

We allocate those pools to the blueprint in Staged -> Resource Management -> Allocation Groups.

In Staged -> Resource management, we organize the resources of our network and use Graph database queries to assign the resources to the devices.

First, we create a group called MyNetwork where we statically assign the backbone ASN 65000.



Root / MyNetwork

Group

Create

Details

Data	{}
Assignments	Not Assigned

Resources

Query: All 1-8 of 8

Page Size: 25

Name	Type	Value	Generated By	Allocated From	Assigned To	Actions
Backbone-ASN	ASN	65000	Manually created	Manually allocated	Not Assigned	 

From this group, we create a resource generator called Backbone-Links that will automatically generate a /31 network to each backbone link.

Name *

Backbone-Links

Container Type

Group

Scope *

1 `node('link', role="internal", name='target', tag=has_any(['mpls_interface']))`

Graph query that selects all the links with the tag "mpls_interface"

Type

IPv4

Allocation Group

Links

Name of the IP pool previously created

Subnet Prefix Length

31

We can see the result directly in the resource management menu and in the links tab:

Name	Type	Value	Generated By	Allocated From	Assigned To
Backbone-Links	IPv4	192.168.0.4/31	Backbone-Links	Links	PE3<->P2
Backbone-Links	IPv4	192.168.0.6/31	Backbone-Links	Links	P1<->PE4
Backbone-Links	IPv4	192.168.0.2/31	Backbone-Links	Links	P2<->PE4
Backbone-Links	IPv4	192.168.0.0/31	Backbone-Links	Links	PE3<->P1

Dashboard

Analytics

Staged

Uncommitted

Active

Time Voyager

Physical

Resource Management

Catalog

Tasks

Find by tags

Topology

Systems

Links

Aggregate Links

Query: All

1-7 of 7

Columns (12/14)

Page Size: 25

Filter selected by

☒ all

☐ selected only

☐ unselected only

					Endpoint 1				Endpoint 2			
	Name	Role	Tags	Speed	Name	Interface Name	IPv4 address	IPv6 address	Name	Interface Name	IPv4 address	IPv6 address
☐	Blue-CE-1->PE3	external		40G	Blue-CE-1		172.16.0.0/31	Not assigned	PE3	et-0/0/1	172.16.0.1/31	Not assigned
☐	P1<->PE4	internal		40G	PE1	et-0/0/49	192.168.0.6/31	Not assigned	PE4	et-0/0/28	192.168.0.7/31	Not assigned
☐	P2<->PE4	internal		40G	PE2	et-0/0/49	192.168.0.3/31	Not assigned	PE4	et-0/0/29	192.168.0.2/31	Not assigned
☐	PE3<->P1	internal		40G	PE3	et-0/0/28	192.168.0.0/31	Not assigned	PE1	et-0/0/48	192.168.0.1/31	Not assigned
☐	PE3<->P2	internal		40G	PE3	et-0/0/29	192.168.0.4/31	Not assigned	PE2	et-0/0/48	192.168.0.5/31	Not assigned
☐	Red-CE-1->PE3	external		40G	Red-CE-1		172.16.0.5/31	Not assigned	PE3	et-0/0/31	172.16.0.4/31	Not assigned
☐	Red-CE-2->PE4	external		40G	Red-CE-2		172.16.0.2/31	Not assigned	PE4	et-0/0/31	172.16.0.3/31	Not assigned

We do the same operation for the links between the CEs and the PEs:

Name *

PE-CE-Links

Container Type

Group

Scope *

1 `node('link', role='external', name='target')`

Graph query that selects all the links with the role "external"

Type

IPv4

Allocation Group

External-links

Name of the IP pool previously created

Subnet Prefix Length

31

We can see the result directly in the resource management menu and in the links tab:

Name ↕	Type ↕	Value ↕	Generated By	Allocated From	Assigned To
PE-CE-Links	IPv4	172.16.0.0/31	PE-CE-Links	External-links	Blue-CE-1↔PE3
PE-CE-Links	IPv4	172.16.0.2/31	PE-CE-Links	External-links	Red-CE-2↔PE4
PE-CE-Links	IPv4	172.16.0.4/31	PE-CE-Links	External-links	Red-CE-1↔PE3

Dashboard

N/A

Analytics

N/A

Staged

Uncommitted

Active

N/A

Time Voyager

Physical

Resource Management

Catalog

Tasks

Find by tags

Topology

Systems

Links

Aggregate Links

Query: All

1-7 of 7

Columns (12/14)

Page Size: 25

Filter selected by

☒ all

☐ selected only

☐ unselected only

					Endpoint 1				Endpoint 2			
☐	Name ↕	Role ↕	Tags	Speed ↕	Name ↕	Interface Name ↕	IPv4 address ↕	IPv6 address ↕	Name ↕	Interface Name ↕	IPv4 address ↕	IPv6 address ↕
☐	Blue-CE-1↔PE3	external		40G	Blue-CE-1		172.16.0.0/31	Not assigned	PE3	et-0/0/1	172.16.0.1/31	Not assigned
☐	P1↔PE4	internal	mpls_interface	40G	PE1	et-0/0/49	192.168.0.6/31	Not assigned	PE4	et-0/0/28	192.168.0.7/31	Not assigned
☐	P2↔PE4	internal	mpls_interface	40G	PE2	et-0/0/49	192.168.0.3/31	Not assigned	PE4	et-0/0/29	192.168.0.2/31	Not assigned
☐	PE3↔P1	internal	mpls_interface	40G	PE3	et-0/0/28	192.168.0.0/31	Not assigned	PE1	et-0/0/48	192.168.0.1/31	Not assigned
☐	PE3↔P2	internal	mpls_interface	40G	PE3	et-0/0/29	192.168.0.4/31	Not assigned	PE2	et-0/0/48	192.168.0.5/31	Not assigned
☐	Red-CE-1↔PE3	external		40G	Red-CE-1		172.16.0.5/31	Not assigned	PE3	et-0/0/31	172.16.0.4/31	Not assigned
☐	Red-CE-2↔PE4	external		40G	Red-CE-2		172.16.0.2/31	Not assigned	PE4	et-0/0/31	172.16.0.3/31	Not assigned

For better clarity in the web UI, we create a group generator for the PEs and another one for the CEs:

Group Generator Name *

Backbone_devices

Parent

MyNetwork

Scope *

1 `node('system', system_type='internal', name='target', tag=has_any(['backbone_device']))`

Group Generator Name *

Parent

MyNetwork

Scope *

1 `node('system', system_type='external', name='target')` 

Inside the backbone devices group, we generate a loopback IP:

Name *

Container Type

Group Generator

Group Generator Scope

```
node('system', system_type='internal', name='target', tag=has_any(['backbone_device']))
```

 Parent group generator's scope will be used for this resource generator

Type

IPv4

Allocation Group

Subnet Prefix Length

Inside the external devices group, we generate an ASN:

Name *

Container Type

Group Generator

Group Generator Scope

```
node('system', system_type='external', name='target')
```

 Parent group generator's scope will be used for this resource generator

Type


ASN

Allocation Group

All the generated resources can be monitored in the Resource management menu but also in the Device Context of each device. We will use the Device Context to access the resources from the config templates.

Here is an example for PE4 :



The screenshot shows the Apstra UI for a device named 'pe4'. The 'Device Context' section is highlighted with a red box. Below it, the 'Device Context' JSON output is shown, with the 'resources' field highlighted by a red box.

```

{
  "all_resources": { ... },
  "chassis_config": { ... },
  "interfaces": { ... },
  "resources": { ... },
  "system_tags": { ... }
}

```

The 'resources' field contains the following data:

```

{
  "aos_version": "4.1.2",
  "configured_system_type": "internal",
  "deploy_mode": "deploy",
  "hostname": "pe4",
  "id": "uJY7VYR-Eb208x5DrUU",
  "interface_resources": {},
  "management_ip": null,
  "model": "Juniper_QFX5200-32C.*",
  "name": "PE4",
  "os_family": "Junos",
  "property_sets": {},
  "reference_architecture": "freeform",
  "routing_instance_supported": true,
  "system_type": "internal"
}

```

With all resources now generated, we can proceed to generate the configurations for each individual device.

1.5 MPLS Network Config Templates

Our objective is to develop dynamic configuration templates using jinja, which will automatically generate the appropriate configuration file whenever a new device is added to the network.

Let's create the following templates:

- "loopback.jinja"
- "MPLS-OSPF.jinja"

- “ASN.jinja”
- “Fullmesh-iBGP.jinja”
- “Backbone_junos_configuration”

The functions used in those templates to get the resources are documented in the Jinja function reference page provided with the Apstra instance.

Name *

Backbone_junos_configuration.jinja

Config Preview

Device Context

? Jinja function reference

1.5.1 loopback.jinja This template configures the loopback IP as well as the router-id of all backbone devices :

```

1  {% set loopback_ipv4 = function.get_resource_value(resources, 'Loopback', 'MyNetwork', '
    Backbone_devices') %}
2  interfaces {
3      lo0 {
4          unit 0 {
5              family inet {
6                  address {{loopback_ipv4}};
7              }
8          }
9      }
10 }
11 {% set router_id = loopback_ipv4|to_ip %}
12 routing-options {
13     replace: router-id {{router_id}};
14 }

```

Configuration rendering on PE3:

```

1  interfaces {
2      lo0 {
3          unit 0 {
4              family inet {
5                  address 10.0.10.3/32;
6              }
7          }
8      }
9  }
10 routing-options {
11     replace: router-id 10.0.10.3;
12 }

```

1.5.2 MPLS-OSPF.jinja

This template configures LDP and OSPF on all backbone interfaces as well as the loopback interface:

```

1  protocols {
2      replace: ldp {
3          interface lo0.0;
4      }
5      replace: ospf {
6          area 0.0.0.0 {
7              interface lo0.0 {
8                  passive;
9              }
10         }
11     }

```

```

12 }
13
14 {% for interface_name,interface_dict in interfaces.items() %}
15 {% if "mpls_interface" in interface_dict.link_tags%}
16 interfaces {
17     {{interface_name}} {
18         unit 0 {
19             family mpls;
20         }
21     }
22 }
23 protocols {
24     ldp {
25         interface {{interface_name}}.0;
26     }
27     mpls {
28         interface {{interface_name}}.0;
29     }
30     ospf {
31         area 0.0.0.0 {
32             interface {{interface_name}}.0;
33         }
34     }
35 }
36 {% endif %}
37 {% endfor %}

```

Configuration rendering on PE3:

```

1 protocols {
2     replace: ldp {
3         interface lo0.0;
4     }
5     replace: ospf {
6         area 0.0.0.0 {
7             interface lo0.0 {
8                 passive;
9             }
10        }
11    }
12 }
13 interfaces {
14     et-0/0/28 {
15         unit 0 {
16             family mpls;
17         }
18     }
19 }
20 protocols {
21     ldp {
22         interface et-0/0/28.0;
23     }
24     mpls {
25         interface et-0/0/28.0;
26     }
27     ospf {
28         area 0.0.0.0 {
29             interface et-0/0/28.0;
30         }
31     }
32 }
33 interfaces {
34     et-0/0/29 {
35         unit 0 {
36             family mpls;
37         }
38     }
39 }
40 protocols {
41     ldp {
42         interface et-0/0/29.0;
43     }
44     mpls {
45         interface et-0/0/29.0;
46     }
47     ospf {
48         area 0.0.0.0 {
49             interface et-0/0/29.0;
50         }
51     }

```

```
52 }
```

1.5.3 ASN.jinja

This template configures the ASN on all backbone devices:

```
1 {% set asn = function.get_resource_value(resources, 'Backbone-ASN', 'MyNetwork') %}
2
3 routing-options {
4     replace: autonomous-system {{asn}};
5 }
```

Configuration rendering on PE3:

```
1 routing-options {
2     replace: autonomous-system 65000;
3 }
```

1.5.4 Fullmesh-iBGP.jinja

This template create a full mesh iBGP peering between all PE devices:

```
1 {% set local_IP = function.get_resource_value(resources, 'Loopback', 'MyNetwork', '
   Backbone_devices') %}
2 {% set local_IP_no_mask = local_IP|to_ip%}
3 protocols {
4     bgp {
5         group full_mesh {
6             type internal;
7             local-address {{local_IP_no_mask}};
8             family inet-vpn {
9                 unicast;
10            }
11        }
12    }
13 }
14 protocols {
15     bgp {
16         group full_mesh {
17             {% for system, system_dict in all_resources.items() %}
18             {% for loopback in function.get_all_resources(all_resources[system], 'Loopback', '
               MyNetwork', 'Backbone_devices') %}
19             {% if loopback['value'] != local_IP %}
20             {% set IP = loopback['value']|to_ip %}
21             neighbor {{IP}};
22             {% endif %}
23             {% endfor %}
24             {% endfor %}
25         }
26     }
27 }
```

Configuration rendering on PE3:

```
1 protocols {
2     bgp {
3         group full_mesh {
4             type internal;
5             local-address 10.0.10.3;
6             family inet-vpn {
7                 unicast;
8             }
9         }
10    }
11 }
12 protocols {
13     bgp {
14         group full_mesh {
15             neighbor 10.0.10.0;
16             neighbor 10.0.10.2;
```

```

17     neighbor 10.0.10.1;
18   }
19 }
20 }

```

1.5.5 Backbone_junos_configuration

This template includes all templates including the initial template provided by default with the Apstra instance.

This template will be assigned to all devices.

```

1  {# junos_system.jinja handles the system hostname #}
2  {% include "junos_system.jinja" %}
3
4  {# junos_chassis.jinja handles chassis options, such as fpc config for
5   channelized port break-outs on certain device platforms. This also handles
6   aggregate-devices ethernet device-count for port-channel (aeX) interfaces. #}
7  {% include "junos_chassis.jinja" %}
8
9  {# junos_interfaces.jinja handles front-panel interface configuration, including
10   interface description, ipv4/ipv6 address assignment, and physical link properties
11   derived from device profiles. #}
12  {% include "junos_interfaces.jinja" %}
13
14  {# junos_protocols.jinja initiates LLDP collection on all ports for telemetry
15   purposes #}
16  {% include "junos_protocols.jinja" %}
17  {% include "loopback.jinja" %}
18  {% include "ASN.jinja" %}
19  {% include "MPLS-OSPF.jinja" %}
20  {% include "Fullmesh-iBGP.jinja" %}

```

1.6 IPVPN design and configuration

This network provides IPVPN services. Let's design our Freeform Blueprint to provision IPVPNs.

In the resource management menu, we create a group for each IPVPN : Blue_VRF and Red_VRF. Each VRF needs an RT, an RD, a loopback IP and PE-CE interfaces. We'll generate the RT/RD with the RT_RD integer previously created and we'll generate the loopback IP with a resource generator.

The screenshot displays the Apstra Freeform Resource Management interface. On the left, a tree view shows the network hierarchy, with 'VRFs' expanded and 'Blue_VRF (Blue-CE-1, PE3)' selected. The main panel shows the 'Details' for the selected VRF, including a 'Data' section with 'group_type: vrf' and an 'Assignments' section listing 'Blue-CE-1' and 'PE3'. Below this, the 'Resources' section shows a table of resources assigned to the VRF.

Name	Type	Value	Generated By	Allocated From	Assigned To	Actions
RT_RD	Integer	1	Manually created	RT-RD	Not Assigned	[Edit] [Delete]
VRF_LB	IPv4	10.0.10.5/32	VRF_LB	Loopback	PE3	[Edit] [Delete]

Here is the jinja template to configure the VRFs:

```

1  {% set all_vrf = function.get_resource(resources, 'VRFs', 'MyNetwork') %}
2  {%- if all_vrf|length -%}
3      {% set loopback_ipv4 = function.get_resource_value(resources, 'Loopback', 'MyNetwork', '
        Backbone_devices' ) %}
4      {% set loopback_no_mask = loopback_ipv4|to_ip %}
5      {% set asn = function.get_resource_value(resources, 'Backbone-ASN', 'MyNetwork' ) %}
6      {%- for get_vrfs in all_vrf['groups'] -%}
7          {% set ns = namespace() %}
8          {% set ns.name = "" %}
9          {%- for vrf_name in get_vrfs['label'] -%}
10             {% set ns.name = ns.name + vrf_name %}
11             {%- endfor -%}
12             {% set RT_RD = function.get_resource_value(resources, 'RT_RD', 'MyNetwork', 'VRFs', ns.name) %}
13             {% set VRF_loopback = function.get_resource_value(resources, 'VRF_LB', 'MyNetwork', 'VRFs',
                ns.name) %}
14         interfaces {
15             lo0 {
16                 unit {{RT_RD}} {
17                     family inet {
18                         address {{VRF_loopback}};
19                     }
20                 }
21             }
22         }
23         routing-instances {{ns.name}} {
24             instance-type vrf;
25             interface lo0.{{RT_RD}};
26             route-distinguisher {{loopback_no_mask}}:{{RT_RD}};
27             vrf-target target:{{asn}}:{{RT_RD}};
28             vrf-table-label;
29             {% set ALL_VRF_info = function.get_resource(resources, ns.name, 'MyNetwork', 'VRFs') %}
30             {%- for vrf_member in ALL_VRF_info['assigned_to'] -%}
31                 {%- for interface_name, iface in interfaces.iteritems() -%}
32                     {%- if iface.get('neighbor_interfaces') -%}
33                         {%- for nb in iface.get('neighbor_interfaces') -%}
34                             {%- if (nb['system_id'] == vrf_member) and (nb['link_role'] == "external") -%}
35                                 interface {{ interface_name }}.0;
36                                 protocols {
37                                     bgp {
38                                         group CE {
39                                             {% set peer_asn = function.get_resource_value(all_resources[vrf_member], 'ASN
                                                ', 'MyNetwork', 'External_Devices') %}
40                                             peer-as {{peer_asn}};
41                                             neighbor {{nb['ipv4_address']}};
42                                         }
43                                     }
44                                 }
45                             {% endif -%}
46                         {%- endfor -%}
47                     {%- endif -%}
48                 {%- endfor -%}
49             {% endfor %}
50         }
51     {% endfor %}
52 {%- endif -%}

```

Here is the rendered configuration for Blue_VRF on PE3:

```

1  interfaces {
2      lo0 {
3          unit 1 {
4              family inet {
5                  address 10.0.10.5/32;
6              }
7          }
8      }
9  }
10 routing-instances Blue_VRF {
11     instance-type vrf;
12     interface lo0.1;
13     route-distinguisher 10.0.10.3:1;
14     vrf-target target:65000:1;
15     vrf-table-label;
16     interface et-0/0/1.0;
17     protocols {
18         bgp {
19             group CE {
20                 peer-as 65003;
21                 neighbor 172.16.0.0;

```

```


22     }
23   }
24 }
25 }

```


1.7 Operations and troubleshooting

By default, Freeform provides many monitoring features. For example, Apstra checks the status of the network against the intent described in the Freeform blueprint: configuration files, interfaces state, cabling, hostname...


Here is the main dashboard:



In the Analytics dashboard, Apstra monitors much more information: health of the devices (CPU, memory, temperature, power supplies, fans...).




All interface counters are monitored and stored allowing the administrator the observation of network's bandwidth and configuring an anomaly threshold:



It is also easy to monitor other states like BGP peerings, optics.

In this example, we monitor BGP peerings inside RED_VRF:



1.8 Conclusion

Freeform proves to be a robust and powerful automation tool that helps you configure, operate and monitor any network composed of Juniper supported devices.

Apstra Freeform offers numerous other interesting features beyond what has been presented in this blog-post:

- device management with ZTP, inventory and NOS upgrade,
- time voyager that allows to rollback the network to any saved state,

- more analytics and Junos schema driven telemetry
- use of property sets to enrich jinja templates
- RBAC
- logging

1.9 Glossary

- ASN: Autonomous System Number
- BGP: Border Gateway Protocol
- ESI: Ethernet Segment Identifier
- EVPN: Ethernet Virtual Private Network
- MPLS: MultiProtocol Label Switching
- NOS: Network Operating System
- RBAC: Role Based Access Control
- RD: Route Distinguisher
- RT: Route Target
- ZTP: Zero Touch Provisioning

1.10 Acknowledgments

I would like to thank Andy Ford for reviewing this article.



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

HPE

