



DC – AI – Routing – Switching – Security – Wireless – Automation

Implementing RBAC for Juniper Apstra Using ClearPass TACACS+ Server

An HPE Juniper Networking Techpost

Victor Ganjian

2026-03-23

HPE



Contents

1	Implementing RBAC for Juniper Apstra Using ClearPass TACACS+ Server	2
1.1	Introduction	2
1.2	Apstra	2
1.3	Roles	2
1.4	Role Mappings	2
1.5	Providers	3
1.6	ClearPass	4
1.7	Configuration	4
1.7.1	Network - Add Device	4
1.7.2	Identity	4
1.7.3	Enforcement	6
1.7.4	Service	9
1.8	Verification	11
1.9	Apstra Login	11
1.9.1	Administrator	11
1.9.2	Operator	11
1.9.3	Log File	12
1.10	ClearPass Monitoring	12
1.11	Useful links	13
1.12	Glossary	14

1 Implementing RBAC for Juniper Apstra Using ClearPass TACACS+ Server

Victor Ganjian - 03/23/2026

How to integrate Juniper Apstra with Aruba ClearPass using TACACS+ to centralize authentication and implement role-based access control (RBAC)? This article details the configuration of both systems, including user roles, policies, and enforcement mechanisms, and concludes with verification steps to validate correct authorization behavior.

1.1 Introduction

This document outlines the steps to configure HPE Juniper Apstra (version 6.0.0) to authenticate user logins against an Aruba ClearPass Policy Manager (CPPM) server (version 6.12) using the TACACS+ protocol. This integration allows for centralized user management, enabling role-based access control (RBAC) within Apstra based on group membership defined in ClearPass.

As a Proof of Concept (POC), this example involves two user accounts that are defined on the CPPM sever. The first user is classified as an 'administrator' with full access to Apstra, and the second user is considered an 'operator' with read-only access.

Once configured, Apstra sends authentication and authorization requests to ClearPass, which returns the required 'aos-group' attribute. This returned attribute maps the user to a specific Apstra role which determines the user's authorization level.

1.2 Apstra

The Apstra is the TACACS+ client, and management user logins are authenticated against the TACACS+ authentication server, in this case the ClearPass server. Once authenticated, TACACS+ authorization takes place where the server returns attributes which map to a "Role" in Apstra.

1.3 Roles

In the Apstra GUI, navigate to Platform -> User Management -> Roles. The Apstra contains several pre-defined roles. In addition, custom Roles can be defined. In this example, the pre-defined 'administrator' and 'viewer' roles are used.

1.4 Role Mappings

The TACACS+ server is configured to return a group name (i.e. the 'aos-group' attribute, more details later in the ClearPass -> Configuration -> Enforcement section below) to the Apstra client which corresponds to a "Provider Group" defined on the Apstra which maps to a "Role". To define the "Provider Group" to "Role" mappings, navigate to External Systems -> Providers. Then click the "Provider Role Mapping" tab.

In this example, there are 2 unique groups that are returned by the TACACS+ server that are mapped to the 2 pre-defined roles on Apstra. Create the following user to group mappings:

Apstra Role	Provider Group
administrator	network-admins
viewer	network-operators

1.5 Providers

The next step in the Apstra GUI is to define the connection to the TACACS+ server. Navigate to the External Systems → Providers and click “Create Provider.”

Under “Common Parameters”, set the Name, select “TACACS+” as the “Vendor”, and make the service “Active”.

In the “Connection Settings” section, set the TCP port to 49 and the IP address of the ClearPass server.

This is an active provider, editing this provider will cause all the users to be logged out.

Common Parameters

Name *

Clearpass-TACACS-37-36

Vendor *

☐ LDAP ☐ Active Directory ☒ TACACS+ ☐ RADIUS

Active?

☒ ON

Connection Settings

Port *

49

Hostname FQDN IP(s) *

10.161.37.36

[Add an address](#)

Provider-specific Parameters

Shared Key *

••••••••

Auth Mode *

☒ ASCII ☐ PAP ☐ CHAP

[Advanced Config](#)

☐ Create Another?

Create

Finally, under “Provider-specific Parameters”, set the shared secret. This must match the shared secret configured on the TACACS+ server.

Click “Create” when finished.

After defining the TACACS+ server, note that local logins remain active, you will not be locked out of the Apstra server.

1.6 ClearPass

Aruba ClearPass is an authentication server that supports various protocols including RADIUS and TACACS+. The steps below assume that the ClearPass server has been installed and is reachable from Apstra.

For more information about installing CPPM, start at the [HPE Networking support site](#), and then search for ClearPass to download the software, view documentation, and request a demo license. If you do not have access to the support site, please contact your local HPE account team or reseller for further assistance.

1.7 Configuration

Below is an overview of the various ClearPass objects to be configured and their relationship with one another. Please reference this diagram as you step through the configuration in the sections below.

1.7.1 Network - Add Device

Under Configuration -> Network -> Devices click “Add”. In the “Add Device” popup window, define the TACACS+ client information including the “Name”, IP address, and shared secret that matches the value set on the Apstra. Set the “Vendor Name” to “Juniper” although this should not make any difference if not set.

Add Device					
Device	SNMP Read Settings	SNMP Write Settings	CLI Settings	OnConnect Enforcement	Attributes
Name:	Apstra-RT1				
IP or Subnet Address:	10.161.32.2 (e.g., 192.168.1.10 or 192.168.1.1/24 or 2001:db8:a0b:12f0::1 or 2001:db8:a0b:12f0::1/64)				
Description:					
RADIUS Shared Secret:		Verify:			
TACACS+ Shared Secret:	••••••••••	Verify:	••••••••••		
Vendor Name:	Juniper				
Enable RADIUS Dynamic Authorization:	☒ Port: 3799				
Enable RadSec:	☐				

Add Cancel


1.7.2 Identity

Roles

Define 2 roles that correspond to the two categories of users, ‘administrators’ and ‘operators’. Note that these roles are specific to ClearPass and separate from the roles that are defined, or pre-defined, in Apstra.

In ClearPass, as part of the authentication process, the user is mapped to a ‘Role’ which determines which Enforcement Profile to apply. The profile, defined in the next section below, determines the authorization attributes returned to the TACACS+ Client.

Navigate to Configuration → Identity → Roles. Click “Add” and set the name of the role (ex. Role-Network-Admin) and click “Save”.



The screenshot shows a web form titled "Add New Role". It has two main input areas: "Name:" and "Description:". The "Name:" field contains the text "Role-Network-Admin". The "Description:" field is empty. At the bottom right of the form are two buttons: "Save" (blue) and "Cancel" (red).

Repeat for the ‘operators’ role (ex. Role-Network-Operator).

Users

In this example, authentication of the users is performed using the CPPM’s local database. There are 2 user accounts, each of which is mapped to a unique ClearPass role.

Login User Name	ClearPass Role
user-admin	Role-Network-Admin
user-oper	Role-Network-Operator

To define the local user accounts, navigate to Configuration → Identity → Local Users and click “Add”.

Set the “User ID” (i.e. the username used for login), “Name”, “Password”, and the “Role” to match the previously defined corresponding ClearPass role.

Add Local User

User ID:	user-admin
Name:	Network Admin
Password:	
Verify Password:	
Enable User:	☒ (Check to enable user)
Change Password:	☐ (Check to force change password on next TACACS+ login)
Role:	Role-Network-Admin

Attributes	
Attribute	Value
1.	Click to add...

Add

Cancel

Click on the “Add” button when finished. Then repeat the steps for the user ‘user-oper’.

1.7.3 Enforcement

Create Custom Service Dictionary - ‘aos-exec’

The ClearPass server is preconfigured with many different vendor service dictionaries, however the service dictionary required for Apstra is not included. Therefore, before creating the Enforcement Profiles and Policy, it is required to create the Apstra service dictionary and its attributes.

The Apstra TACACS+ client requests the ‘aos-exec’ service during the authorization phase when communicating with the TACACS+ server. The service contains the ‘aos-group’ attribute .which matches the “Provider Group” value configured in Apstra (see the Apstra → Role Mappings section above).

To create a dictionary for Apstra, navigate to Administration → Dictionaries → TACACS+ Services. Select the checkbox for the existing ‘shell’ service and then click “Export”. Save the XML service definition file to your local device.

Open the XML file in a text editor and edit/replace the text with the new service dictionary entry called “aos-exec” containing two attributes, one for privilege level and one for the ‘aos-group’ which also includes the allowed values:

```

1 <?xml version="1.0" encoding="UTF-8" standalone="yes"?>
2 <TipsContents xmlns="http://www.avendasys.com/tipsapiDefs/1.0">
3   <TipsHeader exportTime="Fri Nov 07 14:15:54 PST 2025" version="6.12"/>
4   <TacacsServiceDictionaries>
5     <TacacsServiceDictionary dispName="aos-exec" name="aos-exec">
6       <ServiceAttribute dataType="Unsigned32" dispName="Privilege level" name="priv-lvl"/>
7       <ServiceAttribute allowedValuesCsv="network-admins,network-operators" dataType="String"
        dispName="aos-group" name="aos-group"/>

```

```

8     </TacacsServiceDictionary>
9     </TacacsServiceDictionaries>
10    </TipsContents>

```

Save the changes, and then “Import” the file. Click on the new “aos-exec” service dictionary to view the attributes. The ‘aos-group’ attribute is listed with the allowed values

TACACS+ Service Dictionary Attributes				
Display Name:	aos-exec			
#	Name	Display Name	Type	Allowed Values
1.	aos-group	aos-group	String	network-admins, network-operators
2.	priv-lvl	Privilege level	Unsigned32	-

Enforcement Profiles

The next step is to create Enforcement Profiles for the two categories of users, ‘administrators’ and ‘operators’. This is where the returned attributes are defined including the mandatory ‘aos-group’ which determines the users’ permissions when working in the Apstra GUI.

Navigate to Configuration → Enforcement → Profiles, then click “Add” at the top right of the window.

Set the profile “Template” type to “TACACS+ Based Enforcement” and set a “Name”:

Configuration » Enforcement » Profiles » Add Enforcement Profile

Enforcement Profiles

Profile Services Summary

Template:	TACACS+ Based Enforcement
Name:	Profile-Apstra-Admins
Description:	
Type:	TACACS+
Action:	☒ Accept ☐ Reject ☐ Drop
Device Group List:	Ren

Click the “Services” tab.

First, set the “Privilege Level” to “15” and then under “Selected Services” select the newly created service ‘aos-exec’. At the bottom of the window set the “Service Attributes”. For example, for the users classified as ‘administrators’, select “Type” of “aos-exec”, select “Name” “aos-group” and the “Value” “network-admins”. Add another attribute for a “priv-lvl” of “15”.

Enforcement Profiles

Profile Services Summary

Privilege Level: 15 (Privileged)

Selected Services: aos-exec Remove

Authorize Attribute Status: ADD

Custom Services: To add new TACACS+ services / attributes, upload the modified dictionary xml - [Update TACACS+ Services Dictionary](#)

Service Attributes				
	Type	Name	=	Value
1.	aos-exec	aos-group	=	network-admins
2.	aos-exec	priv-lvl	=	15

Click “Save” when done.

Then repeat the steps above to create an Enforcement Profile for the users classified as ‘operators’ that returns the group ‘network-operators’ and a privilege level of ‘1’.

Enforcement Policy

The Enforcement Policy determines which Enforcement Profile to use based on the user’s ClearPass Role.

Under Configuration → Enforcement → Policies, click “Add” at the top right of the window.

Set the “Name” and then under “Enforcement Type” click “TACACS+”.

The “Default Profile” specifies the Enforcement Profile to use if none of the policy’s rules match. These rules are defined on the next tab. In this case, if there is no match, the user should have ‘operator’ level read-only access, so set the value to “Profile-Apstra-Operators”.

Configuration » Enforcement » Policies » Add

Enforcement Policies

Enforcement Rules Summary

Name: Policy-Apstra-TACACS-Logins

Description:

Enforcement Type: ☐ RADIUS ☒ TACACS+ ☐ WEBAUTH (SN)

Default Profile: Profile-Apstra-Operators View Details

Click the “Rules” tab. This is where the ClearPass server is directed to the appropriate Enforcement Profile based on the user’s ClearPass Role.

Click “Add Rule” and then define the rule conditions for the ‘administrator’ level users.

Set the “Type” to “Tips”, “Name” to “Role”, “Operator” to “EQUALS”, and “Value” to the “Role-Network-Admin” ClearPass role defined previously. Then under “Profile Names:”, select the corresponding Enforcement Profile “Profile-Apstra-Admins”.

Rules Editor

Conditions

Match ALL of the following conditions:

	Type	Name	Operator	Value
1.	Tips	Role	EQUALS	Role-Network-Admin
2.	Click to add...			

Enforcement Profiles

Profile Names:

Move Up ↑
Move Down ↓
Remove

--Select to Add--

Save **Cancel**

Click “Save” when done.

Next, click “Add Rule” again, and add a similar rule for the users classified as ‘operators’.

When finished click “Save”.

Verify the configuration by selecting it and viewing the “Summary”. The policy contains 2 rules to direct ClearPass to the appropriate Enforcement Profile based on the user’s ClearPass Role:

Enforcement Policies - Policy-Apstra-TACACS-Logins

Summary **Enforcement** **Rules**

Enforcement:

Name:	Policy-Apstra-TACACS-Logins
Description:	
Enforcement Type:	TACACS+
Default Profile:	Profile-Apstra-Operators

Rules:

Rules Evaluation Algorithm:	First applicable
-----------------------------	------------------

Conditions	Actions
1. (Tips:Role EQUALS Role-Network-Admin)	Profile-Apstra-Admins
2. (Tips:Role EQUALS Role-Network-Operator)	Profile-Apstra-Operators

1.7.4 Service

Overview

The ClearPass server supports multiple authentication methods, or services, including RADIUS, TACACS+, 802.1x, Web-based authentication, and MAC address authentication. Many of these services are pre-configured on the server.

The services defined determined how the server handles incoming authentication requests. Each service definition includes the authentication type, optional match criteria based on the information contained in the client request, the authentication methods and sources to use, and the Enforcement Policy to apply.

Create Service

In this example, a new TACACS+ service is defined. The service definition instructs the ClearPass server to use the local database for authentication, and to use the previously configured Enforcement Policy.

Navigate to Configuration → Services, and click “Add”.

On the “Service” tab, set the “Type” to “TACACS+ Enforcement” and the “Name” (i.e. Service-Apstra-Login). In this case there are no matching conditions.

Click the “Authentication” tab. Then under “Authentication Sources”, select “[Local User Repository][Local SQL DB]” as the users are authenticated against the local user database.

Click the “Enforcement” tab and under “Enforcement Policy”, select the previously defined policy (i.e. Policy-Apstra-TACACS-Logins).

Services - Service-TACACS-Apstra

Summary
Service
Authentication
Roles
Enforcement

Service:

Name:	Service-TACACS-Apstra
Description:	
Type:	TACACS+ Enforcement
Status:	Enabled
Monitor Mode:	Disabled
More Options:	-

Service Rule

Match ANY of the following conditions:

Type	Name	Op
------	------	----

Authentication:

Authentication Sources:	[Local User Repository] [Local SQL DB]
Strip Username Rules:	-

Roles:

Role Mapping Policy:	-
----------------------	---

Enforcement:

Use Cached Results:	Disabled
Enforcement Policy:	Policy-Apstra-TACACS-Logins

When finished click “Save” at the bottom right of the window. Below is a summary of the configuration:

Change Order

The services are evaluated in the order that they are displayed in the GUI. In this case, the newly configured TACACS+ service is moved near the top of the list to ensure that it is evaluated, and matched, before other pre-defined TACACS+ services.

Click the “Reorder” button and then follow the instructions in the GUI to move the new service near the top of the list:

Filter: Name contains					Go	Clear Filter	Show 20 records	
#	Order	Name	Type	Template	Hit Count	Status		
1.	☐ 1	[Policy Manager Admin Network Login Service]	TACACS+	TACACS+ Enforcement	-	✗		
2.	☐ 2	Service-Apstra-Login	TACACS+	TACACS+ Enforcement	-	✓		
3.	☐ 3	[AirGroup Authorization Service]	RADIUS	RADIUS Enforcement (Generic)	-	✓		
4.	☐ 4	[Aruba Device Access Service]	TACACS+	TACACS+ Enforcement	-	✓		
5.	☐ 5	[Guest Operator Logins]	Application	Aruba Application Authentication	-	✓		
6.	☐ 6	[Insight Operator Logins]	Application	Aruba Application Authentication	-	✓		
7.	☐ 7	[Device Registration Disconnect]	WEBAUTH	Web-based Authentication	-	✓		

Showing 1-7 of 7

Reorder Copy Export Delete

1.8 Verification

1.9 Apstra Login

1.9.1 Administrator

Open a web browser and connect to the Apstra server. On the login page, login with username 'user-admin'.

Once logged in, click the user icon at the bottom left of the window and select "Profile".

The "User profile" shows that the user's role is 'administrator'.

User profile

Username	user-admin
First Name	
Last Name	
Email	
Roles	administrator

1.9.2 Operator

Log out, and then login with username 'user-oper'. Check the "User profile" again and note that no "Roles" are displayed.

User profile

Username	user-oper
First Name	
Last Name	
Email	

Navigate the GUI and notice that the user has read only access:

1.9.3 Log File

The login/logout activity appears in the Apstra server's Event Log which can be viewed in the GUI under 'Platform'.

The returned TACACS+ attributes can be viewed in the `/var/log/auth/AuthAgent.err` file:

```
1 admin@aos-server:/var/log/aos/auth$ sudo grep 'aos-group' *
2 AuthAgent.err:2025-11-11 15:26:27,712 29:INFO:RBAC:TACACS group response: ['aos-group=network-
  admins', 'priv-lvl=15']
3 AuthAgent.err:2025-11-11 15:30:14,336 29:INFO:RBAC:TACACS group response: ['aos-group=network-
  operators']
```

Reference: <https://supportportal.juniper.net/s/article/Juniper-Apstra-Authentication-and-Authorization-Debugging>

1.10 ClearPass Monitoring

In the ClearPass GUI, navigate to Monitoring → Live Monitoring → Access Tracker. A list of client authentication sessions is listed. Find the entries corresponding to the recent logins to the Apstra server at the top of the list and select one of them.

A pop-up window is displayed containing the session details. On the "Request" tab, note that the authentication status is "PASS" for the user and the authentication request type is "TACACS+".

TACACS+ Session Details	
Summary	Request
Username:	user-admin
Session ID:	T00000036-01-69b41beb
Time:	Mar 13, 2026 07:15:07 PDT
Status:	AUTHEN_STATUS_PASS
Request Type:	TACACS+_AUTHENTICATION
Message:	-
Client IP (Port):	10.161.32.2
Remote IP:	python_device

On the “Policies” tab, the matching service, authentication source, ClearPass role, and applied Enforcement Profile are displayed. The output confirms that the appropriate service was matched, the user was mapped to the correct ClearPass role, and the policy pointed to the proper profile which returned the correct attributes.

TACACS+ Session Details	
Summary	Request
Policies	Authorizations
Alerts	
Policies Used -	
Service Name:	Service-TACACS-Apstra
Authentication Source:	[Local User Repository]
Role:	[User Authenticated], Role-Network-Admin
Profiles:	Profile-Apstra-Admins

For additional troubleshooting, click the “Show logs” button for a detailed log corresponding to the session displayed in a new pop up window.

1.11 Useful links

- <https://supportportal.juniper.net/s/article/Juniper-Apstra-Authentication-and-Authorization-Debugging>

1.12 Glossary

- 802.1X: IEEE 802.1X Port-Based Network Access Control -> Standard for network access control (IEEE, official standard)
- API: Application Programming Interface -> Standard term in computing (ISO/IEC 2382)
- CPPM: ClearPass Policy Manager -> Aruba ClearPass Policy Manager (HPE Aruba documentation)
- DB: Database -> Structured collection of data (ISO/IEC 2382)
- GUI: Graphical User Interface -> Visual interface for user interaction (ISO/IEC 2382)
- HPE: Hewlett Packard Enterprise -> Company name (official corporate naming)
- ID: Identifier -> Unique identifying value (ISO/IEC 2382)
- IEEE: Institute of Electrical and Electronics Engineers -> Standards organization (IEEE official)
- IP: Internet Protocol -> Network layer protocol (IETF RFC 791)
- MAC: Media Access Control -> Sub-layer of data link layer (IEEE 802 standards)
- POC: Proof of Concept -> Demonstration to validate feasibility (widely used engineering term)
- RADIUS: Remote Authentication Dial-In User Service -> AAA protocol (IETF RFC 2865)
- RBAC: Role-Based Access Control -> Access control model (NIST, 2004 standard model)
- SQL: Structured Query Language -> Language for managing relational databases (ISO/IEC 9075)
- TCP: Transmission Control Protocol -> Transport layer protocol (IETF RFC 793)
- TACACS: Terminal Access Controller Access-Control System -> AAA protocol (historical, Cisco-origin)
- TACACS+: Terminal Access Controller Access-Control System Plus -> Enhanced AAA protocol (Cisco documentation)
- XML: eXtensible Markup Language -> Markup language for structured data (W3C Recommendation)



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

HPE

