



DC – AI – Routing – Switching – Security – Wireless – Automation

Secure BGP with ASPA Preventing and fixing route leaks

An HPE Juniper Networking Techpost

Anton Elita

2026-07-13

HPE



Contents

1	Secure BGP with ASPA: Preventing and fixing route leaks	4
1.1	Introduction	4
1.2	Where filtering stands today	4
1.3	Reference Topology and Business Relations between Network Operators	6
1.4	Preventing Route Leaks: BGP Roles	8
1.5	Fixing Route Leaks: ROA, ASPA	9
1.6	ASPA: Operational and Monitoring Aspects	15
1.7	References	16
1.8	Acknowledgments	16

List of Figures

1	ROA Validation	5
2	BGP Roles, ROA, and ASPA: in one picture	6
3	Reference Topology	7
4	Examples of Valleys	11
5	Validating ROA and ASPA on BGP import	12
6	Leaking from AS3333 to an upstream	14

List of Tables

1	Business relations between Autonomous Systems	7
2	Business Relations represented as ASPA objects	10
3	Validation result and action	11

1 Secure BGP with ASPA: Preventing and fixing route leaks

Anton Elita - 07/13/2026

BGP runs on trust, and route leaks and hijacks are what happen when that trust is misplaced. This article shows how three complementary mechanisms close the gap - BGP Roles with Only-To-Customer attribute prevent and detect leaks several hops from the source, and - if the leak already happened - RPKI Route Origin Authorization (ROA) helps validate the origin AS, and Autonomous System Provider Authorization (ASPA) confirms the full AS PATH is valley-free.

1.1 Introduction

Any BGP speaker can advertise a syntactically valid route for almost any prefix. Commercial relationships between autonomous systems, such as customer, provider, and peer, are supposed to constrain BGP prefix advertisements. When those relationships are violated - by mistake or by intent - the result is a route leak or hijack, and many related outages have been observed on the Internet. [RFC7908](#) provides a taxonomy and classification of route leaks based on these relationships. This article examines the three complementary mechanisms that allow enforcing business relationships into routing policies.

Three mechanisms defined at IETF are converging to enforce the relation policies and avoid leaks

- Route Origin Authorization (ROA) [[RFC9582](#)]: a signed object that helps validate the origin AS of a prefix
- BGP Roles [[RFC9234](#)]: prevents route leaks from happening
- Autonomous System Provider Authorization (ASPA) [[draft](#)]: signed object, helps validate the whole AS path is valley-free, thus aiding in the detection of a critical case where prefixes with possibly valid origin, but being advertised over an illegitimate AS path.

Note: ASPA validation in Junos is a planned feature for a later release. The CLI examples below are based on unreleased Junos code. *

Beyond the protocol mechanics, we cover the combined ROA + ASPA decision logic, examples of Junos import policies, CLI, and observability. The takeaway: these three-layered mechanisms turn “we trust BGP speakers on the internet behaved” into “we can verify they did.”

1.2 Where filtering stands today

Operators already mitigate leaks with per-neighbor prefix lists (often IRR-derived, sometimes inconsistent, and sources are somewhat random), RPKI route origin validation, AS_PATH filtering such as peer-lock, max-prefix limits, and community-based tagging of customer/peer/uplink routes. These work, but are maintenance-heavy and depend on operator discipline. Solutions from the IETF stack below make the policy itself verifiable.

Since 2012, Junos has supported RPKI route origin validation. This process can be summarized as follows:

- Network operators create cryptographically signed objects within RPKI repositories that prove the origin AS for a prefix
- Users of RPKI ROA can run RPKI cache validators to download the verified ROA objects via RRDP or rsync

- Routers use the RPKI-RTR protocol to download the data from cache validators
- Every prefix can be evaluated in the BGP ingress policy for validity: valid, invalid, or NotFound.
- Finally, the policy may specify an action to be taken based on the validation result: accept, reject, modify the preference, attach community, among others.




Figure 1: ROA Validation

For AS Path validation using ASPA records, the above procedure is extended as follows:

- Network operators can add their providers to the RPKI repository
- Routers can fetch ASPA records as specified by the RPKI-RTR v2 protocol
- Policies can be enhanced to validate both ASPA and ROA

Together with BGP roles, the process of preventing and fixing route leaks would look like this:




Figure 2: BGP Roles, ROA, and ASPA: in one picture

Let us go deeper into the details of this architecture.

1.3 Reference Topology and Business Relations between Network Operators

Below is a small topology of three “leaf” customers (CE1, CE2, CE3), two mid-size transit AS (PEER-A and PEER-B, they peer with each other) and one transit-free AS labeled as Tier-1.




Figure 3: Reference Topology

The business relations between all of them can be described in this table:

Table 1: Business relations between Autonomous Systems

Business Relations
AS 68 is a customer of AS 293
AS 293 is a customer of AS 6939
AS 2121 is a customer of AS 3333
AS 3303 is a customer of AS 6939
AS 3333 is a customer of AS 6939
AS 3333 may be a peer of AS 293

Let’s consider a prefix 130.55.0.0/16 originated by AS 68, and propagated to AS 293. From the perspective of the “Tier-1” node, this prefix may arrive only from the “Peer-A” node (AS_PATH 68 293), but not from the “Peer-B” (AS_PATH 3333 293 68) – because AS 3333 is allowed to send prefixes received from a peer only downstream to its customers, but not upstream or laterally to other peers.

Route Origin Validation alone would show the prefix as valid:

```

1 aelita@tier-1# run show validation database record 130.55.0.0/16
2 RV database: default
3 Prefix Origin-AS Session State Mismatch
4 130.55.0.0/16-16 68 11.254.254.61 valid
5   IPv4 records: 1
6   IPv6 records: 0

```

1.4 Preventing Route Leaks: BGP Roles

Roles formalize relationships as negotiated BGP capabilities. Each session side declares its local role:

```

1 set protocols bgp group X neighbor Y otc-local-role [ customer | peer | provider ] [ strict ]

```

The keyword **strict** should be used when we don't want a BGP session to come up if the remote speaker is not trying to negotiate this capability. Without **strict**, a session would come up, and the behavior regarding the OTC attribute and AS_PATH validation would be the same as if the role had been negotiated.

As the next step, let us configure all BGP roles as per the “business relations” table above. There is only a single “peer” neighborhood; all others are “customer-provider”.

After properly setting the roles, the BGP session is expected to bounce once and come up with the proper roles.

The role (**Type 9**) is carried in the **BGP OPEN** capability set and negotiated at session establishment.

```

1 [-] Border Gateway Protocol - OPEN Message
2   Marker: ffffffffffffffffffffffffffffffffff
3   Length: 68
4   Type: OPEN Message (1)
5   Version: 4
6   My AS: 68
7   Hold Time: 90
8   BGP Identifier: 11.5.6.2
9   Optional Parameters Length: 39
10  [-] Optional Parameters
11    [+] Optional Parameter: Capability
12    [+] Optional Parameter: Capability
13    [+] Optional Parameter: Capability
14    [+] Optional Parameter: Capability
15    [+] Optional Parameter: Capability
16    [+] Optional Parameter: Capability
17    [-] Optional Parameter: Capability
18       Parameter Type: Capability (2)
19       Parameter Length: 3
20    [-] Capability: BGP Role
21       Type: BGP Role (9)
22       Length: 1
23       BGP Role: Customer (3)

```

From the perspective of the CE2 device, the roles can be observed in the operational commands:

```

1 aelita@ce2# run show bgp neighbor
2 Peer: 11.5.6.1+179 AS 293 Local: 11.5.6.2+60884 AS 68
3   Group: peer-ce2 Routing-Instance: master
4   Forwarding routing-instance: master
5   Type: External State: Established Flags: <Sync>
6   Last State: OpenConfirm Last Event: RecvKeepAlive
7   [...]
8   Options: <BgpOTCRoleRouteLeakDetection>
9   [...]
10  Local role: customer Peer role: provider
11  [...]

```

Should the roles be wrongly configured in an unsupported combination, the BGP session will not go into Established:

```

1 Jun 11 14:33:56 tier-1 rpd[18844]: bgp_process_role_cap:201: NOTIFICATION sent to 11.3.4.2 (
  External AS 3333): code 2 (Open Message Error) subcode 11 (role mismatch)

```

An OTC attribute on the wire is set only when a prefix is advertised to a customer or peer, and must not be overwritten by other BGP speakers. An example for Peer-B sending a prefix towards Peer-A:

```

1 [-] Border Gateway Protocol - UPDATE Message
2   Marker: ffffffffffffffffffffffffffffffff
3   Length: 58
4   Type: UPDATE Message (2)
5   Withdrawn Routes Length: 0
6   Total Path Attribute Length: 31
7   [-] Path attributes
8     [+] Path Attribute - ORIGIN: IGP
9     [+] Path Attribute - AS_PATH: 3333 2121
10    [+] Path Attribute - NEXT_HOP: 11.4.5.1
11    [-] Path Attribute - OTC: 3333
12      [+] Flags: 0xc0, Optional, Transitive, Complete
13        Type Code: OTC (35)
14        Length: 4
15        Only to Customer: 3333
16  [-] Network Layer Reachability Information (NLRI)
17    [+] 193.0.24.0/21

```

Once the OTC attribute was set, a BGP speaker – even if located multiple hops away - can detect a leak. In this case, “Peer-A” was on purpose configured to improperly announce a prefix from “Peer-B” towards “Tier-1”, where the leak was recognized and stopped:

```

1 aelita@tier-1# run show route receive-protocol bgp 11.3.5.2 hidden extensive
2 inet.0: 10006 destinations, 10009 routes (5015 active, 0 holddown, 4992 hidden)
3 193.0.24.0/21 (2 entries, 1 announced)
4   Nexthop: 11.3.5.2
5   AS path: 293 3333 2121 I
6   Only-to-customer: 3333
7   Hidden reason: Route leak detected

```

We encourage to use `show bgp diagnostics` command for more details in troubleshooting BGP:

```

1 aelita@tier-1# run show bgp diagnostics route 193.0.24.0/21 from 11.3.5.2 table inet.0
2 Table: inet.0
3 Route: 193.0.24.0/21 (0x1bf45a20)
4 State: Hidden Ext Changed
5 Reason: Route leak detected
6 Suggestion: Follow these steps to figure out why route leak is detected
7   1. Use "show route hidden extensive" to find attribute Only-to-customer > 0
8   2. Use "show bgp neighbor" to find Peer role
9   3. If a route with the OTC Attribute is received from a Customer or
10      an RS-Client, then it is a route leak and MUST be considered ineligible
11      If a route with the OTC Attribute is received from a Peer (i.e.,
12      remote AS with a Peer Role) and the Attribute has a value that is
13      not equal to the remote (i.e., Peer's) AS number, then it is a
14      route leak and MUST be considered ineligible.

```

We will not dive further into the implementation of BGP roles to keep this article shorter. A link to more details is available in the References section.

While it takes time until most BGP speakers on the Internet negotiate their roles, let’s investigate how **ASPA** can help in the meantime. At this step, we removed the BGP roles from the configurations.

1.5 Fixing Route Leaks: ROA, ASPA

RPKI infrastructure has been built to act as a source of truth for:

- which AS is entitled to be the origin of a prefix - ROA
- inter-AS relations (customer/provider) - ASPA

and can be characterized by the following:

- Cryptographic certificates protect the data
- well-defined transports for downloading the databases: RRDP, rsync
- trusted organizations that store the signed data: RIRs/LIRs like RIPE, ARIN, APNIC, LACNIC

Route Origin Validation has been known for quite a while, so please check the References below for more details. We'll concentrate on ASPA instead. ASPA describes BGP relations between players on the Internet. Only "customers" are needed to publish their "providers":

- peers need not be registered
- single RPKI ASPA object for one AS: all providers are listed as a set of AS numbers.

The table describing business relations can be "translated" into ASPA objects. We've taken the most recent RPKI database at the time of writing. Only AS numbers relevant to our topology have been considered.

Table 2: Business Relations represented as ASPA objects

ASPA Business Relations	ASPA Objects
	Customer
AS 68 is a customer of AS 293	68
AS 293 is a customer of AS 6939	293
AS 2121 is a customer of AS 3333	2121
AS 3303 is a customer of AS 6939	3303
AS 3333 is a customer of AS 6939	3333
AS 3333 may be a peer of AS 293	-
AS 6939 is Tier-1 - no upstream	6939

Note: if an AS has no upstream – example being a tier-1 ISP, or an IXP network – they can register AS0 as their "provider" ASPA object: *

```

1 aelita@tier-1# run show validation database aspa-record 3257
2 RV database: default
3 Customer-AS Provider-AS Session
4 3257 0 11.254.254.61

```

The use of AS0 is defined in RFC 7607. The validation process with ASPA makes sure that an AS_PATH is valley-free. A valley occurs when a BGP speaker propagates a prefix received from a non-customer (i.e., an upstream or peer) to another non-customer.




Figure 4: Examples of Valleys

With both Route Origin and ASPA validation, there are several ways to build an import policy. If we want to reject a prefix if either ROA or ASPA is invalid:

```

1 set policy-options policy-statement RV term invalid from validation-database invalid
2 set policy-options policy-statement RV term invalid then validation-state invalid
3 set policy-options policy-statement RV term invalid then reject
4 set policy-options policy-statement RV term aspa-invalid from validation-database aspa-invalid
5 set policy-options policy-statement RV term aspa-invalid then validation-state invalid
6 set policy-options policy-statement RV term aspa-invalid then reject
7 set policy-options policy-statement RV term unknown from validation-database unknown
8 set policy-options policy-statement RV term unknown then validation-state unknown
9 set policy-options policy-statement RV term unknown then accept
10 set policy-options policy-statement RV term aspa-unknown from validation-database aspa-unknown
11 set policy-options policy-statement RV term aspa-unknown then validation-state unknown
12 set policy-options policy-statement RV term aspa-unknown then accept
13 set policy-options policy-statement RV term valid then validation-state valid
14 set policy-options policy-statement RV term valid then accept

```

If we want to implement a more sophisticated policy, where any combination of ROA and ASPA can be matched, and a desired validation result and action can be chosen, like in the table below:

Table 3: Validation result and action

ROA	ASPA	Validation Result	Example Action
valid	valid	valid	accept
valid	invalid	invalid	reject(strict),oraccept + lower preference(loose)
valid	unknown	valid	accept

ROA	ASPA	Validation Result	Example Action
invalid	*	invalid	reject
unknown	*	unknown	accept

Such a workflow in an import policy can be represented by this figure:




Figure 5: Validating ROA and ASPA on BGP import

Please note, this is an example policy, and Junos allows other combinations of matches and resulting actions.

In this example workflow, Junos can first validate ASPA and tag a prefix based on the validation result. Then, it can validate the origin and take a decision based on the combined ROA and ASPA validation results.

A policy chain can be assigned from two import policies: the first validates ASPA and passes to the second policy, which then checks the ROA and defines the action and validation state.

```

1 set protocols bgp group tier1-peerb import [ aspa-validate rpki-validate-strict-aspa ]
2
3 set policy-options policy-statement aspa-validate term unknown from validation-database aspa-
  unknown
4 set policy-options policy-statement aspa-validate term unknown then tag 64
5 set policy-options policy-statement aspa-validate term unknown then next policy
6 set policy-options policy-statement aspa-validate term valid from validation-database aspa-valid
7 set policy-options policy-statement aspa-validate term valid then tag 65
8 set policy-options policy-statement aspa-validate term valid then next policy
9 set policy-options policy-statement aspa-validate term invalid from validation-database aspa-
  invalid
10 set policy-options policy-statement aspa-validate term invalid then tag 66
11 set policy-options policy-statement aspa-validate term invalid then next policy
12 set policy-options policy-statement aspa-validate term Z then next policy
13
14 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-valid from
  protocol bgp
15 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-valid from
  validation-database valid
16 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-valid from tag
  65
17 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-valid then
  validation-state valid
18 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-valid then
  accept
19 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-unknown from
  protocol bgp
20 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-unknown from
  validation-database valid
21 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-unknown from
  tag 64
22 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-unknown then
  validation-state valid
23 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-unknown then
  accept
24 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-invalid from
  protocol bgp
25 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-invalid from
  validation-database valid
26 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-invalid from
  tag 66
27 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-invalid then
  validation-state invalid
28 set policy-options policy-statement rpki-validate-strict-aspa term roa-valid-aspa-invalid then
  reject
29 set policy-options policy-statement rpki-validate-strict-aspa term roa-invalid-aspa-any from
  protocol bgp
30 set policy-options policy-statement rpki-validate-strict-aspa term roa-invalid-aspa-any from
  validation-database invalid
31 set policy-options policy-statement rpki-validate-strict-aspa term roa-invalid-aspa-any then
  reject
32 set policy-options policy-statement rpki-validate-strict-aspa term roa-unknown-aspa-any from
  protocol bgp
33 set policy-options policy-statement rpki-validate-strict-aspa term roa-unknown-aspa-any from
  validation-database unknown
34 set policy-options policy-statement rpki-validate-strict-aspa term roa-unknown-aspa-any then
  validation-state unknown
35 set policy-options policy-statement rpki-validate-strict-aspa term roa-unknown-aspa-any then
  accept

```

Examples of ASPA Validation:

With the policies above, let's see if the following leak can be detected:




Figure 6: Leaking from AS3333 to an upstream

“Tier-1” is the validating node. Without BGP roles configured anywhere, and with missing ASPA objects for both AS6939 and AS3333, ASPA validation cannot detect a leak, just because AS3333 might theoretically also be a provider of AS6939...

```

1 aelita@tier-1# run show route 130.55.0.0/16 detail next-hop 11.3.4.2
2 130.55.0.0/16 (2 entries, 1 announced)
3   BGP Preference: 170/-101
4     Next hop type: Router, Next hop index: 623
5     Address: 0x99cd910
6     Next-hop reference count: 3, Next-hop session id: 320
7     Kernel Table Id: 0
8     Source: 11.3.4.2
9     Next hop: 11.3.4.2 via ge-0/0/3.0, selected
10    Session Id: 320
11    State: <Ext Changed>
12    Inactive reason: AS path
13    Local AS: 6939 Peer AS: 3333
14    Age: 33:44
15    Validation State: valid
16      Tag: 65
17    Task: BGP_3333.11.3.4.2
18    AS path: 3333 293 68 I
19    Accepted

```

How to fix that?

Add BGP role as “provider” on “Tier-1” towards “Peer-B”:

```

1 aelita@tier-1# set protocols bgp group tier1-peerb neighbor 11.3.4.2 otc-local-role provider
2 aelita@tier-1# commit
3

```

```

4 aelita@tier-1# run show route 130.55.0.0/16 detail next-hop 11.3.4.2 hidden
5 130.55.0.0/16 (2 entries, 1 announced)
6     BGP /-101
7         Next hop type: Router, Next hop index: 623
8         Address: 0x99c4890
9         Next-hop reference count: 3, Next-hop session id: 320
10        Kernel Table Id: 0
11        Source: 11.3.4.2
12        Next hop: 11.3.4.2 via ge-0/0/3.0, selected
13        Session Id: 320
14        State: <Hidden Ext Changed>
15        Inactive reason: Unusable path
16        Local AS: 6939 Peer AS: 3333
17        Age: 18
18        Validation State: invalid
19            Tag: 66
20        Task: BGP_3333.11.3.4.2
21        AS path: 3333 293 68 I
22        Localpref: 100
23        Router ID: 11.3.4.2
24        Hidden reason: Rejected by import policy

```

The leak was stopped because “Tier-1” now has the missing piece of the puzzle: when both AS3333 and AS293 are customers of AS6939, then the AS_PATH above is a valley, i.e., a prefix leak.

1.6 ASPA: Operational and Monitoring Aspects

A set of Junos commands has been extended to provide insights into ASPA validation operations.

```

1 aelita@pe2# run show validation session
2 Session Version State Flaps Uptime #IPv4/IPv6 records ASPA records
3 11.254.254.61 2. Up 0 1d 04:30:49 687395/216202 2033

```

Version of RPKI-RTR protocol now includes support for RFC8210bis, which introduced ASPA data retrieval.

```

1 aelita@pe2# run show validation session detail
2 Session 11.254.254.61 Version 2, , State: up, Session index: 3
3 Group: RPKI, Preference: 100
4 Local address: 11.254.254.3, Port: 3323
5 Refresh time: 600s
6 Hold time: 1800s
7 Record Life time: 7200s
8 Serial (Full Update): 1176
9 Serial (Incremental Update): 1182
10 Session flaps: 2
11 Session uptime: 01:10:03
12 Last PDU received: 00:05:07
13 IPv4 prefix count: 707324
14 IPv6 prefix count: 216444
15 ASPA record count: 2034

```

Per autonomous-system ASPA record query:

```

1 aelita@pe2# run show validation database aspa-record 2121
2 RV database: default
3 Customer-AS Provider-AS | Session
4 2121 3333 56595 11.254.254.61
5 ASPA records: 1

```

gNMI paths include global stats, as well as per-prefix validation state:

```

1 state
2   routing-instances
3     routing-instance [name=]
4       protocols
5         bgp
6           rib
7             afi-safis
8               afi-safi
9                 ipv4-unicast | ipv6-unicast
10                  loc-rib
11                  | routes

```

```
12 | route [path-id=][prefix=][origin=]
13 | origin-validation-state
14 +-- statistics
15 |   validation-state-invalid
16 |   validation-state-unknown
17 |   validation-state-unverified
18 |   validation-state-valid
```

Example replies would look like these:

```
1 juniper:state/routing-instances/routing-instance[name=DEFAULT]/protocols/bgp/rib/afi-safis/afi-
  safi[name=ipv4-unicast]/ipv4-unicast/loc-rib/statistics/validation-state-invalid: 1
2 juniper:state/routing-instances/routing-instance[name=DEFAULT]/protocols/bgp/rib/afi-safis/afi-
  safi[name=ipv4-unicast]/ipv4-unicast/loc-rib/statistics/validation-state-unknown: 3336
3 juniper:state/routing-instances/routing-instance[name=DEFAULT]/protocols/bgp/rib/afi-safis/afi-
  safi[name=ipv4-unicast]/ipv4-unicast/loc-rib/statistics/validation-state-unverified: 0
4 juniper:state/routing-instances/routing-instance[name=DEFAULT]/protocols/bgp/rib/afi-safis/afi-
  safi[name=ipv4-unicast]/ipv4-unicast/loc-rib/statistics/validation-state-valid: 2255
5 juniper:state/routing-instances/routing-instance[name=DEFAULT]/protocols/bgp/rib/afi-safis/afi-
  safi[name=ipv4-unicast]/ipv4-unicast/loc-rib/routes/route[path-id=0][prefix=193.0.24.0/21][
  origin=11.3.4.2]/origin-validation-state: rpki-validation-valid
```

1.7 References

- [Details of BGP roles implementation](#)
- [BGP Origin Validation](#)

1.8 Acknowledgments

I would like to thank Santosh Kolenchery and the entire BGP software engineering team for making these features a reality, and for reviewing this techpost.