



DC – AI – Routing – Switching – Security – Wireless – Automation

Service Mapping to Colored MPLS Paths

An HPE Juniper Networking Techpost

Anton Elita

2023-01-18

HPE



Contents

1	Service Mapping to Colored MPLS Paths	3
1.1	Introduction	3
1.2	Basic Network Setup	3
1.3	Mapping LDP-based VPNs to colored transport tunnels	7
1.3.1	L2circuit	7
1.3.2	VPLS with LDP signaling	8
1.4	Mapping BGP-based VPNs to colored transport tunnels	9
1.4.1	L2VPN	9
1.4.2	VPLS with BGP signaling	10
1.4.3	EVPN-ELAN, EVPN-VPWS, EVPN-ETREE	10
1.4.4	L3VPN	13
1.4.5	Plain IPv4 and IPv6	14
1.5	Summary	15
1.6	Useful links	15
1.7	Glossary	15
1.8	Acknowledgements	15

List of Figures

1	Topology	4
---	--------------------	---

1 Service Mapping to Colored MPLS Paths

Anton Elita - 01/18/2023

Mapping modern and legacy services to colored MPLS paths, achieving business differentiation.

1.1 Introduction

People say there are no greenfield service providers (SPs). Some networks grow organically, some by acquisitions and merges. Growth takes time, and technology does not stay idle, speaking not only of interface speeds, but as well of the used protocols. Sooner or later, a more efficient network would require protocols to be updated or changed: solving scaling challenges, providing more flexible underlays and overlays, enabling new businesses.

Many SPs already moved to SR-MPLS or are in the process of transition. Now is the time to use the advantages of this technology, for example one or multiple flavors of traffic engineering (SR-TE). In this TechPost, we will see how to map virtual private networks (VPNs) or plain IPv4/IPv6 prefixes to colored traffic-engineered paths in an MPLS network.

Junos is doing great job in helping network operators to change a technology. To name just one example: coexistence of VPLS and EVPN, allowing for site-by-site migration and saving the investments in VPLS. Check [this post](#) for more details.

The same applies to migration between different transport protocols. Junos allows mapping of new (for example EVPN) and old (for example LDP-based) services to traffic-engineered transport paths established by RSVP, SR-TE, BGP-CT or Flex-Algo.

In this article we're reviewing *colored* TE transport tunnels, carrying different services between same pairs of PE endpoints. Color is required to differentiate transport tunnels between a pair of PE endpoints, each using a single Loopback IP address. It's a great business enabler, allowing different SLAs for various service types.

1.2 Basic Network Setup

Throughout this TechPost we will use this reference network:




Figure 1: Topology

Please note that this network is running on vMX with Junos 22.4R1. Support for mapping services to colored MPLS LSPs appeared in Junos in 2019, gradually adding new features on all platforms like MX, PTX, ACX, and even more features to come, as the protocols and products evolve!

ISIS is serving as internal protocol (IGP), but OSPF is supported as well. Each link has an IGP metric (green color) and a delay metric (red). IGP metric can be thought of being proportional to the link bandwidth, and the delay metric represents a static or a dynamic link latency value in milliseconds. There is a single Flex-Algo 128 which uses delay metrics for shortest path calculation. Other constraints like link affinities might be used, but for brevity are not included here.

All services are running between PE1 and PE2. Some will be BGP-signaled, and some use LDP. PE devices either have a direct iBGP session or exchange prefixes via a route reflector. Basic PE configuration is independent of the carried services:

```

1 aelita@pe2# show groups SR
2 policy-options {
3   policy-statement PS-ADD-FLEX-ALGO {
4     term TR-FA128 {
5       from {
6         interface lo0.0;
7         route-filter 192.0.2.6/32 exact;
8       }
9       then {
10        prefix-segment {
11          algorithm 128 index 106 node-segment;
12          index 6;
13          node-segment;
14        }
15        accept;
16      }
17    }
18  }
19 }
20 routing-options {
21   flex-algorithm 128 {
22     definition {
23       metric-type delay-metric;
24     }
25     color 128;

```

```

26     use-transport-class;
27 }
28 route-distinguisher-id 192.0.2.6;
29 resolution {
30     preserve-nexthop-hierarchy;
31 }
32 transport-class {
33     auto-create;
34     name tc-128 {
35         color 128;
36     }
37 }
38 }
39 protocols {
40     isis {
41         source-packet-routing {
42             node-segment ipv4-index 6;
43             flex-algorithm 128;
44         }
45         export PS-ADD-FLEX-ALGO;
46     }
47     mpls {
48         label-range {
49             srgb-label-range 100000 135999;
50         }
51     }
52 }

```

A few notes on the above configuration:

- SRGB allocation is configured at “protocols mpls” level, and effectively creates a shared common label block for protocols like ISIS and BGP
- Flex-Algo 128 is configured for both participation (required on every participating node) and definition (required on at least one node per ISIS level)
- A policy is used to advertise both regular SID and Flex-Algo 128 SID in ISIS
- “resolution preserve-nexthop-hierarchy” must be enabled for correct next-hop resolution in services like VPLS
- Transport-Class is used for the colored paths

Transport classes have been introduced in Junos 21.1R1 and represent sets of transport tunnels with common TE characteristics. They simplify mapping of service routes to transport routes, with desired SLA and fallback characteristics. Matching happens by comparing color community attached to the service prefix with the color of the transport class, where transport tunnel reside. Transport tunnels can be initiated by RSVP-TE, SR-TE, Flex-Algo or BGP-CT.

Each transport class can have own fallback configuration, which allows using next-hops from a different colored transport class or uncolored tunnels.

Mapping to transport classes is facilitated via new route target called “transport-target”, acting as a mapping community to resolve routes via respective transport classes.

```

1 aelita@pe2# run show routing transport-class all
2 Transport Class: junos-tc-128 Configured name: tc-128
3   Color: 128, References: 6
4   Transport Endpoints: IPv4 5 IPv6 0
5   Mapping community: color:0:128
6   Route Target: transport-target:0:128
7   Routing instance: junos-rti-tc-128
8
9 Transport Class: junos-tc-best-effort
10  Color: 0, References: 2
11  Transport Endpoints: IPv4 5 IPv6 0
12  Mapping community: color:0:0
13  Routing instance: master
14  ExportDisabled
15
16 aelita@pe2# run show route resolution scheme all

```

```

17 Resolution scheme: junos-resol-schem-tc-128-v4-service
18   AutoCreated
19   References: 1
20   Mapping community: color:0:128
21   Resolution Tree: 0x9782400, index: 6, Nodes: 5
22   Policy: [__resol-schem-common-import-policy__]
23   Contributing routing tables: junos-rti-tc-128.inet.3 inet.3
24
25 Resolution scheme: junos-resol-schem-tc-128-v4-transport
26   AutoCreated
27   References: 1
28   Mapping community: transport-target:0:128
29   Resolution Tree: 0x9783c00, index: 8, Nodes: 5
30   Policy: [__resol-schem-common-import-policy__]
31   Contributing routing tables: junos-rti-tc-128.inet.3

```

The above output shows two types of resolution schemes, for transport and service. Transport can be any of RSVP-TE, SR-TE, Flex-Algo and other types of underlay transport tunnels, and uses transport-target as a mapping community. Service refers to L3VPN, EVPN, L2VPN and other types of payload and uses color community for mapping.

```

1 aelita@pe2# run show route table junos-rti-tc-128.inet.3
2
3 192.0.2.1/32 *[L-ISIS/14] 2d 22:11:52, metric 101
4   > to 10.0.36.1 via ge-0/0/0.0, Push 100101
5 192.0.2.2/32 *[L-ISIS/14] 2d 22:12:03, metric 50
6   > to 10.0.26.1 via ge-0/0/1.0
7 192.0.2.3/32 *[L-ISIS/14] 2d 22:11:40, metric 50
8   > to 10.0.36.1 via ge-0/0/0.0
9 192.0.2.4/32 *[L-ISIS/14] 2d 22:11:26, metric 112
10  > to 10.0.36.1 via ge-0/0/0.0, Push 100104
11 192.0.2.5/32 *[RSVP/7/1] 00:03:58, metric 30
12  > to 10.0.36.1 via ge-0/0/0.0, label-switched-path LSP-PE1
13   [SPRING-TE/8] 00:09:03, metric 1, metric2 30
14  > to 10.0.26.1 via ge-0/0/1.0, Push 100005
15   to 10.0.36.1 via ge-0/0/0.0, Push 100005
16   [L-ISIS/14] 2d 22:12:23, metric 163
17  > to 10.0.36.1 via ge-0/0/0.0, Push 100105
18
19 aelita@pe2# run show isis route flex-algorithm-id 128
20 IS-IS routing table Current version: L1: 0 L2: 390
21 IPv4/IPv6 Routes
22 -----
23 Prefix L Version Metric Type Interface NH Via Backup Score
24 192.0.2.1/32 2 348 101 int ge-0/0/0.0 IPV4 p3
25 192.0.2.2/32 2 348 50 int ge-0/0/1.0 IPV4 p2
26 192.0.2.3/32 2 348 50 int ge-0/0/0.0 IPV4 p3
27 192.0.2.4/32 2 348 112 int ge-0/0/0.0 IPV4 p3
28 192.0.2.5/32 2 348 163 int ge-0/0/0.0 IPV4 p3
29 192.0.2.6/32 2 348 0 int
30 [...]

```

The CLI outputs show which transport classes exist, their fallback configuration, and the contents of the respective routing tables. Table *junos-rti-tc-128.inet.3* shows routes from different protocols like RSVP-TE, SR-TE and ISIS Flex-Algo.

Color assignment for Flex-Algo is by default taking the value of Flex-Algo itself, for example 128. For RSVP-TE or SR-TE, color can be configured like this:

```

1 aelita@pe2# show protocols mpls
2 label-switched-path LSP-PE1 {
3   to 192.0.2.5;
4   transport-class tc-128;
5 }
6 aelita@pe2# show groups SR protocols source-packet-routing
7 source-routing-path SP-PE1 {
8   to 192.0.2.5;
9   color 128;
10  primary {
11    SL-PE1 {
12      compute;
13    }
14  }

```

```
15 }
```

Above LSPs do not have strict path or other constraints, and Junos will calculate the path - provided that the TED is populated by IGP. More on TED can be found in [this techpost](#).

1.3 Mapping LDP-based VPNs to colored transport tunnels

1.3.1 L2circuit

L2circuit is a very widespread technology supporting layer-2 point-to-point VPNs. With a simple configuration knob, l2circuits can be mapped to underlying colored transport tunnels:

```
1 aelita@pe2# show groups L2CIRCUIT
2 interfaces {
3   ge-0/0/2 {
4     encapsulation ethernet-ccc;
5     unit 0;
6   }
7 }
8 policy-options {
9   community CM-128 members color:0:128;
10 }
11 protocols {
12   l2circuit {
13     neighbor 192.0.2.5 {
14       interface ge-0/0/2.0 {
15         virtual-circuit-id 19202501;
16         community CM-128;
17       }
18     }
19   }
20   ldp {
21     interface lo0.0;
22   }
23 }
```

The only thing we needed to add to regular l2circuit definition is the color community, that was an easy job!

Note that the only interface where LDP is enabled is Lo0.0 on the PE device. Core (transit) nodes do not need to run LDP at all.

Junos will pick up the next-hop with the lowest distance from the transport class table matching community:

```
1 aelita@pe2# run show route table junos-rti-tc-128.inet.3 192.0.2.5/32
2
3 192.0.2.5/32 *[RSVP/7/1] 00:39:22, metric 30
4   > to 10.0.36.1 via ge-0/0/0.0, label-switched-path LSP-PE1
5   [SPRING-TE/8] 00:44:27, metric 1, metric2 30
6   > to 10.0.26.1 via ge-0/0/1.0, Push 100005
7   to 10.0.36.1 via ge-0/0/0.0, Push 100005
8   [L-ISIS/14] 2d 22:47:47, metric 163
9   > to 10.0.36.1 via ge-0/0/0.0, Push 100105
10
11 aelita@pe2# run show route table l2circuit.0 expanded-nh
12 192.0.2.5:CtrlWord:5:19202501:Local/96
13   *[L2CKT/7] 00:11:47, metric2 30
14   > to 10.0.36.1 via ge-0/0/0.0, label-switched-path LSP-PE1
```

We can remove the RSVP-TE LSP to verify that l2circuit will be re-mapped to the next available transport tunnel:

```
1 aelita@pe2# deactivate protocols mpls label-switched-path LSP-PE1
2
3 [edit]
4 aelita@pe2# commit
5 commit complete
6
7 aelita@pe2# run show route table l2circuit.0 expanded-nh
```

```

8
9 l2circuit.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
10 + = Active Route, - = Last Active, * = Both
11
12 192.0.2.5:CtrlWord:5:19202501:Local/96
13     *[L2CKT/7] 00:14:23, metric2 30
14     > to 10.0.26.1 via ge-0/0/1.0, Push 100005
15     to 10.0.36.1 via ge-0/0/0.0, Push 100005

```

Now we remove SR-TE LSP as well, so that only Flex-Algo with color 128 is the only contributor to the traffic-class table with the ID 128:

```

1 aelita@pe2# deactivate groups SR protocols source-packet-routing source-routing-path SP-PE1
2
3 [edit]
4 aelita@pe2# commit
5 commit complete
6
7 aelita@pe2# run show route table junos-rti-tc-128.inet.3 192.0.2.5/32
8
9 192.0.2.5/32 *[L-ISIS/14] 3d 00:14:03, metric 163
10 > to 10.0.36.1 via ge-0/0/0.0, Push 100105
11
12 [edit]
13 aelita@pe2# run show route table l2circuit.0 expanded-nh
14
15 192.0.2.5:CtrlWord:5:19202501:Local/96
16     *[L2CKT/7] 00:00:34, metric2 163
17     > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

The outgoing transport label is clearly confirming the use of Flex-Algo 128 label. The metric of 163 is a sum of delay metrics following this lowest latency path: PE2, P2, P3, P1, P4 -PE1

1.3.2 VPLS with LDP signaling

Similar to L2circuits, VPLS with LDP signaling uses LDP to allocate the label, but does not require LDP-enabled core and can be mapped to colored transport tunnels.

I will skip the full VPLS configuration for brevity, as it's already well documented in the guides for Junos.

Before applying the mapping onto colored transport tunnels:

```

1 aelita@pe2# run show route table l2circuit.0 expanded-nh
2
3 l2circuit.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
4 + = Active Route, - = Last Active, * = Both
5
6 192.0.2.5:NoCtrlWord:5:192003:Local/96
7     *[VPLS/7] 00:01:05, metric2 30
8     to 10.0.26.1 via ge-0/0/1.0, Push 100005
9     > to 10.0.36.1 via ge-0/0/0.0, Push 100005
10
11 aelita@pe2# run show route 192.0.2.5
12 [...]
13
14 inet.3: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
15 + = Active Route, - = Last Active, * = Both
16
17 192.0.2.5/32 *[L-ISIS/14] 3d 02:22:06, metric 30
18 > to 10.0.26.1 via ge-0/0/1.0, Push 100005
19 to 10.0.36.1 via ge-0/0/0.0, Push 100005
20
21 junos-rti-tc-128.inet.3: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
22 + = Active Route, - = Last Active, * = Both
23
24 192.0.2.5/32 *[L-ISIS/14] 3d 02:22:06, metric 163
25 > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

Junos used transport label from the *inet.3* table because we hadn't applied the color community yet. Let's change that:

```

1 aelita@pe2# set groups VPLS-LDP routing-instances RI-VPLS protocols vpls community CM-128
2 aelita@pe2# set groups VPLS-LDP policy-options community CM-128 members color:0:128
3 [edit]
4 aelita@pe2# commit
5
6 aelita@pe2# run show route table l2circuit.0
7
8 192.0.2.5:NoCtrlWord:5:192003:Local/96
9      *[VPLS/7] 00:00:04, metric2 163
10     > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

Next-hop now expectedly points to the colored next-hop.

1.4 Mapping BGP-based VPNs to colored transport tunnels

1.4.1 L2VPN

L2VPN with BGP signaling would by default use any valid next-hop from the inet.3 table, where uncolored tunnels are located. To instruct a PE to use a colored MPLS path to the remote end, we will add a community matching traffic-class configuration. Setting the color community will be part of a BGP policy. Such policy can be applied flexibly: it can be configured on the egress PE by using VRF export policy, or BGP export policy per group or per neighbor. Alternatively, color community can be applied on the ingress PE by using BGP import policy per group or per neighbor.

```

1 aelita@pe2# show groups L2VPN
2 interfaces {
3   ge-0/0/2 {
4     encapsulation ethernet-ccc;
5     unit 0;
6   }
7 }
8 policy-options {
9   policy-statement PL-ADD-COLOR {
10    term A {
11     then {
12      community add CM-128;
13     }
14   }
15 }
16 community CM-128 members color:0:128;
17 }
18 routing-instances {
19   RI-L2VPN {
20     instance-type l2vpn;
21     protocols {
22       l2vpn {
23         site pe2 {
24           interface ge-0/0/2.0 {
25             remote-site-id 1;
26           }
27           site-identifier 2;
28         }
29         encapsulation-type ethernet;
30       }
31     }
32     interface ge-0/0/2.0;
33     vrf-target target:100:1;
34   }
35 }
36 protocols {
37   bgp {
38     group GR-iBGP {
39       local-address 192.0.2.6;
40       import PL-ADD-COLOR;
41       family l2vpn {
42         signaling;
43       }
44       peer-as 100;
45       local-as 100;
46       neighbor 192.0.2.5;

```

```

47     }
48   }
49 }
50
51 aelita@pe2# run show route table RI-L2VPN.l2vpn.0 expanded-nh
52
53 192.0.2.5:65532:1:1/96
54     *[BGP/170] 00:13:45, localpref 100, from 192.0.2.5
55     AS path: I, validation-state: unverified
56     > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

The other side PE1 does not have any coloring applied, so it will resolve via regular L-ISIS route with ECMP:

```

1  aelita@pe1# run show route table RI-L2VPN.l2vpn.0 expanded-nh
2
3 192.0.2.6:65533:2:1/96
4     *[BGP/170] 00:15:12, localpref 100, from 192.0.2.6
5     AS path: I, validation-state: unverified
6     to 10.0.15.1 via ge-0/0/0.0, Push 100006
7     > to 10.0.45.1 via ge-0/0/1.0, Push 100006
8
9  aelita@pe1# run show route 192.0.2.6 table inet.3
10
11 192.0.2.6/32 *[L-ISIS/14] 3d 00:32:37, metric 30
12     > to 10.0.15.1 via ge-0/0/0.0, Push 100006
13     to 10.0.45.1 via ge-0/0/1.0, Push 100006

```

Metric 30 is the sum of regular IGP metrics via either southern or northern paths in our topology.

1.4.2 VPLS with BGP signaling

VPLS with BGP signaling uses the same address family as L2VPN above. BGP policies to add color community are same too. VPLS configuration itself is well known, so can be skipped.

Verification of the route programming in Junos, and traffic class being applied:

```

1  aelita@pe2# run show route table RI-VPLS.l2vpn.0 expanded-nh
2
3 RI-VPLS.l2vpn.0: 2 destinations, 2 routes (2 active, 0 holddown, 0 hidden)
4 + = Active Route, - = Last Active, * = Both
5
6 192.0.2.5:9:1:1/96
7     *[BGP/170] 00:18:45, localpref 100, from 192.0.2.5
8     AS path: I, validation-state: unverified
9     > to 10.0.36.1 via ge-0/0/0.0, Push 100105
10
11 aelita@pe2# run show route forwarding-table family vpls detail
12 Routing table: RI-VPLS.vpls
13 VPLS:
14 Enabled protocols: ACKed by all peers,
15 Destination Type RtRef Next hop Type Index NhRef Netif
16 default perm 0 dscd 609 1
17 vt-0/0/0.1048576 intf 0 indr 1048574 4
18     10.0.36.1 Push 25, Push 100105(top) 616 2 ge-0/0/0.0

```

The label used corresponds to the Flex-Algo node SID of the egress PE1:

```

1  aelita@pe2# run show route 192.0.2.5/32 table junos-rti-tc-128
2
3 192.0.2.5/32 *[L-ISIS/14] 3d 01:47:53, metric 163
4     > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

1.4.3 EVPN-ELAN, EVPN-VPWS, EVPN-ETREE

Junos 23.1R1 makes possible EVPN mapping to colored SR-TE or Flex-Algo transport tunnels using “transport classes”. With older Junos releases, *inet[6]color* tables with [resolution-maps](#) can be used for service mapping.

Below is configuration and verification example for EVPN-ELAN and EVPN-VPWS.

```

1  aelita@pe2# show
2  interfaces {
3      ge-0/0/2 {
4          flexible-vlan-tagging;
5          encapsulation flexible-ethernet-services;
6          unit 0 {
7              encapsulation vlan-ccc;
8              vlan-id 10;
9              esi {
10                 00:00:00:00:01:00:00:00:00:01;
11                 all-active;
12             }
13         }
14         unit 11 {
15             encapsulation vlan-bridge;
16             vlan-id 11;
17             esi {
18                 00:00:00:00:02:00:00:00:00:01;
19                 all-active;
20             }
21         }
22     }
23 }
24 policy-options {
25     policy-statement PL-ADD-COLOR {
26         term A {
27             then {
28                 community add CM-128;
29             }
30         }
31     }
32     community CM-128 members color:0:128;
33 }
34 routing-instances {
35     RI-EVPN-VPWS {
36         instance-type evpn-vpws;
37         protocols {
38             evpn {
39                 interface ge-0/0/2.0 {
40                     vpws-service-id {
41                         local 2;
42                         remote 1;
43                     }
44                 }
45             }
46         }
47         interface ge-0/0/2.0;
48         vrf-target target:100:1;
49     }
50     RI-EVPN-ELAN {
51         instance-type evpn;
52         protocols {
53             evpn;
54         }
55         vlan-id 11;
56         interface ge-0/0/2.11;
57         vrf-target target:100:2;
58     }
59 }
60 protocols {
61     bgp {
62         group GR-iBGP {
63             local-address 192.0.2.6;
64             import PL-ADD-COLOR;
65             family evpn {
66                 signaling;
67             }
68             peer-as 100;
69             local-as 100;
70             neighbor 192.0.2.5;
71         }
72     }
73 }
74
75 [edit groups EVPN]
```

VLANs 10 and 11 carry different EVPN services: VPWS and ELAN. Here again we assign extended color commu-

nity *color:0:128* on the ingress BGP group level, but this can be changed to vrf-export (or BGP group/neighbor export) on egress PE side.

Verification for VPWS service:

```

1 aelita@pe2# run show evpn vpws-instance RI-EVPN-VPWS
2 Instance: RI-EVPN-VPWS, Instance type: EVPN VPWS, Encapsulation type: MPLS
3 Route Distinguisher: 192.0.2.6:65534
4 Number of local interfaces: 1 (1 up)
5
6 Interface name ESI Mode Role Status Control-Word Flow-Label-Tx Flow-Label-Rx
7 ge-0/0/2.0 00:00:00:00:01:00:00:00:01 all-active Primary Up No No No
8 Local SID: 2 Advertised Label: 34
9 Remote SID: 1
10 PE addr ESI Label End.Dx2 SID Mode Role TS Status
11 192.0.2.5 00:00:00:00:01:00:00:00:02 37 all-active Primary 2022-12-28 01:42:58.619
12 Resolved
13 Number of protect interfaces: 0
14
15 Fast Convergence Information
16 ESI: 00:00:00:00:01:00:00:00:02 Number of PE nodes: 1
17 PE: 192.0.2.5
18 Advertised SID: 1

```

Check that the transport tunnel picks up the right label for Flex-Algo 128:

```

1 aelita@pe2# run show route table RI-EVPN-VPWS.evpn.0 expanded-nh
2
3 1:192.0.2.5:::010000000002::FFFF:FFFF/192 AD/ESI
4 * [BGP/170] 00:05:36, localpref 100, from 192.0.2.5
5 AS path: I, validation-state: unverified
6 > to 10.0.36.1 via ge-0/0/0.0, Push 100105
7 1:192.0.2.5:65533:::010000000002::1/192 AD/EVI
8 * [BGP/170] 00:05:36, localpref 100, from 192.0.2.5
9 AS path: I, validation-state: unverified
10 > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

Check the full label stack:

```

1 aelita@pe2# run show route forwarding-table ccc ge-0/0/2.0 extensive
2 Routing table: default.mpls [Index 0]
3 MPLS:
4
5 Destination: ge-0/0/2.0 (CCC)
6 Route type: user
7 Route reference: 0 Route interface-index: 0
8 Multicast RPF nh index: 0
9 P2mpidx: 0
10 Flags: sent to PFE, prefix load balance
11 Nexthop:
12 Next-hop type: composite Index: 573 Reference: 3
13 Load Balance Label: Push 37, None
14 Next-hop type: indirect Index: 1048574 Reference: 2
15 Nexthop: 10.0.36.1
16 Next-hop type: Push 100105 Index: 621 Reference: 2
17 Load Balance Label: None
18 Next-hop interface: ge-0/0/0.0

```

EVPN-ELAN service allows verification of the learned MAC addresses, provided that you have any active hosts:

```

1 aelita@pe2# run show evpn database
2 Instance: RI-EVPN-ELAN
3 VLAN DomainId MAC address Active source Timestamp IP address
4 11 56:04:1d:00:a5:c1 00:00:00:00:02:00:00:00:00:02 Dec 28 02:07:43 1.1.1.1
5
6 aelita@pe2# run show route forwarding-table matching "56:04:1d:00:a5:c1" extensive
7 Routing table: RI-EVPN-ELAN.evpn [Index 9]
8 EVPN:
9 Enabled protocols: Single VLAN, ACKed by all peers, EVPN, ARP/NDP suppression,
10
11 Destination: 56:04:1d:00:a5:c1/48
12 Learn VLAN: 0 Route type: user
13 Route reference: 0 Route interface-index: 336
14 Multicast RPF nh index: 0

```

```

15 P2mpidx: 0
16 IFL generation: 0 Epoch: 0
17 Sequence Number: 0 Learn Mask: 0x00000000
18 L2 Flags: control, control_dyn
19 Flags: sent to PFE
20 Next-hop type: indirect Index: 1048576 Reference: 4
21 Nexthop:
22 Next-hop type: composite Index: 627 Reference: 2
23 Load Balance Label: Push 41, None
24 Nexthop: 10.0.36.1
25 Next-hop type: Push 100105 Index: 621 Reference: 4
26 Load Balance Label: None
27 Next-hop interface: ge-0/0/0.0

```

1.4.4 L3VPN

After having covered enough of layer 2 VPN service types, it's time to have a look at L3 services. We can start with L3VPN for IPv4 and IPv6 families.

Let's configure a policy setting the extended community on the egress PE side, as part of the VRF export policy.

Configuration on the egress PE1 side:

```

1 aelita@pe1# show groups L3VPN
2 interfaces {
3   ge-0/0/6 {
4     unit 0 {
5       family inet {
6         address 1.1.1.2/24;
7       }
8       family inet6 {
9         address 2001:100::1:1/127;
10      }
11    }
12  }
13 }
14 policy-options {
15   policy-statement PL-ADD-COLOR {
16     term A {
17       then {
18         community add CM-128;
19         community add CM-RT-100-1;
20         accept;
21       }
22     }
23   }
24   community CM-128 members color:0:128;
25   community CM-RT-100-1 members target:100:1;
26 }
27 routing-instances {
28   RI-L3VPN {
29     instance-type vrf;
30     interface ge-0/0/6.0;
31     vrf-export PL-ADD-COLOR;
32     vrf-target target:100:1;
33     vrf-table-label;
34   }
35 }
36 protocols {
37   bgp {
38     group GR-iBGP {
39       local-address 192.0.2.5;
40       family inet-vpn {
41         unicast;
42       }
43       family inet6-vpn {
44         unicast;
45       }
46       peer-as 100;
47       local-as 100;
48       neighbor 192.0.2.6;
49     }
50   }

```

```

51     mpls {
52         ipv6-tunneling;
53     }
54 }

```

Remember that we need MPLS IPv6 tunneling for IPv4-based BGP next-hops.

Verification on the ingress PE2 node:

```

1  aelita@pe2# run show route receive-protocol bgp 192.0.2.5 detail | match "\*|comm|label"
2  * 1.1.1.0/24 (1 entry, 1 announced)
3      VPN Label: 48
4      Communities: target:100:1 color:0:128
5  * 192.0.2.5:10:1.1.1.0/24 (1 entry, 0 announced)
6      VPN Label: 48
7      Communities: target:100:1 color:0:128
8  * 2001:100::1:0/127 (1 entry, 1 announced)
9      VPN Label: 48
10     Communities: target:100:1 color:0:128
11 * 192.0.2.5:10:2001:100::1:0/127 (1 entry, 0 announced)
12     VPN Label: 48
13     Communities: target:100:1 color:0:128
14
15 aelita@pe2# run show route 1.1.1.0/24
16
17 RI-L3VPN.inet.0: 3 destinations, 3 routes (3 active, 0 holddown, 0 hidden)
18 + = Active Route, - = Last Active, * = Both
19
20 1.1.1.0/24 *[BGP/170] 00:09:18, localpref 100, from 192.0.2.5
21     AS path: I, validation-state: unverified
22     > to 10.0.36.1 via ge-0/0/0.0, Push 48, Push 100105(top)
23
24 aelita@pe2# run show route 2001:100::1:0/127
25
26 RI-L3VPN.inet6.0: 5 destinations, 5 routes (5 active, 0 holddown, 0 hidden)
27 + = Active Route, - = Last Active, * = Both
28
29 2001:100::1:0/127 *[BGP/170] 00:09:57, localpref 100, from 192.0.2.5
30     AS path: I, validation-state: unverified
31     > to 10.0.36.1 via ge-0/0/0.0, Push 48, Push 100105(top)

```

We receive the route, recognize the color community, and set the next-hop to Flex-Algo 128!

1.4.5 Plain IPv4 and IPv6

Plain IPv4 or IPv6 is not much different from L3VPN. All what's needed is to add a color community to chosen prefix(es): either on the egress PE as part of the BGP export policy, or on the ingress PE in the BGP import policy.

```

1  aelita@pe2# run show route receive-protocol bgp 192.0.2.5 detail | match "\*|comm|label"
2  * 1.1.1.0/24 (1 entry, 1 announced)
3      Communities: color:0:128
4  * 2001:100::1:0/127 (1 entry, 1 announced)
5      Communities: color:0:128
6
7  aelita@pe2# run show route protocol bgp table inet.0
8
9  1.1.1.0/24 *[BGP/170] 00:00:48, localpref 100, from 192.0.2.5
10     AS path: I, validation-state: unverified
11     > to 10.0.36.1 via ge-0/0/0.0, Push 100105
12
13 aelita@pe2# run show route protocol bgp table inet6.0
14
15 2001:100::1:0/127 *[BGP/170] 00:01:05, localpref 100, from 192.0.2.5
16     AS path: I, validation-state: unverified
17     > to 10.0.36.1 via ge-0/0/0.0, Push 100105

```

1.5 Summary

Junos allows a very granular mapping of complete services (or service prefixes) to colored MPLS tunnels. SR-TE, RSVP-TE, BGP-CT or Flex-Algo are all supported contributors to the transport tunnels. In addition to the above-mentioned services, Junos allows transport class mapping for IPv6 and flowspec address families.

1.6 Useful links

- [RFC9085](#): Border Gateway Protocol - Link State (BGP-LS) Extensions for Segment Routing
- [Transport-Classes](#)
- [BGP-CT](#)
- [Resolution Maps](#)

1.7 Glossary

- BGP Border Gateway Protocol
- BGP-CT BGP Classful Transport
- ECMP Equal-Cost Multipath
- EVPN Ethernet Virtual Private Network
- IGP Interior Gateway Protocol
- LSP Label-switched path
- MPLS Multiprotocol Label Switching
- PE Provider Edge
- SP Service Provider
- SPF Shortest Path First
- SR Segment Routing
- SR-TE Segment Routing Traffic Engineering
- TE Traffic Engineering
- TED Traffic Engineering Database
- VPLS Virtual Private LAN Service

1.8 Acknowledgements

Thanks to Krzysztof Szarkowicz for the review and suggestions.



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

HPE

