



DC – AI – Routing – Switching – Security – Wireless – Automation

SRX Dynamic IP Objects aka Feed-server

An HPE Juniper Networking Techpost

Karel Hendrych

2025-11-30

HPE



Contents

1	SRX Dynamic IP Objects aka Feed-server	3
1.1	Introduction	3
1.2	The Demo Setup	4
1.3	Practical Example, The Lab Grade Way	5
1.4	Practical Example, The Production Grade Way	8
1.4.1	Foundation setup with server validation	8
1.4.2	SRX Password Authentication	11
1.4.3	SRX mutual certificate authentication	11
1.5	Tunables	12
1.5.1	Session-scan	12
1.5.2	Routing-instance	13
1.6	Conclusion	13
1.6.1	Appendix 1 – Scale and Performance	13
1.7	Useful links	15
1.8	Glossary	15
1.9	Acknowledgements	15

List of Figures

1	SRX Dynamic IP Objects aka Feed-server	3
2	SRX configuration / feed-server contents relationship	4
3	Features of the two feed-servers	5
4	Transmit vs Receive rate time series when loading and unloading dynamic IP object with 500k records	14

1 SRX Dynamic IP Objects aka Feed-server

Karel Hendrych - 11/30/2025

For a long time, the SRX has been able to periodically download IPv4 and IPv6 prefixes from external sources and map them to objects used in firewall policies. Essentially, this is the easiest way to automate the firewall rule base when rules act as templates, and IP sources or destinations are dynamic objects influenced by external automation. This Tech Post aims to provide a quick-start guide.




Figure 1: SRX Dynamic IP Objects aka Feed-server

1.1 Introduction

In environments with frequent changes to firewall rule base objects, where a static address book would be excessively large and where DNS objects do not apply, a viable option is the use of dynamic IP objects fetched by the SRX from an HTTPS server. The scale depends on the SRX platform; generally, hundreds of thousands of IPv4 and IPv6 prefix records can be loaded onto the firewall and updated periodically—without a commit operation. The interval for retrieving IP prefixes from the server is at minimum every 30 seconds, allowing changes to security policies to be implemented relatively quickly. The process is optimized by the SRX checking whether the file containing the prefixes has changed using the HTTP HEAD method.

In a simplified manner, the following graphic illustrates the relationship between the SRX *dynamic-address* configuration, typical web server contents, and security policy by using objects suitable for both source and destination match criteria in firewall rules for either blocking or allowing traffic.




Figure 2: SRX configuration / feed-server contents relationship

Specifically, access to the /32 IP prefixes 2.2.2.1 and 2.2.2.2, represented by the object *blacklist-1*, would be blocked. To implement any changes, the contents of the blacklist-1 file would need to be modified, and the *feed-1.tgz* file would need to be recreated. The object *whitelist-1* serves solely as a second sample object. Scale and performance aspects are partially covered in Appendix 1.

Multiple feed formats are supported; a detailed description is available in the [documentation](#). This article focuses on the bundle archive mode using *.tgz* archives. Most importantly, the following example types of IP addresses are supported:

- Single IP: 192.0.2.1, 2001:db8::1
- Prefix: 192.0.2.32/28, 2001:db8:1::/64
- IP range: 192.0.2.5-192.0.2.20, 2001:db8::5-2001:db8::20

Note - the skeleton configuration shown in the infographic is insecure because it lacks server certificate validation.

1.2 The Demo Setup

The demo setup covers the following scenarios:

- A simple feed server reachable by IP address, with no server certificate validation (using a self-signed certificate) and no SRX client authentication. This is the lab grade approach with the first Linux server hosting *feed-1.tgz*.
- Production grade, where the SRX validates the server certificate, incorporating the following authentication options for the SRX acting as an HTTP client:
 - No SRX client authentication (anonymous access)
 - SRX username-password authentication
 - SRX mutual certificate authentication

Implemented with the second Linux server hosting *feed-2.tgz*.

A non-goal is to provide a perfect setup that automatically renews the SRX certificate, checks revocation status, or hardens the HTTPS feed server service, including high availability.




Figure 3: Features of the two feed-servers

The prerequisites are a (v)SRX and a Linux system(s); specifically, this demonstration uses [Debian Linux 13](#) and an [SRX1600](#) with Junos 25.2R1-S1. Junos 25.2 is required for simple username/password authentication to the feed server.

1.3 Practical Example, The Lab Grade Way

The first step is to install a web server; [nginx](#) is one of the options. To install a lightweight version, including the *ssl-cert* utility for generating certificates, where the second command generates a sample “snakeoil” self-signed certificate used as the default demo certificate by Debian Linux:

```
1 apt install nginx-light ssl-cert
2 make-ssl-cert generate-default-snakeoil
```

Then, the following lines need to be uncommented in `/etc/nginx/sites-enabled/default`. The *snakeoil.conf* configuration line refers to the self-signed certificate and key generated by *make-ssl-cert* in the previous step:

```
1 listen 443 ssl default_server;
2 listen [::]:443 ssl default_server;
3
4 include snippets/snakeoil.conf;
```

nginx webserver service restart:

```
1 systemctl restart nginx
```

To test whether *nginx* is serving requests, the *openssl s_client* tool is handy for connecting to TLS-enabled sockets. The output should look similar to the one below:

```
1 openssl s_client -connect localhost:443
2
3 <SNIP>
4 Server certificate
```

```

5 -----BEGIN CERTIFICATE-----
6 MIIDBzCCAe+gAwIBAgIUHHM4yqsKDKagycJfR00vxwn6UQIwDQYJKoZIhvcNAQEL
7 BQAwGTEXMBUGA1UEAwOZGViaWFuLWVvYXItMDEwHhcNMjUxMDIwMjMyMzQ0WhcN
8 <SNIP>

```

To create bundle archive style feed data for ingestion by the SRX:

```

1 cd /var/www/html/
2 mkdir feed-1
3 echo 1.1.1.1 > feed-1/whitelist-1
4 echo 2.2.2.2 > feed-1/blacklist-1
5 tar czf feed-1.tgz feed-1/

```

Ideally, use the 2nd terminal window to follow the logs:

```
1 tail -f -n0 /var/log/nginx/access.log
```

Then, on the SRX, the following configuration:

- Sets up the feed server by its IP address, overrides the default update interval of 5 minutes, and adjusts the holding period for feed contents (if the feed cannot be reached) from one day to a week.
- Additionally, it defines the address objects *whitelist-1* and *blacklist-1*, linking them to the feed contents as explained in the infographics above.

```

1 set security dynamic-address feed-server debian-1 url https://10.0.0.10/feed-1.tgz
2 set security dynamic-address feed-server debian-1 update-interval 60
3 set security dynamic-address feed-server debian-1 hold-interval 604800
4 set security dynamic-address feed-server debian-1 feed-name whitelist-1 path feed-1/whitelist-1
5 set security dynamic-address feed-server debian-1 feed-name blacklist-1 path feed-1/blacklist-1
6 set security dynamic-address address-name whitelist-1 profile feed-name whitelist-1
7 set security dynamic-address address-name blacklist-1 profile feed-name blacklist-1

```

Upon committing the configuration, the status of the feed server and its feeds on the SRX can be viewed using the following command:

```

1 show security dynamic-address summary
2
3 Dynamic-address session scan status : Disable
4 Hold-interval for dynamic-address session scan : 10 seconds
5
6   Server Name : debian-1
7     Hostname/IP : https://10.0.0.10/feed-1.tgz
8     Update interval : 60
9     Hold interval : 604800
10    TLS Profile Name : ---
11    User Name : ---
12
13   Feed Name : blacklist-1
14     Mapped dynamic address name : blacklist-1
15     URL : https://10.0.0.10/feed-1.tgz
16     Feed update interval : 60 Feed hold interval : 604800
17     Total update : 0
18     Total IPv4 entries : 1
19     Total IPv6 entries : 0
20     Total download errors : 0 Last occurrence N/A
21     Total db errors : 0 Last occurrence N/A
22     Total other errors : 0 Last occurrence N/A
23     Total ageout : 0 Last occurrence N/A
24     Next update time : Thu Oct 23 16:18:25 2025
25     Next expire time : Thu Oct 30 16:40:26 2025
26     Flags : 0x8
27     Last update file size : 0
28     Last update IPv4 entries : 1
29     Last update IPv6 entries : 0
30     Last update begin time : N/A
31     Last update end time : Thu Oct 23 16:17:25 2025
32     Last update time cost(s) : 1761229045
33     Last download begin time : N/A
34     Last download end time : N/A
35     Last update status : 10
36     Last download time cost(s) : --
37

```

```
38 <SNIP>
```

Dynamic IP addresses can be viewed on the SRX using the following command:

```
1 show security dynamic-address
2
3 No. IP-start IP-end Feed Address
4 1 1.1.1.1 1.1.1.1 whitelist-1 whitelist-1
5 2 2.2.2.2 2.2.2.2 blacklist-1 blacklist-1
```

The following entries should appear on the console tailing access.log. The first log entry shows the data fetch, while the subsequent two entries indicate probes to determine whether the file has changed:

```
1 10.0.0.2 - - [23/Oct/2025:12:42:59 +0200] "GET /feed-1.tgz HTTP/1.1" 200 229 "-" "-"
2 10.0.0.2 - - [23/Oct/2025:12:43:59 +0200] "HEAD /feed-1.tgz HTTP/1.1" 200 0 "-" "-"
3 10.0.0.2 - - [23/Oct/2025:12:44:58 +0200] "HEAD /feed-1.tgz HTTP/1.1" 200 0 "-" "-"
```

On the SRX, feeds are processed by the ipfd process, and the related logs provide visibility into the events:

```
1 show log messages | match ipfd
2
3 ipfd[8259]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-1) download data(https://10.0.0.10/feed-1.
  tgz) status (succeeded) start time (<SNIP>)
4 ipfd[8259]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-1) download data(https://10.0.0.10/feed-1.
  tgz) status (succeeded<file not changed>) start time (<SNIP>)
5 ipfd[8259]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-1) download data(https://10.0.0.10/feed-1.
  tgz) status (succeeded<file not changed>) start time (<SNIP>)
```

To validate whether updates to the feed contents are being propagated to the SRX:

```
1 cd /var/www/html
2 echo 1.1.1.2 >> feed-1/whitelist-1
3 tar czf feed-1.tgz feed-1/
```

According to the *nginx* logs, SRX detected change of the file and did a new download:

```
1 tail -f -n0 /var/log/nginx/access.log
2 <SNIP>
3 10.0.0.2 - - [23/Oct/2025:13:02:59 +0200] "HEAD /feed-1.tgz HTTP/1.1" 200 0 "-" "-"
4 10.0.0.2 - - [23/Oct/2025:13:02:59 +0200] "GET /feed-1.tgz HTTP/1.1" 200 229 "-" "-"
```

Also reflected in the SRX logs:

```
1 ipfd[8259]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-1) download data(https://10.0.0.10/feed-1.
  tgz) status (succeeded) start time (<SNIP>)
```

And in the dynamic address listing:

```
1 show security dynamic-address
2
3 No. IP-start IP-end Feed Address
4
5 1 1.1.1.1 1.1.1.1 whitelist-1 whitelist-1
6 2 1.1.1.2 1.1.1.2 whitelist-1 whitelist-1
7 3 2.2.2.2 2.2.2.2 blacklist-1 blacklist-1
```

Finally, to apply the dynamic-object in the firewall policy:

```
1 set security policies from-zone trust to-zone untrust policy block-some match destination-
  address ?
2
3 Possible completions:
4 <SNIP>
5 blacklist-1
6 whitelist-1
```

1.4 Practical Example, The Production Grade Way

In this more complex example, the demo setup will use a demonstration PKI to closely resemble a real-world scenario. In the first stage, the SRX will access the feed server anonymously while validating the server certificate. The next stage will implement username and password authentication, followed by mutual certificate authentication as the final stage.

1.4.1 Foundation setup with server validation

As a first step, the PKI needs to be set up. While a professional PKI should be considered for real-world applications, for demonstration purposes, a simple *OpenSSL* wrapper called [SRX_VPN_demo_CA](#), originally designed to support SRX PKI-based VPN demos, will suffice. To install and set up the CA on a Linux host (e.g., the feed server itself):

```
1 apt install git
2 git clone https://github.com/JNPRAutomate/SRX_VPN_demo_CA
3 cd SRX_VPN_demo_CA
4 chmod 755 .needed_binaries.sh *.sh
```

Using the *sed* line editor, the default certificate subjects need to be altered in the next step.

- The first line swaps *srx.domain.tld* with the string *debian-2* in a file that lists the server certificates to be generated (*cert_list_server*), which will then be used by the SRX as the hostname for reaching out to the feed server.
- The second *sed* line deletes the default sample record for *user2* and replaces *user1* with the string *srx-1* in the *cert_list_user* file (to be used in the mutual certificate authentication stage).

```
1 sed -i "s/srx.domain.tld/debian-2/" cert_list_server
2 sed -i -e "/user2@cert.auth/d" -e "s/user1@cert.auth/srx-1/" cert_list_user
```

The following commands initialize the CA key and certificate with the subject *IPFD_CA*, valid for 10 years, along with the keys and certificates for the SRX and *nginx*, each with subject defined in the previous step and valid for two years:

```
1 ./1_CA_init.sh IPFD_CA 3650
2 ./2_CA_gencerts_from_cert_list-server.sh 730
3 ./3_CA_gencerts_from_cert_list-user.sh 730
```

Similar to the first example, the first step on the Linux machine is to install a web server; this time, however, it will be done without a *snakeoil* sample self-signed certificate and will include the *apache2-utils* package for creating HTTP authentication credentials:

```
1 apt install nginx-light apache2-utils
```

Place the CA key, certificate, and key into the corresponding locations for use by *nginx*. The files are located in the CA sub-folder within the *SRX_VPN_demo_CA* folder. The CA certificate will be used by the webserver in the final stage for mutual client authentication:

```
1 cp CA/cacert.pem /etc/ssl/certs/IPFD_CA.pem
2 cp CA/debian-2-cert.pem /etc/ssl/certs/
3 cp CA/debian-2-key.pem /etc/ssl/private/
```

A basic good practice is to restrict access to the private key so that only the root user has permission to access it:

```
1 chmod 600 /etc/ssl/private/debian-2-key.pem
```

Then, the following lines need to be uncommented in `/etc/nginx/sites-enabled/default`. However, instead of uncommenting `snakeoil.conf`, a custom include line needs to be added:

```
1 listen 443 ssl default_server;
2 listen [::]:443 ssl default_server;
3 # include snippets/snakeoil.conf;
4 include snippets/IPFD.conf;
```

The contents of `/etc/nginx/snippets/IPFD.conf` need to point to the certificate and private key generated in the PKI setup step:

```
1 ssl_certificate /etc/ssl/certs/debian-2-cert.pem;
2 ssl_certificate_key /etc/ssl/private/debian-2-key.pem;
```

To complete the web server setup, restart the service using the following command:

```
1 systemctl restart nginx
```

To validate if the TLS socket is enabled, again the `openssl s_client` tool is helpful:

```
1 openssl s_client -connect localhost:443
2
3 Connecting to ::1
4 CONNECTED(00000003)
5 Can't use SSL_get_servername
6 depth=0 CN=debian-2
7 verify error:num=20:unable to get local issuer certificate
8 verify return:1
9 depth=0 CN=debian-2
10 verify error:num=21:unable to verify the first certificate
11 verify return:1
12 depth=0 CN=debian-2
13 verify return:1
14 Server certificate
15 -----BEGIN CERTIFICATE-----
16 MIIFGjCCAwKgAwIBAgIBAjANBgkqhkiG9w0BAQsFADASMRAdGgYDVQQDDAdJUEZE
```

Initial feed data setup:

```
1 cd /var/www/html/
2 mkdir feed-2
3 echo 10.1.1.1 > feed-2/whitelist-2
4 echo 10.2.2.2 > feed-2/blacklist-2
5 tar czf feed-2.tgz feed-2/
```

Ideally in the 2nd terminal window logs to be followed:

```
1 tail -f -n0 /var/log/nginx/access.log
```

On the SRX, before importing the CA certificate, the CA profile needs to be configured.

```
1 set security pki ca-profile IPFD_CA ca-identity IPFD_CA revocation-check disable
```

Note - no revocation checking is enabled for the sake of simplicity, although the demonstration CA can create a Certificate Revocation List (CRL).

Creating the CA profile is followed by loading the CA certificate. Before doing so, the `cacert.pem` file from the CA sub-folder located in the `SRX_VPN_demo_CA` folder needs to be uploaded to the SRX.

```
1 request security pki ca-certificate load ca-profile IPFD_CA filename cacert.pem
```

It is good practice to validate the CA certificate on the SRX to ensure its integrity and proper configuration. This can be done using the following command:

```

1 request security pki ca-certificate verify ca-profile IPFD_CA
2 CA certificate IPFD_CA verified successfully. revocation check disabled

```

Note – if a non-trusted issuer is used (e.g., if the CA certificate has not been loaded onto the SRX), the following log message would occur during certificate validation:

```

1 show log messages | match ipfd
2
3 ipfd[8259]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-2) download data(https://debian-2/feed-2.
  tgz) status (failed<connection error: SSL peer certificate or SSH remote key was not OK>)
  start time (<SNIP>)

```

Then, on the SRX, the following configuration:

- Sets up the feed server by its hostname recorded in static-host-mapping (this is needed unless it is present in DNS).
- Configures SSL initiation profile with trusted CA referenced in the feed-server configuration.
- Overrides the default update interval of 5 minutes and defines the holding period for feed contents if the feed cannot be reached, adjusting it from one day to a week.
- Defines the objects *whitelist-1* and *blacklist-1*, linking them with the feed contents as explained in the introduction's infographics.
- Server certificate validation will be enforced by referring to the trusted CA and ensuring that the subject's common name or subject alternative name matches the configured feed server name.

```

1 set system static-host-mapping debian-2 inet 10.0.1.10
2 set services ssl initiation profile srx-1_IPFD_CA trusted-ca IPFD_CA
3
4 set security dynamic-address feed-server debian-2 url https://debian-2/feed-2.tgz
5 set security dynamic-address feed-server debian-2 update-interval 60
6 set security dynamic-address feed-server debian-2 hold-interval 86400
7 set security dynamic-address feed-server debian-2 tls-profile srx-1_IPFD_CA
8 set security dynamic-address feed-server debian-2 validate-certificate-attributes subject-or-
  subject-alternative-names
9 set security dynamic-address feed-server debian-2 feed-name whitelist-2 path feed-2/whitelist-2
10 set security dynamic-address feed-server debian-2 feed-name blacklist-2 path feed-2/blacklist-2
11 set security dynamic-address address-name whitelist-2 profile feed-name whitelist-2
12 set security dynamic-address address-name blacklist-2 profile feed-name blacklist-2

```

The dynamic IP addresses can be viewed on the SRX using the following command:

```

1 show security dynamic-address
2
3 No. IP-start IP-end Feed Address
4 1 10.1.1.1 10.1.1.1 whitelist-2 whitelist-2
5 2 10.2.2.2 10.2.2.2 blacklist-2 blacklist-2

```

Note – in case of issues, in addition to reviewing the logs, use *show security dynamic-address summary* command on the SRX to display status of dynamic addresses.

The following entries should appear on the console that was previously used to tail access.log. The first log entry indicates the fetch of the data, while the subsequent two entries represent probes to check whether the file has changed:

```

1 tail -f /var/log/nginx/access.log
2
3 <SNIP>
4 10.0.1.2 - - [23/Oct/2025:14:47:36 +0200] "GET /feed-2.tgz HTTP/1.1" 200 220 "-" "-"
5 10.0.1.2 - - [23/Oct/2025:14:48:36 +0200] "HEAD /feed-2.tgz HTTP/1.1" 200 0 "-" "-"
6 10.0.1.2 - - [23/Oct/2025:14:48:36 +0200] "HEAD /feed-2.tgz HTTP/1.1" 200 0 "-" "-"

```

Note – to trigger as certificate attribute validation issue, a simple test can be performed by changing the hostname from *debian-2* to *debian-3* in both the static host mapping and the feed URL:

```
1 set system static-host-mapping debian-3 inet 10.0.1.10
2 set security dynamic-address feed-server debian-2 url https://debian-3/feed-2.tgz
```

Sample error logs after changing the hostname:

```
1 show log messages | match ipfd
2
3 ipfd[8259]: IPFD_DA_FEED_CERT_SUBJ_CHECK_FAIL: Certificate attributes subject/subject-
  alternative-names do not match feed server host name debian-3!
4 ipfd[8259]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-2) download data(https://debian-3/feed-2.
  tgz) status (failed<connection error: SSL peer certificate or SSH remote key was not OK>)
```

1.4.2 SRX Password Authentication

With Junos 25.2R1, basic HTTP authentication can be used by the SRX acting as the client. To configure the web server, the following needs to be added to */etc/nginx/sites-enabled/default*:

```
1 location / {
2     auth_basic "Restricted Area";
3     auth_basic_user_file /etc/nginx/htpasswd;
4     <SNIP>
5 }
```

Username and password creation, where *-c* creates a new file and *-b* uses the supplied password after the username *srx*:

```
1 htpasswd -c -b /etc/nginx/htpasswd srx juniper123
```

To complete the web server adjustment, restart the service using the following command:

```
1 systemctl restart nginx
```

Since then, the SRX won't be able to reach the feed, which will be reflected in the logs as follows:

```
1 show log messages | match ipfd
2
3 ipfd[8095]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-2) download data(https://debian-2/feed-2.
  tgz) status (failed<http return error code 401>) start time (<SNIP>)
```

SRX side configuration expanded by username and password setting:

```
1 set security dynamic-address feed-server debian-2 user-name srx
2 set security dynamic-address feed-server debian-2 password juniper123
```

After the settings in the previous step, the feed data is successfully fetched:

```
1 show log messages | match ipfd
2
3 ipfd[8095]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-2) download data(https://debian-2/feed-2.
  tgz) status (succeeded) start time (<SNIP>)
```

1.4.3 SRX mutual certificate authentication

To enhance security, access to a particular folder on the web server can be protected by requiring the client to present its certificate during the TLS handshake. A granular approach allows this requirement to be optional and enforceable on specific folders, as shown in the example of */etc/nginx/sites-enabled/default* below. The

password authentication mentioned in the previous paragraph can either be left intact or commented out; the former option enables both password and mutual certificate authentication.

```

1      ssl_client_certificate /etc/ssl/certs/IPFD_CA.pem;
2      ssl_verify_client optional;
3
4      location / {
5          if ($ssl_client_verify != SUCCESS) {
6              return 403;
7          }
8          <SNIP>
9      }

```

Upon restarting *nginx*, the SRX will be unable to access the feed data, and the following logs will appear:

```

1  show log messages | match ipfd
2
3  ipfd[8095]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-2) download data(https://debian-2/feed-2.
    tgz) status (failed<http return error code 403>) start time (<SNIP>)

```

In the next step, the *srx-1-cert.pem* and *srx-1-key.pem* files located in the CA sub-folder within the *SRX_VPN_demo_CA* need to be uploaded to the SRX, followed by loading them to the SRX storage:

```

1  request security pki local-certificate load certificate-id srx-1_IPFD_CA filename srx-1-cert.pem
    key srx-1-key.pem

```

Similarly to CA certificate validation, the device certificate can be validated to ensure its integrity and proper configuration:

```

1  request security pki local-certificate verify certificate-id srx-1_IPFD_CA
2  local certificate srx-1_IPFD_CA verification success

```

Then, the SRX configuration needs to be expanded to include a reference to the client certificate in the SSL initiation profile, which was previously used only for validating the server certificate issued by a specific CA:

```

1  set services ssl initiation profile srx-1_IPFD_CA client-certificate srx-1_IPFD_CA

```

Upon committing the changes, the feed contents can be fetched again, this time with mutual certificate authentication enabled between the SRX and the web server:

```

1  show log messages | match ipfd
2
3  ipfd[8095]: IPFD_DA_FEED_HTTPS_STATUS: Feed(whitelist-2) download data(https://debian-2/feed-2.
    tgz) status (succeeded) start time (<SNIP>)

```

1.5 Tunables

1.5.1 Session-scan

The SRX is capable of reconciling existing sessions when addresses are added to the feeds (not removed). To enable this functionality:

```

1  set security dynamic-address session-scan

```

Session scanning works with policies that have a deny or reject action. For instance, when removing an address from *whitelist-1* (which permits otherwise blocked HTTP access), that address needs to be added to *blacklist-1* (at least temporarily, until all sessions are removed) so that the *reject-http* rule is triggered:

```

1  policy reject-http {
2      match {

```

```

3      source-address any;
4      destination-address blacklist-1;
5      application junos-http;
6  }
7  then {
8      reject;
9  }
10 }
11 policy permit-http {
12     match {
13         source-address any;
14         destination-address whitelist-1;
15         application junos-http;
16     }
17     then {
18         permit;
19     }
20 }
21 policy deny-http-all {
22     match {
23         source-address any;
24         destination-address any;
25         application junos-http;
26     }
27     then {
28         deny;
29     }
30 }

```

1.5.2 Routing-instance

In some cases, the feed server may be reachable through a custom routing instance instead of the master *inet.0* instance. To accommodate this situation, the following hidden configuration stanza exists. The format is *table.inet* without the typical trailing *.0* character. For example:

```

1 set routing-instances vr-1 instance-type virtual-router
2 set security dynamic-address feed-server debian-1 routing-table vr-1.inet

```

1.6 Conclusion

Dynamic IP objects on SRX platforms provide a simple yet powerful mechanism for automating security policies in environments with frequent address changes. By leveraging feed servers that deliver IP prefixes, administrators can maintain flexible, scalable rule bases without manual intervention or potentially disruptive commit operations. While the lab grade approach offers simplicity, implementing certificate validation and authentication ensures a more secure, production-ready setup. Performance tests confirm that SRX devices can handle large-scale dynamic updates efficiently, but careful planning and validation remain essential for large-scale deployments. Ultimately, dynamic IP objects enable faster policy adaptation, improved operational agility, and a stronger security posture in modern, dynamic networks.

1.6.1 Appendix 1 – Scale and Performance

The scale of the IP dynamic-address objects is dependent on the SRX platform. For example, here are three sample SRX platforms:

Platform	Junos	Max IPv4	Max IPv6	Servers	Objects	Feeds
SRX300	23.4R2	600k	300k	256	256	256

Platform	Junos	Max IPv4	Max IPv6	Servers	Objects	Feeds
SRX1600	25.2R1	1M	500k	5k	5k	5k
SRX4700	25.2R1	1M	500k	5k	5k	5k

The maximum scale data can be retrieved from /var/log/ipfd. However, if a large scale is being considered, it is always recommended to validate using testing equipment. IPv4 and IPv6 scale is logical AND. Below is a sample of raw scale data from the ipfd log for SRX1600 running Junos 25.2R1-S1.4:

```

1  Setup Matching Platform Capacity Config
2  -----
3  Matching platform :
4  Model Name = srxtvp
5  Hardware Model = srxtvp
6  Description = srxtvp
7  Dynamic address capacity:
8  max IP entries: 1000000
9  max IPv6 entries: 500000
10 max servers: 5000
11 max dynamic address names: 5000
12 max feeds: 5000
13  -----

```

The time-series chart below shows indicative measurements for dynamic IP address load and unload operations in the SRX PFE (SRX1600, Junos 25.2R1-S1)

- In the synthetic test, 500,000 IPv4 endpoints were sending 500,000 Packets Per Second (PPS) to another set of 500,000 endpoints (1:1 communication with 1 PPS per endpoint pair).
- The red line represents the transmit rate, while the blue line represents the receive rate.
- At approximately 3:14 (when statistics were cleared), the SRX downloaded, according to the logs, a dynamic address object containing the 500,000 IPv4 /32 prefixes used as source addresses for allowing.
- At around 3:54, the receive rate matched the transmit rate, indicating no packet loss (all the objects became effective in the PFE).
- Conversely, when the 500,000 IP addresses were moved from a whitelist to a blacklist (with session scan enabled), it took approximately 50 seconds to drop all communication.



Figure 4: Transmit vs Receive rate time series when loading and unloading dynamic IP object with 500k records

Note - the time to load or unload dynamic objects in such a test is impacted by the packet rate causing PFE load, even if the traffic is subjected to drops (the [drop-flow](#) feature was disabled to avoid interfering with the traffic getting allowed). Once traffic is permitted, an effective connection in the session table is established for each of the permitted flows, up to 500,000 concurrent connections.

1.7 Useful links

- <https://www.juniper.net/documentation/us/en/software/junos/security-policies/topics/topic-map/security-policy-configuration.html#id-dynamic-address-groups-in-security-policies>
- <https://www.juniper.net/us/en/dm/download-next-gen-vsrx-firewall-trial.html>
- <https://www.debian.org/distrib/>
- <https://nginx.org/>

1.8 Glossary

- CA: Certificate Authority
- CLI: Command Line Interface
- CRL: Certificate Revocation List
- DNS: Domain Name System
- HTTP: Hypertext Transfer Protocol
- HTTPS: Hypertext Transfer Protocol Secure
- IP: Internet Protocol
- PFE: Packet Forwarding Engine
- PKI: Public Key Infrastructure
- PPS: Packets Per Second
- SSH: Secure Shell
- SSL: Secure Socket Layer
- TLS: Transport Layer Security
- UDP: User Datagram Protocol
- VPN: Virtual Private Network

1.9 Acknowledgements

I would like to thank Nicolas Fevrier for overseeing the Tech Posts site and handling all the publishing tasks. I also want to acknowledge all the colleagues who provided valuable feedback, namely Mark Barrett, Steven Jacques and Laurent Paumelle. A special thanks goes to the vSRX/SRX development and product teams for delivering the Swiss Army knife of security and networking! Finally, things would be complicated without all the brilliant open-source software.



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

HPE

