



DC – AI – Routing – Switching – Security – Wireless – Automation

SRX/CloudATP Multi-Tenant DNS Filtering

An HPE Juniper Networking Techpost

Karel Hendrych

2024-12-28

HPE



Contents

1	SRX/CloudATP Multi-Tenant DNS Filtering	3
1.1	Introduction	3
1.2	Topology	3
1.3	Summary of Steps	4
1.3.1	CloudATP Setup	4
1.3.2	CloudATP Tenant Realms	6
1.3.3	CloudATP API Setup	9
1.3.4	SRX Settings	10
1.4	Verification	12
1.4.1	Encrypted DNS	13
1.5	Appendix: Configurations	14
1.5.1	Appendix 1: base SRX config	14
1.5.2	Appendix 2: Sample CloudATP Enrollment	15
1.6	Conclusion	15
1.7	Useful links	16
1.8	Glossary	16
1.9	Acknowledgments	16

List of Figures

1	demo setup topology	4
2	CloudATP realm setup	5
3	CloudATP SRX enrollment	6
4	list of enrolled SRX devices	6
5	setup of subordinate realms	7
6	sub-ordinate realm attachment	7
7	selection of realms from DNSF-ROOT	8
8	assignment of devices to sub-ordinate realm	8
9	device association to sub-ordinate realms	8
10	device view from sub-ordinate realm	9
11	API token setup	9
12	CloudATP tenant DNS action view	13

1 SRX/CloudATP Multi-Tenant DNS Filtering

Karel Hendrych - 12/28/2024

Describes the ability of the Juniper SRX, in conjunction with the CloudATP service, to enforce DNS query blocking through an API-driven, multi-tenant approach. Each tenant has its own virtual router, ingress zone, dedicated API token, and independent visibility for granular control and operational separation.

1.1 Introduction

Lately, security intelligence services on perimeter firewalls that categorize threat levels for IP addresses and URLs have become a common basic measure to prevent access to known malicious destinations. Companies are also utilizing their own threat intelligence data to enhance vendor and third-party feeds. In certain situations, multi-tenancy with custom threat intelligence on the same physical or virtual firewall may be required. This includes separation from the perspective of the API used to modify the lists of DNS queries to block or sinkhole, as well as ensuring corresponding visibility regarding the actions taken. For example, this could apply to an IoT security use case.

In more detail, the following text explains the ability of [CloudATP](#)-enabled SRX devices to filter DNS queries by using per-tenant security intelligence feeds. This is achieved by assigning the SRX device to a CloudATP realm, mapping individual routing instances to API-enabled subordinate realms, and enabling granular DNS query control.

This feature set is available on premium-tier licensed SRX devices because of the use of the CloudATP API. However, an easy way to try it out is by using vSRX with a security subscription [Trial license](#) available for registered customers and partners. Alternatively, licenses can be obtained through Juniper sales representatives.

1.2 Topology

Let's consider the following topology. The base configuration of the SRX is detailed in Appendix 1, while the expansion through Secintel settings will be addressed in the upcoming sections. Two tenants, designated as green-colored T1 and blue-colored T2, each have their own virtual router instance linked to the corresponding zone (T1 or T2) via an interface. The default gateway is imported from the VR-COMMON routing instance, which has an interface assigned to the common source NAT-enabled UNTRUST zone leading to the Internet. This default gateway import is unidirectional, utilizing the established flow for return traffic.




Figure 1: demo setup topology

1.3 Summary of Steps

In summary, the approach involves the administrator of the entire setup to:

- Enroll the SRX into a CloudATP realm called, for example, DNSF-ROOT.
- Follow this with the creation of two additional CloudATP realms, DNSF-T1 and DNSF-T2, which are attached to DNSF-ROOT.
- In the Managed Security Services Provider (MSSP) style DNSF-ROOT realm, assign VRs T1 and T2 to the corresponding realms.
- Once the SRX-CloudATP setup is complete, establish API tokens for the tenant realms.
- Follow this with the SRX-side feed and enforcement configuration.
- Complete the API data load and verification as the final steps.

In this specific example, a challenging aspect of DNS is the use of encryption methods such as DNS over TLS (DoT) and DNS over HTTPS (DoH) by clients, which can evade DNS filtering. This topic will be discussed in the Encrypted DNS section.

1.3.1 CloudATP Setup

The prerequisite is either a commercial Premium CloudATP tier or any Premium trial assigned on the cloud side to the physical SRX serial number. In the case of vSRX, Premium entitlement to the software serial number of the ATP license on the cloud side is required. For vSRX, a [Trial license](#) set can be immediately used by registered users.

To establish a Cloud ATP realm, a Juniper account must be used in the corresponding region selected on [the global CloudATP page](#).

ATP Cloud ?

●

●

●

Realm InfoContact InfoUser Credentials

Version 3.0 | Create security realm

Use this page to create a security realm with a name that is meaningful to your organization. A realm name can only contain alphanumeric characters and the dash symbol. Once created, this name cannot be changed.

[Terms of use](#)

Security Realm Name* ?

demo-dnsf-root

Company Name* ?

Juniper Networks

Figure 2: CloudATP realm setup

In the next step, the SRX device needs to be enrolled by executing the proposed request command in the SRX CLI:




Figure 3: CloudATP SRX enrollment

Note: in case of enrollment issues, the output can be compared to the successful enrollment output provided in Appendix 2.

Upon CloudATP enrollment, the list of devices will include the actual physical or virtual SRX, as well as arbitrary devices representing routing instances:

☐	Host	Realm	Serial Number	Model Number	Tier
☐	vsrx-dnsf:[root logical domain]:vr-t1		f8ef568918e0@20161111	VSRX	premium
☐	vsrx-dnsf:[root logical domain]:vr-t2		f8ef568918e0@20161111	VSRX	premium
☐	vsrx-dnsf:[root logical domain]:vr-common		f8ef568918e0@20161111	VSRX	premium
☐	vsrx-dnsf		f8ef568918e0@20161111	VSRX	premium

Figure 4: list of enrolled SRX devices

1.3.2 CloudATP Tenant Realms

In the next steps, realms for attaching to the DNSF-ROOT realm need to be created from the initial CloudATP page using the same process for both DNSF-T1 and DNSF-T2, as there is no separate process for subordinate realms:

ATP Cloud ?

● — ○ — ○

Realm Info Contact Info User Credentials

Version 3.0 | Create security realm ?

Use this page to create a security realm with a name that is meaningful to your organization. A realm name can only contain alphanumeric characters and the dash symbol. Once created, this name cannot be changed.

[Terms of use](#)

Security Realm Name* ?

Company Name* ?

Figure 5: setup of subordinate realms

Newly created realms must be attached in the DNSF-ROOT under Misc Configuration/Realm Management:

The screenshot shows the 'Attach Realm' dialog box in the DNSF-ROOT interface. The dialog box is titled 'Attach Realm ?' and contains the instruction 'Provide credentials to attach a realm.' It has three input fields: 'Username*', 'Password*', and 'Realm*'. At the bottom of the dialog box are 'Cancel' and 'OK' buttons. In the background, the 'Realm Management' section of the DNSF-ROOT interface is visible, showing a table with columns for 'Attach Realm' and 'Date Added'.

Figure 6: sub-ordinate realm attachment

After attaching the realms, a drop-down for realm selection will be available in the upper right corner of the DNSF-ROOT:




Figure 7: selection of realms from DNSF-ROOT

As the next step, in the DNSF-ROOT realm management, device association (Virtual Routers) to realms is configured:




Figure 8: assignment of devices to sub-ordinate realm

For example, the resulting list of MSSP-style realms and their associated VR devices:




Figure 9: device association to sub-ordinate realms

Naturally, when logging in as the DNSF-T1/T2 admin, the management scope is limited to the specific realm, with no realm selection drop-down available:




Figure 10: device view from sub-ordinate realm

1.3.3 CloudATP API Setup

As noted in the introduction, the purpose of the API is to provide a programmatic approach to loading a custom list of prohibited domains. In an MSSP environment, one tenant may permit certain domains while others may block them, with each having separate API access.

For the next steps, create folders representing tenants on a Linux/Unix machine equipped with bash and curl, e.g., demo-dnsf-t1 and demo-dnsf-t2.

API token setup is done individually at the tenant realm, either by selecting a particular realm from DNSF-ROOT or by logging in directly. API tokens are created in Administration under Application Tokens:




Figure 11: API token setup

Insert the individual API tokens for both tenants into the api-token.txt file located in the corresponding folder created in the previous step:

```
1 # echo "DNSF-T1-API-TOKEN" > demo-dnsf-t1/api-token.txt
2 # echo "DNSF-T2-API-TOKEN" > demo-dnsf-t2/api-token.txt
```

The Juniper Threat Intelligence Open API ([documentation](#)) offers a patch option for manipulating feed data (recommended method); however, the easiest option for a lab trial is to recreate the feed object.

A simple one-liner script, `api-create-feed.sh`, taking the first argument as the DNS feed name and the second as the submitted file containing domain names, may look as follows:

```
1 #!/bin/bash
2 curl --form file=@$2 --request POST \
3 --url https://threat-api.sky.junipersecurity.net/v2/cloudfeeds/DNS/file/$1 \
4 --header "Authorization: Bearer `cat api-token.txt`" \
```

Similarly, here is a one-liner `api-delete-feed.sh` script for deleting the DNS feed, which accepts the DNS feed name as the first argument:

```
1 #!/bin/bash
2 curl --request DELETE \
3 --url https://threat-api.sky.junipersecurity.net/v2/cloudfeeds/DNS/param/$1 \
4 --header "Authorization: Bearer `cat api-token.txt`" \
5 --header 'Content-Type: multipart/form-data' \
6 --form 'server=*
```

For example, the `domains.txt` file contains a list of arbitrary sample domains with a threat level of 10 (which can be referenced in policies in terms of actions).

```
1 smartweb2595.com,10
2 newstore1460.com,10
3 topapp5226.com,10
4 topstore7658.com,10
5 newapp5634.com,10
6 topweb8022.com,10
7 happyzone8922.com,10
8 smartzone3594.com,10
9 smartspace9672.com,10
10 newstore4752.com,10
```

Finally, this may be a simple wrapper script, `xreload_feed.sh`, that calls the previously created one-liner scripts for creating and deleting the feed for DNSF-T2:

```
1 #!/bin/bash
2 ./api-delete-feed.sh demo_dnsf_t2
3 ./api-create-feed.sh demo_dnsf_t2 domains.txt
```

Sample reload of DNS feeds for both tenants from their corresponding folders:

```
1 demo-dnsf-t1# ./xreload_feed.sh
2 {"message":"Successfully deleted feed.", "request_id":"0bd1e788-f2ab-41c6-b6c1-2d8aee6b8c58"}
3 {"request_id":"7a0fdadb-9850-4061-8192-d45fc6178c33"}
4
5 demo-dnsf-t2# ./xreload_feed.sh
6 {"message":"Successfully deleted feed.", "request_id":"6a0096e7-2411-445d-8c10-be12b740e534"}
7 {"request_id":"73fa6064-33ec-4ea7-bec9-20b16fac2128"}
```

1.3.4 SRX Settings

In addition to the sample base configuration available in Appendix 1, the following configuration sets up the SRX Security Intelligence to use the API-created feeds. All matching DNS domain requests flagged with a threat level of 10 will be discarded and logged:

```
1 set services security-intelligence profile t1 category DNS
2 set services security-intelligence profile t1 rule 1 match feed-name demo_dnsf_t1
3 set services security-intelligence profile t1 rule 1 match threat-level 10
4 set services security-intelligence profile t1 rule 1 then action block drop
5 set services security-intelligence profile t1 rule 1 then log
6 set services security-intelligence profile t2 category DNS
7 set services security-intelligence profile t2 rule 1 match feed-name demo_dnsf_t2
8 set services security-intelligence profile t2 rule 1 match threat-level 10
```

```

9  set services security-intelligence profile t2 rule 1 then action block drop
10 set services security-intelligence profile t2 rule 1 then log

```

Note: if the Juniper-supplied DNS threat feed is not used in any other profile, the following configuration can be used to disable it:

```

1  set services security-intelligence global-disable-feed feed-name global_dns

```

Then, the profiles are referenced by the Security Intelligence policy:

```

1  set services security-intelligence policy t1 DNS t1
2  set services security-intelligence policy t2 DNS t2

```

And Security Intelligence policies are referenced by the actual firewall policies:

```

1  edit security policies
2  set from-zone t1 to-zone common policy t1 then permit application-services security-intelligence
   -policy t1
3  set from-zone t2 to-zone common policy t2 then permit application-services security-intelligence
   -policy t2

```

To receive Secintel logs in the CloudATP portal via the data plane channel, the source interface needs to be specified due to the use of a non-default routing table towards the Internet. Additionally, for simple on-box logging, the JWeb report infrastructure can be used:

```

1  set services advanced-anti-malware connection source-interface ge-0/0/0.0
2  set security log report

```

The first place to verify whether the DNS feeds have been loaded is in the summary view of Secintel categories, where 'Vrf name' represents the Virtual Router attribute of the feed. Internally, the SRX adds an extra dimension of the routing instance to the feeds received from the CloudATP DNSF-ROOT realm:

```

1  > show services security-intelligence category summary
2
3  Category name :DNS
4  Status :Enable
5  Description :DNS sinkhole
6  Update interval :60s
7  TTL :3456000s
8  Feed name :demo_dnsf_t1
9  logical-system:root-logical-system
10 Vrf name :vr-t1
11 Version :20241125.0
12 Objects number:10
13 Create time :2024-11-25 09:33:50 CET
14 Update time :2024-11-25 09:40:27 CET
15 Update status :Store succeeded
16 Expired :No
17 Status :Active
18 Options :N/A
19 Feed name :demo_dnsf_t2
20 logical-system:root-logical-system
21 Vrf name :vr-t2
22 Version :20241125.0
23 Objects number:10
24 Create time :2024-11-25 09:34:58 CET
25 Update time :2024-11-25 09:40:27 CET
26 Update status :Store succeeded
27 Expired :No
28 Status :Active
29 Options :N/A

```

The content of the feed for the DNS category can be viewed as follows:

```

1  > show services security-intelligence category detail category-name DNS feed-name demo_dnsf_t1
2
3  Category name :DNS
4  Feed name :demo_dnsf_t1
5  logical-system:root-logical-system

```

```

6  Vrf name :vr-t1
7  Version :20241125.0
8  Objects number:10
9  Create time :2024-11-25 09:33:50 CET
10 Update time :2024-11-25 09:41:03 CET
11 Update status :Store succeeded
12 Expired :No
13 Options :N/A
14 { url:coolsite3022.com threat_level:10}
15 { url:fastweb7639.com threat_level:10}
16 { url:greatsite8880.com threat_level:10}
17 { url:greattech2443.com threat_level:10}
18 { url:happyworld5071.com threat_level:10}
19 { url:mytech2524.com threat_level:10}
20 { url:newapp1289.com threat_level:10}
21 { url:smartweb881.com threat_level:10}
22 { url:smartworld7813.com threat_level:10}
23 { url:topworld938.com threat_level:10}

```

1.4 Verification

One of the many options is to validate using the host command (from the bind9-host package). DNS resolution works for juniper.net, but times out for the hostname listed in the feed:

```

1 # host juniper.net
2 juniper.net has address 44.224.71.252
3
4 # host coolsite3022.com
5 ;; connection timed out; no servers could be reached

```

Note: in the case of an allowed DNS query to a non-existent domain, an NXDOMAIN status would be returned.

Secintel counters indicate the actions taken per DNS query type:

```

1 > show services security-intelligence dns-statistics profile t1
2
3 Category DNS:
4 Profile t1:
5   DNS Query Type Requests Sinkhole Drop Permit Log
6
7   UDP Counter:
8     A 4 0 2 0 2
9     AAAA 1 0 0 0 0
10    MX 1 0 0 0 0
11    CNAME 0 0 0 0 0
12    SRV 0 0 0 0 0
13    SRV NoErr 0 0 0 0 0
14    TXT 0 0 0 0 0
15    TXT NoErr 0 0 0 0 0
16    ANY 0 0 0 0 0
17    MISC 0 0 0 0 0
18 <SNIP>
19 Total 6 0 2 0 2

```

Details about the drop can be found in the SRX logs:

```

1 > show security log report in-detail dns threat-severity 10
2
3 2024-11-30T19:26:44 vsrx-dnsf RT_SECINTEL - DNSF_ACTION_LOG [sub-category="custom" query-type="A
  " protocol-id="17" feed-name="demo_dnsf_t1" source-address="10.1.1.10" destination-address
  ="1.1.1.1" category="dns" query="coolsite3022.com" action="drop" source-port="58866"
  destination-port="53" policy-name="t1" profile-name="t1" username="N/A" session-id="10"
  source-zone-name="t1" destination-zone-name="common" threat-severity="10"]

```

And the corresponding CloudATP realm log:




Figure 12: CloudATP tenant DNS action view

In the case of no logs appearing in the CloudATP realm, the first place to check is the CloudATP data plane connection to see if there is any active connection, as shown below:

```

1 > show services advanced-anti-malware status
2
3 Server connection status:
4   Server hostname: srxapi.eu-west-1.sky.junipersecurity.net
5   Server realm: demo-dnsf-root
6   Server port: 443
7   Proxy hostname: None
8   Proxy port: None
9   Control Plane:
10    Connection time: 2024-11-25 10:20:44 CET
11    Connection status: Connected
12   Service Plane:
13    master
14    Connection active number: 1
15    Connection retry statistics: 1

```

1.4.1 Encrypted DNS

Obviously, encrypted DNS, such as DoH and DoT, evades filtering unless interception capability exists. Another method is to prohibit encrypted DNS communication and allow the clients to fall back to traditional unencrypted DNS.

The following would reconfigure Tenant 1 policies to reject the L7 meta-application DNS-ENCRYPTED, representing DoH and DoT, and turn classic firewall rules into a unified NGFW style by using dynamic-application match:

```

1 delete security policies from-zone t1 to-zone common
2 edit security policies from-zone t1 to-zone common
3 set policy t1-reject match source-address any
4 set policy t1-reject match destination-address any
5 set policy t1-reject match application any
6 set policy t1-reject match dynamic-application junos:DNS-ENCRYPTED
7 set policy t1-reject then reject
8 set policy t1-reject then log session-init
9 set policy t1 match source-address any
10 set policy t1 match destination-address any
11 set policy t1 match application any
12 set policy t1 match dynamic-application any
13 set policy t1 then permit application-services security-intelligence-policy t1
14 set security policies global policy reject-log match dynamic-application any

```

Sample logs of Application Firewall reject action for DoH:

```

1 > show security log report in-detail session deny
2
3 2024-11-30T19:27:43 vsrx-dnsf RT_FLOW - RT_FLOW_SESSION_DENY [application="SSL" source-address
   ="10.1.1.10" destination-address="8.8.8.8" nested-application="DNS-ENCRYPTED" username

```

```
=10.1.1.10" policy-name="t1-reject" packet-incoming-interface="ge-0/0/1.181" source-zone-
name="t1" destination-zone-name="common" session-id="13" source-port="35058" destination-
port="443" protocol-id="TCP" reason="Rejected by policy"]
```

1.5 Appendix: Configurations

1.5.1 Appendix 1: base SRX config

```
1 set version 24.2R1-S1.10
2 set system host-name vsrx-dnsf
3 set system syslog file messages any any
4 set system syslog file messages archive size 5m
5 set system syslog file messages archive files 5
6 set services application-identification
7 set security log mode stream
8 set security alg h323 disable
9 set security alg mgcp disable
10 set security alg msrpc disable
11 set security alg sunrpc disable
12 set security alg rtsp disable
13 set security alg sctp disable
14 set security alg sip disable
15 set security alg talk disable
16 set security alg tftp disable
17 set security alg pptp disable
18 set security flow tcp-session strict-syn-check
19 set security nat source rule-set common from zone t1
20 set security nat source rule-set common from zone t2
21 set security nat source rule-set common to zone common
22 set security nat source rule-set common rule common match source-address 0.0.0.0/0
23 set security nat source rule-set common rule common match destination-address 0.0.0.0/0
24 set security nat source rule-set common rule common then source-nat interface
25 set security policies from-zone t1 to-zone common policy t1 match source-address any
26 set security policies from-zone t1 to-zone common policy t1 match destination-address any
27 set security policies from-zone t1 to-zone common policy t1 match application any
28 set security policies from-zone t1 to-zone common policy t1 then permit
29 set security policies from-zone t2 to-zone common policy t2 match source-address any
30 set security policies from-zone t2 to-zone common policy t2 match destination-address any
31 set security policies from-zone t2 to-zone common policy t2 match application any
32 set security policies from-zone t2 to-zone common policy t2 then permit
33 set security policies global policy reject-log match source-address any
34 set security policies global policy reject-log match destination-address any
35 set security policies global policy reject-log match application any
36 set security policies global policy reject-log match to-zone common
37 set security policies global policy reject-log then reject
38 set security policies global policy reject-log then log session-init
39 set security zones security-zone common interfaces ge-0/0/0.0 host-inbound-traffic system-
services ping
40 set security zones security-zone t1 interfaces ge-0/0/1.181 host-inbound-traffic system-services
ping
41 set security zones security-zone t1 tcp-rst
42 set security zones security-zone t2 interfaces ge-0/0/1.182 host-inbound-traffic system-services
ping
43 set security zones security-zone t2 tcp-rst
44 set interfaces ge-0/0/0 unit 0 family inet address 203.0.113.10/24
45 set interfaces ge-0/0/1 vlan-tagging
46 set interfaces ge-0/0/1 unit 181 vlan-id 181
47 set interfaces ge-0/0/1 unit 181 family inet address 10.1.1.1/24
48 set interfaces ge-0/0/1 unit 182 vlan-id 182
49 set interfaces ge-0/0/1 unit 182 family inet address 10.2.1.1/24
50 set policy-options policy-statement import-from-common term 1 from instance vr-common
51 set policy-options policy-statement import-from-common term 1 from route-filter 0.0.0.0/0 exact
52 set policy-options policy-statement import-from-common term 1 then accept
53 set policy-options policy-statement import-from-common term 100 then reject
54 set routing-instances vr-common instance-type virtual-router
55 set routing-instances vr-common routing-options static route 0.0.0.0/0 next-hop 203.0.113.1
56 set routing-instances vr-common interface ge-0/0/0.0
57 set routing-instances vr-t1 instance-type virtual-router
58 set routing-instances vr-t1 routing-options instance-import import-from-common
59 set routing-instances vr-t1 interface ge-0/0/1.181
60 set routing-instances vr-t2 instance-type virtual-router
61 set routing-instances vr-t2 routing-options instance-import import-from-common
62 set routing-instances vr-t2 interface ge-0/0/1.182
```

1.5.2 Appendix 2: Sample CloudATP Enrollment

```
1 Platform is supported by ATP Cloud: VSRX.
2 Version 24.2R1-S1.10 is valid for bootstrapping.
3 Enrolling with ATP Cloud license serial number: 20161111.
4 Going to enroll single device for VSRX: f8ef568918e0@20161111 with hostname vsrx-dnsf.
5 Not finding Application Signature DB on this device.
6 Installing Application Signature DB.
7 Start downloading Application Signature DB update...
8 Check Application Signature DB download status...
9 Wait for Application Signature DB signature download status...
10 Start installing Application Signature DB update...
11 Communicate with cloud...
12 License type for this device: premium.
13 License of your device will expire in 714 days.
14 Remove related security-intelligence service configurations...
15 Remove related advanced-anti-malware service configurations...
16 Remove related SSL service configurations...
17 Remove related PKI configurations...
18 Clear local certificate aamw-srx-cert...
19 Clear key pair: aamw-srx-cert...
20 Clear CA profile aamw-cloud-ca...
21 Clear CA profile aamw-secintel-ca...
22 Configure CA...
23 Request aamw-secintel-ca CA...
24 Wait aamw-secintel-ca CA download status...
25 Load aamw-secintel-ca CA...
26 Request aamw-cloud-ca CA...
27 Wait aamw-cloud-ca CA download status...
28 Load aamw-cloud-ca CA...
29 Retrieve CA profile aamw-ca...
30 CA certificate ready: aamw-ca...
31 CA certificate ready: aamw-cloud-ca...
32 CA certificate ready: aamw-secintel-ca...
33 Generate key pair: aamw-srx-cert...
34 Enroll local certificate aamw-srx-cert with CA server...
35 Configure SSL service...
36 Configuration added successfully for SSL service.
37 Configure advanced-anti-malware service...
38 Configuration added successfully for advanced-anti-malware service.
39 Configure security-intelligence service...
40 Configuration added successfully for security-intelligence service.
41 Check configuration on device...
42 SSL profile: [OK]
43 SecIntel CA: [OK]
44 Cloud CA: [OK]
45 Client cert found: [OK]
46 SSL profile action: [OK]
47 URL for advanced-anti-malware: [OK]
48 Profile for advanced-anti-malware: [OK]
49 URL for security-intelligence: [OK]
50 Profile for security-intelligence: [OK]
51 All configurations are correct for enrollment.
52 Communicate with cloud...
53 Wait for aamw connection status...
54 Device enrolled successfully!
55 Please see following links for more information:
56 ATP Cloud sample config:
57   https://www.juniper.net/documentation/en_US/release-independent/sky-atp/topics/example/
   configuration/sky-atp-policy-creating-cli.html
58 ATP Cloud quick start guide:
59   http://www.juniper.net/documentation/en_US/release-independent/sky-atp/information-products/
   topic-collections/sky-atp-qsg.pdf
60 ATP Cloud technical documents:
61   http://www.juniper.net/documentation/en_US/release-independent/sky-atp/information-products/
   pathway-pages/index.html
62 It is recommended to run diagnostic process with the following cli command to make sure all
   configurations are valid:
63   request services advanced-anti-malware diagnostics srxapi.eu-west-1.sky.junipersecurity.net
   detail
```

1.6 Conclusion

The discussed feature set brings the following benefits:

- Strengthens defense by allowing organizations to block or sinkhole malicious DNS queries with precision.
- Allows combining vendor-provided intelligence with custom threat feeds to address unique business risks.
- Facilitates granular threat intelligence enforcement for multiple tenants on a single SRX device, reducing infrastructure complexity and costs.
- Empowers tenants with independent control, visibility, and API access, improving customer satisfaction in managed service environments.

1.7 Useful links

- <https://www.juniper.net/documentation/us/en/software/atp-cloud/atp-cloud-admin-guide/topics/concept/atp-cloud-about.html>
- <https://www.juniper.net/documentation/us/en/quick-start/software/atp-cloud/atp-cloud-quick-start/topics/topic-map/id-step-1-begin.html>
- <https://www.juniper.net/documentation/us/en/software/atp-cloud/atp-cloud-api-setup/topics/concept/atp-cloud-api-overview.html>
- <https://www.juniper.net/us/en/dm/download-next-gen-vsrx-firewall-trial.html>
- <https://www.juniper.net/us/en/products/security/srx-series.html>

1.8 Glossary

- API: Application Programming Interface
- ATP: Advanced Threat Prevention
- CLI: Command Line Interface
- DNS: Domain Name System
- DoH: DNS over HTTPS
- DoT: DNS over TLS
- GUI: Graphical User Interface
- HTTPS: Hyper Text Transfer Protocol Secure
- MSSP: Managed Security Services Provider
- NGFW: Next Generation Firewall
- TLS: Transport Layer Security
- VR: Virtual Router

1.9 Acknowledgments

All the people who provided valuable feedback: Mark Barrett, Kelly Brazil, Tim Carlens, Javier Grizzuti, Steven Jacques, Matthijs Nagel - and others from team JNPR! Finally, vSRX/SRX dev and product teams for delivering the Swiss army knife for security and networking.



DC – AI – Routing – Switching – Security – Wireless – Automation

© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty.

Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Trademark acknowledgments, if needed. All third-party marks are the property of their respective owners.

HEWLETT PACKARD ENTERPRISE

HPE.com

