

P1) <http://www.botiga.com/productes/vins/comprarRioja.php>

ID: 1A

HTTP Request

```
GET /productes/vins/comprarRioja.php HTTP/1.1
Accept: */* Accept-Encoding: gzip, deflate, br, zstd
Accept-Language: en-US,en;q=0.9
Connection: keep-alive
Host: www.botiga.com
User-Agent: Mozilla/5.0
\r\n
```

ID: 1B

HTTP Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Nov 2024 13:39:37 GMT
Server: Apache/2.4.62 (Debian)
X-Powered-By: PHP/8.3.13
Set-Cookie: cart=rioja; expires=Wed, 11 Dec 2024 13:39:37 GMT; Max-Age=2592000; path=/
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
\r\n
<!DOCTYPE>...
```

P2) <http://www.botiga.com/productes/vins/consultaPenedes.php>

ID: 2A

HTTP Request

```
GET /productes/vins/consultaPenedes.php HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate, br, zstd
Accept-Language: en-US,en;q=0.9
Connection: keep-alive
Cookie: cart=rioja
Host: www.botiga.com
User-Agent: Mozilla/5.0
\r\n
```

ID: 2B

HTTP Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Nov 2024 13:39:37 GMT
Server: Apache/2.4.62 (Debian)
X-Powered-By: PHP/8.3.13
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
\r\n
<!DOCTYPE>...
```

P3) <http://www.botiga.com/productes/vins/comprarPenedes.php> .

ID: 3A

HTTP Request

```
GET /productes/vins/comprarPenedes.php HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate, br, zstd Accept-Language: en-US,en;q=0.9
Connection: keep-alive
Cookie: cart=rioja
Host: www.botiga.com
User-Agent: Mozilla/5.0
\r\n
```

ID: 3B

HTTP Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Nov 2024 13:39:37 GMT
Server: Apache/2.4.62 (Debian)
X-Powered-By: PHP/8.3.13
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
Set-Cookie: cart=rioja,penedes; expires=Wed, 11 Dec 2024 13:56:45 GMT; Max-Age=2592000; path=/
\r\n
<!DOCTYPE>...
```

P4) Sessions

p4.1) <http://www.botiga.com/productes/vins/comprarRioja.php>

ID: 41A

HTTP Request

```
GET /productes/vins/comprarRioja.php HTTP/1.1
Accept: */* Accept-Encoding: gzip, deflate, br, zstd
Accept-Language: en-US,en;q=0.9
Connection: keep-alive
Host: www.botiga.com
User-Agent: Mozilla/5.0
\r\n
```

ID: 41B

HTTP Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Nov 2024 13:39:37 GMT
Server: Apache/2.4.62 (Debian)
X-Powered-By: PHP/8.3.13
Set-Cookie: PHPSESSID=dca1bf0b73ac93cf5fecc5da72e86a7e; path=/
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
\r\n
<!DOCTYPE>...
```

P4.2) <http://www.botiga.com/productes/vins/consultaPenedes.php>

ID: 42A

HTTP Request

```
GET /productes/vins/consultaPenedes.php HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate, br, zstd Accept-Language: en-US,en;q=0.9
Connection: keep-alive
Cookie: PHPSESSID=dca1bf0b73ac93cf5fecc5da72e86a7e; path=/
Host: www.botiga.com
User-Agent: Mozilla/5.0
\r\n
```

ID: 42B

HTTP Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Nov 2024 13:39:37 GMT
Server: Apache/2.4.62 (Debian)
X-Powered-By: PHP/8.3.13
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
\r\n
<!DOCTYPE>...
```

P4.3) <http://www.botiga.com/productes/vins/comprarPenedes.php>

ID: 43A

HTTP Request

```
GET /productes/vins/consultaPenedes.php HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate, br, zstd Accept-Language: en-US,en;q=0.9
Connection: keep-alive
Cookie: PHPSESSID=dca1bf0b73ac93cf5fecc5da72e86a7e; path=/
Host: www.botiga.com
User-Agent: Mozilla/5.0
\r\n
```

ID: 43B

HTTP Response

```
HTTP/1.1 200 OK
Date: Mon, 11 Nov 2024 13:39:37 GMT
Server: Apache/2.4.62 (Debian)
X-Powered-By: PHP/8.3.13
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
\r\n
<!DOCTYPE>...
```

P5) Què canviaria si la connexió fos de tipus close?

En totes les peticions i respostes la capçalera “Connection: keep-alive” es canviaria per “Connection: close”, de manera que després de cada petició/resposta, en client i el servidor tancarien els sockets que han obert per fer la comunicació. Múltiples peticions del mateix client al mateix servidor utilitzarien un socket different per la petició/resposta.