

Amazon Interactive Video Service

Quality of Experience Monitoring Dashboard



Purpose











Monitor quality of service


- Capture metrics on delivery performance and viewing experience
- Build dashboards and alerts for operations teams to proactively understand customer experience

Measure quality of experience

- Monitor and measure interactions
- Understand consumption behavior and user interactions




Solution Components





Client Architecture



```
"metric_type":"PLAYBACK_SUMMARY",
    "client_platform":"web",
    "channel_watched":"xhP3ExfcX80N",
    "is_live":true,
    "error_count":0,
    "playing_time_ms":60030,
    "buffering_time_ms":0,
    "rendition_name":"720p",
    "rendition_height":720,
    "startup_latency_ms":0,
    "live_latency_ms":2
}
```




Sample JS Player

To get started: please read the web/IVSplayer/README.md

The sample player by default plays an IVS test channel, generating one QoS event each minute (configurable, tradeoff between latency and cost)



Waiting for the next question





JSON Schema

Metrics of user activity (concurrent viewers, etc.) and QoS (buffering, latency,

etc.)

Field Name	Data Type	Note
		// event type (QoS, timed metadata feedback, etc.)
metric_type	string	"PLAYBACK_SUMMARY" for QoS event
		// client platform and content
client_platform	string	e.g., "web", "android", "ios"
channel_watched	string	the string after ".channel." in the playback URL, e.g., "xhP3ExfcX8ON" for the test channel
is_live	boolean	
		// playback summary
error_count	integer	
playing_time_ms	integer	the duration (in ms) of the player SDK staying in the "PLAYING" state
buffering_time_ms	integer	the duration (in ms) of the player SDK staying in the "BUFFERING" state
rendition_name	string	e.g., "Source", "720p60", "720p", "480p", "240p", "160p" (snapshot taken right before the event is sent)
rendition_height	integer	(snapshot taken right before the event is sent)
startup_latency_ms	integer	latency in ms from load() being called to state becoming PLAYING. Value is only valid in the very first event of playing a channel, and is set to 0 in following events, i.e., the 2nd/3rd/ minute of the playback session
live_latency_ms	integer	latency in ms based on "getLiveLatency()" covering the latency from ingest to playback (i.e., not include the latency of broadcast tool), live only. set to -1, if VOD




Implementation

Check section 3.1.3 of web/IVSplayer/README.md

Search "QoS event" in web/IVSplayer/js/ivs.js

Most logic is in the transition of player state






Verification

Multiple test cases with simulated network conditions (use Chrome Developer Tool to throttle network)

Test Case	Which QoS Event	Expected startupLatencyMs	playingTimeMs	bufferingTimeMs	renditionHeight	LiveLatencyMs	errorCount
#1	1st	~2s	~58s	~0s	720	~3s	~0
	Following	0s	~60s	~0s	720	~3s	~0
#2	1st	~2s	~58s	~0s	720	~3s	~0
	2nd	0s	~60s	~0s	720	~3s	~0
	3rd	0s	>55s	<5s	360	<6s	~0
	4th	0s	~60s	~0s	360	<6s	~0
#3	1st	~5s	~55s	~0s	360	<5s	~0
	2nd	0s	~60s	~0s	360	<5s	~0
	3rd	0s	~60s	~0s	720	<5s	~0
	4th	0s	~60s	~0s	720	<5s	~0



Backend Architecture: Analytics







Dashboard Options

CloudWatch	ElasticSearch	QuickSight
Near real time	Near real time	Long term
Operational metrics- notifications	More flexibility Developer comfort	Business reporting




Dashboards – metrics on popularity









Dashboards – metrics on experience








Dashboards – metrics on experience





Beyond QoS/E – building interactions





Cost Estimates

Components	Costs	Cost variability by traffic		
Ingests	\$218.40 per Million Hours	High		
Kinesis Analytics Processing	\$84.20 per Month (1 KPU)	Stepwise		
CloudWatch Dashboards	\$4.50 per Month	Consistent		
ElasticSearch Dashboards	\$232.50 per Month (2x m4.large w/ 100GB storage)	Stepwise		
QuickSight Dashboards	\$12/user/month + S3 Data scan charges	Usage based		



Next Steps

https://github.com/aws-samples/amazon-ivs-qos-dashboard-timed-metadata-sample



