Republic of the Philippines
Department of the Interior and Local Government
Bureau of Fire Protection

(Region)
(District/Provincial Office)
(STATION)
(Station Address)

FIRE SAFETY INSPECTION CHECKLIST

for CONVEYANCE CLEARANCE

(CONVEYANCE OF HAZARDOUS MATERIALS AND CHEMICALS IN VEHICLES)

Date_____

Control No._____

Name of Operator_____
Address _____
Name of Driver _____ Driver License No._____
Type of Vehicle _____ Plate No. _____
Motor(Engine)Number _____ Chassis No._____
Quantity & Description_____ Validity of Registration _____
If with trailer, Trailer No._____

Instruction: (√) Check the appropriate box (Yes/No), if the following condition is provided:

	CONDITIONS	Yes	No
1	LTO Certificate of Registration & Updated LTO Official Receipt (OR) of vehicle available.		
2	Business Permit and Fire Safety Inspection Certificate Num._____& date issued_____ for Business (Operator).		
3	Certification of the design, construction & testing of tank from manufacturer shall readily available (for new tank vehicle).		
4	With hydrotest certificate per compartment from fabricator at 3psi for 5 min. (NFPA-385).		
5	Each compartment provided with internal/emergency valve (pneumatic/ mechanical).		
6	Hazardous Material Identification System (HMIS) label. Referred to (NFPA 400, Globally Harmonized System (GHS) and other Internationally recognized standards. Material Safety Data Sheet (MSDS)of products being loaded shall be available at all times.		
7	"NO SMOKING" sign within 50 ft. (Rear & both sides). Signage size atleast (273mm) in height and the text indicating the "NO SMOKING" sign should be atleast (41mm).		
8	"FLAMMABLE LIQUID" or "FLAMMABLE GAS" sign. (Rear & both sides). Signage size atleast (273mm)in height and the text indicating the "FLAMMABLE LIQUID" or "FLAMMABLE GAS" sign should be atleast (41mm).		
9	Atleast one (1)-unit portable fire extinguishers with appropriate rating based on the products and shall be properly maintained at all times located conspicuously and good operational condition.		
10	Wheel chocks are readily available with two (2) pieces (with truck body number painted on it) to prevent motion of the vehicle while it is being loaded, unloaded or parked.		
11	Bonding/grounding system for tank vehicle shall be provided/available.		
12	Piping & hoses are maintained in good condition while in service.		
13	Basic oil spill containment kit available (absorbent pads/ pail of sand with towel).		
14	Warning cones four (4) pieces and atleast two (2) feet high.		
15	Early warning device (triangular in shape) two(2) pieces available and not damaged.		
16	All tires in good condition.		
17	Whistle with audible sound for emergency attraction shall be provided for driver.		
18	Medical first aid kit available.		

Prohibited Acts:

* Smoking is prohibited within 50ft in the vicinity of pipeline.
* Kaingin/Intentional grass fire at the vicinity of pipeline.

DEFECTS / DEFICIENCIES NOTED DURING INSPECTION:

_____
_____
_____
_____
_____
_____
_____

RECOMMENDATIONS:

_____
_____
_____
_____
_____

ACKNOWLEDGED BY:

_____ _____
Signature Over Printed Name of Owner/Representative Fire Safety Inspector/s

Date & Time _____

_____
Team Leader

RECOMMEND ISSUANCE OF FSC for Conveyance:

_____
CHIEF, FIRE SAFETY ENFORCEMENT SECTION

APPROVED / DISAPPROVED:

_____
CITY / MUNICIPAL FIRE MARSHAL

PAALALA: "MAHIGPIT NA IPINAGBABAWAL NG PAMUNUAN NG BUREAU OF FIRE PROTECTION SA MGA KAWANI NITO ANG MAGBENTA O MAGREKOMENDA NG ANUMANG BRAND NG FIRE EXTINGUISHER"

"FIRE SAFETY IS OUR MAIN CONCERN"