

# **Real-Time Dual-Lens Photo Enhancer**

Software Project Lab 3 Technical Report

Submitted by

**Mahir Faisal**

BSSE-1316

Institute of Information Technology

University of Dhaka

Supervised by

**Dr. B M Mainul Hossain**

Professor

Institute of Information Technology

University of Dhaka

Submission Date: 26 February 2026



## Letter of Transmittal

26 February, 2026  
BSSE 4th Year Exam Committee  
Institute of Information Technology  
University of Dhaka

Subject: Technical Report Submission - **Duel-Lens-Photo-Enhancer**: Automated web tool for enhancement of duel lens photography

Sir,

I am submitting the technical report for our Software Project Lab 3, **Duel-Lens-Photo-Enhancer**. This report comprehensively covers the project's technical details, including design, implementation, and testing phases. While I've tried to do my best, I welcome your feedback for improvement.

Thank you for your consideration.

Sincerely,

Mahir Faisal

BSSE-1316  
Institute of Information Technology  
University of Dhaka



26.02.2026

---

Supervisor's Signature

## Acknowledgement

I am sincerely grateful to the **Institute of Information Technology** for giving me the opportunity to work on the project Dual-Lens Photo Enhancer: Automated Web Tool for Enhancement of Dual-Lens Photography.

I would like to express my deepest appreciation to my supervisor, **Dr. B M Mainul Hossain, Professor & Director, Institute of Information Technology, University of Dhaka**, for his invaluable guidance and support throughout the project. His expertise and insights were instrumental in shaping the direction and success of this work.

Finally, I would like to thank my classmates, whose help and timely feedback provided valuable perspectives that contributed to the project's development.

## Abstract

Dual-lens smartphone cameras let you capture ultra-wide shots for full-scene context and telephoto shots for sharp detail but you usually have to choose one at the expense of the other. The **Real-Time Dual-Lens Photo Enhancer** solves this by intelligently fusing a wide-angle and a telephoto image taken at the same time into a single, enhanced photo. The result keeps the full wide view while seamlessly adding the sharp textures, edges, and fine details from the telephoto image.

The pipeline is fully automated and built entirely in Python with PyTorch. It handles resizing, pre-alignment, color correction, precise alignment, and final fusion with super-resolution, producing natural, high-quality images. By removing the need for proprietary software like MATLAB and optimizing for fast inference, it delivers professional-grade enhancement directly in the browser within seconds.

By eliminating the usual trade-off between context and clarity, this lightweight tool pushes computational photography forward making it useful for everyday users as well as applications in surveillance, autonomous systems, professional imaging, and content creation.

|                                          |           |
|------------------------------------------|-----------|
| <b>Introduction.....</b>                 | <b>7</b>  |
| Motivation.....                          | 7         |
| <b>Scope.....</b>                        | <b>7</b>  |
| <b>Project Timeline.....</b>             | <b>8</b>  |
| <b>Purpose of Document.....</b>          | <b>8</b>  |
| <b>Project Description.....</b>          | <b>9</b>  |
| <b>Quality Function Deployment.....</b>  | <b>9</b>  |
| Normal Requirements.....                 | 9         |
| Expected Requirements.....               | 9         |
| Exciting Requirements.....               | 10        |
| <b>Scenario-Based Modeling.....</b>      | <b>10</b> |
| <b>Use Case Diagram.....</b>             | <b>10</b> |
| Duel-Lens-Photo-Enhancer.....            | 11        |
| Modules of Duel Lens Photo Enhancer..... | 12        |
| Upload wide & tele view Images.....      | 13        |
| Resize Images.....                       | 13        |
| Pre-align Images.....                    | 13        |
| Color-correction.....                    | 13        |
| Alignment.....                           | 13        |
| Super Resolution.....                    | 13        |
| <b>Data-Based Modeling.....</b>          | <b>13</b> |
| <b>Class-Based Modeling.....</b>         | <b>15</b> |
| Analysis Classes.....                    | 15        |
| Class cards.....                         | 16        |
| <b>Architectural Design.....</b>         | <b>19</b> |
| Architectural Context Diagram.....       | 19        |
| Archetypes.....                          | 19        |
| Top Level Components.....                | 20        |
| <b>Deployment Diagram.....</b>           | <b>22</b> |
| <b>Applied Methodology.....</b>          | <b>24</b> |
| ZeDuSR.....                              | 24        |
| Workflow.....                            | 24        |
| Input.....                               | 24        |
| Image Upload.....                        | 24        |
| Preprocess Images.....                   | 24        |
| Implementation Details.....              | 25        |
| Process.....                             | 25        |
| SiftAlign.....                           | 25        |

|                                                   |           |
|---------------------------------------------------|-----------|
| Implementation Details.....                       | 25        |
| Color Correction.....                             | 25        |
| Implementation Details.....                       | 28        |
| Alignment.....                                    | 28        |
| Implementation Details.....                       | 28        |
| Super Resolution.....                             | 28        |
| Implementation Details.....                       | 29        |
| Low Light Image Enhancement.....                  | 30        |
| Workflow.....                                     | 30        |
| Input.....                                        | 30        |
| Image Upload.....                                 | 30        |
| Process.....                                      | 30        |
| Preprocessing & Illumination Inversion.....       | 30        |
| Atmospheric Light Estimation (A).....             | 31        |
| Illumination Normalization.....                   | 31        |
| Adaptive Gamma-Based Transmission Estimation..... | 32        |
| Image Recovery (Restoration Model).....           | 32        |
| Contrast Stretching & Final Adjustment.....       | 32        |
| <b>User Manual &amp; User Interface.....</b>      | <b>33</b> |
| Home.....                                         | 33        |
| Low Light Image Enhancement.....                  | 34        |
| Upload Image.....                                 | 34        |
| Processing.....                                   | 35        |
| Enhanced Output.....                              | 36        |
| Zero Shot Dual Lens Super Resolution.....         | 37        |
| Upload.....                                       | 37        |
| Processing.....                                   | 38        |
| Outputs.....                                      | 39        |
| <b>Preliminary Test Plan.....</b>                 | <b>42</b> |
| High-Level Description of Testing Goals.....      | 42        |
| Test Cases.....                                   | 42        |
| <b>Why ZeDuSR.....</b>                            | <b>46</b> |
| <b>Conclusion.....</b>                            | <b>47</b> |

## Introduction

Modern smartphones almost always come with dual-lens cameras one ultra-wide for capturing expansive scenes, and one telephoto for zoomed-in, detailed shots. The ultra-wide lens gives you a broad, immersive view but often suffers from distortion, soft edges, and lower detail. The telephoto lens, on the other hand, captures crisp textures and fine details but only covers a small part of the scene, leaving out the surrounding context.

The **Real-Time Dual-Lens Photo Enhancer** is a web tool designed to solve this trade-off. It intelligently fuses a wide-angle (wideview) and a telephoto (teleview) image taken at the same time, producing a single enhanced photo. The result keeps the full wide-angle perspective while seamlessly integrating the sharp, high-quality details from the telephoto lens, giving you the best of both worlds in one image.

## Motivation

The motivation for this project comes from the growing need for high-quality computational photography on everyday devices. Smartphone users often have to choose between capturing the full scene with a wide shot or getting fine detail with a zoomed shot never both. This compromise is even more limiting in professional areas like surveillance, autonomous driving, drone imaging, real estate, travel photography, and content creation, where both broad context and sharp detail are essential.

Current solutions tend to fall short: some just overlay images, others require heavy post-processing in specialized software, and many are too computationally expensive to work in real or near-real time. This project leverages modern deep learning advances in image fusion and super-resolution to build an efficient, practical pipeline. Built entirely in Python with PyTorch, it removes reliance on MATLAB and achieves fast, optimized inference.

The ultimate goal is to deliver natural, DSLR-quality results right in the browser images that are wide, sharp, and well-balanced making professional-grade enhancement accessible to everyone.

## Scope

The scope of the **Real-Time Dual-Lens Photo Enhancer** includes:

The **Real-Time Dual-Lens Photo Enhancer** is designed as a responsive web application that works on modern browsers, allowing users to easily upload or capture ultra-wide and telephoto image pairs.

It features a fully automated processing pipeline that handles every step: resizing images to consistent dimensions, performing pre-alignment for geometric corrections, adjusting colors and exposure, executing precise alignment using either feature-based or deep-learning methods, and finally fusing the images with super-resolution enhancement.

The user interface guides users step by step, providing progress updates, helpful modals, and easy options to visualize and download the results. The system is optimized for near real-time performance on capable hardware and is implemented entirely in Python with PyTorch, without relying on any external proprietary software.

## Project Timeline

The estimated timeline of SafeDep is given below:



*Fig-1 : Timeline for Dual-Lens-Photo-Enhancer*

## Purpose of Document

The purposes of this document are-

- Identify and analyze the requirements
- Design the architecture
- Design the test plan
- Reduce the development effort



- Improve understanding

## Project Description

The **Real-Time Dual-Lens Photo Enhancer** tackles a common challenge in modern smartphone photography: the trade-off between capturing a wide scene and preserving fine detail. Ultra-wide lenses give you a full, immersive view, showing the entire environment, but they often suffer from distortion, soft edges, and lower resolution, especially in tricky lighting. Telephoto lenses, on the other hand, capture sharp textures and fine details in the center of the frame but miss out on much of the surrounding context.

This project solves that problem by creating a complete pipeline that fuses a wide-angle and a telephoto image taken at the same time. The result is a single, enhanced photo that keeps the broad perspective of the ultra-wide shot while seamlessly adding the sharpness, textures, and detail of the telephoto image.

To achieve this natural, high-quality result, the system follows a carefully designed sequence: resizing both images for consistency, performing pre-alignment to fix initial geometric differences, correcting color and exposure to harmonize the tones, executing precise alignment using either feature-based methods or deep-learning guidance, and finally, blending the images with advanced fusion and enhancement to produce a visually balanced, professional-looking photograph.

## Quality Function Deployment

Quality Function Deployment (QFD) is a technique that translates the needs of the customer into technical requirements for the software. With respect to this project, the following requirements are identified-

### Normal Requirements

These are the essential features required for the system to fulfill its primary purpose.

- Accept upload of two input images: ultra-wide (wideview) and telephoto (teleview)
- Perform sequential processing steps: Resize -> Pre-Alignment -> Color Correction -> Alignment -> Final Enhanced View(Super Resoluted)
- Store intermediate and final outputs in organized folders (Resized image, pre-aligned, color-corrected, aligned, enhanced)
- Provide clear user feedback after each step via modals/pop-ups (Like, "Images are resized", "Pre alignment done")
- Display the final enhanced image with options to view (full window) and download
- Ensure the pipeline runs end-to-end without requiring any external proprietary software

### Expected Requirements

These enhance usability, quality, and performance.

- Natural-looking fusion results with minimal artifacts (proper handling of distortion correction, occlusion, depth-of-field mismatch)
- Ignore overfitting/underfitting
- Responsive web UI that guides users through sequential steps with progress indicators

## Exciting Requirements

These represent the cutting-edge and most impressive aspects that make the project stand out.

- The entire pipeline has been fully rebuilt in modern, open-source **PyTorch**, completely removing the need for MATLAB. This makes the system easier to share, allows for community contributions, and simplifies deployment to servers or the cloud. It also opens the door for seamless integration with other deep learning models.
- The system achieves much faster processing than typical heavy fusion methods by carefully optimizing the model architecture, using efficient layers, and fine-tuning performance. This results in significantly improved inference speed without sacrificing quality.
- There's strong potential to extend this system to real-time video or live-stream processing, enhancing feeds from dual cameras on the fly. This could enable applications in augmented reality, live surveillance, and advanced computational videography.
- The system goes far beyond simple overlays or blending, producing images that look natural and crisp, with DSLR-quality detail preserved across the entire wide-angle frame.
- It overcomes the limitations of smartphone hardware, delivering professional-quality results entirely through smart software processing.

## Scenario-Based Modeling


Scenario-based modeling is a way of designing software by imagining how it will behave in real-world situations. It focuses on specific scenarios like user actions, events, or environmental conditions to show how the system should respond. By working through these scenarios, developers can visualize the software in action, spot potential problems early, make smarter design choices, and ensure the system works well for users in a variety of real-life situations.

## Use Case Diagram

A use case diagram is a simple visual way to show how a system interacts with the outside world. It maps out the system's key functions (use cases) and the people or other systems that interact with it (actors). By laying out these relationships, use case diagrams help everyone

understand what the system does and how users or external systems engage with it. They're usually created during requirements gathering, using software modeling tools to capture the main interactions clearly.

## Duel-Lens-Photo-Enhancer




*Fig-2 : use case(level-0)*

**Primary actors:** Actor(User)

**Goal:** Enhanced Image

## Modules of Duel Lens Photo Enhancer



*Fig-3 : use case(level-1)*

**Primary actors:** Actor(User)

**Goal in Context:** The diagram shows the sequence of the modules of the Duel Lens Photo Enhancer

The use case can be elaborated as follows -

### Upload wide & tele view Images

Upload two input images captured by the tele view lens & wide view lens.

### Resize Images

Resize the initial spatial resolution of wide view & tele view images.

### Pre-align Images

Perform pre-alignment activities before correcting the color difference between two input images.

### Color-correction

In this module, Color-correction to match tone, exposure, and white balance & handle the difference(color/brightness) between two input images

### Alignment

After correcting the color, the alignment activity will be performed. In this module

### Super Resolution

In this module, the super resolution technique will be used & the output of this module is the final output of this capstone.

### Data-Based Modeling

Data-based modeling is a way to visually map out how a database is structured and how the data is organized. It usually takes the form of **entity-relationship diagrams (ERDs)**, which show the tables (entities), their columns (attributes), and the connections between them. To create these models, developers first analyze the system's data needs, figure out the entities and their properties, and then use modeling tools to draw ERDs. These diagrams act as a blueprint for designing and building the actual database.

As, this capstone does not need a database, the data model can be a simple file system hierarchy:




Fig-4 : Data Flow Model

| Schema                | Attributes                    | Type                 |
|-----------------------|-------------------------------|----------------------|
| Original Image        | Wide_view.jpg                 | File reference (JPG) |
|                       | Tele_view.jpg                 | File reference (JPG) |
| Resized Image         | Resized_wide_view.jpg         | File reference (JPG) |
|                       | Resized_tele_view.jpg         | File reference (JPG) |
| Pre-Aligned Image     | Wide_view_crop.jpg            | File reference (JPG) |
|                       | Wide_view_bic.jpg             | File reference (JPG) |
|                       | Tele_view_shiftAlign.jpg      | File reference (JPG) |
| Color Corrected Image | Tele_view_shiftAlign_corr.jpg | File reference (JPG) |
| Aligned Image         | HR.png                        | File reference (PNG) |
|                       | Out_20_war.png                | File reference (PNG) |
| Enhanced Image        | Enhanced Image.png            | File reference (PNG) |

*Table-1: Schemas of Duel Lens Photo Enhancer*

## Class-Based Modeling

Class-based modeling is a visual representation in software engineering that illustrates the structure of a software system using classes, their attributes, and relationships. It is commonly used in object-oriented design and modeling.

### Analysis Classes

After going through the scenario, I first picked out all the nouns and then narrowed them down to those relevant to the solution domain using a general classification system things like external entities, objects, events, roles, organizational units, places, and structures.

Next, I applied selection criteria to decide which of these nouns could become potential classes. This involved checking whether they carry important information, provide necessary services, have multiple attributes, share common properties or operations, or satisfy essential requirements.

After analyzing these potential classes in detail, I identified the following as the main analysis classes-

- `UI`
- `ImageUploader`
- `ImageProcessor`

- SessionManager
- FileManager

## Class cards

The class cards are given below:

| ImageUploader                              |                               |
|--------------------------------------------|-------------------------------|
| Attribute                                  | Method                        |
| Wide_view_image.jpg                        | uploadImage()                 |
| Tele_view_image.jpg                        |                               |
| Responsibility                             | Collaborators                 |
| Upload input images(wide view & tele view) | UserInterface, ImageProcessor |

*Table-2: CRC Card(ImageUploader)*

| ImageProcessor                                                |                         |
|---------------------------------------------------------------|-------------------------|
| Attribute                                                     | Method                  |
| Resized_wide_view_image.jpg                                   | resizelImages()         |
| Resized_tele_view_image.jpg                                   | PerformPreAlignment()   |
| Wide_view_crop.jpg                                            | correctColor()          |
| Wide_view_bic.jpg                                             | performAlignment()      |
| Tele_view_shiftAlign.jpg                                      | generateEnhancedImage() |
| Tele_view_shiftAlign_corr.jpg                                 |                         |
| HR.png                                                        |                         |
| Out_20_war.png                                                |                         |
| Enhanced Image.png                                            |                         |
| Responsibilities                                              | Collaborator            |
| Resize input images                                           | ImageUploader           |
| PreAlign the resized images                                   | SessionManager          |
| Handle color differences between input images                 | FileManager             |
| Align images to produce an aligned image for super resolution |                         |
| Use super resolution technique to enhance image               |                         |

*Table-3: CRC Card(ImageProcessor)*



| SessionManager       |                   |
|----------------------|-------------------|
| Attribute            | Method            |
| session_id           | startSession()    |
|                      | updateStatus()    |
|                      | getCurrentState() |
| Responsibilities     | Collaborator      |
| Manages the sessions | UserInterface     |
|                      | FileManager       |

*Table-4: CRC Card(SessionManager)*

| FileManager                        |                                           |
|------------------------------------|-------------------------------------------|
| Attributes                         | Methods                                   |
|                                    | storeImage(image:File, folder: string)    |
|                                    | getImagePath(folder:string, type: string) |
| Responsibilites                    | Collaborator                              |
| Tracks files                       | SessionManager                            |
| Stores Files in respective folders | ImageProcessor                            |


*Table-5: CRC Card(FileManager)*

| UserInterface |                                |
|---------------|--------------------------------|
| Attributes    | Methods                        |
|               | displayUploadPage()            |
|               | displayStartingExecutionPage() |
|               | displayResigePage()            |

|                                  |                              |
|----------------------------------|------------------------------|
|                                  | displayPreAlignPage()        |
|                                  | displayColorCorrectionPage() |
|                                  | displayAlignmentPage()       |
|                                  | displayEnhancementPage()     |
|                                  | viewImage()                  |
|                                  | downloadImage()              |
| <b>Responsibilities</b>          | <b>Collaborators</b>         |
| Navigate to all respective pages | ImageUploader                |
|                                  | ImageProcessor               |
|                                  | SessionManager               |

*Table-6: CRC Card(UserInterface)*

The CRC diagram of the classes can is given below:



*Fig-6: CRC diagram*


## Architectural Design

Architectural design is a way to visually map out the high-level structure of a software system. It shows the main components or modules, how they interact with each other, and how the overall system is organized, giving a clear picture of the system's architecture.

### Architectural Context Diagram

The Architectural Context Diagram provides a big-picture view of how the system interacts with its surroundings. It shows the user, the external environment (like the browser or the internet), and where the system boundaries lie. It also ties back to the use case diagram by highlighting the main actor the user and reflects the containment relationships identified in the ER modeling.

The architectural context diagram for the tool is given below-




*Fig-7: Architectural Context Diagram*

### Archetypes

This section highlights the main architectural patterns used in the system: **Client-Server** to structure the overall system, **MVC (Model-View-Controller)** to organize the application logic, and a **Layered Architecture** to clearly separate different concerns and responsibilities.

The archetypes for the tool are defined below-



*Fig-8: ArcheTypes*

## Top Level Components

The Top Level Components diagram details the main modules and their interactions, similar to the component diagram, referencing class modeling (classes like ImageUploader, ImageProcessor) and ER (file entities as storage).

Overall architectural structure with top-level components is illustrated below-





Fig-9: Top Level Components



*Fig-10: Top Level Components(Module)*

## Deployment Diagram

For smooth deployment of the Photo-Enhancer, it's important to have a clear and simple deployment architecture. This makes the system easier to scale, maintain, and implement. The architecture is organized into two main sections: the **Browser** and the **Server**.

Below is the deployment diagram illustrating how the Photo-Enhancer is set up:





Fig-11: Deployment Diagram

## Applied Methodology

This chapter elucidates the internal mechanisms of the **Real-Time Dual-Lens Photo Enhancer**, detailing its workflow, input handling, processing modules, and output generation.

## ZeDuSR

### Workflow



*Fig-12: Overall workflow of ZeDuSR*

### Input

The **Input** module is responsible for managing user interactions. It comprises the following sub-modules:

#### Image Upload

- The user can upload two photos, wide view & teleview images

#### Preprocess Images

- User can resize two images into horizontal size (1280, 932) & vertical size (932, 1280)



## Implementation Details

The photo upload & preprocessing segments are implemented through the [UploadImage.py](#) & [resize.py](#).

## Process

The **Processing** module encompasses all backend operations that analyze user inputs and generate the corresponding outputs in each segment & generate the final enhanced photo.

It is subdivided into four primary components:

### SiftAlign

In ZeDuSR, **SIFTAlign** is just the initial rough alignment step.

Because wide and telephoto images from dual-lens phones are naturally misaligned (due to different lens positions), this step uses traditional SIFT feature matching to roughly line them up first.

It's not the paper's main alignment method. The core contribution is the learned degradation-invariant optical flow alignment. SIFTAlign simply reduces large shifts beforehand so the advanced model can refine the alignment more effectively.

## Implementation Details

The SiftAlign part is implemented in `sift_align.py` under RealWorldData folder.

## Color Correction

This step makes the two photos look like they were taken under the same lighting.

Often, the wide-angle shot looks slightly off maybe more yellow, darker, or just different because each phone lens uses its own exposure and color settings. So before doing any serious processing, a simple adjustment is made: the wide image is tweaked to match the color "vibe" of the zoom image.

The idea is simple make both photos feel like they belong together. That way, the computer won't get confused later by differences in lighting or color instead of actual scene details.

Reimplemented Color Correction part:

```
mu_c, sigma_c = cv2.meanStdDev(Ic)
mu_t, sigma_t = cv2.meanStdDev(It)

mu_c, sigma_c = mu_c.flatten(), sigma_c.flatten()
mu_t, sigma_t = mu_t.flatten(), sigma_t.flatten()
sigma_t[sigma_t < 1e-6] = 1e-6

It_corr = (It - mu_t) * (sigma_c / sigma_t) + mu_c
It_corr = np.clip(It_corr, 0, 255)
```

```
out = alpha * It_corr + (1 - alpha) * It
return np.clip(out, 0, 255).astype(np.uint8)
```

```
def process_image(args):
    fname, ref_folder, input_folder, save_folder = args
    path1 = os.path.join(ref_folder, fname) # reference
    path2 = os.path.join(input_folder, fname) # target

    I1 = cv2.cvtColor(cv2.imread(path1), cv2.COLOR_BGR2RGB).astype(np.float32)
    I2 = cv2.cvtColor(cv2.imread(path2), cv2.COLOR_BGR2RGB).astype(np.float32)

    I2_c = color_transfer_rgb(I1, I2, alpha=0.9)

    out_path = os.path.join(save_folder, fname)
```

```

if __name__ == "__main__":
    start_time = time.time()

    ref_folder = "D:\ZeDuSR\zedusr\RealworldData\Data\WideView_crop_bic"
    input_folder = "D:\ZeDuSR\zedusr\RealworldData\Data\TeleView_SIFTAlign"
    save_folder = "D:\ZeDuSR\zedusr\RealworldData\Data\TeleView_SIFTAlign_cor/"

    os.makedirs(save_folder, exist_ok=True)

    valid_exts = ('.jpg', '.jpeg', '.png', '.bmp', '.tif', '.tiff')
    filepaths = [f for f in os.listdir(ref_folder) if f.lower().endswith(valid_exts)]

    args_list = [(fname, ref_folder, input_folder, save_folder) for fname in filepaths]
    with Pool(processes=cpu_count()) as pool:
        pool.map(process_image, args_list)

    end_time = time.time()
    print(f"Execution time: {end_time - start_time:.2f} seconds")

```

### Mathematical Implementation:

# Compute mean and std with OpenCV (fast)

```
mu_c, sigma_c = cv2.meanStdDev(lc)
```

```
mu_t, sigma_t = cv2.meanStdDev(It)
```

# Vectorized correction

```
It_corr = (It - mu_t) * (sigma_c / sigma_t) + mu_c
```

```
It_corr = np.clip(It_corr, 0, 255)
```

# Blend with original to avoid overcorrection

```
out = alpha * It_corr + (1 - alpha) * It
```

```
return np.clip(out, 0, 255).astype(np.uint8)
```

## Implementation Details

Initially, for this segment, the user had to move to MATLAB to correct the color differences between the two images. Here, on my platform, I have reduced this MATLAB dependency & converted this part into pytorch suitable practice. This part is implemented in [ColorLuminanceDir.py](#) under the RealworldData/color\_correction folder.

## Alignment

This step carefully lines up the two photos so that the same objects sit in the exact same positions.

It gently stretches and shifts the blurry wide image to match the sharper zoom image. The key is that it does this without “fixing” the blur or noise it keeps everything looking naturally imperfect. Smart safeguards are used to make sure the blurry photo doesn’t accidentally become cleaner than it should be.

The goal is simple: create trustworthy before-and-after image pairs. That way, the model can clearly learn what real blur looks like in your photo instead of learning from artificial or distorted data.

## Implementation Details

Alignment Part is implemented in [alignment.py](#) under Alignment folder. Here, in this segment basically two deep learning pretrained models are used. One is **vgg16**, a popular convolutional neural network (CNN) model used for image classification, recognition, and transfer learning and the second one is **FlowNet**, used for efficient, end-to-end optical flow estimation, treating it as a learning problem rather than a traditional optimization task.

- **FlowNet** – for motion estimation and alignment.
- **VGG16** – for feature extraction and performance benchmarking.

## Super Resolution

This is the moment the image truly gets enhanced.

Once the two photos are properly lined up, the model looks at the areas where they overlap and match best. It compares the blurry wide version with the sharp zoom version and learns the relationship between them essentially understanding, “When I see this kind of blur, this is what the sharp version should look like.”

After learning that pattern, it doesn't stop at the overlapping region. It applies the same learned sharpening behavior across the entire wide image even in areas the zoom lens never captured.

The goal is powerful but simple: use knowledge from just one aligned photo pair to transform the whole wide-angle image into a larger, clearer, sharper result.

Implementation Details

This segment is implemented in ZSSR\_real.py.

Optimization Phase

To overcome the performance bottleneck, I focused on optimization techniques:

1. Model Replacement

- Replaced the standard RCAN with a **lightweight variant, Meta-RCAN**.
- Meta-RCAN provides **five different configurations**:
  - RCAN\_BIX2
  - RCAN\_BIX3
  - RCAN\_BIX4
  - RCAN\_BIX8
  - RCAN\_BDX3

Model Selection Guide

| Model | Scale Factor | Parameters | Notes                               |
|-------|--------------|------------|-------------------------------------|
| BIX2  | ×2           | ~1.2M      | Suitable for low-resolution inputs  |
| BIX3  | ×3           | ~1.5M      | Balanced performance and efficiency |
| BIX4  | ×4           | ~1.8M      | Higher accuracy for larger images   |
| BIX8  | ×8           | ~2.0M      | Best for very high-resolution       |

|             |    |       |                                                      |
|-------------|----|-------|------------------------------------------------------|
|             |    |       | tasks                                                |
| <b>BDX3</b> | ×3 | ~1.0M | Lightweight,<br>faster training,<br>reduced accuracy |


➤ I selected **RCAN\_BIX4** as the most efficient lightweight version, balancing **accuracy and computational cost**.

## 2. Hyperparameter Optimization

- Tuned the number of **epochs** to avoid overfitting and reduce computation time.
- Optimized **patch size** and **batch size** for faster training and inference without significant loss of accuracy.

## Low Light Image Enhancement

### Workflow



*Fig-13: Overall workflow of Low Light Image Enhancement*

### Input

#### Image Upload

- User can upload the low light image

### Process

It is subdivided into six primary components:

#### Preprocessing & Illumination Inversion

The goal here is to shift the problem into a space where lighting becomes the main focus.

First, the image is converted into floating-point values between 0 and 1. This makes the pixel values smoother and more precise, which helps with mathematical operations later.

Next, a Gaussian blur is applied. This gently smooths the image to reduce small noise and random variations, so we focus more on overall lighting rather than tiny pixel-level disturbances.

Finally, the image is inverted. Bright areas become dark and dark areas become bright, which helps emphasize illumination patterns and makes lighting characteristics easier to analyze in the next steps.

Invert Image:

$$D(x) = 1 - \text{GaussianBlur}(I(x))$$

This reframes low-light enhancement as a **dehazing-like restoration problem** (darkness treated analogously to haze).

### Atmospheric Light Estimation (A)

The goal here is to estimate a stable reference for the scene's overall illumination essentially finding a reliable "lighting anchor."

First, the dark channel is computed using morphological erosion. This process looks at small local regions and captures their darkest intensities, which helps reveal areas influenced by global lighting conditions.

From this dark channel image, the top 1% brightest pixels are selected. These pixels are most representative of the scene's ambient light. Instead of averaging them, the median RGB values are calculated to ensure robustness against outliers.

The result is **A**, the ambient light vector a solid estimate of the scene's overall illumination. This acts as the normalization reference for the subsequent enhancement steps.

### Illumination Normalization

The goal of this step is to remove unwanted color tint and uneven lighting from the image.

First, the inverted image is divided by the estimated atmospheric light **A**. This helps cancel out the overall lighting influence, especially any dominant color cast caused by the environment.

After that, each color channel is normalized to the range [0, 1]. This keeps the values stable and comparable across channels.

By doing this, the image's reflectance is separated from the illumination effects. In simple terms, it reduces lighting bias so the model can focus on the actual content of the scene.

## Adaptive Gamma-Based Transmission Estimation

The goal here is to estimate how much light reaches each pixel in other words, how strongly illumination affects different parts of the image.

First, intensity and max-channel maps are computed. These give a sense of overall brightness and the strongest color response at each pixel, helping identify how light is distributed across the scene.

Next, Pixel Adaptive Gamma Correction is applied. Instead of using one global adjustment, the correction adapts to each pixel, enhancing darker regions more carefully while preserving brighter areas.

From these adjusted values, a transmission map is derived. This map represents how much light passes through the scene at every pixel essentially modeling where the image is heavily influenced by lighting and where it isn't.

Derive Transmission map:

$$T(x) = 1 - h_i \cdot (t_d / t_n)$$

Clip to minimum threshold (0.1).

This dynamically adjusts brightness based on local luminance structure.

## Image Recovery (Restoration Model)

**Goal:** Recover enhanced image via physical restoration formula.

$$J(x) = [\{I(x) - 1 + A\} / \{T(x)\}] + 1 - A$$

## Contrast Stretching & Final Adjustment

The goal here is to make the image look clearer and more visually appealing.

First, percentile-based contrast stretching is applied, focusing on the middle 0.5% to 99.5% of pixel values. This expands the useful brightness range while ignoring extreme outliers, enhancing overall contrast.

Next, the values are clipped to ensure they stay within a valid range, then converted back to standard 8-bit format (uint8) for display or further processing.

The result is an image with restored clarity, richer contrast, and a more natural-looking dynamic range.




## User Manual & User Interface

This is a web based tool that help the users to enhance their taken real world photos. Every user can enhance two types of image, firstly the can enhance the low light images captured by them. And secondly, they can enhance the ultra wide & tele view images by merging them in only single frame.

## Home

Users can select anyone from low light image enhancement & zero shot dual lens super resolution.



*Fig-14: Home page of Image Enhancement Suite*

## Low Light Image Enhancement

# Low-Light Image Enhancement

Transform dark, underexposed images into bright, clear visuals using advanced adaptive gamma correction and atmospheric light estimation algorithms.

- ✨ Adaptive gamma correction
- 🎯 Noise reduction & denoising
- 🔍 Detail preservation
- ⚡ Fast processing pipeline

**Start Enhancement →**

*Fig-15: Low light enhancement*

### Upload Image

User can upload the low light image.




Fig-16: Low light image upload

## Processing

Default Gamma value is 6. User can change the value of gamma from 1 to 10.





Fig-17: Low light enhancement process

## Enhanced Output



*Fig-18: Low light enhanced output*

Zero Shot Dual Lens Super Resolution

# Zero-Shot Dual Lens Super Resolution

Achieve remarkable image quality by combining wide-angle and telephoto views using cutting-edge zero-shot learning and dual-lens fusion technology.



Dual-lens image fusion



Super-resolution enhancement



Deep learning alignment




Professional quality output

**Start Processing →**

*Fig-19: ZeDuSR*


Upload

User can upload the wide view & tele view images.



*Fig-20: Upload wide view & tele view image*

## Processing



*Fig-21: Select name for processing*

## Outputs


### Input Images (Resized)

#### Resized TeleView



*Fig-22: Resized Teleview*

### Resized WideView



Wide-angle lens capture resized for processing pipeline

*Fig-23: Resized wideview*

### Intermediate Processing


---

#### Aligned Image




*Fig-24: Aligned Image*





*Fig-25: Enhanced Output after 11 iteration out of 201*

User can download the final enhanced output.



*Fig-26: Downloading final enhanced photo*

## Preliminary Test Plan

In this chapter, a high-level description of testing goals and a summary of features to be tested are presented for the **Real-Time Dual-Lens Photo Enhancer** web tool.

### High-Level Description of Testing Goals

Testing goals for this tool are represented below from a high level:

- To demonstrate that the tool meets its documented functional and non-functional requirements
- To verify that input images (ultra-wide and telephoto) are correctly uploaded, processed, and stored in the appropriate session folders
- To ensure that each processing step (Resize → Pre-Alignment → Color Correction → Alignment → Enhancement) produces expected intermediate and final outputs
- To confirm that the fusion/enhancement algorithm produces visually improved results with transferred sharp details while preserving the wide field of view
- To verify that artifacts, color mismatches, alignment errors, and severe distortions are minimized in the final enhanced image
- To ensure the step-by-step workflow is intuitive, responsive, and provides proper user feedback (modals, progress indicators)
- To confirm the system handles various input image sizes, formats (JPG/JPEG/PNG), and quality levels gracefully
- To ensure the entire pipeline runs smoothly without crashes, memory leaks, or excessive processing time on target hardware

### Test Cases

Test cases for the testing of the **Real-Time Dual-Lens Photo Enhancer** web tool are documented below:

#### Test Case 1: Web Application Access & Initial Load

##### Test Scenario:

- Open the web tool URL in a modern browser (Chrome, Firefox, Edge).
- Verify page loads without JavaScript/console errors.

##### Expected Outcome:

- The upload page displays correctly with “Upload Now” button.

- No critical errors appear in the browser console.

Result: Passed. Upload page displayed.

### **Test Case 2: Image Upload (Teleview & Wideview)**

#### **Test Scenario:**

- Upload one ultra-wide (wideview) and one telephoto (teleview) image of the same scene via drag & drop or file picker.
- Click the “Upload Now” button.

#### **Expected Outcome:**

- Both images are successfully uploaded.
- User is redirected to the next page (“Start Process” button appears).

Result: Passed. Both images are uploaded.

### **Test Case 3: Resize Step**

#### **Test Scenario:**

- On the process page, click “Start Process”.

#### **Expected Outcome:**

- Modal displays “Images are resized”.
- Resized versions of both images are created and stored in /uploads/{session\_id}/resized/.
- Images have consistent dimensions suitable for further processing.

Result: Passed. Images are successfully resized.

### **Test Case 4: Pre-Alignment Step**

#### **Test Scenario:**

- After resizing, proceed to “Perform Pre-Alignment” segment.

#### **Expected Outcome:**

- Modal displays “Pre alignment done”.
- Pre-aligned output (including cropped and SIFT-aligned versions) are generated and stored in /uploads/{session\_id}/pre\_aligned/.
- No crashes during feature detection/matching.

Result: Passed. Sift aligned photo successfully stored in corresponding folder.

### **Test Case 5: Color Correction Step**

#### **Test Scenario:**

- After pre alignment, proceed to “Color Correction” segment

#### **Expected Outcome:**

- Modal displays “Color correction is done”.
- Color-corrected telephoto image is created and saved in /uploads/{session\_id}/color\_corrected/.
- Colors/brightness/exposure between wideview and teleview are noticeably better matched.

Result: Passed. Color corrected photo is generated & stored in respective folder.

### **Test Case 6: Main Alignment & Warping Step**

#### **Test Scenario:**

- After color correction proceed to “Alignment” segment

#### **Expected Outcome:**

- Modal displays “Alignment is done”.
- Aligned outputs (HR.png and out\_20\_warp.png or similar) are generated in /uploads/{session\_id}/aligned/.
- Geometric alignment is accurate with minimal visible misalignment.

Result: Passed. The aligned photo of wide view & tele view images is successfully generated & stored in the respective folder.

### **Test Case 7: Final Enhancement Generation**

#### **Test Scenario:**

- On the final step, after alignment proceed to “Super Resolution enhancement” segment.

#### **Expected Outcome:**

- Processing completes successfully.
- Final enhanced image is saved in /uploads/{session\_id}/enhanced/.

- Two buttons appear: “View Enhanced Image” and “Download Enhanced Image”.
- Clicking “View” opens the result in a proper viewer window.
- Clicking “Download” triggers correct file download (Enhanced\_Image.png).

Result: Passed. Final enhanced photo is generated, two buttons names View Enhanced Image & Download Enhanced Image are appeared. After clicking View, opened the result in a proper viewer window. After clicking Download, triggered to download the enhanced photo.

## Test Case 8: Visual Quality of Enhanced Result

### Test Scenario:

- Compare original wideview and final enhanced image (subjective + objective check) using PSNR metric.

### Expected Outcome:

- Enhanced image shows:
  - Full wide field of view (from wideview)
  - Sharper textures/details transferred from teleview
  - Natural appearance with minimal artifacts, halo, color bleeding, or ghosting.
  - Gradually increasing PSNR value, indicating that the quality of generated enhanced image gradually increasing after each epochs.

Result: Passed. Let's see the PSNR value after 10 successful iterations.

```
warnings.warn(
iter: 0/201, lr: 0.000200000 | PSNR:4.149 | loss: 1.97992 | loss_rec:1.98
5%|  | 10/201 [04:55<1:18:50, 24.77s/it]
iter: 10/201, lr: 0.000100000 | PSNR:19.38 | loss: 0.09086 | loss_rec:0.09086
10%|  | 20/201 [09:24<1:34:30, 31.33s/it]
iter: 20/201, lr: 0.000100000 | PSNR:20.82 | loss: 0.06856 | loss_rec:0.06856
15%|  | 30/201 [14:22<1:13:32, 25.80s/it]
iter: 30/201, lr: 0.000100000 | PSNR:20.93 | loss: 0.06420 | loss_rec:0.0642
20%|  | 40/201 [18:28<1:06:35, 24.81s/it]
iter: 40/201, lr: 0.000100000 | PSNR:21.1 | loss: 0.05840 | loss_rec:0.0584
25%|  | 50/201 [22:30<1:00:42, 24.12s/it]
iter: 50/201, lr: 0.000100000 | PSNR:20.97 | loss: 0.05721 | loss_rec:0.05721
30%|  | 60/201 [26:34<57:02, 24.27s/it]
iter: 60/201, lr: 0.000100000 | PSNR:21.78 | loss: 0.05511 | loss_rec:0.05511
35%|  | 70/201 [30:54<1:00:13, 27.59s/it]
iter: 70/201, lr: 0.000100000 | PSNR:22.69 | loss: 0.05476 | loss_rec:0.05476
40%|  | 80/201 [35:30<58:12, 28.86s/it]
iter: 80/201, lr: 0.000100000 | PSNR:22.08 | loss: 0.05284 | loss_rec:0.05284
```

Fig-27: PSNR metrics value

```

iter: 90/201, lr: 0.000100000 | PSNR:21.3 | loss: 0.05499 | loss_rec:0.05499
50%|██████ | 100/201 [44:25<42:07, 25.02s/it]
iter: 100/201, lr: 0.000100000 | PSNR:23.48 | loss: 0.04887 | loss_rec:0.04887
55%|██████ | 110/201 [48:49<36:58, 24.38s/it]
iter: 110/201, lr: 0.000100000 | PSNR:22.6 | loss: 0.05094 | loss_rec:0.05094
60%|██████ | 120/201 [1:24:07<2:40:09, 118.64s/it]
iter: 120/201, lr: 0.000100000 | PSNR:26.54 | loss: 0.04235 | loss_rec:0.04235
65%|██████ | 130/201 [1:28:03<30:59, 26.18s/it]
iter: 130/201, lr: 0.000100000 | PSNR:23.7 | loss: 0.04824 | loss_rec:0.04824
70%|██████ | 140/201 [1:32:01<24:19, 23.93s/it]
iter: 140/201, lr: 0.000100000 | PSNR:23.31 | loss: 0.04887 | loss_rec:0.04887
75%|██████ | 150/201 [1:36:00<20:20, 23.93s/it]
iter: 150/201, lr: 0.000100000 | PSNR:25.86 | loss: 0.04277 | loss_rec:0.04277
80%|██████ | 160/201 [1:39:58<16:06, 23.58s/it]
iter: 160/201, lr: 0.000100000 | PSNR:22.31 | loss: 0.05038 | loss_rec:0.05038
85%|██████ | 170/201 [1:43:58<12:28, 24.15s/it]
iter: 170/201, lr: 0.000100000 | PSNR:25.39 | loss: 0.04296 | loss_rec:0.04296
90%|██████ | 180/201 [1:47:55<08:19, 23.81s/it]
iter: 180/201, lr: 0.000100000 | PSNR:23.41 | loss: 0.05060 | loss_rec:0.0506
95%|██████ | 190/201 [1:51:53<04:19, 23.63s/it]
iter: 190/201, lr: 0.000100000 | PSNR:23.46 | loss: 0.04831 | loss_rec:0.04831
00%|██████ | 200/201 [1:55:51<00:23, 23.75s/it]
iter: 200/201, lr: 0.000100000 | PSNR:24.82 | loss: 0.04657 | loss_rec:0.04657
00%|██████ | 201/201 [1:56:41<00:00, 34.83s/it]

```

*Fig-28: PSNR metrics value*

## Test Case 9: Error Handling & Robustness

### Test Scenario:

- Upload mismatched images (different scenes), a single image only, a corrupted file.

### Expected Outcome:

- Appropriate error messages/modals are shown to the user.
- System does not crash.
- Invalid sessions are handled gracefully.

Result: Passed. Error message was showed if any mismatched occurred.

## Why ZeDuSR

| Aspect                                            | ZeDuSR (2023)                                         | Generic SISR (SwinIR, RCAN) | Blind/Real-world SR (Real-ESR GAN, BSRGAN, DAN) | Online Platforms (Let's Enhance, Topaz, Waifu2x) | Prior Dual-Lens Methods (DCSR, SelfDZSR)           |
|---------------------------------------------------|-------------------------------------------------------|-----------------------------|-------------------------------------------------|--------------------------------------------------|----------------------------------------------------|
| <b>Training Data Needed</b>                       | None (zero-shot, learns from your pair only)          | Large external dataset      | Large external dataset                          | Pre-trained                                      | External or device-specific data                   |
| <b>Adapts to Exact Image Degradations</b>         | Excellent (image-specific model)                      | Poor (fixed assumption)     | Moderate (blind kernel estimation)              | Poor to moderate                                 | Moderate (self-supervised but not fully zero-shot) |
| <b>Performance on Real Dual-Lens Phone Photos</b> | Best (paper shows highest PSNR/SSIM + visual quality) | Lower (domain gap)          | Good but artifacts common                       | Often over-sharp or unnatural                    | Good, but ZeDuSR beats them in most cases          |
| <b>Quantitative Edge</b>                          | 28.87–32.77 PSNR / 0.75–0.92 SSIM (top in tables)     | 27.90–31.96 PSNR            | 27.82–32.46 PSNR                                | Varies, usually lower perceptual quality         | 27.99–32.02 PSNR                                   |
| <b>Best For</b>                                   | Smartphone wide-angle → sharp upscale using telephoto | General clean images        | Real-world blind restoration                    | Quick single-image upscale                       | Dual-lens but less adaptive                        |

## Conclusion

This report details the full technical framework of the **Real-Time Dual-Lens Photo Enhancer**, a web tool that merges ultra-wide and telephoto images into a single, high-quality photo. The result combines wide context with sharp detail, giving users the best of both lenses.

It covers everything from the project scope and workflow to modeling (use cases, data structures, classes), architectural design (context, archetypes, top-level components), and a structured preliminary test plan. The entire pipeline is built in Python using PyTorch, removing the need for MATLAB and achieving faster, optimized inference.

The system consistently produces natural, high-quality enhanced images, making it suitable for applications in photography, surveillance, autonomous systems, and professional imaging.

Looking ahead, potential improvements include real-time video processing, more advanced AI-based fusion models, user-adjustable parameters, cloud-based scaling, and mobile integration.

Overall, this document provides a clear and comprehensive view of the system's design, implementation, and future possibilities, representing a practical step forward in computational photography.