

CSE 604

Artificial Intelligence

Chapter 6: Constraint Satisfaction Problems

Adapted from slides available in Russell & Norvig's textbook webpage

Dr. Ahmedul Kabir

Outline

- Constraint Satisfaction Problems (CSP)
- Backtracking search for CSPs
- Local search for CSPs

Constraint satisfaction problems (CSPs)


- Standard search problem:
 - **state** is a "black box" – any data structure that supports successor function, heuristic function, and goal test
- CSP:
 - **state** is defined by **variables** X_i with **values** from **domain** D_i
 - **goal test** is a set of **constraints** specifying allowable combinations of values for subsets of variables
- Simple example of a **formal representation language**
- Allows useful **general-purpose** algorithms with more power than standard search algorithms

Example: Map-Coloring



- **Variables:** WA, NT, \mathcal{L}
- **Domains:** $D_i = \{\text{red}, \text{green}, \text{blue}\}$
- **Constraints:** adjacent regions must have different colors
- e.g., $WA \neq NT$ (if the language allows this), or
 $(WA, NT) \in \{(\text{red}, \text{green}), (\text{red}, \text{blue}), (\text{green}, \text{red}), (\text{green}, \text{blue}), (\text{blue}, \text{red}), (\text{blue}, \text{green})\}$


Example: Map-Coloring



- **Solutions** are **complete** and **consistent** assignments,
- e.g., WA = red, NT = green, Q = red, NSW = green, V = red, SA = blue, T = green

Constraint graph

- **Binary CSP:** each constraint relates two variables
- **Constraint graph:** nodes are variables, arcs are constraints



Varieties of CSPs

- Discrete variables

- finite domains:

- n variables, domain size $d \rightarrow O(d^n)$ complete assignments
 - e.g., Boolean CSPs, incl. \sim Boolean satisfiability (NP-complete)

- infinite domains:

- integers, strings, etc.
 - e.g., job scheduling, variables are start/end days for each job
 - need a constraint language, e.g., $StartJob_1 + 5 \leq StartJob_3$

- Continuous variables


- e.g., start/end times for Hubble Space Telescope observations
 - linear constraints solvable in polynomial time by linear programming

Varieties of constraints

- **Unary** constraints involve a single variable,
 - e.g., $SA \neq \text{green}$
- **Binary** constraints involve pairs of variables,
 - e.g., $SA \neq WA$
- **Higher-order** constraints involve 3 or more variables,
 - e.g., alldiff (all values of a set should be different)

Example: Cryptarithmic

$$\begin{array}{r}
 \text{TWO} \\
 + \text{TWO} \\
 \hline
 \text{FOUR}
 \end{array}$$



- **Variables:** $F T U W$
 $R O X_1 X_2 X_3$
- **Domains:** $\{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$
- **Constraints:** $Alldiff(F, T, U, W, R, O)$
 - $O + O = R + 10 \cdot X_1$
 - $X_1 + W + W = U + 10 \cdot X_2$
 - $X_2 + T + T = O + 10 \cdot X_3$
 - $X_3 = F, T \neq 0, F \neq 0$

Real-world CSPs

- Assignment problems
 - e.g., who teaches what class
- Timetabling problems
 - e.g., which class is offered when and where?
- Transportation scheduling
- Factory scheduling
- Notice that many real-world problems involve real-valued variables

Standard search formulation (incremental)

Let's start with the straightforward approach, then fix it

States are defined by the values assigned so far

- **Initial state:** the empty assignment $\{ \}$
 - **Successor function:** assign a value to an unassigned variable that does not conflict with current assignment
fail if no legal assignments
 - **Goal test:** the current assignment is complete
1. This is the same for all CSPs
 2. Every solution appears at depth n with n variables
 - use depth-first search
 3. Path is irrelevant, so can also use complete-state formulation
 4. $b = (n - \ell)d$ at depth ℓ , hence $n! \cdot d^n$ leaves

Backtracking search

- Variable assignments are **commutative**, i.e.,
[WA = red then NT = green] same as [NT = green then WA = red]
- Only need to consider assignments to a single variable at each node
b = d and there are d^n leaves
- Depth-first search for CSPs with single-variable assignments is called **backtracking search**
- Backtracking search is the basic uninformed algorithm for CSPs
- Can solve n -queens for $n \approx 25$

Backtracking search

```
function BACKTRACKING-SEARCH(csp) returns a solution, or failure
    return RECURSIVE-BACKTRACKING( $\{\}$ , csp)

function RECURSIVE-BACKTRACKING(assignment, csp) returns a solution, or failure
    if assignment is complete then return assignment
    var  $\leftarrow$  SELECT-UNASSIGNED-VARIABLE(Variables[csp], assignment, csp)
    for each value in ORDER-DOMAIN-VALUES(var, assignment, csp) do
        if value is consistent with assignment according to Constraints[csp] then
            add { var = value } to assignment
            result  $\leftarrow$  RECURSIVE-BACKTRACKING(assignment, csp)
            if result  $\neq$  failure then return result
            remove { var = value } from assignment
    return failure
```


Backtracking example




Backtracking example



Backtracking example



Backtracking example



Improving backtracking efficiency

- **General-purpose** methods can give huge gains in speed:
 - Which variable should be assigned next?
 - In what order should its values be tried?
 - Can we detect inevitable failure early?


Minimum remaining values (MRV)

- Minimum remaining values:
choose the variable with the fewest legal values




Degree Heuristic

- Tie-breaker among MRV variables
- Degree Heuristic (most constraining variable first):
 - choose the variable with the most constraints on remaining variables (with the highest degree)



Least constraining value


- Given a variable, choose the least constraining value:
 - the one that rules out the fewest values in the remaining variables
- Combining these heuristics makes 1000 queens feasible



Forward checking

- Idea:


- Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values



Forward checking

- Idea:


- Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values



Forward checking

- Idea:


- Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values



Forward checking


- Idea:

- Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values





Example: 4-Queens Problem








	1	2	3	4
1				
2				
3				
4				




Example: 4-Queens Problem





Example: 4-Queens Problem



	1	2	3	4
1				
2				
3				
4				



Example: 4-Queens Problem




Example: 4-Queens Problem





Dead End → Backtrack

Example: 4-Queens Problem

	1	2	3	4
1	★	●	●	●
2	■	●	■	●
3	□	■	●	■
4	■	★	●	●




Example: 4-Queens Problem





Dead End → Backtrack

Example: 4-Queens Problem

	1	2	3	4
1		●		
2	★	●	●	●
3		●		
4			●	




Example: 4-Queens Problem




Example: 4-Queens Problem

	1	2	3	4
1		●		
2	★	●	●	●
3		●	●	
4		★	●	●




Example: 4-Queens Problem

	1	2	3	4
1		●		
2	★	●	●	●
3		●	●	
4		★	●	●




Example: 4-Queens Problem

	1	2	3	4
1		●	★	●
2	★	●	●	●
3		●	●	
4		★	●	●



Example: 4-Queens Problem


	1	2	3	4
1		●	★	●
2	★	●	●	●
3		●	●	
4		★	●	●




Example: 4-Queens Problem

	1	2	3	4
1		●	★	●
2	★	●	●	●
3		●	●	★
4	■	★	●	●


Solution !!!!




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking




Forward Checking



Forward Checking




Forward Checking



Solution !!!

Constraint propagation


- Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:



- NT and SA cannot both be blue!
- Constraint propagation repeatedly enforces constraints locally


Arc consistency

- Simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$ is consistent iff
for **every** value x of X there is **some** allowed y




Arc consistency

- Simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$ is consistent iff
for **every** value x of X there is **some** allowed y



Arc consistency


- Simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$ is consistent iff
for **every** value x of X there is **some** allowed y



- If X loses a value, neighbors of X need to be rechecked

Arc consistency

- Simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$ is consistent iff
for **every** value x of X there is **some** allowed y



- If X loses a value, neighbors of X need to be rechecked
- Arc consistency detects failure earlier than forward checking
- Can be run as a preprocessor or after each assignment

Arc consistency algorithm AC-3

```
function AC-3(csp) returns the CSP, possibly with reduced domains
  inputs: csp, a binary CSP with variables  $\{X_1, X_2, \dots, X_n\}$ 
  local variables: queue, a queue of arcs, initially all the arcs in csp

  while queue is not empty do
     $(X_i, X_j) \leftarrow \text{REMOVE-FIRST}(\textit{queue})$ 
    if RM-INCONSISTENT-VALUES( $X_i, X_j$ ) then
      for each  $X_k$  in NEIGHBORS[ $X_i$ ] do
        add  $(X_k, X_i)$  to queue




---



function RM-INCONSISTENT-VALUES( $X_i, X_j$ ) returns true iff remove a value
  removed  $\leftarrow$  false
  for each  $x$  in DOMAIN[ $X_i$ ] do
    if no value  $y$  in DOMAIN[ $X_j$ ] allows  $(x, y)$  to satisfy constraint( $X_i, X_j$ )
      then delete  $x$  from DOMAIN[ $X_i$ ]; removed  $\leftarrow$  true
  return removed
```

- Time complexity: $O(n^2 d^3)$


Arc Consistency: AC3




Arc Consistency: AC3



Arc Consistency: AC3




Arc Consistency: AC3




If X loses a value, neighbors of X need to be rechecked

Arc Consistency: AC3




If X loses a value, neighbors of X need to be rechecked

Arc Consistency: AC3




If X loses a value, neighbors of X need to be rechecked

Arc Consistency: AC3




If X loses a value, neighbors of X need to be rechecked


Arc Consistency: AC3




Arc Consistency: AC3




Arc Consistency: AC3




Arc Consistency: AC3




Arc Consistency: AC3




Arc Consistency: AC3




Arc Consistency: AC3




Arc Consistency: AC3



Arc Consistency: AC3



Arc Consistency: AC3




Solution !!!

Local search for CSPs


- Hill-climbing, simulated annealing typically work with "complete" states, i.e., all variables assigned
- To apply to CSPs:
 - allow states with unsatisfied constraints
 - operators **reassign** variable values
- Variable selection: randomly select any conflicted variable
- Value selection by **min-conflicts** heuristic:
 - choose value that violates the fewest constraints
 - i.e., hill-climb with $h(n)$ = total number of violated constraints

Example: 4-Queens

- **States:** 4 queens in 4 columns ($4^4 = 256$ states)
- **Actions:** move queen in column
- **Goal test:** no attacks
- **Evaluation:** $h = \text{number of attacking pairs}$



$h = 5$



$h = 2$



$h = 0$

- Given random initial state, can solve n -queens in almost constant time for arbitrary n with high probability (e.g., $n = 10,000,000$)

Summary

- CSPs are a special kind of problem:
 - states defined by values of a fixed set of variables
 - goal test defined by constraints on variable values
- Backtracking = depth-first search with one variable assigned per node
- Variable ordering and value selection heuristics help significantly
- Forward checking prevents assignments that guarantee later failure
- Constraint propagation (e.g., arc consistency) does additional work to constrain values and detect inconsistencies
- Iterative min-conflicts is usually effective in practice