

ANALYSIS OF LIGHT RESPONSES IN SMH 2P

Data obtained by Percival D'Gama at 5dpf. HuC:GCamp6s smh controls (heterozygous and wt) and smh (homozygous) mutants

Codes updated July 2024

Plot Figure 2photon panel D1-F4

```
%Set path to where your codes are  
addpath(genpath('X:\Nathalie\data\github\DGama_et_al_CR_2024'))
```

STEP1 LOAD ALL DATA INTO ONE CELL ARRAY-----

set the path for the 2p data and the number of cell data

```
cfg.pathData='X:\Manuscripts\Dgama etal 2024 smh\data\Figure 3\Panel D1-E1\';
```

load the data into few matrix

```
[ctrlON,ctrlOFF,mutON,mutOFF,time]=nj_load2pdata_v3(cfg);
```

The matrix contain the following information, example for ctrlON

column 1: experimental animal

column 2: the DFF trace of cells that are activated by the ON stimulus

column 3: the DFF trace of cells that are inhibited by the ON stimulus

column 4: the position,x,y,z,brain region of cells that are activated by the ON stimulus

column 5: the position,x,y,z,brain region of cells that are inhibited by the ON stimulus

column 6: the DFF traces of all cells

column 7: the position,x,y,z,brain region of all cells

NB: the DFF traces are the average traces for the 5 stimuli

calculate the number of dataset

```
numCTRL=size(ctrlOFF,1)-1
```

```
numCTRL = 8
```

```
numMUT=size(mutOFF,1)-1
```

```
numMUT = 14
```

SET SOME PARAMETERS FOR THE PLOTS

```
close all  
clear cfg
```

enter some parameters for the plots into one variable called cfg

```
cfg.MutID='SMH' %enter the name of your mutant 'ELIPSA', this is for the title
```

```
cfg = struct with fields:  
    MutID: 'SMH'
```

```
cfg.Mutcolor='m' %enter the color you want for your mutantd display, 'm'= magenta, 'c'=cyan
```

```
cfg = struct with fields:  
    MutID: 'SMH'  
    Mutcolor: 'm'
```

```
cfg.numCTRL=numCTRL;  
cfg.numMUT=numMUT;  
cfg.label=["tel" "OT" "hind" "habenula"];  
cfg.brainRegion=char('telencephalon','TeO/thalamus','Hindbrain', 'Habenula');  
cfg
```

```
cfg = struct with fields:  
    MutID: 'SMH'  
    Mutcolor: 'm'  
    numCTRL: 8  
    numMUT: 14  
    label: ["tel" "OT" "hind" "habenula"]  
    brainRegion: [4×13 char]
```


PLOT THE AVERAGE RESPONSE FOR ALL CELLS PER FISH

plot all response to all fishes


```
[averageON_ALL,averageOFF_ALL]=plot_responseALL_perfish(ctrlON,ctrlOFF,muON,muOFF,time,cfg);
```

SMH Amplitude of ALL responses

black = ON response 8 ctrl and 14 mut fish



Average OFF response 8 ctrl and 14 mut fish




PLOT THE AVERAGE RESPONSE FOR ALL CELLS FOR ALL FISH

generate panel D1-E1


```
plot_responseALL_average(averageON_ALL,averageOFF_ALL,time,cfg);
```

SMH Amplitude of ON and OFF

Average ON for all cells in 8 ctrl and 14 mut fish




Average OFF for all cells in 8 ctrl and 14 mut fish




SMH Amplitude of ON and OFF

Average ON for all cells in 8 ctrl and 14 mut fish responses, SEM



Average OFF for all cells in 8 ctrl and 14 mut fish





PLOT THE AVERAGE RESPONSE FOR ALL CELLS PER FISH

generate statistics for panel D1-E1

```
plot_scatterAll(averageON_ALL,averageOFF_ALL,ctrlON,ctrlOFF, mutON, mutOFF, time,cfg)
```

```
ans =  
'0.022228'
```







ans =
'0.16176'

CALCULATE % RESPONDING CELLS PER BRAIN REGION

generate panel D3-D4-E3-E4

```
plot_response_perregion_v2(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)
```







CALCULATE AMPLITUDE PER BRAIN REGION

generate panel D2-E2

```
plot_amplitude_perregion(ctrlON,ctrlOFF,muON,muOFF,time,cfg)
```

CALCULATE % ON RESPONDING CELLS BASED ON location of cells in x,y,z

chose ON dataset for the analysis

```
cfg.data=1;
```

Identify midline, by plotting OT and using ginput

```
% % ONLY NEEDS TO BE DONE ONCE
% identify_midline(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)
% %
% % [midline_ctrl] = ginput() % select figure of ctrl
% [midline_mut] = ginput() % select figure of ctrl
% % copy values below
cfg.midline_ctrl = [352.102803738318    113.584829143338
370.917573872473    117.231685264341
456.775700934579    117.231685264341
391.951788491446    118.941323733066
391.355140186916    122.365919655480
369.634525660964    118.943096728054
418.118195956454    114.838067459285
423.403426791277    127.500154046618];
cfg.midline_mut = [376.401869158878    115.065469573066
374.183514774495    115.520273800628
444.626168224299    113.662232139248
266.757387247278    105.866776750983
426.401869158879    119.275181874520
393.856920684292    121.840388645827
447.429906542056    120.372432156119
304.276827371695    114.838067459285
422.313084112150    117.159232937755
400.388802488336    119.746625281139
387.1495            119.5109
401.788491446345    113.437603221977
377.803738317757    123.871136966938
467.573872472784    120.372432156118];
```


Location of the responding cells.



High Y axis value is left. In the scatter plots, left is anterior, right is poster, down is left, up is right

In teh shaded error bars are shown SEM

```
plot_respondingXYZ(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg);
```



SMH
ON
scatter of responding cells in
tel








SMH
ON
scatter of responding cells in
OT








SMH
ON
scatter of responding cells in
hind





SMH
ON
scatter of responding cells in
habenula





CALCULATE % OFF RESPONDING CELLS BASED ON location of cells in x,y,z

Choose OFF dataset for the analysis

```
cfg.data=2;
```

Location of the responding cells

```
plot_respondingXYZ(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)
```

NESTED FUNCTIONS

FUNCTION 1 TO PLOT THE AVERAGE DATA FOR ALL CELLS PER ANIMAL FOR ALL ANIMALS ON TOP OF EACH OTHER=====

```
function [averageON_ALL,averageOFF_ALL]=plot_responseALL_perfish(ctrlON,ctrlOFF,mutON,mutOFF,t  
  
figure (30)  
clf  
set(gcf, 'Position',[100 100 400 700])  
str= {[cfg.MutID ' Amplitude of ALL responses black=ctrl']};  
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',14, 'FontWeight', 'bold', 'L  
  
% Average response ON  
subplot(2,1,1)  
for i=2:cfg.numCTRL+1  
shadedErrorBar(time,mean(ctrlON{i,6},1),std(ctrlON{i,6},[],1)/sqrt(size(ctrlON{i,6},1)), 'lineprop  
xlabel('time in sec')  
ylabel('DFF')  
averageON_ALL.ctrl(i-1,:)=mean(ctrlON{i,6},1);  
end  
for i=2:cfg.numMUT+1  
shadedErrorBar(time,mean(mutON{i,6},1),std(mutON{i,6},[],1)/sqrt(size(mutON{i,6},1)), 'lineprop  
xlabel('time in sec')  
ylabel('DFF')  
averageON_ALL.mut(i-1,:)=mean(mutON{i,6},1);  
end  
title(['Average ON response ' num2str(cfg.numCTRL) ' ctrl and ' num2str(cfg.numMUT) ' mut fish  
  
% Average response OFF  
subplot(2,1,2)  
for i=2:cfg.numCTRL+1  
shadedErrorBar(time,mean(ctrlOFF{i,6},1),std(ctrlOFF{i,6},[],1)/sqrt(size(ctrlOFF{i,6},1)), 'li  
xlabel('time in sec')  
ylabel('DFF')  
averageOFF_ALL.ctrl(i-1,:)=mean(ctrlOFF{i,6},1);  
end  
for i=2:cfg.numMUT+1  
shadedErrorBar(time,mean(mutOFF{i,6},1),std(mutOFF{i,6},[],1)/sqrt(size(mutOFF{i,6},1)), 'linepr  
xlabel('time in sec')  
ylabel('DFF')  
averageOFF_ALL.mut(i-1,:)=mean(mutOFF{i,6},1);  
end  
title(['Average OFF response ' num2str(cfg.numCTRL) ' ctrl and ' num2str(cfg.numMUT) ' mut fish
```

end

% FUNCTION2 PLOT THE AVERAGE OF THE AVERAGE OF ALL CELLS FOR ALL ANIMALS ON TOP OF EACH OTHER=====

```
function plot_responseALL_average(averageON_ALL,averageOFF_ALL,time,cfg)

figure (40)
clf
set(gcf, 'Position',[100 100 400 600])
str= {[cfg.MutID ' Amplitude of ON and OFF responses, SEM']};
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',14, 'FontWeight', 'bold', 'l

subplot(2,1,1)
rectangle('Position',[0 -8 60 70],'FaceColor',[0.99 0.99 0.75], 'EdgeColor',[0.99 0.99 0.75]),
shadedErrorBar(time,mean(averageON_ALL.ctrl,1),std(averageON_ALL.ctrl,[],1)/sqrt(size(averageON_A
shadedErrorBar(time,mean(averageON_ALL.mut,1),std(averageON_ALL.mut,[],1)/sqrt(size(averageON_A
title(['Average ON for all cells in' num2str(cfg.numCTRL) ' ctrl and ' num2str(cfg.numMUT) ' mu
xlim([-120 120])
ylim([-5 30])
xlabel('seconds')
ylabel('dF/F')

subplot(2,1,2)
rectangle('Position',[0 -40 60 80],'FaceColor',[0.99 0.99 0.75], 'EdgeColor',[0.99 0.99 0.75]),
shadedErrorBar(time,mean(averageOFF_ALL.ctrl,1),std(averageOFF_ALL.ctrl,[],1)/sqrt(size(average
shadedErrorBar(time,mean(averageOFF_ALL.mut,1),std(averageOFF_ALL.mut,[],1)/sqrt(size(averageO
title(['Average OFF for all cells in' num2str(cfg.numCTRL) ' ctrl and ' num2str(cfg.numMUT) ' r
xlim([-120 120])
ylim([-5 30])
xlabel('seconds')
ylabel('dF/F')

figure (41)
clf
set(gcf, 'Position',[100 100 400 600])
str= {[cfg.MutID ' Amplitude of ON and OFF responses, SEM']};
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',14, 'FontWeight', 'bold', 'l

subplot(2,1,1)
rectangle('Position',[0 -2 60 1], 'FaceColor',[0.99 0.99 0.75], 'EdgeColor',[0.99 0.99 0.75]),
shadedErrorBar(time,mean(averageON_ALL.ctrl,1),std(averageON_ALL.ctrl,[],1)/sqrt(size(averageON
shadedErrorBar(time,mean(averageON_ALL.mut,1),std(averageON_ALL.mut,[],1)/sqrt(size(averageON_A
title(['Average ON for all cells in' num2str(cfg.numCTRL) ' ctrl and ' num2str(cfg.numMUT) ' mu
xlim([-10 60])
ylim([-5 25])
xlabel('seconds')
ylabel('dF/F')

subplot(2,1,2)
```

```

rectangle('Position',[-10 -2 10 1], 'FaceColor',[0.99 0.99 0.75], 'EdgeColor',[0.99 0.99 0.75]),
shadedErrorBar(time,mean(averageOFF_ALL.ctrl,1),std(averageOFF_ALL.ctrl,[],1)/sqrt(size(averageOFF_ALL.ctrl,1)),1),
shadedErrorBar(time,mean(averageOFF_ALL.mut,1),std(averageOFF_ALL.mut,[],1)/sqrt(size(averageOFF_ALL.mut,1)),1),
title(['Average OFF for all cells in' num2str(cfg.numCTRL) ' ctrl and ' num2str(cfg.numMUT) ' mut'])
xlim([-10 60])
ylim([-5 25])
xlabel('seconds')
ylabel('dF/F')

end

```

FUNCTION3 PLOT AVERAGE AMPLITUDE FOR 10SEC AFTER FOR RESPONDING CELLS

```

function plot_scatterAll(averageON_ALL,averageOFF_ALL,ctrlON,ctrlOFF, mutON, mutOFF, time,cfg)

% enter the frames. this is for 10sec
onset=465;
offset=503;

figure (51)
clf
set(gcf, 'Position',[100 100 300 600])
str= {[cfg.MutID ' Amplitude ALL cells, SEM,from ' num2str(time(onset)) 's to ' num2str(time(offset)) 's']}
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',10, 'FontWeight', 'bold', 'align','left')

subplot(2,1,1)
toplotC=averageON_ALL.ctrl(:,onset:offset);
toplotM=averageON_ALL.mut(:,onset:offset);
swarmchart(ones(cfg.numCTRL,1), mean(toplotC,2),'k','filled','MarkerFaceAlpha',0.5,'MarkerEdgeColor','k')
line([0.6 1.4], repmat(mean(mean(toplotC,2)),1,2),'Color','k')
errorbar(1,mean(mean(toplotC,2)), std(mean(toplotC,2)),'Color','k')
swarmchart(2*ones(cfg.numMUT,1), mean(toplotM,2),cfg.Mutcolor,'filled','MarkerFaceAlpha',0.5,'MarkerEdgeColor',cfg.Mutcolor)
line([1.6 2.4], repmat(mean(mean(toplotM,2)),1,2),'Color',cfg.Mutcolor)
errorbar(2,mean(mean(toplotM,2)), std(mean(toplotM,2)),'Color',cfg.Mutcolor)
xlim([0 3]), ylim([0 Inf])
ylabel('amplitude')
text(0.5,1,['p= '...
    num2str(ranksum(mean(toplotC,2),mean(toplotM,2)),'%4f')]);
xticks([1 2])
xticklabels({'ctrl','mut'})
title('ON response')

num2str(ranksum(mean(toplotC,2),mean(toplotM,2)))
clear toplotC toplotM

subplot(2,1,2)
toplotC=averageOFF_ALL.ctrl(:,onset:offset);
toplotM=averageOFF_ALL.mut(:,onset:offset);
swarmchart(ones(cfg.numCTRL,1), mean(toplotC,2),'k','filled','MarkerFaceAlpha',0.5,'MarkerEdgeColor','k')
line([0.6 1.4], repmat(mean(mean(toplotC,2)),1,2),'Color','k')
errorbar(1,mean(mean(toplotC,2)), std(mean(toplotC,2)),'Color','k')
swarmchart(2*ones(cfg.numMUT,1), mean(toplotM,2),cfg.Mutcolor,'filled','MarkerFaceAlpha',0.5,'MarkerEdgeColor',cfg.Mutcolor)
line([1.6 2.4], repmat(mean(mean(toplotM,2)),1,2),'Color',cfg.Mutcolor)

```

```

errorbar(2,mean(mean(toplotM,2)), std(mean(toplotM,2)), 'Color',cfg.Mutcolor)
xlim([0 3]), ylim([0 Inf])
ylabel('amplitude')
text(0.5,1,['p= '...
      num2str(ranksum(mean(toplotC,2),mean(toplotM,2)), '%.4f')]);
xticks([1 2])
xticklabels({'ctrl','mut'})
title('OFF response')

num2str(ranksum(mean(toplotC,2),mean(toplotM,2)))
clear toplotC toplotM
end

```

FUNCTION 4 plots % responding cells per brain region

```

function plot_response_perregion(ctrlON,ctrlOFF,mutON,muTOFF,time,cfg)

close all
%% calculate number of responding cells per region
NumCtrl=[];
NumMut=[];
jj=[1,4,2,3]; %reorder so that Hb is between Tel and OT, added 14.03.2023

% calculate responding cells per brain region
for k=1:cfg.numCTRL
for ik=1:4; %there are four brain region
    j=jj(ik);
    NumCtrl.ON.activated(k,ik)=length(find(ctrlON{k+1, 4}(:,4)==j))/sum(ctrlON{k+1, 7}(:,4)==j)*100;
    NumCtrl.OFF.activated(k,ik)=length(find(ctrlOFF{k+1, 4}(:,4)==j))/sum(ctrlOFF{k+1, 7}(:,4)==j)*100;
    NumCtrl.ON.inhibited(k,ik)=length(find(ctrlON{k+1, 5}(:,4)==j))/sum(ctrlON{k+1, 7}(:,4)==j)*100;
    NumCtrl.OFF.inhibited(k,ik)=length(find(ctrlOFF{k+1, 5}(:,4)==j))/sum(ctrlOFF{k+1, 7}(:,4)==j)*100;

end
end

for k=1:cfg.numMUT
for ik=1:4; %there are four brain region
    j=jj(ik);
    NumMut.ON.activated(k,ik)=length(find(mutON{k+1, 4}(:,4)==j))/sum(mutON{k+1, 7}(:,4)==j)*100;
    NumMut.OFF.activated(k,ik)=length(find(muTOFF{k+1, 4}(:,4)==j))/sum(muTOFF{k+1, 7}(:,4)==j)*100;
    NumMut.ON.inhibited(k,ik)=length(find(mutON{k+1, 5}(:,4)==j))/sum(mutON{k+1, 7}(:,4)==j)*100;
    NumMut.OFF.inhibited(k,ik)=length(find(muTOFF{k+1, 5}(:,4)==j))/sum(muTOFF{k+1, 7}(:,4)==j)*100;

end
end

figure (70),
clf
set(gcf, 'Position',[100 100 800 600])
str= [cfg.MutID ' % responding cells per brain area black=ctrl'];
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',14, 'FontWeight', 'bold', 'align','center');

subplot(2,2,1)
toplotC=NumCtrl.ON.activated;

```

```

toplotM=NumMut.ON.activated;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,'k','filled','MarkerFaceAlpha',0.5,'Marker
for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)),'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,cfg.Mutcolor,'filled','MarkerFaceA
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)),'Color',cfg.Mutcolor, 'Marker','_')
end
xlim([0 5]), ylim([0 80])
ylabel('% of responding cells')
for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-5,num2str(['Tel:' sprintf('%.3f',p(1))...
' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab', 'OT', 'Hind'})
title('ON activated')
clear toplotC toplotM p
hold off

subplot(2,2,2)
toplotC=NumCtrl.ON.inhibited;
toplotM=NumMut.ON.inhibited;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,'k','filled','MarkerFaceAlpha',0.5,'Marker
for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)),'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,cfg.Mutcolor,'filled','MarkerFaceA
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)),'Color',cfg.Mutcolor, 'Marker','_')
end
xlim([0 5]), ylim([-1 10])
ylabel('% of responding cells')

for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-5,num2str(['Tel:' sprintf('%.3f',p(1))...
' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab', 'OT', 'Hind'})
title('ON inhibited')
clear toplotC toplotM p
hold off

subplot(2,2,3)
toplotC=NumCtrl.OFF.activated;
toplotM=NumMut.OFF.activated;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,'k','filled','MarkerFaceAlpha',0.5,'Marker

```

```

for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)), 'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,cfg.Mutcolor,'filled','MarkerFaceAlpha')
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)), 'Color',cfg.Mutcolor, 'Marker','_')
end
xlim([0 5]), ylim([0 80])
ylabel('% of responding cells')
for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-5,num2str(['Tel:' sprintf('%.3f',p(1))...
' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab', 'OT', 'Hind'})
title('OFF activated')
clear toplotC toplotM p
hold off

subplot(2,2,4)
toplotC=NumCtrl.OFF.inhibited;
toplotM=NumMut.OFF.inhibited;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,'k','filled','MarkerFaceAlpha',0.5,'MarkerFaceAlpha')
for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)), 'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,cfg.Mutcolor,'filled','MarkerFaceAlpha')
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)), 'Color',cfg.Mutcolor, 'Marker','_')
end
xlim([0 5]), ylim([-1 25])
ylabel('% of responding cells')
for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-5,num2str(['Tel:' sprintf('%.3f',p(1))...
' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab', 'OT', 'Hind'})
title('OFF inhibited')
clear toplotC toplotM p
hold off
end

```

FUNCTION 5 plots % active cells per region

```

function plot_response_perregion_v2(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)
%% calculate number of responding cells per region

```



```

%close all
NumCtrl=[];
NumMut=[];
jj=[1,4,2,3]; %reorder so that Hb is between Tel and OT, added 14.03.2023

% calculate responding cells per brain region
for k=1:cfg.numCTRL
for ik=1:4; %there are four brain region
    j=jj(ik);
NumCtrl.ON.activated(k,ik)=length(find(ctrlON{k+1, 4}(:,4)==j))/sum(ctrlON{k+1, 7}(:,4)==j)*100;
NumCtrl.OFF.activated(k,ik)=length(find(ctrlOFF{k+1, 4}(:,4)==j))/sum(ctrlOFF{k+1, 7}(:,4)==j)*100;
NumCtrl.ON.inhibited(k,ik)=length(find(ctrlON{k+1, 5}(:,4)==j))/sum(ctrlON{k+1, 7}(:,4)==j)*100;
NumCtrl.OFF.inhibited(k,ik)=length(find(ctrlOFF{k+1, 5}(:,4)==j))/sum(ctrlOFF{k+1, 7}(:,4)==j)*100;

end
end

for k=1:cfg.numMUT
for ik=1:4; %there are four brain region
    j=jj(ik);
NumMut.ON.activated(k,ik)=length(find(mutON{k+1, 4}(:,4)==j))/sum(mutON{k+1, 7}(:,4)==j)*100;
NumMut.OFF.activated(k,ik)=length(find(mutOFF{k+1, 4}(:,4)==j))/sum(mutOFF{k+1, 7}(:,4)==j)*100;
NumMut.ON.inhibited(k,ik)=length(find(mutON{k+1, 5}(:,4)==j))/sum(mutON{k+1, 7}(:,4)==j)*100;
NumMut.OFF.inhibited(k,ik)=length(find(mutOFF{k+1, 5}(:,4)==j))/sum(mutOFF{k+1, 7}(:,4)==j)*100;
end
end

figure (57),
clf
set(gcf, 'Position',[100 100 300 400])
toplotC=NumCtrl.ON.activated;
toplotM=NumMut.ON.activated;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,80,'k','filled','MarkerFaceAlpha',0.5,'MarkerSize',10)
for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)),'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,80,cfg.Mutcolor,'filled','MarkerFaceAlpha',0.5,'MarkerSize',10)
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)),'Color','k', 'Marker','_')
end
xlim([0 5]), ylim([-10 70])
ylabel('% of responding cells')
for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-5,num2str(['Tel:' sprintf('%.3f',p(1))...
    ' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
    ' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab', 'OT', 'Hind'})
title('ON activated')
clear toplotC toplotM p
hold off

```

```

figure (58)
clf
set(gcf, 'Position',[100 100 300 400])
str= {[cfg.MutID ' % ON inhibited']};
toplotC=NumCtrl.ON.inhibited;
toplotM=NumMut.ON.inhibited;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,80,'k','filled','MarkerFaceAlpha',0.5,'Mar
for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)),'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,80,cfg.Mutcolor,'filled','MarkerFae
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)),'Color','k', 'Marker','_')
end
xlim([0 5]), ylim([-2 10])
ylabel('% of responding cells')

for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-1,num2str(['Tel:' sprintf('%.3f',p(1))...
    ' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
    ' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab','OT', 'Hind'})
title('ON inhibited')
clear toplotC toplotM p
hold off

figure (59)
clf
set(gcf, 'Position',[100 100 300 400])
str= {[cfg.MutID ' % OFF activated']};
toplotC=NumCtrl.OFF.activated;
toplotM=NumMut.OFF.activated;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), toplotC,80,'k','filled','MarkerFaceAlpha',0.5,'Mar
for ii=1:4
errorbar(ii,mean(toplotC(:,ii)), std(toplotC(:,ii)),'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), toplotM,80,cfg.Mutcolor,'filled','MarkerFae
for ii=1:4
errorbar(ii+0.5,mean(toplotM(:,ii)), std(toplotM(:,ii)),'Color','k', 'Marker','_')
end
xlim([0 5]), ylim([-10 70])
ylabel('% of responding cells')
for i=1:4
p(i)=ranksum(toplotC(:,i),toplotM(:,i));
end
text(0,-5,num2str(['Tel:' sprintf('%.3f',p(1))...
    ' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
    ' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab','OT', 'Hind'})

```

```

title('OFF activated')
clear topplotC topplotM p
hold off

figure (60)
clf
set(gcf, 'Position',[100 100 300 400])
str= {[cfg.MutID ' % OFF inhibited']};
topplotC=NumCtrl.OFF.inhibited;
topplotM=NumMut.OFF.inhibited;
swarmchart(repmat([1 2 3 4], cfg.numCTRL,1), topplotC,80,'k','filled','MarkerFaceAlpha',0.5,'MarkerSize',10)
for ii=1:4
errorbar(ii,mean(topplotC(:,ii)), std(topplotC(:,ii)),'Color','k', 'Marker','_')
end
swarmchart(repmat([1.5 2.5 3.5 4.5], cfg.numMUT,1), topplotM,80,cfg.Mutcolor,'filled','MarkerFaceAlpha',0.5,'MarkerSize',10)
for ii=1:4
errorbar(ii+0.5,mean(topplotM(:,ii)), std(topplotM(:,ii)),'Color','k', 'Marker','_')
end
xlim([-0 5]), ylim([-2 25])
ylabel('% of responding cells')
for i=1:4
p(i)=ranksum(topplotC(:,i),topplotM(:,i));
end
text(0,-1,num2str(['Tel:' sprintf('%.3f',p(1))...
' Hb:' sprintf('%.3f',p(2)) ' OT:' sprintf('%.3f',p(3))...
' Hind:' sprintf('%.3f',p(4))]))
xticks([1.25 2.25 3.25 4.25])
xticklabels({'Tel', 'Hab', 'OT', 'Hind'})
title('OFF inhibited')
clear topplotC topplotM p
hold off
end

```

FUNCTION calculate amplitude per brain region

```

function plot_amplitude_perregion(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)

onset=465;
offset=503;

jj=[1,4,2,3]; %reorder so that Hb is between Tel and OT, added 14.03.2023

figure (61)
clf
for k=1:4
j=jj(k);
set(gcf, 'Position',[100 100 300 400])
str= {[cfg.MutID ' Amplitude ALL cells ON, from ' num2str(time(onset)) 's to ' num2str(time(offset)) 's']};
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',10, 'FontWeight','bold', 'align','center')

for i=1:cfg.numCTRL
matrixC(i,:)=mean(ctrlON{i+1,6}(ctrlON{i+1,7}(:,4)==j,:),1);
end

```

```

end
for i=1:cfg.numMUT
matrixM(i,:)=mean(mutON{i+1,6}(mutON{i+1,7}(:,4)==j,:),1);
end
toplotC=matrixC(:,onset:offset);
toplotM=matrixM(:,onset:offset);
swarmchart((2*k-2)+ones(cfg.numCTRL,1), mean(toplotC,2),80,'k','filled','MarkerFaceAlpha',0.5,
line((2*k-2)+[0.6 1.4], repmat(mean(mean(toplotC,2)),1,2),'Color','k')
errorbar((2*k-2)+1,mean(mean(toplotC,2)), std(mean(toplotC,2)),'Color','k')
swarmchart((2*k-2)+2*ones(cfg.numMUT,1), mean(toplotM,2),80,cfg.Mutcolor,'filled','MarkerFaceAlpha',0.5,
line((2*k-2)+[1.6 2.4], repmat(mean(mean(toplotM,2)),1,2),'Color','k')
errorbar((2*k-2)+2,mean(mean(toplotM,2)), std(mean(toplotM,2)),'Color','k')
%xlim([0 3]),
ylim([-10 40])
ylabel('amplitude')
text((2*k-2)+0.25,-5,['p= '...
    num2str(ranksum(mean(toplotC,2),mean(toplotM,2)),'%4f')]);
xticks([1.5 3.5 5.5 7.5])
xticklabels({'Tel', 'Hab','OT/Thal', 'Hind'})
%title([cfg.brainRegion(k,:) 'ON response'])
clear toplotC toplotM matrixC matrixM
end

figure (62)
clf
for k=1:4
    j=jj(k);
set(gcf, 'Position',[100 100 300 400])
str= [cfg.MutID ' Amplitude ALL cells OFF, from ' num2str(time(onset)) 's to ' num2str(time(offset)) 's'];
annotation('textbox',[0.05 0.95 0.9 0.05],'String',str, 'FontSize',10, 'FontWeight','bold','align','left');

for i=1:cfg.numCTRL
matrixC(i,:)=mean(ctrlOFF{i+1,6}(ctrlOFF{i+1,7}(:,4)==j,:),1);
end
for i=1:cfg.numMUT
matrixM(i,:)=mean(mutOFF{i+1,6}(mutOFF{i+1,7}(:,4)==j,:),1);
end
toplotC=matrixC(:,onset:offset);
toplotM=matrixM(:,onset:offset);
swarmchart((2*k-2)+ones(cfg.numCTRL,1), mean(toplotC,2),80,'k','filled','MarkerFaceAlpha',0.5,
line((2*k-2)+[0.6 1.4], repmat(mean(mean(toplotC,2)),1,2),'Color','k')
errorbar((2*k-2)+1,mean(mean(toplotC,2)), std(mean(toplotC,2)),'Color','k')
swarmchart((2*k-2)+2*ones(cfg.numMUT,1), mean(toplotM,2),80,cfg.Mutcolor,'filled','MarkerFaceAlpha',0.5,
line((2*k-2)+[1.6 2.4], repmat(mean(mean(toplotM,2)),1,2),'Color','k')
errorbar((2*k-2)+2,mean(mean(toplotM,2)), std(mean(toplotM,2)),'Color','k')
%xlim([0 3]),
ylim([-10 40])
ylabel('amplitude')
text((2*k-2)+0.25,-5,['p= '...
    num2str(ranksum(mean(toplotC,2),mean(toplotM,2)),'%4f')]);
xticks([1.5 3.5 5.5 7.5])
xticklabels({'Tel', 'Hab','OT/Thal', 'Hind'})
%title([cfg.brainRegion(k,:) 'ON response'])
clear toplotC toplotM matrixC matrixM

```

```

end
%close all
end

```

FUNCTION IDENTIFY MIDLINE USING GINPUT

```

function identify_midline(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)

%% plot the scatter of the location of all responding cells
j=2; %this is OT only
% figure,
% suptitle('ctrl ON activated')
% for k=1:cfg.numCTRL
% ID=find(ctrlON{k+1, 4}(:,4)==j);
% subplot(ceil(size(ctrlON,1)/2),2,k)
% scatter(ctrlON{k+1, 4}(ID,1),ctrlON{k+1, 4}(ID,2))
% end

figure,
suptitle('mut ON activated')
for k=1:cfg.numMUT
ID=find(mutON{k+1, 4}(:,4)==j);
subplot(ceil(size(mutON,1)/2),2,k)
scatter(mutON{k+1, 4}(ID,1),mutON{k+1, 4}(ID,2))
end
end

```

FUNCTION PLOT % ACTIVE CELLS ACCORDING TO X,Y,Z

```

function plot_respondingXYZ(ctrlON,ctrlOFF,mutON,mutOFF,time,cfg)

% if you want to plot ON response,
if cfg.data==1
mut=mutON;
ctrl=ctrlON;
TEXT='ON';
elseif cfg.data==2
mut=mutOFF;
ctrl=ctrlOFF;
TEXT='OFF';
end

for j=1:4; %this decide on brain region

clear edges N_ctrlN N_mutN N_ctrl N_mut edges_mut edges_ctrl
% plot the scatter of the location of all responding cells
figure ,
clf
set(gcf, 'Position',[100 100 600 1200])
for k=1:cfg.numCTRL

```

```

ID=find(ctrl{k+1, 4}(:,4)==j);
subplot(ceil(size(ctrl,1)/2)+ceil(size(mut,1)/2),2,k)
scatter(ctrl{k+1, 4}(ID,1)-max(ctrl{k+1, 4}(ID,1)),ctrl{k+1, 4}(ID,2)-cfg.midline_ctrl(k,2),'k')
end
for k=1:cfg.numMUT
ID=find(mut{k+1, 4}(:,4)==j);
subplot(ceil(size(ctrl,1)/2)+ceil(size(mut,1)/2),2,size(ctrl,1)+k)
scatter(mut{k+1, 4}(ID,1)-max(mut{k+1, 4}(ID,1)),mut{k+1, 4}(ID,2)-cfg.midline_mut(k,2),cfg.Mutcolor)
end
suptitle([cfg.MutID, TEXT ' scatter of responding cells in ' ,cfg.label(j)])

% calculate the position in the width
edges=[-150:10:150];
for k=1:cfg.numMUT
ID=find(mut{k+1, 4}(:,4)==j);
[N_mut(k,:),edges_mut(k,:)] = histcounts(mut{k+1, 4}(ID,2)-cfg.midline_mut(k,2),edges);%,'Normalized'
N_mutN(k,:)=100*N_mut(k,:)/sum(mut{k+1, 7}(:,4)==j); % normalize to number of cell per brain region
clear ID
end
for k=1:cfg.numCTRL
ID=find(ctrl{k+1, 4}(:,4)==j);
[N_ctrl(k,:),edges_ctrl(k,:)] = histcounts(ctrl{k+1, 4}(ID,2)-cfg.midline_ctrl(k,2),edges);%,'Normalized'
N_ctrlN(k,:)=100*N_ctrl(k,:)/sum(ctrl{k+1, 7}(:,4)==j);% normalize to number of cell per brain region
clear ID
end
%
figure,
plot(edges(1:end-1),N_ctrlN.','k'), hold on, plot(edges(1:end-1),mean(N_ctrlN,1),'k','LineWidth',2)
plot(edges(1:end-1),N_mutN.','cfg.Mutcolor),plot(edges(1:end-1),mean(N_mutN,1),cfg.Mutcolor,'LineWidth',2)
xlabel('Y position [\mum]')
ylabel('% responding cells')
title([cfg.MutID, TEXT ' Y position of responding cells in ' ,cfg.label(j)])

figure
shadedErrorBar(edges(1:end-1),mean(N_ctrlN,1),std(N_ctrlN,[],1)/sqrt(size(N_ctrlN,1)),'lineprops','k')
shadedErrorBar(edges(1:end-1),mean(N_mutN,1),std(N_mutN,[],1)/sqrt(size(N_mutN,1)),'lineprops',cfg.Mutcolor)
xlabel('Y position [\mum]')
ylabel('% responding cells')
title([cfg.MutID, TEXT ' Y position of responding cells in ' ,cfg.label(j)])

end
end

```