




Developed by Štěpán Žampach, Atelier Simpléz www.ateliersimplez.cz stepan@ateliersimplez.cz 00420 731 511 929



FUNDAMENTAL LOGO IDEA



THE MAIN LOGO MOTIF IS EXPRESSED AS A TREE, SHAPED AND GRAPHICALLY STYLIZED AS A RIBBON. THE TREE SYMBOLIZES THE SOLID FOUNDATION OF CORINTH.



LOGO GEOMETRY



THE LOGO IS MADE UP OF A TEXT COMPONENT AND A GRAPHIC. THE GRAPHIC CAN BE SEPARATED FROM THE TEXT FOR CERTAIN PURPOSES AND CAN BE USED INDEPENDENTLY, BUT THE TEXT COMPONENT SHOULD NOT.

THE MOTIF OF TREE IS FORMED BY AN EQUILATERAL TRIANGULAR. SIDE LENGTH MATCHES THE WIDTH OF THE TEXT. THE GRAPHIC ISN'T CENTERED GEOMETRICALLY, BUT OPTICALLY. THE GEOMETRIC CENTER OF THE GRAPHIC IS EXACTLY ALIGNED WITH THE LETTER "I" IN THE COMPANY NAME TO ACHIEVE GENERAL OPTICAL INTEGRITY.



LOGO COLOR VARIATIONS



THE MAIN COLORS USED ARE

PANTONE 2915 C

AND PANTONE COOL GRAY 9 C. FOR SHADING,

PANTONE 3145 C IS USED.

BOTH THE SHADED

VERSION AND THE TWO-COLOR

VERSION CAN BE USED. WE

RECOMMEND THE SHADED

VERSION WHEN THE LOGO WIDTH

IS BIGGER THAN **5 MM** (PRINTED)

OR **55 PX** (WEB).





PROHIBITED USE OF LOGO





IT IS FORBIDDEN TO CHANGE
THE APPEARANCE AND TEXTURE OF
THE LOGO IN ANY WAY OTHER
THAN AS SPECIFIED IN CORINTH
LOGO GUIDELINES.















GRAYSCALE LOGO VARIANTS / NEGATIVES











1ST: MOTIF: 100%, FONT 100%

2ND: MOTIF: 50%, FONT 50%

3RD: MOTIF: 100%, FONT 50%

4TH: MOTIF: 30%, FONT 30%

5TH: MOTIF: 0%, FONT 0%

6TH: MOTIF: 30%, FONT 30%

7TH: MOTIF: 100%, FONT 100%

8TH: MOTIF: 0%, FONT 0%



LOGO VARIANTS ON VARIOUS BACKGROUNDS



1ST: COLORED, SHADED VARIANT.

2ND: COLORED, UNSHADED VARIANT.

3RD: COLORED, SHADED VARIANT ON GRAY

BACKGROUND.

4TH: LOGO IS NOT ALLOWED TO BE PLACED ON PHOTOS. CORINTH LOGO MUST BE PLACED ON A

WHITE BACKGROUND WITH AT LEAST

90% COVERAGE.

5TH: COLORED, UNSHADED VARIANT ON BLACK

BACKGROUND.


6TH: CORINTH LOGO ON DARK BACKGROUNDS.

7TH: CORINTH LOGO ON PANTONE 1915 C

8TH: CORINTH LOGO ON LIGHT BACKGROUNDS.



LOGO PROTECTION ZONE



THE LOGO PROTECTION ZONE SETS
THE AREA INTO WHICH SURROUNDING ELEMENTS MUST NOT
REACH. THE ZONE IS DETERMINED
BY THE DISTANCE "X" EQUAL TO
THE WIDTH OF THE LETTERS "CO"
IN THE COMPANY NAME.



MINIMUM LOGO SIZE





1ST: THE MINIMUM SIZE FOR COLORED VARIANTS (SHADED AND UNSHADED) IS 15 MM / 40 PX (WIDTH OF LOGO).

2ND: THE MINIMUM SIZE FOR GRAYSCALE LOGO VARIANTS IS 10 MM / 30 PX (WIDTH OF LOGO).

RECOMMENDED MINIMUM SIZE IS **20 MM / 55 PX** FOR COLORED VARIANTS AND **15 MM / 40 PX** FOR GRAYSCALE VARIANTS.