Mario (shenzhen) Technology Co.,LTD
Tel:+86 13510199418
E-mail:mario@mario-sz.com
WhatsApp/WeChat: +8613510199418
Factory Address:Forzen Technology Park,Baoan District,Shenzhen,China

Model No.	PIC		Specification		Price (USD			Package	
Wiodel No.	110			Sample	>100	>1000			
MSY1		Industrial design patent Builtin functions		-	ı	3.8	Giftbox	10*6.5*9.5	CM KG
		Case	Bluetooth, Bluetooth Handsfree, TF card, USB  ABS+Silicon Rubber	+			C.W.	0.24 Export Carton	KG
		Jack	TF/USB/LIN IN/MICRO	+			size	51*41*32	MM
		Power supply	Battery/Micro input	-	4.3		quantity	100	PCS
		Colors	Rose /Black/Gold/Blue/Red				N.W.	25	KG
		Size	83mm*80mm*34mm				C.W.	25	KG
		N.W.	162g					Packing	
		BT version	BT4.2				Speaker	1	рс
		Channel	2.1	6.9			Power	1	рс
				0.5			cable		
		Support	MP3 / WMA / WAV	-			AUX cable	1	pc
		Speaker	Ø52mm/4Ω/3W 30*40mm	-			User Manu	1	pc
		Bass diaphragm Distortion	0.01						
		BT Working range	≥10M	-					
		Frequency Response	20-20KHz	1					
		Signal&noise ratio	80db	1					
		Input power	5V 0.3A						
		Battery	Built-in rechargeable 600mA Lithium Battery						
				Sample	>100	>1000			
		Industrial design patent	LST171206015R		4.5	4	Giftbox	10*6.5*9.5	CM
		Builtin functions	Bluetooth, Bluetooth Handsfree, TF card, USB	1			C.W.	0.24	KG
		Case	ABS+Silicon Rubber	4				Export Carton	
		Jack	TF/USB/LIN IN/MICRO	4			size	51*41*32	MM
		Power supply	Battery/Micro input	4			quantity	100	PCS
		Colors	Wooden color case, Steel net : white/grey				N.W.	25	KG
		N.W.	83mm*80mm*34mm 162g	+			C.W.	25 Packing	KG
		BT version	BT4.2				Speaker	1	рс
				1			Power		
MSA60		Channel	2.1	7			cable	1	pc
		Support	MP3 / WMA / WAV				AUX cable	1	рс
		Speaker	Ø52mm/4Ω/3W				User Manu	1	рс
		Bass diaphragm	30*40mm	_					
		Distortion	0.01	4					
		BT Working range	≥10M	4					
		Frequency Response	20-20KHz	4					
		Signal&noise ratio Input power	80db 5V 0.3A	+					
		Battery	Built-in rechargeable 600mA Lithium Battery	+					
		Dutter y	Sant II. rechargeable cooling Ethium Battery	-					
				Sample	>100	>1000			
			Bluetooth, Bluetooth Handsfree, TF card, USB				Giftbox	12.8*9.4*4.4	CM
		Case	Metal				C.W.	0.21	KG
		Jack	TF/USB/LIN IN/MICRO	4	5	4.5		Export Carton	
		Power supply	Battery/Micro input Rose/Black/Gold/Silver/Red	4			size	8.5*8.5*3.7	MM
		Colors Size	83mm*80mm*34mm	+			quantity N.W.	100 13.3	PCS KG
		N.W.	162g	1			C.W.	20.7	KG
		BT version	BT4.2	1				Packing	
MSA8 (Metal case)		Channel	2.1				Speaker	1	рс
		Support	MP3 / WMA / WAV	7.5			Power	1	рс
(				4			cable		
		Speaker Race diaphragm	Ø52mm/4Ω/3W 30*40mm	+			AUX cable User Manu	1 1	pc
		Bass diaphragm Distortion	0.01	1			oser Manu	1	рс
		BT Working range	≥10M	1					
		Frequency Response	20-20KHz	]					
		Signal&noise ratio	80db	1	>100	ĺ			
		Input power	5V 0.3A	4					
		Battery	Built-in rechargeable 600mA Lithium Battery	Cample		>1000			
		Builtin functions	Bluetooth, Bluetooth Handsfree, TF card, USB	Sample	>100	>1000	Giftbox	12.8*9.4*4.4	CM
		Case	Metal	1			C.W.	0.21	KG
		Jack	TF/USB/LIN IN/MICRO					Export Carton	
		Power supply	Battery/Micro input				size	8.5*8.5*3.7	MM
		Colors	Rose/Black/Gold/Silver/Red	4			quantity	100	PCS
		Size	83mm*80mm*34mm				N.W.	13.3 20.7	KG
							C.W.	20.7 Packing	KG
		N.W.	162g RT4 2	1					
MSAS	(2)	N.W. BT version	BT4.2				Speaker		pc
MSA5 (Metal case)	(6)	N.W. BT version Channel		7.5	5	4.5	Speaker Power	1 1	pc pc
MSA5 (Metal case)		N.W. BT version	BT4.2 2.1	7.5	5	4.5		1	pc pc pc
		N.W. BT version Channel Support Speaker Bass diaphragm	BT4.2 2.1 MP3 / WMA / WAV Ø52mm/4Ω/3W 30*40mm	7.5	5	4.5	Power	1	рс
		N.W. BT version Channel Support Speaker Bass diaphragm Distortion	BT4.2 2.1 MP3 / WMA / WAV 052mm/4Ω/3W 30*40mm 0.01	7.5	5	4.5	Power AUX cable	1 1 1	pc pc
		N.W. BT version Channel Support Speaker Bass diaphragm Distortion BT Working range	BT4.2 2.1 MP3 / WMA / WAV Ø52mm/4Ω/3W 30*40mm 0.01 ≥10M	7.5	5	4.5	Power AUX cable	1 1 1	pc pc
		N.W. BT version Channel Support Speaker Bass diaphragm Distortion BT Working range Frequency Response	BT4.2 2.1 MP3 / WMA / WAV Ø52mm/4Ω/3W 30*40mm 0.01 ≥10M 20-20KHz	7.5	5	4.5	Power AUX cable	1 1 1	pc pc
		N.W. BT version Channel Support Speaker Bass diaphragm Distortion BT Working range Frequency Response Signal&noise ratio	BT4.2 2.1 MP3 / WMA / WAV Ø52mm/4Ω/3W 30*40mm 0.01 ≥10M 20-20KHz 80db	7.5	5	4.5	Power AUX cable	1 1 1	pc pc
		N.W. BT version Channel Support Speaker Bass diaphragm Distortion BT Working range Frequency Response	BT4.2 2.1 MP3 / WMA / WAV Ø52mm/4Ω/3W 30*40mm 0.01 ≥10M 20-20KHz	7.5	5	4.5	Power AUX cable	1 1 1	pc pc