

Network Change Report

YYYY Day-nth of Month – Timezone hh:mm AM/PM

Network Layout

[Network Diagram goes here.]

Rationale: Placed XYZ and ABC into the DMZ, DEF acts as a network filter to the rest of the network; that way systems don't need to handle things like DDoS or brute-force attacks independently, where bans apply network-wide.

Overview

Existing Servers

Hostname Prefix	IP (Local)	IP (Public)	OS
ad	10.10.10.10	36.3.5.10	Windows Server (2025)
admin	10.2.5.20	36.3.5.20	Windows Server (2022)
dev	10.2.5.30	36.3.5.30	Windows Server (2022)
www	10.2.5.40	36.3.5.40	Alma Linux 9
db	10.2.5.50	36.3.5.50	Alma Linux 8.6

Added Servers

Hostname Prefix	IP (Local)	IP (Public)	OS
rsyslog	10.2.5.20	36.3.5.20	Ubuntu Server 24.04 LTS
wazuh	10.2.5.30	36.3.5.30	Ubuntu Server 24.04 LTS

Server ABC (Template)

System & Service Configuration

SSH

Configuration	Old Value	New Value	Rationale
PermitRootLogin	Yes	No	Administrators should go through proper sign-in channels so that accountability may be properly enforced.

LDAP(S)

Configuration	Old Value	New Value	Rationale
Certificate Validation	Disabled	Verify CA Chain	Prevents Man-in-the-Middle (MitM) attacks by ensuring the server certificate is signed by a trusted Authority.

Software

Name	Action	Rationale
Wazuh	+	A File Integrity Monitoring (FIM) service is a much needed piece of software which allows the aggregated monitoring of system security events and integrity.
John the Ripper	-	A cracking tool known for being used to violate the integrity of files and systems should not/does not need to be on a production system.

Codebase

Codebase Name	File Path	Description	Rationale
Frontend 1	/var/lib/www-data/login/success	Replaced visible error verbosity with generic error codes	A security via obscurity type move—reduces information leakage of edge-cases.

Firewall

Firewall Software: FirewallD

Direction	Port	IP	Type	Allowed
In	ALL	ALL	ALL	TCP & UDP
In	ALL	ALL	ALL	TCP & UDP
In	ALL	80	ALL	TCP & UDP
In	ALL	22	ALL	TCP & UDP
In & Out	ALL	ALL	ALL	ICMP timestamp requests
In & Out	ALL	ALL	ALL	ICMP ping packets

Rationale: Having the firewall use a whitelist approach while the outgoing use a blacklist is by far one of the most easiest firewall types to set up as having a whitelist for **outgoing** packets would lead to many levels of breakage if not configured with the utmost care and attention to *everything*. Additionally, a whitelist approach for **incoming** packets strikes a balance of ease of use, usability/availability as the range of packets that for a fact *need* to come in are much more scarce and specific. Touching on the ICMP timestamp request block, those specific type of ICMP pings grab the timestamp of the server which is a form of reconissaince, so it has been negated.

Server XYZ (Copy and fill out as needed)

Fill out using the above example appropriately and remove this tag.