

```
// -----  
// A collection of functions: does not compile  
//  
// Shows differences of interfaces:  
//  
//          functional / procedural  
//  
//          recursive / iterative  
//  
// -----  
  
// Interface: recursive + functional  
// Single return statement  
//  
// Call like this: anchor = list_remove_tail(anchor);  
//  
// Remove tail node of list  
  
node_t* list_remove_tail(node_t* node){  
    node_t* result = node;  
    if(node != NULL) {  
        if (node->next == NULL) {  
            // Remove last node  
            free(node);  
            result = NULL;  
        } else {  
            // Recursive call  
            node->next = list_remove_tail(node->next);  
        }  
    }  
    return result;  
}
```

```
// -----  
  
// Interface: recursive + procedural  
// Single return statement  
//  
// Call like this: list_remove_tail(&anchor);  
//  
// Remove tail node of list  
  
void list_remove_tail(node_t* *pnode){  
    node_t* node = *pnode;  
    node_t* result = node;  
    if (node != NULL) {  
        if (node->next == NULL) {  
            // Remove last node  
            free(node);  
            result = NULL;  
        } else {  
            // Recursive call  
            list_remove_tail(&node->next);  
        }  
    }  
    *pnode = result;  
}
```

```
// -----  
// Interface: iterative + functional  
// Single return statement  
//  
// Call like this: anchor = list_remove_tail(anchor);  
//  
// Remove tail node of list  
  
node_t* list_remove_tail(node_t* node){  
  
    node_t *result = node; // init result  
    if (node != NULL) {  
        node_t* last = NULL;    // Last node before tail node  
  
        // Go to tail node in list  
        while (node->next != NULL) {  
            last = node;  
            // Advance iteration  
            node = node -> next;  
        }  
  
        // node points to tail node in list  
        // Free that node  
        free(node);  
  
        if (last == NULL) {  
            // node was the only node in the list  
            result = NULL;  
        } else {  
            // List had at least two elements.  
            // Terminate list.  
            last->next = NULL;  
        }  
    }  
  
    return result;  
}
```

```
// -----  
// Interface: iterative + procedural  
// Single return statement  
//  
// Call like this: list_remove_tail(&anchor);  
//  
// Remove tail node of list  
  
void list_remove_tail(node_t* *pnode){  
    node_t *node = *pnode;  
    node_t *result = node; // init result  
    if (node != NULL) {  
        node_t* last = NULL; // Last node before tail node  
  
        // Go to tail node in list  
        while (node->next != NULL) {  
            last = node;  
            // Advance iteration  
            node = node -> next;  
        }  
  
        // node points to tail node in list  
        // Free that node  
        free(node);  
  
        if (last == NULL) {  
            // node was the only node in the list.  
            // Update result.  
            result = NULL;  
        } else {  
            // The list had at least two elements.  
            // Terminate the list  
            last->next = NULL;  
        }  
    }  
    *pnode = result;  
}
```