

SDBM Field	TEI Xpath	Notes
ADMINISTRATIVE		
id	n/a [omit]	[Generated internally by SDBM; no data to import.]
manuscript	n/a [omit]	[Generated internally by SDBM; no data to import.]
groups	n/a [omit]	[Generated internally by SDBM; no data to import.]
SOURCE		
source_date	n/a [omit]	[TBD: To be given as date of batch import to SDBM, per LR.]
source_title	n/a [omit]	[To be given as 'Handrit.org,' per LR.]
source_catalog_or_lot_number	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/msIdentifier/idno	
institution	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/msIdentifier/repository /TEI/teiHeader/fileDesc/sourceDesc/msDesc/msIdentifier/institution	[Data to be pulled from both elements: <repository>, <institution>. N.B. Sometimes these data are only given in abbreviated form as values of the attribute @key for either of these elements.]
[Potentially relevant data in <provenance> and <acquisition> tags unfortunately bear no means of differentiating the role played by the person(s) named herein (e.g., 'buyer' vs. 'seller') apart from natural language syntax (i.e., description given using <name> and <date> elements with no way to encode relationships), and thus these SDBM fields were left blank.]		
TRANSACTION INFORMATION		
sale_selling_agent	n/a [omit]	
sale_seller_or_holder	n/a [omit]	
sale_buyer	n/a [omit]	
sale_sold	n/a [omit]	
sale_date	n/a [omit]	
sale_price	n/a [omit]	[No elements or attributes within the TEI encoding scheme pertain to 'sale' or 'price' or any associated monetary or commercial concepts.]
MANUSCRIPT DETAILS		
titles	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/msContents/summary/title	[<title> element is also used under <titleStmt>, but this is often used for the cataloging label identical to <idno> under <msIdentifier>. <title> may also be repeated under <msItem> to describe a discrete item (e.g., a fragment) within the contents of a manuscript.]
authors	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/msContents/author	
dates	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/history/origin/origDate	[Values for date range may be given as attributes of <origDate> (e.g., @notBefore, @notAfter).]
artists	n/a [omit]	[There do not appear to be any elements or attributes within the TEI encoding scheme pertaining to this concept.]
scribes	n/a [omit]	[There do not appear to be any elements or attributes within the TEI encoding scheme pertaining to this concept.]
languages	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/msContents/textLang	
materials	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/physDesc/objectDesc/supportDesc/support/	[Within <support> wrapper, data is often given within <p> tags (though sometimes not); a subsequent <material> tag may be present (there is variability here). @material may also be used as an attribute of <supportDesc> (given as abbreviated, pre-defined values). <material> element may also be used within <bindingDesc>.]
places	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/history/origin/origPlace	
uses	n/a [omit]	[There do not appear to be any elements or attributes within the TEI encoding scheme pertaining to liturgical use or any associated concepts.]
missing_authority_names	n/a [omit]	
folios		
num_columns	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/physDesc/objectDesc/layoutDesc/layout	[@columns is a possible attribute of <layout>.]
num_lines	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/physDesc/objectDesc/layoutDesc/layout	[@writtenLines is a possible attribute of <layout>.]
height	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/physDesc/objectDesc/supportDesc/	[Possible child elements herein are: <extent>, <dimensions>, <height>. The unit of measurement can be given as an attribute of any of the child elements (e.g., unit="mm").]
width	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/physDesc/objectDesc/supportDesc/	[Possible child elements herein are: <extent>, <dimensions>, <width>. The unit of measurement can be given as an attribute of any of the child elements (e.g., unit="mm").]
alt_size	n/a [omit]	
[While data pertaining to the following fields can occasionally be found within <decoDesc> element, these are typically descriptive, whereas the SDBM requires quantitative data (i.e., the number of such features found within a given manuscript), and thus these fields were left blank.]		
Miniatures and Initials		
miniatures_fullpage	n/a [omit]	
miniatures_large	n/a [omit]	
miniatures_small	n/a [omit]	
miniatures_unspec_size	n/a [omit]	
initials_historiated	n/a [omit]	
initials_decorated	n/a [omit]	
[N.B. The child element <dimensions> is sometimes used within <bindingDesc> to provide measurements (already retrieved for 'height' and 'width'), which must be removed.]		
manuscript_binding	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/physDesc/bindingDesc	
manuscript_link	/TEI/teiHeader/fileDesc/sourceDesc/msDesc+xml:id	[URL hyperlink to source record can be generated based on identifier string found here (with modifications).]
other_info	n/a [omit]	
provenance	/TEI/teiHeader/fileDesc/sourceDesc/msDesc/history/provenance/name /TEI/teiHeader/fileDesc/sourceDesc/msDesc/history/acquisition/name	[Given the unstructured data within the <provenance> and <acquisition> elements, any person mentioned (understood as 'provenance agent') was determined to be the most important, so data was retrieved for any <name> element used within these parent elements.]