

---

# TrustFLEX Step by Step Guide

## Accessory Authentication

---

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>3</b>
1.1	Getting started with Jupyter Notebook Tutorials .....	3
1.1.1	Starting Jupyter Notebook.....	3
1.2	Jupyter Notebook Basics .....	3
1.2.1	The Notebook dashboard .....	3
1.3	Introduction to Jupyter Notebook GUI.....	4
<b>2</b>	<b>Jupyter Notebook Tutorials .....</b>	<b>6</b>
<b>3</b>	<b>Resource Generation Notebook .....</b>	<b>7</b>
<b>4</b>	<b>Use Case Prototyping .....</b>	<b>13</b>
4.1	Running Accessory-Authentication example on Jupyter Notebook: .....	13
4.2	Running Accessory-Authentication on Embedded platform .....	17
4.2.1	Atmel Studio .....	17
4.2.2	MPLAB: .....	20
4.3	CryptoAuth TrustPlatform Factory reset.....	23
<b>5</b>	<b>FAQ.....</b>	<b>24</b>

# 1 Introduction

This document gives a detailed walk through of the Accessory Authentication use case implementation. If familiar with Jupyter Notebook, can skip this section and move to Section 2.

## 1.1 Getting started with Jupyter Notebook Tutorials

Jupyter Notebook is open source web application which allows you to create documents that contain code that you can execute in place as well as narrative text. It provides GUI elements, ability to execute code in place, ability to add images and gives it the look and feel that normal code files lack.

Jupyter notebooks are mainly used to explain/evaluate code in an interactive way.

### 1.1.1 Starting Jupyter Notebook

Jupyter notebook can be launched from the Anaconda Navigator main window.



## 1.2 Jupyter Notebook Basics

It is recommended to become familiar with Jupyter basic concepts with the online documentation, <https://jupyter-notebook.readthedocs.io/en/stable/examples/Notebook/Notebook%20Basics.html>

Some of the content is duplicated here for convenience. The online documentation should always be used as a reference.

### 1.2.1 The Notebook dashboard

When you first start the notebook server, your browser will open to the notebook dashboard. The dashboard serves as a home page for the notebook. Its main purpose is to display the notebooks and files in the current directory.

For example, here is a screenshot of the Jupyter dashboard. The top of the notebook list displays clickable breadcrumbs of the current directory. By clicking on these breadcrumbs or on sub-directories in the notebook list, you can navigate your file system.



### 1.3 Introduction to Jupyter Notebook GUI.

Jupyter Notebooks contain cells where you can either write code or markdown text. Notebooks contain multiple cells, some set as code and others markdown. Code cells contain code that can be executed live, and markdown contains text and images to explain the code.

Below image shows some options in a typical Jupyter Notebook. Individual cells can be executed by pressing on the RUN button as shown in the below image.

All cells in the Notebook can be executed in order by **Kernel->Restart & Run All**.

The screenshot shows a Jupyter Notebook window with the following elements and annotations:

- Toolbar:** A red box highlights the **Run** button (a play icon).
- Cell Type Selector:** A red box highlights the **Markdown** dropdown menu.
- Cell Creation:** A red box highlights the **+** button to create a new cell.
- Selected Cell:** A blue vertical band on the left side of the notebook is highlighted with a red box and labeled "Blue band represents currently selected cell".
- Cell Content:**
  - 2. Tutorial:** A markdown cell containing a list of steps: 1. Establish the communication between the host (PC) and the ECC608A, 2. Generate MAC from device, 3. Verify the MAC from device.
  - 2.1. Establish the communication between the host (PC) and the ECC608A:** A markdown cell containing a list of steps: 1. Initialize the library which also loads it, 2. Check if the correct device is connected to the PC. If the wrong device is connected, a ValueError exception will be raised. This cell is labeled "MARKDOWN CELL".
  - 2.1.1. Select the CryptoAuthLib Hardware Abstraction layer to KIT USB HID:** A code cell containing Python code. This cell is labeled "CODE CELL".
  - 2.1.2. Establish the connection with the ECC608A-TLXTLS device on the USB dongle and check its type:** A code cell containing Python code.

To run all cells in sequence.

The screenshot shows the **Kernel** menu in the Jupyter Notebook interface. The **Restart & Run All** option is highlighted with a red box. A tooltip for this option reads: "Restart the Kernel and re-run the notebook".

## 2 Jupyter Notebook Tutorials

The Trust Platform Design Suite comes with Notebook Tutorials to easily prototype popular use cases for TrustFLEX. Here is the list of Jupyter Notebook Tutorials.

<b>Jupyter Notebook Tutorials</b>	<b>Relative Path</b>	<b>Applicable Devices</b>
Manifest Generation	TrustnGO\00_resource_generation\TNGTLS_manifest_file_generation.ipynb	TrustnGO
Resource Generation	TrustFLEX\00_resource_generation\TFLXTLS_resource_generator.ipynb	TrustFLEX
Accessory Authentication	TrustFLEX\01_accessory_authentication\notebook\TFLXTLS_accessory_authentication.ipynb	TrustFLEX
Firmware Validation	TrustFLEX\02_firmware_validation\notebook\TFLXTLS_firmware_validation.ipynb	TrustFLEX
GCP Connect	TrustFLEX\03_gcp_connect\notebook\TFLXTLS_GCP_connect.ipynb	TrustFLEX
IP Protection	TrustFLEX\04_ip_protection\notebook\TFLXTLS_IP_protection.ipynb	TrustFLEX
Secure Public Key Rotation	TrustFLEX\05_public_key_rotation\notebook\TFLXTLS_public_key_rotation.ipynb	TrustFLEX
AWS Custom PKI	TrustFLEX\06_custom_pki_aws\notebook\TFLXTLS_aws_connect.ipynb	TrustFLEX
Azure Connect	TrustFLEX\07_custom_pki_azure\notebook\TFLXTLS_azure_connect.ipynb	TrustFLEX


### 3 Resource Generation Notebook

TFLXTLS device is one of the three devices available in the Trust Platform USB Dongle Board.

TrustFLEX devices come with pre-programmed certificates in slots 10, 11 and 12, also slots 0-4 have pre-generated private keys, other than the mentioned slots all the other slots have no data in them.

The Resource Generator Notebook will create development keys and certificates for all slots that can be further customized. Keys and Certificate chains are stored in the PC filesystem. These keys should never be used for production purposes as their generation is not handled in a secure environment. These development keys will be later used by the other notebooks to implement the various pre-defined use cases.

Within the Jupyter Dashboard, navigate **TrustFLEX\00\_resource\_generation** folder to open **TFLXTLS\_resource\_generator.ipynb** notebook



Run all cells of the Crypto Resource Generator Notebook: Kernel->Restart & Run All

**Note:** Before executing the cells on Crypto Trust Platform, its required to have factory default program running on SAMD21 of Trust Platform. Refer to [4.3 CryptoAuth TrustPlatform Factory reset](#) section for reloading default program.



Crypto Resource Generator notebook is common for all the use case which comes with option to load the signer certificate and device certificate.

So, it will execute and prompt you to choose between MCHP certificate and a custom certificate chain, press "MCHP Cert" option for this use case.

The Notebook will generate several keys and certificates. Make sure you have an error free output before continuing to the next steps of the training.

```
create_manifest_log_signer()
print('\n\nSelect the Certificate Type to prototype')
display(widgets.HBox((mchp_cert_button, cust_cert_button)))

----- Creating Manifest Log Signer -----
Loading Manifest logger key

Generating self-signed logging certificate
Saving to log_signer.crt
-----

Select the Certificate Type to prototype
MCHP Cert Custom Cert
```



```
MCHP Certs processing...
MCHP certificates found in the device
```

## Backing up certificates from device - Success

MIIB8TCCAzegAwIBAgIQd9NtIW7IrmIF5Y46y5hagTAKBggqhkJOPQQDAjBPMSEw  
HwYDVQQKBhNaWNYb2NoaXAgVGvjaG5vbG9neSBjbMxKjAoBgNVBAMMIUNyeXB0  
byBBdXRoZW50aWNhdGlvbISBs290IENBIDAwwMjAgFw0xODExMDgxOTEyMTIaGA8y  
MDU0MTEwODE5MTIxOVowTzEhMB8GA1UECgwYTWljcm9jaGlwIFRlY2hub2xvZ3kg  
SW5jMSowKAYDVOQDDCFDcnlwdG8qOXV0aGVudGljYXRpb24qUm9vdCBDQSAwMDIw

WTATBgcqhkjOPQIBBggqhkJOPQMBBwNCAAS9VOZt44dUhABrU64VgNUKoGnnit9V  
eNhc4tVN1bgwKWv/3W5vclb72Z7xoRaxHTOtSRA6oYWHOdZ65DfhnWNOo1MwUTAd  
BgNVHQ4EFgQUeu19bca3eJ2yOAGI6EqMsKQOKowwHwYDVR0jBBgwFoAUeu19bca3  
eJ2yOAGI6EqMsKQOKowwDwYDVR0TAQH/BAUwAwEB/zAKBggqhkJOPQQDAgNIADBF  
AiEAodxjRZDsgZ7h3luBEmVRrdTCxPjllSgu4EvnaOx8AnMCID5rp06eTArWjCSw  
+y7nk9LmvpRlyhXQ6lvIf1V5mVyt  
-----END CERTIFICATE-----

Validate Root Certificate:  
OK

Signer Certificate:

Certificate:

Data:

Version: 3 (0x2)

Serial Number:

79:0a:a7:d5:7d:73:dc:e9:6d:65:db:66:8b:76:b2:5e

Signature Algorithm: ecdsa-with-SHA256

Issuer: O = Microchip Technology Inc, CN = Crypto Authentication Root CA 002

Validity

Not Before: Dec 14 19:00:00 2018 GMT

Not After : Dec 14 19:00:00 2049 GMT

Subject: O = Microchip Technology Inc, CN = Crypto Authentication Signer F600

Subject Public Key Info:

Public Key Algorithm: id-ecPublicKey

Public-Key: (256 bit)

pub:

04:76:47:41:70:b2:63:e7:99:54:bc:85:bb:12:e9:

fe:70:0c:5b:8d:d4:d6:93:45:98:c2:29:a7:68:02:

0e:4e:0b:6d:48:75:d0:ed:a1:ee:f6:5f:91:5f:c6:

b1:16:46:c5:a1:ca:63:1f:62:55:68:74:47:69:c5:

de:83:b5:89:6a

ASN1 OID: prime256v1

NIST CURVE: P-256

X509v3 extensions:

X509v3 Key Usage: critical

Digital Signature, Certificate Sign, CRL Sign

X509v3 Basic Constraints: critical

CA:TRUE, pathlen:0

X509v3 Subject Key Identifier:

FB:DC:AA:12:8A:FA:C1:B5:92:8F:CD:AB:11:DB:09:3E:CF:4D:BE:F6

X509v3 Authority Key Identifier:

keyid:7A:ED:7D:6D:C6:B7:78:9D:B2:38:01:A5:E8:4A:8C:B0:A4:0E:2A:8C

Signature Algorithm: ecdsa-with-SHA256

30:46:02:21:00:c6:30:31:e9:a9:8b:30:4e:68:7e:06:c5:39:

79:2a:c5:7a:5c:01:4d:30:17:de:dc:d2:7d:d5:1d:cd:86:37:

ff:02:21:00:c6:a2:2c:6e:b1:ae:5f:85:91:49:cb:5d:e7:77:

8b:a3:f3:0b:e9:3d:9b:80:6f:94:bf:3d:90:a5:84:78:61:dc

-----BEGIN CERTIFICATE-----

MIICBTCCAaqgAwIBAgIQeQqn1X1z30ltZdtmi3ayXjAKBggqhkJOPQQDAjBPMSEw  
HwYDVQQKBHNaWNyY2NoaXAgVGJjaG5vbG9neSBjb2N0eSBjbmMxKjAoBgNVBAMMIUNyeXB0  
byBBdXRoZW50aWNhdGlviBSb290IENBIDAuMjA5Fw0xODEyMTQxOTAwMDBaGA8y

MDQ5MTIxNDE5MDAwMFowTzEhMB8GA1UECgwYTWljcm9jaGlwIFRIY2hub2xvZ3kg  
SW5jMSowKAYDVQQDDCFDcnlwdG8gQXV0aGVudGljYXRpb24gU2lnbmVvIEY2MDAw  
WTATBgcqhkjOPQIBBggqhkjOPQMBBwNCAAR2R0FwsmPnmVS8hbsS6f5wDFuN1NaT  
RZjCKadoAg5OC21IddDtoe72X5FfxrEWRsWhymMfYIVodEdpxd6DtYlqo2YwZDAO  
BgNVHQ8BAf8EBAMCAYYwEgYDVR0TAQH/BAgwBgEB/wIBADAdBgNVHQ4EFgQU+9yq  
Eor6wbWSj82rEdsJP9NvvYwHwYDVR0jBBgwFoAUeu19bca3eJ2yOAGl6EqMsKQO  
KowwCgYIKoZIzj0EAwIDSQAwwRgIhAMyWMempizBOaH4GxTI5KsV6XAFNMBfe3NJ9  
1R3Nhjf/AiEAXqIsbrGuX4WRsctd53eLo/ML6T2bgG+Uvz2QpYR4Ydw=  
-----END CERTIFICATE-----

Validate Signer Certificate:  
OK

Device Certificate:  
Certificate:

Data:

Version: 3 (0x2)

Serial Number:

5a:cb:a3:f7:cf:bf:c5:28:92:cd:e1:9f:a3:ac:9d:17

Signature Algorithm: ecdsa-with-SHA256

Issuer: O = Microchip Technology Inc, CN = Crypto Authentication Signer F600

Validity

Not Before: Aug 21 22:00:00 2019 GMT

Not After : Aug 21 22:00:00 2047 GMT

Subject: O = Microchip Technology Inc, CN = 0123867D566FFB7701 ATECC

Subject Public Key Info:

Public Key Algorithm: id-ecPublicKey

Public-Key: (256 bit)

pub:

04:fc:57:67:b6:fb:ae:50:60:ca:96:5a:ef:41:b1:  
c5:d6:a1:60:61:87:8e:a4:78:f4:4d:18:d0:76:9d:  
ad:62:24:b3:68:c2:1a:62:cb:0a:fd:ef:f5:b4:0c:  
e3:55:ec:f0:40:bb:41:83:61:02:ef:20:3c:63:93:  
32:d4:90:41:ab

ASN1 OID: prime256v1

NIST CURVE: P-256

X509v3 extensions:

X509v3 Basic Constraints: critical

CA:FALSE

X509v3 Key Usage: critical

Digital Signature, Key Agreement

X509v3 Subject Key Identifier:

43:9E:4F:45:79:35:CE:DC:D4:35:B9:4F:4A:23:69:E1:2D:89:33:04

X509v3 Authority Key Identifier:

keyid:FB:DC:AA:12:8A:FA:C1:B5:92:8F:CD:AB:11:DB:09:3E:CF:4D:BE:F6

Signature Algorithm: ecdsa-with-SHA256

30:45:02:21:00:83:32:78:25:9c:5a:07:7c:4a:04:f8:b5:c4:  
57:d6:08:70:ee:c3:d4:79:9c:b6:14:8e:5e:86:54:38:50:cf:  
ec:02:20:58:e1:cf:e1:f6:e2:17:08:c3:5a:fc:86:91:31:ef:  
65:09:e0:e4:ba:7e:02:8e:4c:49:d1:4b:e3:ac:35:33:f7

-----BEGIN CERTIFICATE-----

MIIB9TCCAZugAwIBAgIQWsu98+/xSiSzeGfo6ydFzAKBggqhkhjOPQQDAjBPMSEw

HwYDVQQKDBhNaWNyb2NoaXAgaGVjaG5vbG9neSBJamMxKjAoBgNVBAMMIUNyeXB0  
byBBdXRoZW50aWNhdGlviBTaWduZXIgaRjYwMDAgFw0xOTA4MjEyMjAwMDBaGA8y  
MDQ3MDgyMTIyMDAwMFowRjEhMB8GA1UECgwYTWljcm9jaGlwIFRIY2hub2xvZ3kg  
SW5jMSEwHwYDVQQDDDBgwMTIzODY3RDU2NkZGQjc3MDEgQVRFRQ0MwWTATBgqhkJ0  
PQIBBgqhkJOPQMBBwNCAAT8V2e2+65QYMqWWu9BscXWoWBhh46kePRNGNB2na1i  
JLNowhpiywr97/W0DONV7PBAu0GDYQLvIDxjkzLUkEGro2AwXjAMBgNVHRMBAf8E  
AjAAMA4GA1UdDwEB/wQEAwIDiDAdBgNVHQ4EFgQUUQ55PRXk1ztzUNblPSiNp4S2J  
MwQwHwYDVR0jBBgwFoAU+9yqEor6wbWSj82rEdsJP9NvvYwCgYIKoZIJ0EAWID  
SAAwRQIhAIMyeCWcWgd8SgT4tcRX1ghw7sPUeZy2FI5ehIQ4UM/sAiBY4c/h9uIX  
CMNa/IaRMe9lCeDkun4CjKxJ0UvjrDUz9w==  
-----END CERTIFICATE-----

Validate Device Certificate:  
OK

-----  
Generated the manifest file 0123867d566ffb7701\_manifest.json  
MCHP Certificate processing completed successfully  
-----

The Notebook will also generate a manifest file to be uploaded into the public cloud of your choice (Google GCP, AWS IoT and Microsoft Azure).

After running this Notebook, it generates the required resources and program data zone with required secrets, keys and certificates. For this use case, secret key only required, and which is loaded into TrustFLEX device (ATECC608A) in slot 5.

## 4 Use Case Prototyping

This hands-on lab is intended to demonstrate the usage of host to authenticate Accessory device. It uses symmetric authentication where both host and accessory device shares a common secret.

This process uses a challenge-response model. In this model, host authenticates the accessory device based on MAC response. MAC is calculated on the accessory device to prove that it holds the secret key that is shared by the host. Then the calculated MAC will be verified by the host to authenticate the accessory.

MAC calculation on accessory includes device serial number, nonce (number used once) and shared secret key. By including serial number and nonce, host can get unique MAC from each accessory every time, thereby avoiding the replay attacks.


This lab is developed by simulating TrustFLEX device as Accessory and host to authenticate the accessory. In both TrustFLEX Slot5 and host has the same shared secret key.

The resource generation for TrustFLEX device will load a prototyping symmetric key to Slot5 of TrustFLEX device.


Following sections provides detail steps to execute the usecase both on Jupyter Notebook and on Embedded project

### 4.1 Running Accessory-Authentication example on Jupyter Notebook:


1. From the Jupyter Home page, navigate to **TrustFLEX\01\_accessory\_authentication\notebook\TFLXTLS\_accessory\_authentication.ipynb** notebook file and open it.





Opening the notebook from Jupyter home page should load the following on the browser,



2. Run All Cells by using Kernel -> Restart & Run All



- It may take a while to complete, wait for the kernel to complete all processing i.e. from Kernel Running to Kernel Idle state (Check circle above **RED** text)



- Navigate through different cells output for the description of the step and result from the execution.

- There are 2 major steps in this lab

#### **Generate MAC from Accessory (TrustFLEX)**

Code block of this step generates a random challenge and expects Accessory to provide the MAC for this challenge. Accessory calculates the MAC value by including its serial number, shared secret and the challenge received from host.

#### Calculate Nonce

To calculate MAC, nonce is considered. Nonce is calculated based on the challenge which is initiated by host. Then calculated nonce will be stored in tempkey on TrustFLEX and on host.

#### Calculate MAC on accessory device

MAC is calculated on accessory device is to prove that the accessory device has access and holds the secret key which is shared by host. Accessory device MAC is calculated with accessory device serial number, calculated nonce and secret key.

Then calculated MAC will send to the host to authenticate the accessory device.

Below screenshot display the accessory device MAC.

```
In [3]: seed_in = bytearray(20)
rand_out = bytearray(32)
nonce = bytearray()
device_mac = bytearray(32)

# Generate the nonce in device and return the random number
assert atcab_nonce_rand(seed_in,rand_out) == ATCA_SUCCESS, "Random nonce from device failed"

# Calculate the nonce value on the host side
nonce.extend(rand_out[0:32])
nonce.extend(seed_in[0:20])
nonce.append(0x16)
nonce.append(0)
nonce.append(0)
digest = hashes.Hash(hashes.SHA256(), backend=default_backend())
digest.update(bytes(nonce))
nonce = digest.finalize()

# Calculate the mac in device with its symmetric diversified key in slot
assert atcab_mac(MAC_MODE,SHARED_SECRET_SLOT,0,device_mac) == ATCA_SUCCESS, "MAC from Accessory device failed"
print("MAC Received from Accessory device:")
print(pretty_print_hex(device_mac, indent='  '))
```

```
MAC Received from Accessory device:
 3A CA F8 7B BF FF 25 9B 5B DA FA AD 60 C0 3B CB
 67 C6 DD C2 76 00 9D D7 E4 2E 8E 11 0E 6D 48 35
```

### Verify the MAC with host device

Code block of this step generates Verify MAC button. Clicking the button performs checkmac operation to verify the MAC received from Accessory is corresponds to host challenge, Accessory serial number and shared secret key. If any of this mismatch, the checkmac operation fails indicating accessory is not authentic.

```
#uncomment following line to try wrong mac
#host_mac = bytes(b'00000000000000000000000000000000')

print('MAC calculated on host:')
print(pretty_print_hex(host_mac, indent='  '))

if (device_mac == host_mac):
    print('\nAccessory device authenticated successfully!')
    mac_verify.button_style = 'success'
else:
    mac_verify.button_style = 'danger'
    print('\Accessory device not authenticated...')

tooltip = 'Click to perform MAC-Response Verify'
mac_verify = widgets.Button(description = 'Verify MAC', tooltip=tooltip)
mac_verify.on_click(mac_mac_resp_verify)
display(mac_verify)
```

Verify MAC

```
MAC calculated on host:
 3A CA F8 7B BF FF 25 9B 5B DA FA AD 60 C0 3B CB
 67 C6 DD C2 76 00 9D D7 E4 2E 8E 11 0E 6D 48 35
```

Accessory device authenticated successfully!



6. In jupyter notebook, run cells till the end of notebook, you will see a "Verify MAC" button will appear. Press the button, it will turn green if accessory device gets authenticated by MCU or it will turn red.

Pressing the button, turns it Green or Red. Green indicates that the device is authenticated by host and Red indicates the authentication is failed.


## 4.2 Running Accessory-Authentication on Embedded platform

This usecase can also be executed on Embedded platform. Once the resources are generated, both Atmel Studio and MPLAB projects provided can be used to run the application on CryptoAuth Trust Platform.


**Note:** This usecase requires resource generation notebook executed prior to using embedded projects.

### 4.2.1 Atmel Studio


1. Open **accessory\_auth.atsln** project by navigating to Atmel Studio -> File -> open -> **TrustFLEX\01\_accessory\_authentication\c\studio\accessory\_auth.atsln**



2. The application source code accessory\_auth.c is available at **TrustFLEX\01\_accessory\_authentication\c\accessory\_auth.c**. Other supporting files can be found under **assets\dependencies**



3. Program the Crypto Trust platform by navigating to **Debug -> Start Without Debugging**



This step may take some time, wait for Atmel Studio to compile and program the device.

Once the programming is done, the firmware will do Accessory-Authentication operation. Depending on the Accessory-Authentication operation's output, the CryptoAuth Trust Platform board's status LED will blink at different rates.

If Accessory-Authentication operation **succeeds**, LED blinks once every second.  
If Accessory-Authentication operation **fails**, LED blinks five times every second.

It is also possible to view the Console messages by using applications like TeraTerm. Open the application with the COM related to CryptoAuth TrustPlatform with 115200-8-N-1 settings

```
COM35 - Tera Term VT
File Edit Setup Control Window Help

Device revision:
00 00 60 02

MAC received from device:
68 FE E0 73 5D 98 07 46 D1 DE F7 20 CF DE AB 0A
E2 C1 D9 F0 60 66 DC 38 6A 9C DF C4 DF 68 D3 C7


MAC calculated on Host:
68 FE E0 73 5D 98 07 46 D1 DE F7 20 CF DE AB 0A
E2 C1 D9 F0 60 66 DC 38 6A 9C DF C4 DF 68 D3 C7

Accessory device authenticated successfully


Execution completed with status 00
```

#### 4.2.2 MPLAB:


1. Open **accessory\_auth.X** project by navigating to MPLAB -> File -> Open Project -> **TrustFLEX\01\_accessory\_authentication\c\mplab\accessory\_auth.X**




2. The application source code **accessory\_auth.c** is available at **TrustFLEX\01\_accessory\_authentication\c\accessory\_auth.c**. Other supporting files can be found under **assets\dependencies**



3. Program the Crypto Trust platform by navigating to **accessory\_auth** -> **Make and Program Device**



This step may take some time, wait for MPLAB to program the device. Once it is done programming you will see "**Programming complete**" message in Output Window.



```
*****

Currently loaded versions:
Application version.....1.12.448 (0x01.0x0c.0x01c0)
Target voltage detected

Erasing...


The following memory area(s) will be programmed:
program memory: start address = 0x0, end address = 0x61ff
configuration memory

Programming complete
```

Once the programming is done, the firmware will do Accessory-Authentication operation. Depending on the Accessory-Authentication operation's output, the Cryptoauth Trust Platform board's status LED will blink at different rates.

If Accessory-Authentication operation **succeeds**, LED blinks once every second.  
If Accessory-Authentication operation **fails**, LED blinks five times every second.

It is also possible to view the Console messages by using applications like TeraTerm. Open the application with the COM related to CryptoAuth TrustPlatform with 115200-8-N-1 settings



```
VT COM35 - Tera Term VT
File Edit Setup Control Window Help

Device revision:
00 00 60 02

MAC received from device:
68 FE E0 73 5D 98 07 46 D1 DE F7 20 CF DE AB 0A
E2 C1 D9 F0 60 66 DC 38 6A 9C DF C4 DF 68 D3 C7

MAC calculated on Host:
68 FE E0 73 5D 98 07 46 D1 DE F7 20 CF DE AB 0A
E2 C1 D9 F0 60 66 DC 38 6A 9C DF C4 DF 68 D3 C7

Accessory device authenticated successfully
Execution completed with status 00
```

### 4.3 CryptoAuth TrustPlatform Factory reset


Once any of the embedded project is loaded to CryptoAuth TrustPlatform, the default program that enables interaction with TrustPlatform tools will be erased.

Before using the Platform with any other notebook or tools on PC, its required to reprogram the default .hex file. Default hex file is available at

**assets\Factory\_Program.X\CryptoAuth\_Trust\_Platform.hex**

To reprogram using Atmel Studio:

1. Navigate to AtmelStudio -> Tools -> Device Programming
2. Select Tool as nEDBG and Apply
3. Go to Memories and navigate to above path under Flash dropdown
4. Check both Erase Flash and Verify Flash
5. Click on Program



To reprogram using MPLAB:

1. Open **assets\Factory\_Program.X** project in MPLAB IDE
2. Program the Crypto Trust platform by navigating to  
**CryptoAuth\_Trust\_Platform\_Factory\_Program -> Make and Program Device**

Now, CryptoAuth Trust Platform contains factory programmed application that enables interactions with Notebooks and/or PC tools.

## 5 FAQ

### 1. What are the reasons for “**AssertionError: Can't connect to the USB dongle**” error?

There are many possibilities like,

1. Crypto Trust Platform is having different application than factory reset firmware. Refer to “CryptoAuth TrustPlatform Factory reset” section any usecase TrustFLEX Guide for reloading it
2. Check the switch positions on Crypto Trust Platform and/or ATECC608A Trust board
  - a. Correct Trust device should be connected and only one device of that type is allowed on the I2C bus. Multiple devices with same address results in error
3. Check USB connections to Crypto Trust Platform

### 2. How to reload factory default application to Crypto Trust Platform?

Refer to “CryptoAuth TrustPlatform Factory reset” section any usecase TrustFLEX Guide for reloading it.

### 3. Why does my C projects generates No such file or directory with ../../../../TFLXTLS\_resource\_generation/?

C project generates this error when the resources are not generated prior to using embedded projects. Running the resource generation notebook ensures these files and secrets are generated.

### 4. Before running any use case notebook and/or C project, why is it mandate to execute resource generation?

When resource generation notebook is executed, it generates and programs the required resources like secrets, keys and certificates. These are only prototyping keys and cannot be used for production. These keys will be used part of Usecase notebooks and C projects

### 5. How to know the resources being used in a use case?

Refer to individual Usecase description html for details on transaction diagrams, resources being used and other details. The resources required for given use case is mentioned in INFER CRYPTOGRAPHIC ASSETS section.

### 6. When should I select Custom certificates while doing resource generation?

Custom certificates are required when user wants to have their own root, signer instead of MCHP provided. The difference would be organization name, common name and validity are configurable

### 7. How to know whether C project is executing on Trust Platform or not after programming?

Once the programming is done, the firmware will do use case operation. Depending on the use case operation's output, the Crypto Trust Platform board's status LED will blink at different rates.

If use case operation succeeds, LED blinks once every second. If it fails, LED blinks five times every second.



It is also possible to view the Console messages by using applications like TeraTerm.  
Open the application with the COM related to Crypto Trust Platform with 115200-8-N-1 settings

## The Microchip Web Site

---

Microchip provides online support via our web site at <http://www.microchip.com/>. This web site is used as

a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

## Customer Change Notification Service

---

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at <http://www.microchip.com/>. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

## Customer Support

---

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support.

Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: <http://www.microchip.com/support>

## Microchip Devices Code Protection Feature

---

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.

- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as “unbreakable.”

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip’s code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

## Legal Notice

---

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY

OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE.

Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

## Trademarks

---

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq,

Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB,

OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, SAM-BA, SpyNIC, SST,

SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight

Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming,

ICSP, INICnet, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, memBrain, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient

Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE,

Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2018, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN:

## **Quality Management System Certified by DNV**

---

### **ISO/TS 16949**

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California

and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.



# Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
<b>Corporate Office</b> 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: <a href="http://www.microchip.com/support">http://www.microchip.com/support</a> Web Address: <a href="http://www.microchip.com">www.microchip.com</a> <b>Atlanta</b> Duluth, GA Tel: 678-975-9614 Fax: 678-957-1455 <b>Austin, TX</b> Tel: 512-257-3370 <b>Boston</b> Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088 <b>Chicago</b> Itasca, IL Tel: 630-285-0071 Fax: 630-285-0075 <b>Dallas</b> Addison, TX Tel: 972-818-7423 Fax: 972-818-2924 <b>Detroit</b> Novi, MI Tel: 248-848-4000 <b>Houston, TX</b> Tel: 281-894-5983 <b>Indianapolis</b> Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380 <b>Los Angeles</b> Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800 <b>Raleigh, NC</b> Tel: 919-844-7510 <b>New York, NY</b> Tel: 631-435-6000 <b>San Jose, CA</b> Tel: 408-735-9110 Tel: 408-436-4270 <b>Canada - Toronto</b> Tel: 905-695-1980 Fax: 905-695-2078	<b>Australia - Sydney</b> Tel: 61-2-9868-6733 <b>China - Beijing</b> Tel: 86-10-8569-7000 <b>China - Chengdu</b> Tel: 86-28-8665-5511 <b>China - Chongqing</b> Tel: 86-23-8980-9588 <b>China - Dongguan</b> Tel: 86-769-8702-9880 <b>China - Guangzhou</b> Tel: 86-20-8755-8029 <b>China - Hangzhou</b> Tel: 86-571-8792-8115 <b>China - Hong Kong SAR</b> Tel: 852-2943-5100 <b>China - Nanjing</b> Tel: 86-25-8473-2460 <b>China - Qingdao</b> Tel: 86-532-8502-7355 <b>China - Shanghai</b> Tel: 86-21-3326-8000 <b>China - Shenyang</b> Tel: 86-24-2334-2829 <b>China - Shenzhen</b> Tel: 86-755-8864-2200 <b>China - Suzhou</b> Tel: 86-186-6233-1526 <b>China - Wuhan</b> Tel: 86-27-5980-5300 <b>China - Xian</b> Tel: 86-29-8833-7252 <b>China - Xiamen</b> Tel: 86-592-2388138 <b>China - Zhuhai</b> Tel: 86-756-3210040	<b>India - Bangalore</b> Tel: 91-80-3090-4444 <b>India - New Delhi</b> Tel: 91-11-4160-8631 <b>India - Pune</b> Tel: 91-20-4121-0141 <b>Japan - Osaka</b> Tel: 81-6-6152-7160 <b>Japan - Tokyo</b> Tel: 81-3-6880-3770 <b>Korea - Daegu</b> Tel: 82-53-744-4301 <b>Korea - Seoul</b> Tel: 82-2-554-7200 <b>Malaysia - Kuala Lumpur</b> Tel: 60-3-7651-7906 <b>Malaysia - Penang</b> Tel: 60-4-227-8870 <b>Philippines - Manila</b> Tel: 63-2-634-9065 <b>Singapore</b> Tel: 65-6334-8870 <b>Taiwan - Hsin Chu</b> Tel: 886-3-577-8366 <b>Taiwan - Kaohsiung</b> Tel: 886-7-213-7830 <b>Taiwan - Taipei</b> Tel: 886-2-2508-8600 <b>Thailand - Bangkok</b> Tel: 66-2-694-1351 <b>Vietnam - Ho Chi Minh</b> Tel: 84-28-5448-2100	<b>Austria - Wels</b> Tel: 43-7242-2244-39 Fax: 43-7242-2244-393 <b>Denmark - Copenhagen</b> Tel: 45-4450-2828 Fax: 45-4485-2829 <b>Finland - Espoo</b> Tel: 358-9-4520-820 <b>France - Paris</b> Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 <b>France - Saint Cloud</b> Tel: 33-1-30-60-70-00 <b>Germany - Garching</b> Tel: 49-8931-9700 <b>Germany - Haan</b> Tel: 49-2129-3766400 <b>Germany - Heilbronn</b> Tel: 49-7131-67-3636 <b>Germany - Karlsruhe</b> Tel: 49-721-625370 <b>Germany - Munich</b> Tel: 49-89-627-144-0 Fax: 49-89-627-144-44 <b>Germany - Rosenheim</b> Tel: 49-8031-354-560 <b>Israel - Ra'anana</b> Tel: 972-9-744-7705 <b>Italy - Milan</b> Tel: 39-0331-742611 Fax: 39-0331-466781 <b>Italy - Padova</b> Tel: 39-049-7625286 <b>Netherlands - Drunen</b> Tel: 31-416-690399 Fax: 31-416-690340 <b>Norway - Trondheim</b> Tel: 47-7289-7561 <b>Poland - Warsaw</b> Tel: 48-22-3325737 <b>Romania - Bucharest</b> Tel: 40-21-407-87-50 <b>Spain - Madrid</b> Tel: 34-91-708-08-90 Fax: 34-91-708-08-91 <b>Sweden - Gothenberg</b> Tel: 46-31-704-60-40 <b>Sweden - Stockholm</b> Tel: 46-8-5090-4654 <b>UK - Wokingham</b> Tel: 44-118-921-5800 Fax: 44-118-921-5820