TrustFLEX Step by Step Guide Accessory Asymmetric Authentication

Table of Contents

1 Introduction

This document gives a detailed walk through of the Accessory Authentication use case implementation. If familiar with Jupyter Notebook, can skip this section and move to Section 2.

1.1 Getting started with Jupyter Notebook Tutorials

Jupyter Notebook is open source web application which allows you to create documents that contain code that you can execute in place as well as narrative text. It provides GUI elements, ability to execute code in place, ability to add images and gives it the look and feel that normal code files lack.

Jupyter notebooks are mainly used to explain/evaluate code in an interactive way.

1.1.1 Starting Jupyter Notebook

Jupyter notebook can be launched from Trust Platform GUI Main window. Run START -> Trust Platform x.x.x icon. Click on 'Start Jupyter' button to launch Jupyter local server.



Clicking on Start Jupyter should be web browser tab like below,



1.2 Jupyter Notebook Basics

It is recommended to become familiar with Jupyter basic concepts with the online documentation, https://jupyter-notebook.readthedocs.io/en/stable/examples/Notebook/Notebook%20Basics.html

Some of the content is duplicated here for convenience. The online documentation should always be used as a reference.

1.2.1 The Notebook dashboard

When you first start the notebook server, your browser will open to the notebook dashboard. The dashboard serves as a home page for the notebook. Its main purpose is to display the notebooks and files in the current directory.

For example, here is a screenshot of the Jupyter dashboard. The top of the notebook list displays clickable breadcrumbs of the current directory. By clicking on these breadcrumbs or on sub-directories in the notebook list, you can navigate your file system.



1.3 Introduction to Jupyter Notebook GUI.

Jupyter Notebooks contain cells where you can either write code or markdown text. Notebooks contain multiple cells, some set as code and others markdown. Code cells contain code that can be executed live, and markdown contains text and images to explain the code.

Below image shows some options in a typical Jupyter Notebook. Individual cells can be executed by pressing on the RUN button as shown in the below image.

All cells in the Notebook can be executed in order by **Kernel->Restart & Run All**.



To run all cells in sequence.



2 Jupyter Notebook Tutorials

The Trust Platform Design Suite comes with Notebook Tutorials to easily prototype popular use cases for TrustFLEX. Here is the list of Jupyter Notebook Tutorials.

Jupyter Notebook Tutorials	**Relative Path**	**Applicable Devices**
Manifest Generation	TrustnGO\00_resource_generation\TNGTLS_manifest_file_generation.ipynb	Trust&GO
GCP Connect	TrustnGO\05_cloud_connect\notebook\gcp\TNGTLS_GCP_connect.ipynb	Trust&GO
AWS Connect	TrustnGO\05_cloud_connect\notebook\aws\TNGTLS_aws_connect.ipynb	Trust&GO
Azure Connect	TrustnGO\05_cloud_connect\notebook\azure\ TNGTLS_azure_connect.ipynb	Trust&GO
Resource Generation	TrustFLEX\00_resource_generation\TFLXTLS_resource_generator.ipynb	TrustFLEX
Accessory Authentication	TrustFLEX\01_accessory_authentication\notebook\ TFLXTLS_accessory_authentication.ipynb	TrustFLEX
Firmware Validation	TrustFLEX\02_firmware_validation\notebook\ TFLXTLS_firmware_validation.ipynb	TrustFLEX
IP Protection	TrustFLEX\04_ip_protection\notebook\ TFLXTLS_IP_protection.ipynb	TrustFLEX
Secure Public Key Rotation	TrustFLEX\05_public_key_rotation\notebook\ TFLXTLS_public_key_rotation.ipynb	TrustFLEX
Asymmetric authentication	08_asymmetric_authentication\notebook\ TFLXTLS_asymmetric_authentication.ipynb	TrustFLEX
GCP Connect	TrustFLEX\10_cloud_connect\notebook\gcp\TFLXTLS_GCP_connect.ipynb	TrustFLEX
AWS Custom PKI	TrustFLEX\10_cloud_connect\notebook\aws\ TFLXTLS_aws_connect.ipynb	TrustFLEX
Azure Connect	TrustFLEX\10_cloud_connect\notebook\azure\ TLFXTLS_azure_connect.ipynb	TrustFLEX

3 Resource Generation Notebook

TFLXTLS device is one of the three devices available in the Trust Platform USB Dongle Board.

TrustFLEX devices come with pre-programmed certificates in slots 10, 11 and 12, also slots 0-4 have pre-generated private keys, other than the mentioned slots all the other slots have no data in them.

The Resource Generator Notebook will create development keys and certificates for all slots that can be further customized. Keys and Certificate chains are stored in the PC filesystem. These keys should never be used for production purposes as their generation is not handled in a secure environment. These development keys will be later used by the other notebooks to implement the various pre-defined use cases.

Within the Jupyter Dashboard, navigate **TrustFLEX\00_resource_generation** folder to open **TFLXTLS_resource_generator.ipynb** notebook



Run all cells of the Crypto Resource Generator Notebook: Kernel->Restart & Run All

Note: Before executing the cells on Crypto Trust Platform, its required to have factory default program running on SAMD21 of Trust Platform. Refer to Crypto Auth Trust Platform Factory reset section for reloading default program.



Crypto Resource Generator notebook is common for all the use case which comes with option to load the signer certificate and device certificate. The Notebook will generate several keys and certificates. Make sure you have an error free output before continuing to the next steps of the training. Following are 3 different things can be performed,

1. Generating resources to general key slots



The output log should resemble this:

```
-----------------------------------------
Slot 0 is a private key slot, no action required
Slot 1 is a private key slot, no action required
Slot 2 is a private key slot, no action required
Slot 3 is a private key slot, no action required
Slot 4 is a private key slot, no action required
```

Slot 6 is a secret key, created slot_6_secret_key.pem and programmed

NOTE: While writing symmetric key into secure element it has to be encrypted with IO prote ction key. So here, Slot 6 (IO protection key) is written before slot 5 (Symmetric key)

Slot 5 is a secret key, created slot_5_secret_key.pem and programmed
Slot 7 is a secureboot digest slot, slot can only be written through secureboot command
Slot 8 is a general purpose slot of size 416 bytes, no action required
Slot 9 is a secret key, created slot_9_secret_key.pem and programmed
Slot 10 is a certificate slot, no action required now, will be updated as part of Generate Certi ficates
Slot 11 is a certificate slot, no action required now, will be updated as part of Generate Certi ficates
Slot 12 is a certificate slot, no action required now, will be updated as part of Generate Certi ficates
Slot 13 is a public key slot, created slot_13_ecc_key_pair.pem and programmed
Slot 14 is a public key slot, created slot_14_ecc_key_pair.pem and programmed
Slot 15 is a public key slot, created slot_15_ecc_key_pair.pem and programmed

---
Key generation - Success
---

2. Generating MCHP or Custom Certificates

   On selecting Custom certificates, it prompts to enter the organization name, enter the name that will be used as an Organization Name in the certificate template. The name length is limited to 24 characters. For this Usecase, its required to select Custom Certs.



The output log should resemble this:

Custom Certs processing...
Device contains custom device and signer certificates
Building new root certificate
Building new signer csr certificate
Building new signer certificate
Read device serial number...OK (SN: 01233E8A1491F2A601)

Read device public key from slot 0...OK (Public Key: CF1988BC3A6C252026FE70FB34397AD
85A39AE811C722BFA6E5EC1E9CDA9133B3F0E91FD3877F25B8C893B311BAF0203CB5100C
4CDABEBAFDAF3EBD550B00125)
Generating device certificate...OK (saved to device_01233E8A1491F2A601.crt)
Saving signer certificate to device...OK
Saving device certificate to device...OK
Thing ID eabc56113c70227a18c0a62f7c285fc68d75f9cd

Custom certificate generation and provisioning - SUCCESS

Validate root certificate...OK
-----BEGIN CERTIFICATE-----
MIIByjCCAW+gAwIBAgIQeoueybRh8XWwzOkoixtW1jAKBggqhkjOPQQDAjA7MQ0w
CwYDVQQKDAR0ZXN0MSowKAYDVQQDDCFDcnlwdG8gQXV0aGVudGljYXRpb24gUm9v
dCBDQSAwMDIwIBcNMjAwNzAxMDgwNTE5WhgPMjA2MDA2MjEwODA1MTlaMDsxDTAL
BgNVBAoMBHRlc3QxKjAoBgNVBAMMIUNyeXB0byBBdXRoZW50aWNhdGlvbiBSb290
IENBIDAwMjBZMBMGByqGSM49AgEGCCqGSM49AwEHA0IABFf6qcSyPv8iY0uccoTX
SlSstaz0ECCUxXUoqky8Xo40vsOCbPPt5QtlvNHnyy8tAbwza6DsAiz2sGLzDI5h
QhqjUzBRMB0GA1UdDgQWBBRHVPQoljiq65JOG4vu5l32JzmkSTAfBgNVHSMEGDAW
gBRHVPQoljiq65JOG4vu5l32JzmkSTAPBgNVHRMBAf8EBTADAQH/MAoGCCqGSM49
BAMCA0kAMEYCIQCB7FKx5K33xK9E0PsWGKZRaaQxxSRypC66y4hVqWVmMAIhAMlG
22zNUKPHccHQxfQssYH5LfR5SVE+WC3Hyxem/EVj
-----END CERTIFICATE-----

Certificate:
    Data:
        Version: 3 (0x2)
        Serial Number:
            7a:8b:9e:c9:b4:61:f1:75:b0:cc:e9:28:8b:1b:56:d6
        Signature Algorithm: ecdsa-with-SHA256
        Issuer: O=test, CN=Crypto Authentication Root CA 002
        Validity
            Not Before: Jul 1 08:05:19 2020 GMT
            Not After : Jun 21 08:05:19 2060 GMT
        Subject: O=test, CN=Crypto Authentication Root CA 002
        Subject Public Key Info:
            Public Key Algorithm: id-ecPublicKey
                Public-Key: (256 bit)
                pub:
                    04:57:fa:a9:c4:b2:3e:ff:22:63:4b:9c:72:84:d7:
                    4a:54:ac:b5:ac:f4:10:20:94:c5:75:28:aa:4c:bc:
                    5e:8e:34:be:c3:82:6c:f3:ed:e5:0b:65:bc:d1:e7:

```
                cb:2f:2d:01:bc:33:6b:a0:ec:02:2c:f6:b0:62:f3:
                0c:8e:61:42:1a
            ASN1 OID: prime256v1
            NIST CURVE: P-256
        X509v3 extensions:
            X509v3 Subject Key Identifier:
                47:54:F4:28:96:38:AA:EB:92:4E:1B:8B:EE:E6:5D:F6:27:39:A4:49
            X509v3 Authority Key Identifier:
                keyid:47:54:F4:28:96:38:AA:EB:92:4E:1B:8B:EE:E6:5D:F6:27:39:A4:49

            X509v3 Basic Constraints: critical
                CA:TRUE
    Signature Algorithm: ecdsa-with-SHA256
        30:46:02:21:00:81:ec:52:b1:e4:ad:f7:c4:af:44:d0:fb:16:
        18:a6:51:69:a4:31:c5:24:72:a4:2e:ba:cb:88:55:a9:65:66:
        30:02:21:00:c9:46:db:6c:cd:50:a3:c7:71:c1:d0:c5:f4:2c:
        b1:81:f9:2d:f4:79:49:51:3e:58:2d:c7:cb:17:a6:fc:45:63


Validate signer certificate...OK
-----BEGIN CERTIFICATE-----
MIIB3TCCAYKgAwIBAgIQV/RpeXxWfquIIYFCFTDc/TAKBggqhkjOPQQDAjA7MQ0w
CwYDVQQKDAR0ZXN0MSowKAYDVQQDDCFDcnlwdG8gQXV0aGVudGljYXRpb24gUm9v
dCBDQSAwMDIwIBcNMjAwNzAxMDgwMDAwWhgPMjA0MDA3MDEwODAwMDBaMDsxDTAL
BgNVBAoMBHRlc3QxKjAoBgNVBAMMIUNyeXB0byBBdXRoZW50aWNhdGlvbiBTaWdu
ZXIgRkZGRjBZMBMGByqGSM49AgEGCCqGSM49AwEHA0IABCEubbOfXDakettxvfKu
kfG5UhQNDHrPrZiURytSZmQ8p38VacZ682akSAC6XQYDzhiy5/5O4eAHBCuN5rOt
vnOjZjBkMA4GA1UdDwEB/wQEAwIBhjASBgNVHRMBAf8ECDAGAQH/AgEAMB0GA1Ud
DgQWBBRycA/sc+NWXwp0wLudepyPtQtzFzAfBgNVHSMEGDAWgBRHVPQoljiq65JO
G4vu5l32JzmkSTAKBggqhkjOPQQDAgNJADBGAiEA1ThacjiYboKYh69+NllQKiX2
wb7Jztq8zMsY61H/NkYCIQDQc2TQfOl9HBDUoDzUtTZNgIksElkU7ysiSgBhumAA
zQ==
-----END CERTIFICATE-----

Certificate:
    Data:
        Version: 3 (0x2)
        Serial Number:
            57:f4:69:79:7c:56:7e:ab:88:21:81:42:15:30:dc:fd
        Signature Algorithm: ecdsa-with-SHA256
        Issuer: O=test, CN=Crypto Authentication Root CA 002
        Validity
            Not Before: Jul  1 08:00:00 2020 GMT
            Not After : Jul  1 08:00:00 2040 GMT
```

```
        Subject: O=test, CN=Crypto Authentication Signer FFFF
        Subject Public Key Info:
            Public Key Algorithm: id-ecPublicKey
                Public-Key: (256 bit)
                pub:
                    04:21:2e:6d:b3:9f:5c:36:a4:7a:db:71:bd:f2:ae:
                    91:f1:b9:52:14:0d:0c:7a:cf:ad:98:94:47:2b:52:
                    66:64:3c:a7:7f:15:69:c6:7a:f3:66:a4:48:00:ba:
                    5d:06:03:ce:18:b2:e7:fe:4e:e1:e0:07:04:2b:8d:
                    e6:b3:ad:be:73
                ASN1 OID: prime256v1
                NIST CURVE: P-256
        X509v3 extensions:
            X509v3 Key Usage: critical
                Digital Signature, Certificate Sign, CRL Sign
            X509v3 Basic Constraints: critical
                CA:TRUE, pathlen:0
            X509v3 Subject Key Identifier:
                72:70:0F:EC:73:E3:56:5F:0A:74:C0:BB:9D:7A:9C:8F:B5:0B:73:17
            X509v3 Authority Key Identifier:
                keyid:47:54:F4:28:96:38:AA:EB:92:4E:1B:8B:EE:E6:5D:F6:27:39:A4:49

    Signature Algorithm: ecdsa-with-SHA256
        30:46:02:21:00:d5:38:5a:72:38:98:6e:82:98:87:af:7e:36:
        59:50:2a:25:f6:c1:be:c9:ce:da:bc:cc:cb:18:eb:51:ff:36:
        46:02:21:00:d0:73:64:d0:7c:e9:7d:1c:10:d4:a0:3c:d4:b5:
        36:4d:80:89:2c:12:59:14:ef:2b:22:4a:00:61:ba:60:00:cd


Validate device certificate...OK
-----BEGIN CERTIFICATE-----
MIIByDCCAW+gAwIBAgIQdxkpBswUT+e4dShL6tp00jAKBggqhkjOPQQDAjA7MQ0w
CwYDVQQKDAR0ZXN0MSowKAYDVQQDDCFDcnlwdG8gQXV0aGVudGljYXRpb24gU2ln
bmVyIEZGRkYwIBcNMjAwNzAxMDYwMDAwWhgPMjA0ODA3MDEwNjAwMDBaMC4xDTAL
BgNVBAoMBHRlc3QxHTAbBgNVBAMMFHNuMDEyMzNFOEExNDkxRjJBNjAxMFkwEwYH
KoZIzj0CAQYIKoZIzj0DAQcDQgAEzxmIvDpsJSAm/nD7NDl62Fo5roEcciv6bl7B
6c2pEzs/DpH9OHfyW4yJOzEbrwIDy1EAxM2r66/a8+vVULABJaNgMF4wDAYDVR0T
AQH/BAIwADAOBgNVHQ8BAf8EBAMCA4gwHQYDVR0OBBYEFOq8VhE8cCJ6GMCmL3wo
X8aNdfnNMB8GA1UdIwQYMBaAFHJwD+xz41ZfCnTAu516nI+1C3MXMAoGCCqGSM49
BAMCA0cAMEQCIANn/QrqxwmwrRsrcYyQpWJ0o4AxLzGoeCZjfJ5o0FAbAiBFne67
iEzuh6dqwrdQYvgB6+qTxfLyei1kwoFcfVnHvA==
-----END CERTIFICATE-----

Certificate:
```

```
Data:
    Version: 3 (0x2)
    Serial Number:
        77:19:29:06:cc:14:4f:e7:b8:75:28:4b:ea:da:74:d2
    Signature Algorithm: ecdsa-with-SHA256
    Issuer: O=test, CN=Crypto Authentication Signer FFFF
    Validity
        Not Before: Jul  1 06:00:00 2020 GMT
        Not After : Jul  1 06:00:00 2048 GMT
    Subject: O=test, CN=sn01233E8A1491F2A601
    Subject Public Key Info:
        Public Key Algorithm: id-ecPublicKey
            Public-Key: (256 bit)
            pub:
                04:cf:19:88:bc:3a:6c:25:20:26:fe:70:fb:34:39:
                7a:d8:5a:39:ae:81:1c:72:2b:fa:6e:5e:c1:e9:cd:
                a9:13:3b:3f:0e:91:fd:38:77:f2:5b:8c:89:3b:31:
                1b:af:02:03:cb:51:00:c4:cd:ab:eb:af:da:f3:eb:
                d5:50:b0:01:25
            ASN1 OID: prime256v1
            NIST CURVE: P-256
    X509v3 extensions:
        X509v3 Basic Constraints: critical
            CA:FALSE
        X509v3 Key Usage: critical
            Digital Signature, Key Agreement
        X509v3 Subject Key Identifier:
            EA:BC:56:11:3C:70:22:7A:18:C0:A6:2F:7C:28:5F:C6:8D:75:F9:CD
        X509v3 Authority Key Identifier:
            keyid:72:70:0F:EC:73:E3:56:5F:0A:74:C0:BB:9D:7A:9C:8F:B5:0B:73:17

Signature Algorithm: ecdsa-with-SHA256
     30:44:02:20:03:67:fd:0a:ea:c7:09:b0:ad:1b:2b:71:8c:90:
     a5:62:74:a3:80:31:2f:31:a8:78:26:63:7c:9e:68:d0:50:1b:
     02:20:45:9d:ee:bb:88:4c:ee:87:a7:6a:c2:b7:50:62:f8:01:
     eb:ea:93:c5:f2:f2:7a:2d:64:c2:81:5c:7d:59:c7:bc
```

3. Generating Manifest file



The output log should resemble this:

```
------------------------------------------------------
Generating manifest data...OK (saved to TFLXTLS_devices_manifest.json)
------------------------------------------------------
```

The Notebook will also generate a manifest file to be uploaded into the public cloud of your choice (Google GCP, AWS IoT and Microsoft Azure).

After running this Notebook, it generates the required resources and program data zone with generated secrets, keys and certificates.

For this use case, Signer and Device certificates are required along with Root Public Key. When the MCHP certificates are available on device, MCHP cert definition files to be used. When the Cust certificates are generated and loaded to device, generated definition files to be used.

4 Use Case Prototyping

This hands-on lab is intended to demonstrate the usage of host to authenticate Accessory device. It uses asymmetric authentication where host reads certificates from accessory to validate chain of trust, followed by device private key.

This process uses a challenge-response model. In this model, host authenticates the accessory device based on response. Response (Signature) is calculated on the accessory device to prove that it holds the private key associated to its certificate shared to the host. Then the response will be verified by the host using Public key in Device certificate to authenticate the accessory.

This lab is developed by simulating TrustFLEX device as Accessory and host to authenticate the accessory. Since Trust&GO use case demonstrate using MCHP certificates, here we would be Custom certificates to verify the authentication.

The resource generation for TrustFLEX device will load prototyping certificates to device along with custom certificates definition files.

Following sections provides detail steps to execute the usecase both on Jupyter Notebook and on Embedded project

4.1 Running Accessory Asymmetric Authentication example on Jupyter Notebook:

1. From the Jupyter Home page, navigate to **TrustFLEX\08_asymmetric_authentication\notebook\TFLXTLS_asymmetric_authentication.ipynb** notebook file and open it.



Opening the notebook from Jupyter home page should load the following on the browser,



2. Run All Cells by using Kernel -> Restart & Run All



3. It may take a while to complete, wait for the kernel to complete all processing i.e. from Kernel Running to Kernel Idle state (Check circle above **RED** text)





4. Navigate through different cells output for the description of the step and result from the execution.

5. There are 2 major steps in this lab
   Verify Certificate Chain
   The certificate chain verification process includes reading the certificates from device, validating its signatures using CA's Public Key.

   The host MCU contains the Root's Public Key stored on it. Certificate chain verification process starts by reading both Signer and Device certificates. Since, these certificates are stored as compressed certificates on the device, its required to rebuild them using certificate definition information.

These definition files can be regenerated based on the certificate templates.

Select certificate templates
On executing all the cells, the following buttons will be available to choose the certificate templates.



Since the root certificate or its details are not stored on Secure element, its required to provide the actual root that should be used to validate Signer certificate.

For Signer and Device certificates select the template certificates i.e. one generated in resource generation.

Authenticate Accessory/Node
In the above step, we have provided required certificates information to fetch and validate Signer and Device certificates from Secure element.

On clicking 'Authenticate Node' button, the process of rebuilding certificates, validation and Accessory authentication gets triggered.



Client Rebuild Certificates:
In this step Signer and Device certificate definitions will be regenerated based on root certificate and template certificates provided.

Once the definitions are generated, host triggers set of commands to know the max size of the certificate and read the actual certificates from secure element. One can see root, signer and device certificates in the log.

Host to verify certificate chain:
On reading the certificates, host starts certificate chain verification. This step is currently limited to signature verification only.

In the resource generation root certificate is created as self-signed certificate. Hence, root certificate is validated using its own public key. Once its validated, Signer certificate is validated using root public key and device certificate is validated using Signer public key provided in the signer certificate.

Challenge-Response-Verify:
Once the certificates are validated, its important to check the accessory holds the original private key used to generate device certificate signing request. This will be done through a challenge response method.

Host generates as random challenge and sends to accessory for signing. Accessory would sign the challenge using the private key used for Device CSR. Once, host receives the signature from accessory, it verifies the same using public key provided in the Device certificate.

The result will be success only if the private and public key corresponds to each other, this indicates the connected accessory is authentic.

In case if private key is not associated to public key in the device certificate, this verification step would fail, this indicates the connected accessory is not authentic.

Pressing the button, turns it Green or Red. Green indicates that the device is authenticated by host and Red indicates the authentication is failed.

4.2 Running Accessory Asymmetric Authentication example on Embedded platform

This usecase can also be executed on Embedded platform. Once the resources are generated, both Atmel Studio and MPLAB projects provided can be used to run the application on Crypto Auth Trust Platform.

Note: This usecase requires resource generation notebook executed prior to using embedded projects.

4.2.1 MPLAB:

1. Open **asymmetric_auth.X** project by navigating to MPLAB -> File -> Open Project -> **TrustFLEX\08_asymmetric_authentication\firmware\asymmetric_auth.X**

2. The application source code asymmetric_auth.c is available at **TrustFLEX\08_asymmetric_authentication\firmware\asymmetric_auth.c.** Other supporting files can be found under **assets\dependencies**

3. Program the Crypto Trust platform by navigating to **asymmetric_auth -> Make and Program Device**

   This step may take some time, wait for MPLAB to program the device. Once it is done programming you will see "**Programming complete**" message in Output Window.



Once the programming is done, the firmware will do Accessory Asymmetric Authentication operation. Depending on the output, the Crypto Auth Trust Platform board's status LED will blink at different rates.

If succeeds, LED blinks once every second.
If fails, LED blinks five times every second.

It is also possible to view the Console messages by using applications like TeraTerm. Open the application with the COM related to Crypto Auth Trust Platform with 115200-8-N-1 settings


COM32 - Tera Term VT
File Edit Setup Control Window Help
Device revision: 00 00 60 02
Device serial number: 01 23 29 79 CB 29 3B A5 01
CLIENT: Rebuilt Signer Certificate:
-----BEGIN CERTIFICATE-----
MIICBTCCAaqgAwIBAgIQeQqn1X1z3OltZdtmi3ayXjAKBggqhkjOPQQDAjBPMSEw
HwYDVQQKDBhNaWNyb2NoaXAgVGVjaG5vbG9neSBJbmMxKjAoBgNVBAMMIUNyeXB0
byBBdXRoZW50aWNhdGlvbiBSb290IENBIDAwMjAgFw0xODEyMTQxOTAwMDBaGA8y
MDQ5MTIxNDE5MDAwMFowTzEhMB8GA1UECgwYTWljcm9jaGlwIFR1Y2hub2xvZ3kg
SW5jMSowKAYDVQQDDCFDcnlwdG8gQXV0aGVudGljYXRpb24gU2lnbmVyIEY2MDAw
WTATBgcqhkjOPQIBBggqhkjOPQMBBwNCAAR2R0FwsmPnmVS8hbsS6f5wDFuN1NaT
RZjCKadoAg5OC21IddDtoe72X5FfxrEWRsWhymMfY1VodEdpxd6DtY1qo2YwZDAO
BgNVHQ8BAf8EBAMCAYYwEgYDVR0TAQH/BAgwBgEB/wIBADAdBgNVHQ4EFgQU+9yq
Eor6wbWSj82rEdsJPs9NvvYwHwYDVR0jBBgwFoAUeu19bca3eJ2yOAG16EqMsKQO
KowwCgYIKoZIzj0EAwIDSQAwRgIhAMYwMempizBOaH4GxTl5KsV6XAFNMBfe3NJ9
1R3Nhjf/AiEAxqIsbrGuX4WRSctd53eLo/ML6T2bgG+Uvz2QpYR4Ydw=
-----END CERTIFICATE-----
CLIENT: Rebuilt Device Certificate:
-----BEGIN CERTIFICATE-----
MIIB9TCCAZugAwIBAgIQYlvNgfJuMqdIpWEADSpuWzAKBggqhkjOPQQDAjBPMSEw
HwYDVQQKDBhNaWNyb2NoaXAgVGVjaG5vbG9neSBJbmMxKjAoBgNVBAMMIUNyeXB0
byBBdXRoZW50aWNhdGlvbiBTaWduZXIgRjYwMDAgFw0xOTA3MzEyMTAwMDBaGA8y
MDQ3MDczMTIxMDAwMFowRjEhMB8GA1UECgwYTWljcm9jaGlwIFR1Y2hub2xvZ3kg
SW5jMSEwHwYDVQQDDBgwMTIzMjk3OUNCMjkzQkE1MDEgQURFQ0MwWTATBgcqhkjO
PQIBBggqhkjOPQMBBwNCAASZ2Oqd0R6AEDuObwxdFLwJjT16yq7HGqThiaLpkN0K
eG5qZOJl0HCPdBoWplEsDcw26q0X6uIMuqyrRTL883Reo2AwXjAMBgNVHRMBAf8E
AjAAMA4GA1UdDwEB/wQEAwIDiDAdBgNVHQ4EFgQUCwT6mxFlijOMO0UmHxvIo1ox
k8EwHwYDVR0jBBgwFoAU+9yqEor6wbWSj82rEdsJPs9NvvYwCgYIKoZIzj0EAwID
SAAwRQIgGnifKevE7ZIp2mpAQIW6OWHfitgH4uJlCof1DWkGb18CIQDii8oVy/HU
aLN9cpDc2FfRDRGf5UdU1ZR35Jv/I6VChw==
-----END CERTIFICATE-----
HOST: Signer certificate verified against root public key!
HOST: Device certificate verified against signer public key!
HOST: Generated challenge:
06 E6 31 DB 55 4B B3 62 3A 37 71 5F 21 19 2B F7
B5 B2 92 E3 2C 95 FB BB 77 FB 63 29 70 5C 2A 5F
CLIENT: Calculated response to host challenge:
4F DB B1 06 07 FC 6B 2B 7B 37 4E 00 99 03 19 B1
83 9E 41 D3 AE F1 86 14 E7 1A F6 6C 48 0E 8A 20
C2 CF 48 44 53 1E 35 90 0A 9C 58 93 55 D1 08 B1
95 93 4A 12 69 EC 04 63 CE 61 8A 15 58 13 01 D4
HOST: Device public key from certificate:
99 D8 EA 9D D1 1E 80 10 3B 8E 6F 0C 5D 14 BC 09
8D 3D 7A CA AE C7 1A A4 E1 89 A2 E9 90 DD 0A 78
6E 6A 64 E2 65 D0 70 8F 74 1A 16 A6 51 2C 0D CC
36 EA AD 17 EA E2 0C BA AC AB 45 32 FC F3 74 5E
HOST: Device response to challenge verified!
Accessory device authenticated successfully
Execution completed with status 00

4.2.2 Atmel Studio (Deprecated)

1. Open **asymmetric_auth.atsln** project by navigating to Atmel Studio -> File -> open -> **TrustFLEX\08_asymmetric_authentication\ deprecated_studio \asymmetric_auth.atsln**

2. The application source code asymmetric_auth.c is available at **TrustFLEX\08_asymmetric_authentication\firmware\asymmetric_auth.c.** Other supporting files can be found under **assets\dependencies**

3. Program the Crypto Trust platform by navigating to **Debug -> Start Without Debugging**

   This step may take some time, wait for Atmel Studio to compile and program the device.

   Once the programming is done, the firmware will do Accessory Asymmetric Authentication operation. Depending on the result, the Crypto Auth Trust Platform board's status LED will blink at different rates.

   If succeeds, LED blinks once every second.
   If fails, LED blinks five times every second.

   It is also possible to view the Console messages by using applications like TeraTerm. Open the application with the COM related to Crypto Auth Trust Platform with 115200-8-N-1 settings


COM32 - Tera Term VT
File Edit Setup Control Window Help
Device revision: 00 00 60 02
Device serial number: 01 23 29 79 CB 29 3B A5 01
CLIENT: Rebuilt Signer Certificate:
-----BEGIN CERTIFICATE-----
MIICBTCCAaqgAwIBAgIQeQqn1X1z3OltZdtmi3ayXjAKBggqhkjOPQQDAjBPMSEw
HwYDVQQKDBhNaWNyb2NoaXAgVGVjaG5vbG9neSBJbmMxKjAoBgNVBAMMIUNyeXB0
byBBdXRoZW50aWNhdGlvbiBSb290IENBIDAwMjAgFw0xODEyMTQxOTAwMDBaGA8y
MDQ5MTIxNDE5MDAwMFowTzEhMB8GA1UECgwYTWljcm9jaGlwIFR1Y2hub2xvZ3kg
SW5jMSowKAYDVQQDDCFDcnlwdG8gQXV0aGVudGljYXRpb24gU2lnbmVyIEY2MDAw
WTATBgcqhkjOPQIBBggqhkjOPQMBBwNCAAR2R0FwsmPnmVS8hbsS6f5wDFuN1NaT
RZjCKadoAg5OC21IddDtoe72X5FfxrEWRsWhymMfY1VodEdpxd6DtY1qo2YwZDAO
BgNVHQ8BAf8EBAMCAYYwEgYDVR0TAQH/BAgwBgEB/wIBADAdBgNVHQ4EFgQU+9yq
Eor6wbWSj82rEdsJPs9NvvYwHwYDVR0jBBgwFoAUeu19bca3eJ2yOAG16EqMsKQO
KowwCgYIKoZIzj0EAwIDSQAwRgIhAMYwMempizBOaH4GxTl5KsV6XAFNMBfe3NJ9
1R3Nhjf/AiEAxqIsbrGuX4WRSctd53eLo/ML6T2bgG+Uvz2QpYR4Ydw=
-----END CERTIFICATE-----
CLIENT: Rebuilt Device Certificate:
-----BEGIN CERTIFICATE-----
MIIB9TCCAZugAwIBAgIQYlvNgfJuMqdIpWEADSpuWzAKBggqhkjOPQQDAjBPMSEw
HwYDVQQKDBhNaWNyb2NoaXAgVGVjaG5vbG9neSBJbmMxKjAoBgNVBAMMIUNyeXB0
byBBdXRoZW50aWNhdGlvbiBTaWduZXIgRjYwMDAgFw0xOTA3MzEyMTAwMDBaGA8y
MDQ3MDczMTIxMDAwMFowRjEhMB8GA1UECgwYTWljcm9jaGlwIFR1Y2hub2xvZ3kg
SW5jMSEwHwYDVQQDDBgwMTIzMjk3OUNCMjkzQkE1MDEgQURFQ0MwWTATBgcqhkjO
PQIBBggqhkjOPQMBBwNCAASZ2Oqd0R6AEDuObwxdFLwJjT16yq7HGqThiaLpkN0K
eG5qZOJl0HCPdBoWplEsDcw26q0X6uIMuqyrRTL883Reo2AwXjAMBgNVHRMBAf8E
AjAAMA4GA1UdDwEB/wQEAwIDiDAdBgNVHQ4EFgQUCwT6mxFlijOMO0UmHxvIo1ox
k8EwHwYDVR0jBBgwFoAU+9yqEor6wbWSj82rEdsJPs9NvvYwCgYIKoZIzj0EAwID
SAAwRQIgGnifKevE7ZIp2mpAQIW6OWHfitgH4uJlCof1DWkGb18CIQDii8oVy/HU
aLN9cpDc2FfRDRGf5UdU1ZR35Jv/I6VChw==
-----END CERTIFICATE-----
HOST: Signer certificate verified against root public key!
HOST: Device certificate verified against signer public key!
HOST: Generated challenge:
06 E6 31 DB 55 4B B3 62 3A 37 71 5F 21 19 2B F7
B5 B2 92 E3 2C 95 FB BB 77 FB 63 29 70 5C 2A 5F
CLIENT: Calculated response to host challenge:
4F DB B1 06 07 FC 6B 2B 7B 37 4E 00 99 03 19 B1
83 9E 41 D3 AE F1 86 14 E7 1A F6 6C 48 0E 8A 20
C2 CF 48 44 53 1E 35 90 0A 9C 58 93 55 D1 08 B1
95 93 4A 12 69 EC 04 63 CE 61 8A 15 58 13 01 D4
HOST: Device public key from certificate:
99 D8 EA 9D D1 1E 80 10 3B 8E 6F 0C 5D 14 BC 09
8D 3D 7A CA AE C7 1A A4 E1 89 A2 E9 90 DD 0A 78
6E 6A 64 E2 65 D0 70 8F 74 1A 16 A6 51 2C 0D CC
36 EA AD 17 EA E2 0C BA AC AB 45 32 FC F3 74 5E
HOST: Device response to challenge verified!
Accessory device authenticated successfully
Execution completed with status 00

4.3 Crypto Auth Trust Platform Factory reset

Once any of the embedded project is loaded to Crypto Auth Trust Platform, the default program that enables interaction with Trust Platform tools will be erased.

Before using the Platform with any other notebook or tools on PC, its required to reprogram the default .hex file. Default hex file is available cloned repository at **assets\Factory_Program.X\CryptoAuth_Trust_Platform.hex**

If Trust Platform GUI is provided with MPLAB X IDE installation location, notebooks can program the Factory reset hex file if its not available by default.

This can also be done manually by MPLAB and Atmel Studio

To reprogram using MPLAB:

1. Open **assets\Factory_Program.X** project in MPLAB IDE
2. Program the Crypto Trust platform by navigating to **CryptoAuth_Trust_Platform_Factory_Program -> Make and Program Device**

To reprogram using Atmel Studio:

1. Navigate to AtmelStudio -> Tools -> Device Programming
2. Select Tool as nEDBG and Apply
3. Go to Memories and navigate to above path under Flash dropdown
4. Check both Erase Flash and Verify Flash
5. Click on Program



Now, Crypto Auth Trust Platform contains factory programmed application that enables interactions with Notebooks and/or PC tools.

5 FAQ

1. **What are the reasons for "AssertionError: Can't connect to the USB dongle" error?**
   There are many possibilities like,
   1. Crypto Trust Platform is having different application than factory reset firmware. Refer to "Crypto Auth Trust Platform Factory reset" section any usecase TrustFLEX Guide for reloading it
   2. Check the switch positions on Crypto Trust Platform and/or ATECC608A Trust board
      a. Correct Trust device should be connected and only one device of that type is allowed on the I2C bus. Multiple devices with same address results in error
   3. Check USB connections to Crypto Trust Platform

2. **How to reload factory default application to Crypto Trust Platform?**
   Refer to "Crypto Auth Trust Platform Factory reset" section any usecase TrustFLEX Guide for reloading it.

3. **Why does my C projects generates No such file or directory with ../../../00_resource_generation/?**
   C project generates this error when the resources are not generated prior to using embedded projects. Running the resource generation notebook ensures these files and secrets are generated.

4. **Before running any use case notebook and/or C project, why is it mandate to execute resource generation?**
   When resource generation notebook is executed, it generates and programs the required resources like secrets, keys and certificates. These are only prototyping keys and cannot be used for production. These keys will be used part of Usecase notebooks and C projects

5. **How to know the resources being used in a use case?**
   Refer to individual Usecase description html for details on transaction diagrams, resources being used and other details. The resources required for given use case is mentioned in INFER CRYPTOGRAPHIC ASSETS section.

6. **When should I select Custom certificates while doing resource generation?**
   Custom certificates are required when user wants to have their own root, signer instead of MCHP provided. The difference would be organization name, common name and validity are configurable

7. **How to know whether C project is executing on Trust Platform or not after programming?**
   Once the programming is done, the firmware will do use case operation. Depending on the use case operation's output, the Crypto Trust Platform board's status LED will blink at different rates.
   If use case operation succeeds, LED blinks once every second. If it fails, LED blinks five times every second.

It is also possible to view the Console messages by using applications like TeraTerm. Open the application with the COM related to Crypto Trust Platform with 115200-8-N-1 settings

The Microchip Web Site

Microchip provides online support via our web site at http://www.microchip.com/. This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Customer Change Notification Service

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at http://www.microchip.com/. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support.

Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: http://www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.

- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as “unbreakable.”

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip’s code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Legal Notice

Trademarks

ISBN:

Quality Management System Certified by DNV

ISO/TS 16949

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California
and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
http://www.microchip.com/support
Web Address:
www.microchip.com
Atlanta
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455
Austin, TX
Tel: 512-257-3370
Boston
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088
Chicago
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075
Dallas
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924
Detroit
Novi, MI
Tel: 248-848-4000
Houston, TX
Tel: 281-894-5983
Indianapolis
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380
Los Angeles
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800
Raleigh, NC
Tel: 919-844-7510
New York, NY
Tel: 631-435-6000
San Jose, CA
Tel: 408-735-9110
Tel: 408-436-4270
Canada - Toronto
Tel: 905-695-1980
Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney
Tel: 61-2-9868-6733
China - Beijing
Tel: 86-10-8569-7000
China - Chengdu
Tel: 86-28-8665-5511
China - Chongqing
Tel: 86-23-8980-9588
China - Dongguan
Tel: 86-769-8702-9880
China - Guangzhou
Tel: 86-20-8755-8029
China - Hangzhou
Tel: 86-571-8792-8115
China - Hong Kong SAR
Tel: 852-2943-5100
China - Nanjing
Tel: 86-25-8473-2460
China - Qingdao
Tel: 86-532-8502-7355
China - Shanghai
Tel: 86-21-3326-8000
China - Shenyang
Tel: 86-24-2334-2829
China - Shenzhen
Tel: 86-755-8864-2200
China - Suzhou
Tel: 86-186-6233-1526
China - Wuhan
Tel: 86-27-5980-5300
China - Xian
Tel: 86-29-8833-7252
China - Xiamen
Tel: 86-592-2388138
China - Zhuhai
Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444
India - New Delhi
Tel: 91-11-4160-8631
India - Pune
Tel: 91-20-4121-0141
Japan - Osaka
Tel: 81-6-6152-7160
Japan - Tokyo
Tel: 81-3-6880- 3770
Korea - Daegu
Tel: 82-53-744-4301
Korea - Seoul
Tel: 82-2-554-7200
Malaysia - Kuala Lumpur
Tel: 60-3-7651-7906
Malaysia - Penang
Tel: 60-4-227-8870
Philippines - Manila
Tel: 63-2-634-9065
Singapore
Tel: 65-6334-8870
Taiwan - Hsin Chu
Tel: 886-3-577-8366
Taiwan - Kaohsiung
Tel: 886-7-213-7830
Taiwan - Taipei
Tel: 886-2-2508-8600
Thailand - Bangkok
Tel: 66-2-694-1351
Vietnam - Ho Chi Minh
Tel: 84-28-5448-2100

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393
Denmark - Copenhagen
Tel: 45-4450-2828
Fax: 45-4485-2829
Finland - Espoo
Tel: 358-9-4520-820
France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79
France - Saint Cloud
Tel: 33-1-30-60-70-00
Germany - Garching
Tel: 49-8931-9700
Germany - Haan
Tel: 49-2129-3766400
Germany - Heilbronn
Tel: 49-7131-67-3636
Germany - Karlsruhe
Tel: 49-721-625370
Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44
Germany - Rosenheim
Tel: 49-8031-354-560
Israel - Ra'anana
Tel: 972-9-744-7705
Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781
Italy - Padova
Tel: 39-049-7625286
Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340
Norway - Trondheim
Tel: 47-7289-7561
Poland - Warsaw
Tel: 48-22-3325737
Romania - Bucharest
Tel: 40-21-407-87-50
Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91
Sweden - Gothenberg
Tel: 46-31-704-60-40
Sweden - Stockholm
Tel: 46-8-5090-4654
UK - Wokingham
Tel: 44-118-921-5800
Fax: 44-118-921-5820