AEGIS: No Tool Call Left Unchecked — A Pre-Execution Firewall and Audit Layer for AI Agents

Aojie Yuan
University of Southern California
Los Angeles, California, USA
aojieyua@usc.edu

Zhiyuan Su
University of California, Davis
Davis, California, USA
azysu@ucdavis.edu

Yue Zhao
University of Southern California
Los Angeles, California, USA
yue.z@usc.edu

ABSTRACT

AI agents now execute tool calls—database queries, shell commands, payments, email—and most agent frameworks forward those calls to execution with nothing in between. Observability records what an agent did; it cannot stop it.

Aegis is an open-source control point between an agent's decision to call a tool and the tool running.[1] Integration is two lines and covers 15 agent frameworks in Python, JavaScript and Go, plus an MCP proxy and a provider-compatible egress proxy. Each call is decided by layers ordered by what they may observe—pattern rules over the call string, a behavioural anomaly stack over the agent's own history, an *instruction-provenance* check over which channel of the conversation authorised the call, and a declarative policy over all of their facts—and returns `allow`, `block`, or `pending`, which suspends the agent until a person—or, as a configured first reviewer, the alignment auditor—decides. A refusal comes back where a tool result would, so a blocked agent explains itself and continues. Every allow carries an Ed25519-signed receipt an executor can verify, and every decision is recorded in a hash-chained trace.

On AgentDojo, with a gpt-4o-mini agent, Aegis reduces attack success from 29.7% to **1.4%**, the lowest of the defenses compared, against 5.4% for an LLM tool filter. The cost is holds: with no reviewer, clean-task utility falls from 69.1% to 38.1%; with the alignment auditor as first reviewer it is 56.7% and 11 of 97 tasks reach a person. With a locally served qwen3:8b as agent and auditor on two suites, the shipped gateway with the auditor shown the agent's evidence lets 1 of 249 attacks execute at 13 of 37 clean tasks against 19 undefended; on two held-out suites it costs no utility (17 of 60 against 16) and cuts attacks from 23 to 4 of 700. A check takes 0.44 ms at the median, and one gateway process sustains about 2,300–3,000 checks per second. On tool calls live agents emitted under attack, content inspection is at chance and the provenance layer separates them, and we report where it does not: an injection that stays inside the tool the user already asked for. Against an adaptive attacker on AgentDojo, with a complying agent and the pack's rules in hand, four rounds of rewriting escape none of the 60 attacks the gateway flags. Running the shipping gateway under nineteen agent harnesses found and fixed twenty-four defects no unit test had caught, which we list. Numbers reported in this paper's first version are withdrawn; an appendix gives the audit.

KEYWORDS

AI Agent Safety, Tool-Call Interception, LLM Guardrails, Runtime Compliance

[1]Open-source (MIT). Code, harnesses and corpus: https://github.com/Justin0504/Aegis.

1 INTRODUCTION

AI agents do not only generate text; they take actions. ReAct [39] showed that LLMs can interleave reasoning with tool invocations, and modern frameworks such as LangChain [4], CrewAI [9], and LlamaIndex [27] have made tool-augmented agents widely accessible. However, these capabilities create a direct path from model output to real-world side effects—a path that can be triggered by adversarial prompt injection [13] or hallucinated reasoning. In most current stacks, once the model emits a tool call, the framework forwards it to execution with no pre-execution control point.

Post-execution observability platforms such as Langfuse [23] and Arize [1] can record these events, but they cannot prevent side effects before they occur. Existing defenses sit at two extremes: rule-based layers are fast (<1 ms) but see only the call string, while LLM-judge layers can read the call against the user's task but add seconds of latency per call.

Aegis is that control point. It stands between an *unmodified* agent and its tools, decides each call before it runs with layers ordered by **what they may observe**—the call string, the agent's history, the conversation's trust channels, the stated task—and returns the decision in-band, so a refusal reads to the agent like a tool error it can recover from, and a hold suspends the turn until someone answers.

The question a deployment asks of such a system is not how a detector scores single calls but what happens to its agents. On AgentDojo (§4.1), the benchmark the closest systems report against, Aegis cuts attack success from 29.7% to 1.4%. It does so mostly through the instruction-provenance layer, which asks which turn of the conversation authorised a call rather than what the call contains, and which costs under a millisecond and no model call (§4.2). Its cost is holds, and we report them as such: the share of clean tasks that need a person, and how far the alignment auditor, used as first reviewer, brings that down. We also report what the layer cannot see (§4.7).

The paper is written for someone deciding whether to put this in front of their agents. Section 2 describes the system; Section 4 measures it end to end, in cost, and per call on attacks live agents actually emitted; Section 3 walks through it on a real agent; and Appendix B runs the shipping gateway under nineteen agent harnesses—the exercise that found most of the defects this version fixes.

Our contributions are:

(1) A **pre-execution control point** for unmodified agents: two lines in 15 frameworks across Python, JavaScript and Go, an MCP proxy and an egress proxy, returning allow, block or a hold before any side effect, in-band, with every decision in a hash-chained trace and every allow carrying a signed receipt.




Figure 1: Aegis on the tool-execution path, drawn as the loop it is. Outbound, a call reaches the Gateway one of three ways—the SDK's `auto()` across 15 frameworks, the MCP proxy, or the egress proxy (the egress proxy decides inline and cannot hold)—and the Gateway applies layers ordered by *observation scope* rather than only by cost: L1 sees the call string, L2 the agent's own history, L_p the conversation's trust channels, the alignment auditor (L3) the user's stated task, and the policy DSL all of their facts. L_p (accent, dashed) is the instruction-provenance layer of §4, optional and toggleable during the demonstration; L3 (dashed) is not an inline stage of the check but an SDK-side pre-check and a post-hoc trace judge. The lower row is what stands around the decision (§2.4–§2.10). Inbound is what distinguishes a control point from a monitor: `allow` lets the tool run, `block` returns a refusal *in the slot a tool result would occupy*—which is why a blocked agent explains itself and continues rather than failing (Figure 10(b))—and `pending` suspends the turn until a person decides. Circled numbers mark the three places an attendee acts. Every allow returns a signed receipt; every decision lands in a hash-chained trace.

(2) **Instruction provenance** as a decision layer: a per-session ledger of the conversation's trust channels and a measure of which channel explains a call, enforced by a shipped policy pack, and its limit—an injection that stays inside the tool the user asked for.
(3) An **end-to-end evaluation** on AgentDojo against AgentDojo's own defenses, with utility reported as holds and the tasks that need a person, an overhead measurement under concurrent load, and an **adaptive attacker** with a complying agent that the gateway holds against.
(4) A **per-call corpus of agent-emitted attacks** built by compromising a live agent, with a matched control, on which content inspection is at chance; and the audit that withdraws this paper's first-version numbers (Appendix C).
(5) A **compatibility matrix** of nineteen harnesses run against the shipping gateway, and the twenty-four defects it found.

2 SYSTEM ARCHITECTURE

Aegis is organised around one commitment: every tool call an agent emits passes through a point at which it can be decided on, and that decision is returned to the agent in-band, before any side effect occurs. This section follows a single call through the system (Figure 1): how it is captured, what each layer may observe about it, how a policy turns those observations into a decision, what happens when a person must be involved, and how the whole episode is made auditable afterwards.

2.1 Threat Model and Trust Boundary

The LLM is an *untrusted component*. It may emit a harmful tool call because its context was poisoned by indirect prompt injection [13], because it hallucinated an action, or because it was jailbroken. Nothing the model writes is treated as an authority. The trust boundary runs between two channels of the agent's context: what the *principal* typed, and everything that entered from outside—tool returns, retrieved documents, fetched pages, email bodies. A tool return is untrusted even when the tool is one the operator wrote and the server is one the operator runs, because the content it carries may not be theirs. The SDK and Gateway are trusted enforcement components; Aegis does not defend against an agent that bypasses the SDK entirely, and it does not defend the gateway host.

2.2 Interposition: Three Ways In, One Gateway

SDK instrumentation. The primary path patches the model client at import time:

```
import agentguard
agentguard.auto()  # patches every detected SDK in-process
```

`auto()` wraps the request method of each model client it finds—Anthropic and OpenAI (sync and async), LangChain and LangGraph (through `langchain_core` tools), CrewAI, AutoGen, Gemini, the Google GenAI client, Bedrock, Mistral, LiteLLM, LlamaIndex, Pydantic AI, smolagents [19], the OpenAI Agents SDK (at the tool), and a generic HTTP-tool shim; fifteen targets (the Claude Agent SDK is integrated separately, as a `PreToolUse` hook)—and exposes two hooks. On the *response* side it extracts every `tool_use` block, sends `(tool_name, arguments, session_id)` to the Gateway, and suspends dispatch until a decision returns. On the *request* side, which is new in this version, it reads the outgoing `messages` array and classifies each span by trust channel before the model is called (§2.3), into one ledger per process unless the host names its sessions, so the two lines stay two lines. The agent's code, prompts and tool definitions are untouched. Where the decision is *enforced* is a switch, `enforce_at`: at the response, the SDK raises out of the model call before dispatch; at the tool, the model-level patch only observes and a tool-level patch on the framework's own dispatch method (LangGraph, CrewAI, AutoGen, LlamaIndex, Pydantic AI, the OpenAI Agents SDK) returns the refusal as the tool's result (on smolagents it raises, which that framework reports to the model as a tool error), so the model sees it in the slot a result would occupy. A stack with no such method to patch—a hand-written loop, LiteLLM, the Google GenAI client—gets the same behaviour from one line that wraps its dispatcher, `agentguard.guarded(execute_tool)`. The JavaScript SDK patches Anthropic, OpenAI and LangChain and ships the same `enforceAt` switch and `guarded` helper; the Go SDK is an explicit `Wrap(tool, args, fn)` that checks, holds, runs and traces.

MCP proxy. For agents that reach tools over the Model Context Protocol, a stdio proxy (`python -m agentguard.mcp_proxy`) sits between the host and the MCP server, sends every `tools/call` through the full `/api/v1/check` pipeline, holds a `pending` until a person decides, and rewrites refused calls into tool errors. Nothing in the host changes. (The gateway also serves an MCP endpoint over WebSocket that runs schema validation, L1, the policy DSL and the kill switch in-process.) The stdio proxy also pins the server's tool list: a tool's name, description and schema are hashed at first sight, a later change marks it *changed*, and a description that reads like an instruction to the model marks it *suspicious*; either is refused until an operator re-pins it, with both texts in front of them, and is withheld from the tool list the host shows the model, since the description is the attack and would otherwise still reach the model's context and steer a call to some other tool. This is the supply-chain case—a server that changes a tool's description after approval, OWASP's MCP03—which a check on the call alone cannot see, because the description that induced the call is not in the call.

Egress proxy. For stacks where neither is available, the gateway accepts the model provider's own API surface at `/api/v1/llm-proxy/`, so pointing `OPENAI_BASE_URL` or its equivalent at Aegis is a complete integration. The proxy decides inline: it runs the detector chain of §2.3 and the tenant's policy over every tool call in the model's response, and because an inline HTTP response cannot be held for a person, a `pending` decision is treated as `block` and the audit record says so. A policy is written once and applies on all three paths, but what it can match differs: on the egress proxy a rule sees the tool, agent, tenant and workflow, not the classifier, anomaly, provenance or alignment facts, which the SDK and MCP paths get from the full `/api/v1/check` pipeline. Figure 2 places the three paths in a deployment: what runs on the operator's agent hosts, what runs in the control plane, and what crosses each boundary.

2.3 The Decision Pipeline

A call that reaches `/api/v1/check` is decided by layers ordered by *what each may observe*, not only by cost. The ordering matters because the measurement in §4 turns on it: layers that see only the call string are blind to a class of attack that layers which see the conversation can resolve.

Identity and scope. Before any content is read, the call is attributed. The agent is looked up in the registry (and created on first sight), an agent the operator has suspended or the kill switch has revoked is refused with no receipt, and an agent with a *declared tool scope* may only call the tools it declared: a call to an undeclared tool is blocked as `unattested-tool` before extraction. Scope is opt-in per agent, so an unscoped agent is not blocked by a check it never asked for.

Extraction. Arguments are walked recursively (depth limit 32, 10,000-string cap) and every string-bearing leaf is collected. This is what L1 sees.

L1: pattern rules (<1 ms). 28 risk patterns in 11 types (Table 2) are matched against the extracted strings. A hit is an immediate block with a named reason. L1 is the right tool for a *payload* that is itself hostile—a SQL statement with a stacked `DROP`, a path with `../`, a shell string with `${IFS}`—and, as §4 shows, nearly inert against a call whose arguments are ordinary.

L2: behavioural anomaly (in-process). Rather than a second look at the call string, L2 scores the call against the agent's own history. A 16-dimensional behaviour vector—tool novelty, frequency and recency; argument drift (Jaccard distance, length z-score, key-count ratio); hour and interval deviation; burst ratio; sequence surprise under a PPM-C model and bigram unlikeliness; cost z-score; risk ordinal and high-risk rate; the agent's call rate and this tool's rate against their baselines—is scored by an Isolation Forest [42], half-space trees and Mahalanobis distance, calibrated into conformal p-values, with ADWIN [3] flagging drift so thresholds adapt rather than decay. A new agent is observed, not scored, during a learning phase; once it is scored, an agent with too little history for statistics of its own is seeded from its tenant's aggregate baseline, and operator approve/reject feedback is folded back into the scorer. L2 can escalate or block an otherwise-allowed call and never relaxes one. It catches an agent behaving unlike itself; it does not




Figure 2: Deployment. Agent hosts change by one import, one MCP proxy, or one base URL; the gateway, its store, its signing key and the Cockpit run on the operator's side of the trust boundary; what leaves it—traces to a SIEM, Merkle roots to witnesses, receipts to a tool executor—is signed. The model endpoints the auditor and policy compiler use are selected by priority and can be cut to local-only with one switch (§2.7).

catch a single ordinary-looking call, and §4 measures that limit directly: on the rebuilt corpus no surface feature of the call (Table 1) exceeds AUC 0.585, because a successful injection does not make the call look unusual.

Detector chain (proxy path). On the egress proxy the same facts are produced by a registry of pluggable detectors keyed to an ATT&CK-style agent threat ontology: indirect prompt injection, data exfiltration, sensitive-context exfiltration by taint tracking (the agent read a secret, then calls outward), memory poisoning (instruction-shaped writes to scratchpads and vector stores), reconnaissance, lateral movement, tool scope against an agent's declared tool list, budget, cross-agent correlation and PII, with the L1 classifier and the L2 stack wrapped as detectors of the same interface. Operators register their own, and a coverage map reports which ontology techniques the deployed set actually covers.

L_p: instruction provenance (<1 ms). This layer asks a different question: not what the call contains but *which turn authorised it*. The Gateway keeps a per-session *context ledger*—a bounded record (64 events, 256 KB) of every span that entered the agent's context, tagged `user`, `untrusted` or `model`—populated by the SDK's request-side hook. Four grounded features are computed from the ledger and the call: `user_licence` and `untrusted_licence`, the fraction of the call's vocabulary (tool name split on case, argument keys, argument values) that each channel accounts for; `authority_margin`, their difference; and `tool_named_in_untrusted`, how much more untrusted text than the principal names the tool being called. A fifth fact, `untrusted_only_values`, lists the call's argument values that appear in untrusted text and nowhere in the user's turns; the pack's destination rules match on it. The licence measure is asymmetric by design—it scores how much of the *call* a channel explains, not how similar two texts are—which is what makes the obvious evasion (copying the user's request into the injection) inert (§4). The result is a verdict in {`user`, `untrusted`, `unclear`, `unknown`} (Figure 3). `unknown` is reported, never inferred: a session with no reported user turn yields it, and every provenance rule in the shipped policy pack requires a decided verdict, so an un-instrumented deployment sees no behaviour change rather than a wall of false blocks. Ledgers are namespaced by tenant; without that, an attacker who guessed a session id could write a `user` event into another tenant's session and launder an injected instruction into an authority.

L3: alignment auditor (1–2 s). A frontier model receives the tool name, arguments and the user's stated task and returns whether the call serves that task, with a rationale. In the shipping gateway this is not an inline stage of the check: the SDK may call the auditor (`/api/v1/alignment/check`) before the check and attach its verdict, which the policy can match on (`alignment.score`); and a trace judge scores recorded traces after the fact. The judge of §4 is the evaluation harness's own, run as a detector over the corpus; it makes the same comparison, and it is the only configuration meaningfully above chance on real injected calls before L_p existed. Its cost is roughly 1600× the rules path.

Policy. The layers emit facts; a declarative policy turns facts into a decision. Policies are written in a small DSL over dotted field paths— `tool.name`, `classifier.category`, `anomaly.score`, `alignment.score`, `provenance.authorised_by`—with `all`, `any` and `not` composition, and comparators including regular expressions. The DSL is *fail-safe*: a rule can tighten a decision (allow →




Figure 3: Instruction provenance on a record from the corpus of §4. *Left:* the per-session context ledger, every span tagged by the channel it arrived through. *Centre:* the call the agent emitted and its vocabulary, each token coloured by the channel that explains it—nothing the user said is in this call. *Right:* the four grounded features and the verdict. *Bottom:* why the measure is asymmetric: echoing the user's request inside the injection changes nothing, because the licence scores how much of the *call* a channel explains; only carrying the user's words into the call's arguments raises the price (§4.5).

pending → block) and can never relax a block imposed by schema validation or anomaly detection to allow. Rules are compiled once per tenant and evaluated by one bounded pass over the tenant's rules per call. Eight packs ship ready-made—GLBA, PCI DSS, SOX, DORA, HIPAA, FedRAMP, a fintech agent-payments pack, and the instruction-provenance pack of §4—each carrying a citation to the clause it addresses so an auditor can cross-check. A natural-language compiler drafts DSL from prose for operators who do not want to write it by hand; the compiled rule, not the prose, is what runs.

Decision. The call resolves to one of three outcomes, each with a distinct return path. `allow`: the tool runs and its result returns normally, together with a *receipt*—the check id, agent, tool and a hash of the arguments, signed with the gateway's Ed25519 key—so an executor or a downstream service can verify offline that this gateway allowed this call with these arguments, rather than take the agent's word for it; an agent that skipped the check, or changed an argument after it, holds no valid receipt (`GET /api/v1/check/receipt-key`, `agentguard.receipts.verify_receipt`). `block`: the tool never runs, and a structured refusal is returned *in the slot a tool result would have occupied*—which is why a blocked agent explains itself and continues the conversation rather than failing (Figure 10). `pending`: the turn suspends until a person decides. Figure 4 draws the pipeline as a whole, and Figure 5 the two mechanisms that reach past the call itself: the receipt an allowed call carries, and the pin on the description that induced it.

Table 1: The fifteen content features used as the *content* block in §4.5. They describe the call string only; on agent-emitted attacks none exceeds AUC 0.585.

#	Feature	Description
1	arg_count	Number of top-level arguments
2	total_arg_chars	Total character count
3	max_string_depth	Deepest nesting level
4	url_count	URLs in arguments
5	ip_literal_count	Raw IP addresses
6	digit_ratio	Fraction of digit characters
7	uppercase_ratio	Fraction of uppercase chars
8	punct_ratio	Fraction of punctuation
9	json_depth	JSON nesting depth
10	has_path_sep	Contains / or \
11	has_curly_braces	Contains { or }
12	shannon_entropy	Bits per character
13	longest_run	Longest repeated character run
14	base64_like	Base64 heuristic score [0,1]
15	hex_like	Hex string heuristic [0,1]




Figure 4: The decision pipeline. A call is attributed before it is read; each later layer sees more of the world than the one before it, from the call string to the agent's history to the conversation split by channel; layers emit facts, and one policy turns them into a decision that rules may tighten but never relax. The alignment auditor sits off the check path: the SDK calls it first and its score arrives as a fact. Inset: the egress proxy runs a detector chain into the same policy and turns a hold into a block.




Figure 5: Two things a check on the call cannot see. Top: an allowed call carries a receipt that binds the gateway's decision to this agent, tool and argument hash, so an executor refuses a call that skipped the check or changed an argument after it. Bottom: the MCP proxy pins each tool's description and schema; a description that changes after approval, or reads like an instruction to the model, is refused until an operator re-pins it (OWASP MCP03). Example descriptions are illustrative.

2.4 Human-in-the-Loop, Containment, and Learning

A `pending` decision places the call, its arguments, every layer's facts and the matched rule in an approval queue; the agent polls and resumes within one cycle (2 s in Python, 1 s in the JavaScript and Go SDKs) of a person choosing Allow or Block. A hold that nobody decides expires at the gateway after ten minutes as a block; the SDKs stop waiting sooner, after five minutes by default (`human_approval_tim` and treat that as a block too. A deployment can put the alignment auditor in front of the person (`AEGIS_HOLD_REVIEWER=auditor`, §2.9): it releases a hold it finds serves the user's request, the release carries a receipt naming it, and the person sees only the holds it would not release, with its verdict attached. Two controls contain an *agent* rather than a call, and one holds back a call already allowed. A *kill switch* suspends an agent, by an operator's hand or after a configured number of refusals in a window (3 per hour by default; counted on the WebSocket MCP path always and on `/check` when `KILL_SWITCH_AUTO` is set, since at that rate it would also stop an agent that is merely under attack), and every path

Table 2: L1 risk patterns as shipped (28 entries, 11 risk types). PII (ten types, eleven patterns) is detected separately, in traces and by the proxy's detector chain.

Risk type	#	Techniques covered
SQL injection	7	OR/UNION, blind (pg_sleep, WAITFOR, BENCHMARK, SLEEP), hex, CONCAT, stacked
Path traversal	4	../, URL-encoded, double-encoded, null byte
Shell injection	4	Metachar, curl/wget+URL, ${IFS} splitting, process subst.
Sensitive files	1	16 paths: passwd, shadow, .ssh, .aws, .kube, .env, .npmrc, …
Prompt injection	1	17 sub-patterns: ignore/forget/ jailbreak/DAN/bypass/roleplay
Data exfiltration	2	Large payload; payload + external URL
Plaintext URL	1	Unencrypted endpoint in arguments
Supply chain	8	Source-map leak (3), unsafe publish (3), secret in build (2)

then refuses the agent's calls. A *budget guard* bounds spend per day, month, agent and session in dollars, with a configured action of `log`, `warn` or `block`; in this version it runs on the egress-proxy path only. For actions that cannot be undone—sending mail, moving money, posting publicly—a tenant can route a tool through an *effect outbox*: an allowed call to it is not run by the agent but queued by the gateway, which dispatches it to the operator's endpoint after a configured delay, and until then an operator can cancel it with no side effect (`POST /api/v1/outbox/cancel`). The agent is told the call was queued, in the slot a result would occupy; the answer is shaped so that no SDK, of any version or threshold, runs the call itself, since the side effect would then happen twice. A held call that a person later allows goes the same way.

Learning without a labelled corpus. The behavioural layer (L2) is the part of the system that learns, and it is built so that learning cannot make a young deployment *more* dangerous. Each agent's profile passes through three cold-start phases. While *learning*, the layer only observes. While *graduated*, its decision is capped at `flag`: a profile that has seen too few calls to know what normal is cannot escalate or block. Only an *active* profile may. Before the Isolation Forest has thirty samples it is replaced by a weighted fallback over nine fixed signals, and when an agent is first scored with too little history of its own, its feature statistics are seeded from its tenant's aggregate baseline. The decision thresholds the ensemble score against adaptive bounds (the agent's running mean plus a multiple of its deviation, or fixed defaults before there is one); a split-conformal p-value is computed and reported beside it, not used to decide. ADWIN detects distribution drift and resets the feature-normalisation statistics, keeping the forest's reservoir. An approve or reject a person makes on a held call that L2 scored above 0.3 flows back into the reservoir and the score tracker (active anomaly discovery), so the layer moves toward the operator's notion of normal.

Across agents. Two detectors on the egress-proxy path look across agents: a cross-agent correlator flags an agent sharing a session with one that has already raised a critical signal, and a lateral-movement detector flags a credential or token from one agent's traffic replayed in another's arguments. (A detector for one agent reading what another just wrote to a shared sink is implemented but not registered in this version.) Each agent's profile, anomaly timeline and the operator's feedback on past alerts are visible in the Cockpit (Appendix D).

2.5 Audit and Integrity

Agents carry an identity card—an EdDSA-signed JWT minted by the gateway and bound to the agent's registry status—which the proxy path verifies. Every decision, with the facts that produced it, becomes a trace: the SDK carries the gateway's verdict into the trace record it writes for the call (`safety_validation`, `approval_status` and for an allow its check id and receipt), so a blocked call, a held call and the person's answer to it sit in the same chain as the calls that ran, and the gateway records the same decision in its violations table. Traces are linked into a SHA-256 hash chain in which each record commits to its predecessor and to its content (input, reasoning, call, result); editing that content, or inserting or deleting a record inside the chain, breaks verification for every record after it. Two limits: the decision fields are outside the hash, so it is the receipt, signed with the gateway's Ed25519 key [2], that makes an allow verifiable, and a block or hold is not signed; and per-trace signatures with a per-agent key exist in the SDK but are off in `auto()`. The chain belongs to the agent, not to a process: before its first trace, an SDK asks the gateway where the agent's chain ends and continues from there, so a restarted agent extends one chain rather than starting a second (a defect the compatibility matrix exposed, since every row there runs in a fresh process). The gateway's own record—admin actions, evidence packs, rollbacks, outbox releases, pre-deployment scans—is appended to a Merkle transparency log with signed roots, which registered external *witnesses* can countersign, so an operator cannot quietly rewrite that history even with the gateway's key; an offline verifier checks inclusion, consistency and the witnesses' signatures. Every ten minutes by default the gateway also appends each agent's newest trace-chain head (sequence and hash) to that log, and verification (`/api/v1/integrity/verify`, `agentguard verify`) compares each chain with the heads the log committed to, reading the expected hash from the log entry itself. A chain rewritten wholesale, which still links, or cut short at the head, which leaves nothing to break, then fails; records removed from the old end by retention do not. The demonstration invites attendees to edit one stored record and watch verification fail (Figure 6). Compliance evidence packs assemble traces, policies and verification results into the artefacts an audit expects (SOC 2 control evidence, EU AI Act Article 12 record-keeping). Retention is a policy too: per-tenant, per-resource retention periods (traces, violations, anomaly events, judge verdicts, admin audit log) are purged on a schedule, each tenant's policy touching only its own rows, so a deployment can satisfy a deletion obligation without an operator deleting rows by hand—and a purge that removes the oldest records leaves the chain verifiable from the first retained one.




Figure 6: Each trace commits to its own content and to its predecessor's hash. Editing one field of record t fails verification for t and everything after it; attendees are invited to do exactly this to a stored record.

2.6 Recovery

Not every harmful call is caught before it runs. For tools that register a compensating action, Aegis records enough to undo: for tools a tenant configures, the pre-state captured at `/check`, before the agent is told to proceed (the call's arguments, or what the operator's snapshot endpoint returns); a saga of applied steps; and a causal rollback that reverts a call together with the calls that depended on its output. Each tool is classed as reversible, compensable or irreversible, and rollback uses the class to say what it can and cannot undo. (The policy DSL does not see the class; the provenance pack's destructive-action rule matches tool names instead.)

2.7 Failure Modes and Fallback

A control point on the hot path has to say what happens when it is slow, down, or unable to decide. Aegis's answers are explicit and configured, not emergent. Figure 7 summarises the four cases below.

When the gateway is unreachable. The SDK's blocking check carries a 3 s timeout. What happens on timeout is a single switch, `fail_open`: open means the call proceeds, and its trace carries no gateway verdict; closed means it is refused with `gateway-unreachable` as the reason. The shipped default is open, because an SDK that silently stops an agent when a sidecar restarts is the first thing an operator removes; the compatibility runs in Appendix B set it closed, which is what we recommend once a deployment is past evaluation. Traces are never lost to an outage: the transport retries with exponential backoff (0.5 s base, 30 s cap), a circuit breaker opens after five consecutive failures so that sends fail fast instead of stalling the agent, and while it is open traces go to a local disk queue that is replayed on the next start. The in-memory queue is bounded (10,000 traces); past it, traces spill to the same disk queue (or are dropped, if the local fallback is off), so a long outage costs disk, not memory.

When a person does not answer. A held call expires at the gateway after ten minutes as a block, and the agent receives that block in the same slot an approval would have arrived in; with the SDKs' defaults the agent stops waiting at five minutes and reports a block itself. On the egress-proxy path, which cannot hold an inline HTTP response, a `pending` decision is applied as a block and the audit record is tagged so the operator sees why.

When a compensator fails. Recovery (§2.6) depends on compensating actions that are themselves calls to the operator's systems. A compensator that fails despite retries lands in a dead-letter queue the operator can inspect, retry or discard through the gateway's API (`/api/v1/rollback/dlq`; the Cockpit has no view of it yet), so a failed undo is a recorded item, not a silent inconsistency.

When there is no model. Three features call a language model: the natural-language policy compiler, the alignment auditor and the trace judge (§2.9). The compiler and the auditor select a client by a fixed priority—a local OpenAI-compatible endpoint (vLLM, Ollama, LocalAI) if one is configured, then Anthropic, then OpenAI—and a single switch, `AEGIS_OFFLINE`, severs their cloud calls without touching the keys. Two paths do not yet honour it: the trace judge, which takes its provider and key per request, and the Cockpit's own natural-language policy page, which calls a cloud API directly; an air-gapped deployment leaves both unconfigured. With no model at all the policy compiler falls back to a heuristic backend, and the decision pipeline itself never needed one: L1, L2, L_p and the policy DSL run without a model call.

2.8 Static Analysis Before Deployment

Runtime mediation decides calls as they happen; a static scan decides what an agent *could* do before it runs, and the two share a policy vocabulary. The pre-deployment scanner parses an agent's repository with an AST and taint-tracking scanner (we integrate agent-audit rather than maintain a second regex scanner), enumerates every model call, tool definition and MCP server configuration, and applies agent-audit's rules (the version the gateway recommends is pinned in `predeploy-scan.ts`), mapped to the OWASP Agentic Top 10, so a finding carries the same category an auditor will ask about. Scans are kept as history, and a scan-to-scan diff partitions findings into *added*, *fixed* and *persisting*, which is the form in which a reviewer wants to see a pull request: not "this agent has twelve findings" but "this change introduced one". A code shield applies a small set of high-precision rules to code an agent is about to commit, execute or hand back, in the spirit of LlamaFirewall's CodeShield but kept deliberately narrow; and the runtime's L1 patterns include a supply-chain family (source-map leak, unsafe publish, secret in a build artefact) that fires on the publish and build tool calls an agent makes, so the static and dynamic views meet at the same boundary.

2.9 LLM as Judge: Where It Sits, and How It Is Calibrated

A language model is the only component that can read a call against the user's stated task and say whether the one serves the other. Aegis uses one in two places, deliberately neither of them inline on the check path (§2.3). The *alignment auditor* receives the declared goal and the proposed call and returns a score, a drift flag against a configured threshold, the signals it relied on and a rationale; the SDK can call it before the check and attach the verdict, which the policy DSL matches like any other fact (`alignment.score`), so the operator decides what a low score *does*. The *trace judge* scores recorded traces after the fact on eight dimensions—safety, helpfulness, correctness, compliance, efficiency, privacy, robustness, transparency—and feeds the Cockpit's evaluation views.

The auditor reads what the agent read. A held call is usually held because its arguments came from a tool, and a judge shown only the goal and the call cannot tell a bill's IBAN from an attacker's: in the first AgentDojo runs the auditor refused legitimate calls "without evidence of having reviewed the file" and approved a transfer of the whole balance to an "unfamiliar recipient account". Given a `session_id`, the gateway now adds that session's recent tool output from the context ledger (§2.3), scoped to the caller's tenant and fenced as data, with one instruction: an action that carries out an instruction found only inside the data, and not asked for by the goal, has drifted. Showing a judge the injected text is itself a risk—the judge can be injected too—which is why the change is reported with its attack success, not only its utility (§4.1). The Python and




Figure 7: Four failure modes and the configured answer to each: what the agent sees, and what the operator sees. Every branch is a switch an operator sets; the decision pipeline (L1, L2, L_p, policy) needs no model in any of them.



Figure 8: The alignment auditor. Left: a held call is reviewed against the user's declared goal and the session's tool output, fenced as data and scoped to the tenant (the request and call are those of Appendix card G1); the auditor releases the call or passes it to a person. Right: the calibration harness's reliability diagram for a Claude Haiku 4.5 judge on the built-in 30-case benchmark, with per-category ECE. Its confidence is not a probability, which is why its score is a fact the policy thresholds rather than a decision.

JavaScript helpers forward the session the SDK already reports context under.

Calibration is reported, not assumed. A judge that says "block, confidence 0.9" is only useful if 0.9 means something. The gateway ships a calibration harness that runs a judge over a benchmark, records decision, confidence and latency per case, and reports expected calibration error with reliability bins, following the binning estimator of Guo et al. [14] as used in the guard-model literature [25], overall and per category. The built-in benchmark is small and deliberately mixed: 30 cases—10 normal, 5 clear blocks, 5 jailbreaks, 3 indirect injections, 2 PII egress, 5 borderline—so that a judge's calibration on the easy cases does not hide its behaviour on the hard ones. Run with Claude Haiku 4.5 as the judge, it is confident and often wrong: accuracy 63.3% at a mean confidence of 92.5%, an expected calibration error of 29.2% (Figure 8, right). Judge adapters for Anthropic and OpenAI ship with retry; a mock judge

Table 3: Where Aegis attaches. Inbound connectors deliver tool calls to the decision point; outbound connectors deliver decisions and evidence to the operator's systems. Every row has tests in the gateway's or its SDK's suite; the inbound rows are also exercised live in Appendix B.

Inbound	
Python SDK	`auto()` patches 15 targets: Anthropic, OpenAI (chat and Responses), LangChain/LangGraph, CrewAI, AutoGen, Gemini, Bedrock, Mistral, LiteLLM, LlamaIndex, Pydantic AI, smolagents, OpenAI Agents SDK (tool-level), Google GenAI, HTTP-tool shim; the Claude Agent SDK by its own `PreToolUse` hook
JS/TS SDK	Anthropic, OpenAI, LangChain; CommonJS build patched
Go SDK	`Wrap(tool, args, fn)`: explicit check, hold, trace
MCP proxy	stdio proxy for any MCP server and client; refusals are tool errors; tool pinning
Egress proxy	provider-shaped endpoints for OpenAI, Anthropic, Gemini, Mistral; self-hosted upstreams (vLLM, Ollama) by one variable
Outbound	
SIEM sinks	declarative `http` / `syslog` / `stdout` sinks with field-mapping templates (Splunk HEC, Datadog, Sumo, QRadar, Graylog), bounded DLQ and retry
Alerts	webhooks, Slack, PagerDuty on block, pending, anomaly
Traces	OTLP export to any OpenTelemetry backend, GenAI semantic conventions
Evidence	signed compliance bundles mapping SOC 2, ISO 27001, NIST AI RMF and EU AI Act controls to live evidence; evidence packs for audits
Identity	
People	OIDC and SAML single sign-on, SCIM 2.0 provisioning, role-based access
Agents	registry with declared tool scope, status and budget; EdDSA-signed identity cards

runs the harness offline. The same mechanism is what §4 uses to report that the judge is the only content-side configuration above chance on agent-emitted attacks, at roughly 1600× the cost of the rules path—and what motivates L_p, which recovers the comparison the judge was making from the conversation's channel split in under a millisecond.

2.10 Connectors

Aegis is meant to sit inside an existing stack rather than replace one, so most of its surface is connectors (Table 3).

Two design rules hold across the table. First, a connector is configuration, not code: a tenant adds a Splunk sink or a PagerDuty destination by writing a config row, and the gateway picks it up on the next event without a release. Second, nothing outbound is on the decision path: sinks, alerts and exports are fire-and-forget




Figure 9: Compliance Cockpit overview on seven real AgentDojo runs replayed through the SDK and gateway (Appendix D): calls, holds awaiting a person, blocks, chain integrity, and the activity feed in plain language.

with their own queues and dead-letter handling, so a slow SIEM cannot slow an agent. The gateway runs as one Node.js service with SQLite behind it (PostgreSQL stores are implemented but not yet wired into the server), and ships with Docker Compose, a Helm chart and one-click configurations for the common hosts.

2.11 Compliance Cockpit

The Cockpit (Figure 9) is the operator's view of all of the above. Three views carry the design. *Activity* shows each agent run as a timeline titled by its request, every step a sentence with the app's or website's logo and AEGIS's decision. *Approvals* shows a held call with its evidence—what the person asked, the passage the agent read with the attributed value highlighted, the arguments as fields—because a reviewer shown an agent id and a JSON blob approves by default. *Security 360* lists ten agent attack surfaces, whether this deployment covers each—six read from the live gateway, four fixed by what the gateway always or never does—and the step that covers the rest. Around them sit per-agent profiles, policy authoring in the DSL or natural language, rollback history, scan results, and the exportable audit log with its verification status. It runs locally beside the gateway. Its only outside requests are for app logos (a favicon service, which learns the hosts an agent touched) and, when a licence key is entered, a licence check; `NEXT_PUBLIC_AEGIS_OFFLINE=1` keeps logos local, and the Cockpit then makes none.

3 WALKTHROUGH ON A LIVE AGENT

The demonstration runs entirely on a laptop. Nothing is pre-recorded and nothing is mocked: attendees type into a live agent, and every decision they see is produced by the same gateway binary the repository ships.

Setup. A Claude-powered research agent is connected to a SQLite database, a scratch file system, and a shell tool. Aegis is enabled by adding two lines to the agent:

```
agentguard.auto(blocking_mode=True, enforce_at="tool")
    execute_tool = agentguard.guarded(execute_tool)
```

(`auto()` without the flag observes and audits but never blocks; the flag is the firewall. The demo's own call also sets `fail_open=False`,

a 300 s approval timeout and a 2 s poll interval; the SDK's default is fail-open, §2.7.) The first line patches the model client, so every tool call the model emits is traced; the second wraps the agent's own tool dispatcher, so the decision is taken there and a refusal is returned as the tool's result. An agent built on a framework with a tool-execution hook needs only the first line (the SDK patches the framework's dispatch entry point); this demo agent is a plain Anthropic loop, and so uses both. Beyond those lines the demo agent does three things for the demonstration's sake, all in `demo/live-agent/app.py`: it installs the DSL rule that holds S3, imports the SDK's exception type to print a block, and names AEGIS in its page header. Its tools and the model's prompts are not changed by the integration.

3.1 Three scenarios

S1 — A benign call, and what mediation costs. An attendee asks the agent to summarise the feedback in the reviews table (the scripted prompts name the tool, so that every run emits a call). The agent emits a `SELECT`; Aegis extracts the argument strings, finds no pattern, passes policy validation, and returns `allow`. The gateway decides in about 2 ms; the Cockpit's live feed shows the call, at 7 ms for the step end to end.

The point of running this first is calibration. A firewall that is only ever shown blocking things tells you nothing about what it costs when nothing is wrong, and the most common objection to pre-execution mediation is that it will sit in the hot path. Attendees see the end-to-end turn complete at its normal speed with the gateway in the loop.

S2 — Interception, and what the agent does next. An attendee asks the agent to "install the monitoring agent the usual way" and gives it the usual way: `curl -s https://…/install.sh | sh`. The agent does as asked and emits `run_shell(command="curl -s …| sh")`. Aegis blocks it at L1—the shell-metacharacter pattern, which fires on the pipe—in a few milliseconds. The same payload is the S2 of the compatibility matrix (Appendix B), where it is blocked in all 18 harnesses that emitted it (Gemini's provider returned 503 and no call was made); the earlier version's `DROP TABLE` payload is one that current Claude models decline to emit on their own, which is a defence layer of its own but not the one being demonstrated, and the appendix records that choice.

What we most want attendees to look at is not the block but Figure 10(b): the agent receives a structured refusal, and continues the conversation—telling the user what was blocked and why (a pipe into a shell interpreter), and offering alternatives (download the script and run it as a separate step, ask the operations team, or use a package manager). This matters for a demo audience because the common objection to blocking is that it breaks the agent. It does not: the decision is returned in-band as a tool result, so the model recovers the way it recovers from any tool error.

S3 — Human-in-the-loop, live. An attendee asks for something genuinely destructive (`kubectl delete pod`). The call matches the DSL rule `hold-kubectl-delete` (`then: decision pending`), so Aegis returns `pending` and the agent *suspends*—the turn does not complete, and the attendee can see the agent waiting.

The call appears in the Cockpit's approval queue with its full arguments and risk signals. A second attendee, at a second laptop, clicks Allow or Block. The first attendee's agent resumes within one or two polling cycles of 2 s (4.0 s from hold to resume in the recorded runs). Passing the decision between two people is the part of the system that is hard to convey on paper and immediate in person.

3.2 What attendees can do themselves

The session is adversarial by design. Attendees are invited to:

(1) **Try to get a payload past L1.** Encodings, nesting, unicode homoglyphs, and splitting a statement across arguments are all fair game. Recursive extraction to depth 32 handles most of it; some attempts succeed, and we would rather attendees find those than not.
(2) **Try to make the agent emit an attack that L1 cannot see.** This is the case §4 shows is the hard one, and the demo does not hide it: an indirect injection that causes an ordinary-looking call passes L1 and L2; with L_p toggled off it is allowed, and with it on the attendee watches provenance catch what content inspection could not. This is the S4 column of the compatibility matrix (Appendix B): a file the agent is asked to summarise tells it to forward its contents, and the `send_email` it emits is blocked by the provenance pack in six of the matrix's harnesses. The demonstration agent has no e-mail tool, so this item is shown from the matrix's recorded runs.
(3) **Verify the audit trail.** Each trace is hash-chained to the one before it and chain heads are anchored in the signed Merkle log (per-trace Ed25519 signatures exist but are off in `auto()`); the Cockpit exports a PDF/CSV report, and `agentguard verify` has the gateway recompute the chain. Attendees are encouraged to edit a stored record's content and watch verification fail.
(4) **Install it.** The two-line integration runs against an attendee's own agent on their own laptop, with the gateway and Cockpit local; only the agent's own model calls leave the machine.

3.3 Practical requirements

One laptop suffices; two make S3 better. The gateway is a single Node.js service, the Cockpit a Next.js app, and both run locally with no GPU. The demonstration agent calls Claude and so needs the network; the gateway's own model features (the auditor, the policy compiler) can run on a local model (§2.7), and the recorded runs of Figure 10 stand in if the network fails.

3.4 Compatibility: One Gateway, Nineteen Ways In

A demonstration that only works with the demonstrator's agent proves little, so the same scenarios—the benign query of S1, a call the agent is talked into that L1 catches, a destructive call a policy holds for a second person, and, on every path that reports context, an indirect injection through a tool return that only the provenance layer can see (S4)—are run against nineteen harnesses: plain SDK loops in three languages, six open-source frameworks, three closed harnesses (the OpenAI Agents SDK on both of its APIs, the Claude Agent SDK running the Claude Code runtime, Google's GenAI SDK), an RL-trained open-weight model served locally, and the two non-SDK transports (the MCP proxy and the egress proxy,




Figure 10: The three demonstration scenarios. The S2 and S3 panels are unretouched crops of real sessions of the demonstration agent and the shipping Cockpit (S2 from the 2026-10-12 session, S3 from 10-18); S1's figure is the gateway's recorded decision time, drawn rather than cropped. S1 establishes what mediation costs when nothing is wrong, which is the usual objection to sitting in the hot path. S2 is the one to watch and is given the space accordingly: asked for a routine install, the agent emits a remote script piped to a shell, the call is blocked at L1, and because the refusal returns in-band as a tool result the agent explains what happened and offers alternatives rather than failing. S3 suspends the agent mid-turn; the held call reaches the Cockpit with its arguments and a second attendee, at a second laptop, presses Allow or Block.

the latter against both OpenAI and a self-hosted model). Every row uses the integration the paper describes and nothing else; the gateway is the shipping build; the language-model calls are real. Appendix B gives the matrix (Table 14) and the harness code is in the repository.

The exercise was worth more than the table. Running it found, and the current version fixes, twenty-four defects that no unit test had caught; all are listed here: every SDK started a new hash chain at sequence zero in every process, so an agent restarted once failed chain verification (the Cockpit's chain counter, screenshotted against the matrix, showed it); the violations table carried foreign keys that no pre-execution decision can satisfy, so every `/check` block and hold was silently dropped from the Cockpit's counts; the Go SDK's traces were in a shape the gateway would have rejected, and never reached it anyway because the process exited before the final flush; the MCP proxy's own trace record had the same shape problem, so the transport that needs no SDK left no audit record; the Python SDK replaced any human-readable agent id with a random UUID, so policies and approvals keyed to the agent's name never matched; its OpenAI patch crashed on streaming responses and did not see the Responses API or the current Google GenAI client at all; the Pydantic AI patch sat at the wrong layer and scanned the user's prompt instead of the tool call; the LangGraph patch passed the ToolCall envelope as the arguments, so policies matching on an argument never fired; the CrewAI and AutoGen patches sat on methods their current versions override or never call, so neither framework was guarded at the tool; the Go SDK read a field the gateway does not send and blocked every call; the JavaScript SDK treated a held call as a block instead of waiting; the MCP proxy re-advertised output schemas it could not satisfy, so strict clients rejected every result; the L1 shell-metacharacter rule fired on the semicolon of an ordinary SQL statement; a free-tier agent cap silently switched new agents to audit-only; and blocking mode held failed validations for a person rather than blocking them. The S4 scenario, added in this version, found the next two: the SDK's request-side context hook—the code that classifies each span of the messages array and reports it to the gateway's ledger, on which the whole provenance layer depends—was implemented and unit-tested and never called by `auto()`, so every ledger stayed empty and no provenance rule had ever fired outside its own tests; and L1's shell-metacharacter rule was applied to every string argument of every tool, so the semicolon in an injected email body was blocked as shell injection before the provenance layer was asked, and the cell would have credited the wrong layer. The twenty-second is the most instructive, because the matrix itself had reported it as a pass. The Python SDK applies a `block_threshold` (default `HIGH`) to the gateway's risk tier before it reads the decision, so a policy hold on a `LOW`-risk call was returned to the agent as `allow`: the tool ran at once, the agent never waited, and the approval queue filled with holds that nobody was waiting on. The S3 column had been scored from the approvals table, where the second attendee's decision was duly recorded three seconds later; it was the traces, which stayed at `PENDING_APPROVAL` because no agent ever resolved them, and the S3 wall-clock times, indistinguishable from S1's, that gave it away. The SDK now honours `pending` and any rule-produced `block` regardless of tier, the

matrix records how long each agent actually waited, and since this version the threshold's default enforces every block the gateway returns, as the evaluation's harness does and the JavaScript and Go SDKs always did. The twenty-third was the request-side hook missing from Anthropic's beta endpoint, which Pydantic AI uses (Appendix B). The twenty-fourth surfaced only at evaluation scale: a self-hosted gateway, with no Stripe and therefore every organisation on the hosted Free plan, refused every check past the plan's monthly quota (then 1,000); the matrix makes 98 checks over its 76 cells, AgentDojo about five thousand. Quotas now apply only where hosted billing is configured. Each is the kind of gap that appears only when a real framework drives the real gateway, which is the argument for keeping the matrix in the repository and running it on every release.

4 EVALUATION

We evaluate Aegis three ways, from the outside in. End to end (§4.1): on AgentDojo, does an agent behind the gateway still finish what its user asked, and does the attacker's goal still happen? In cost (§4.2): what does a check add, and how does the gateway hold up under concurrent agents? And per call (§4.3–§4.5): on tool calls live agents emitted under attack, which layer separates them and why. Every number is produced by a command in the repository (§6).

4.1 End to End: AgentDojo

Per-call numbers say whether a detector flags a call; a deployment is judged per task. AgentDojo v1.2.1 [11] measures exactly that, and is the benchmark CaMeL, Progent and LlamaFirewall report against: 97 user tasks in four environments (workspace, travel, banking, Slack), each run clean for *utility* and against each of the suite's injection tasks for *attack success*, 949 pairs in all, with the `important_instructions` attack. The agent is gpt-4o-mini-2024-07-18 in the main run. Aegis is placed where a deployment puts it: AgentDojo's tool executor is replaced by one that, before every tool runs, reports the conversation's new spans to the ledger exactly as the SDK's request-side hook classifies them, asks the shipping gateway's `/check`, and on a refusal returns the reason in the tool-result slot so the agent continues (`research/agentdojo/run_agentdojo.py`; one fresh gateway per configuration). AgentDojo's own defenses—spotlighting [17], prompt repetition and an LLM tool filter [11]—are run alongside for reference. Table 4 gives the results.

Security. Undefended, the attack succeeds on 29.7% of pairs. Aegis with the instruction-provenance pack brings that to **1.4%**, the lowest of any configuration and a quarter of the tool filter's 5.4%, at a check cost under a millisecond and no model call. The rules alone halve attack success (16.0–17.0%), not because they recognise the injections—they contain no payload—but because the default policy holds every outbound message for a person and, with nobody to answer, a hold is a refusal. On the 829 pairs every configuration completed, the numbers are 30.0%, 5.4% and 1.4%. One injection task inflates every interposition defense's count: AgentDojo judges Slack `injection_task_5` on the calls the agent *emitted*, not on what they did, so an invite the gateway refused still scores as a successful attack. Counting only calls that ran (`rescore_executed.py`; column *Executed*), Aegis with the pack is at 0.9% (8 of 843) and the rules alone at 15.3–16.4%; the undefended agent and AgentDojo's own defenses, which do not refuse calls, are unchanged. We report AgentDojo's score as the headline, since it is what other systems report.

Utility, and where it goes. The price is paid in holds. With no reviewer present, every hold refuses a call, and Aegis with the pack completes 38.1% of clean tasks against 69.1% undefended. That number measures the absence of the person a hold is for, so the table also counts the tasks that needed one: 34 of 97. Two changes, both on the same principle, came out of this run. The first version held any tool the classifier filed as communication, so `search_emails` was held like `send_email`, and the pack's review rule held every call whose arguments came from an earlier tool result, which is what reading a hotel's reviews before booking it looks like: 671 holds on 97 clean tasks, 62 tasks needing a person, 33.0% utility. A hold is for a call that *acts*; reading changes nothing, and what an injection can do with a read needs a later call that writes, sends or pays, which is still held. The gateway now derives a `tool.read_only` fact from the name's own verbs—conservatively: a name with any write verb, an unknown verb, or a network read is not read-only—and both the default communication hold and the pack's two review rules apply only to calls that are not read-only. Tasks needing a person fall from 62 to 34 and utility rises from 33.0% to 38.1%, at an unchanged 1.4% attack success. Because the revision was motivated by this benchmark, the first version stays in the table, and the revision is checked on the independent corpus of §4.3: there it costs per-call recall (95.4% to 75.5%, the data-stealing reads it now allows) and barely moves two-step false positives (23.7% to 20.7%), which is the honest shape of the trade.

With the auditor as first reviewer. A deployment does not leave holds unanswered, and the design's own answer is the alignment auditor (§2.9): in the last row each hold goes to the gateway's `/alignment/check` with the user's request as the declared goal, and is released if the auditor finds the call serves it (not drifted, score ≥ 0.5). The harness made that call itself; the gateway now does the same on its own when a deployment sets `AEGIS_HOLD_REVIEWER=audito` taking the request, the agent's recent reasoning and the tool output it read from the session's ledger, with the same release rule. Clean utility returns to **56.7%**, inside the tool filter's interval, and only 11 of 97 tasks still reach a person. Its attack run did not complete—the OpenAI account ran out of credit before it started producing results—so with this agent, whether the auditor releases attack calls the pack held is not measured; the second model below measures it. What the table does establish is the split of labour: L_p decides in under a millisecond which calls need a second look, and only those pay for one.

A second agent model, served locally. To measure what the credit stopped, and to leave the hosted-model family, we reran the banking and Slack suites (37 user tasks, 249 attack pairs) with qwen3:8b served by Ollama, reasoning off, as both the agent and the auditor (Table 5). Undefended, 47 of 249 attacks succeed. With holds going to the auditor first, *none* do—but clean utility falls from 19 of 37 to 9, and the rows below that one are what we changed to get it back, each motivated by what the run before it showed, and each reported.

Table 4: AgentDojo v1.2.1 end to end (four suites; 97 user tasks; 949 user×injection pairs with the `important_instructions` attack), agent gpt-4o-mini-2024-07-18. Percentages with 95% Wilson intervals. In the Aegis rows a hold has no reviewer, so it is a refusal; *needs a person* counts the clean tasks, of 97, in which at least one call was held, the utility a deployment buys back by answering holds. In the last row each hold goes first to the gateway's alignment auditor with the user's request as the goal; *needs a person* then counts the tasks where the auditor refused. v1 is the gateway as first submitted; the unmarked rows apply holds only to calls that act (§4.1). *Pairs* is the number of the 949 attack pairs that completed: the OpenAI account ran out of credit near the end of the run; on the 829 pairs every configuration completed the ordering is unchanged (`results/matched_pairs.json`). *Executed* rescores the one injection task AgentDojo judges on the calls the agent *emitted* rather than on their effect (Slack `injection_task_5`), counting only calls that ran; for an undefended agent the two coincide.

Configuration	Utility (%)	Util. under attack (%)	Attack success (%) ↓	Executed	Pairs	Needs a person
No defense	69.1 [59,77]	38.8 [36,42]	29.7 [27,33]	29.7	949	—
Spotlighting (delimiters)	68.0 [58,76]	43.8 [41,47]	25.2 [23,28]	25.2	949	—
Repeat user prompt	66.0 [56,75]	50.1 [47,53]	10.6 [9,13]	10.6	907	—
Tool filter (LLM)	63.9 [54,73]	59.6 [56,63]	5.4 [4,7]	5.4	949	—
Aegis rules, v1	48.5 [39,58]	36.1 [33,39]	16.0 [14,18]	15.3	949	29/97
Aegis + L_p, v1	33.0 [24,43]	27.2 [24,30]	**1.4** [1,2]	1.1	949	62/97
Aegis rules	53.6 [44,63]	45.0 [42,48]	17.0 [15,20]	16.4	907	21/97
Aegis + L_p	38.1 [29,48]	40.5 [37,44]	1.4 [1,2]	0.9	843	34/97
holds reviewed by L3	56.7 [47,66]	*not run: API credit*			—	11/97

Table 5: Second agent model: qwen3:8b served locally (Ollama, reasoning off), AgentDojo banking and Slack suites (37 user tasks, 249 attack pairs). The auditor is the same local model. This run used the gateway with the destination rule of §4.5; the gpt-4o-mini runs of Table 4 predate it. Aegis with holds refused was run for utility only. In the last row the operator has demoted the pack's two destination-sensitive block rules to holds through the DSL API, so those calls also go to the auditor; in the row after it the auditor is also shown the tool output the agent read; the last row is the shipped gateway with the fixes those runs exposed. *Exec.* counts attacks whose calls ran, as in Table 4.

Configuration	Utility (%)	Util. under attack (%)	Attack success (%)	Exec.
No defense	51.4 [36,67] (19/37)	40.6 [35,47] (101/249)	18.9 [15,24] (47/249)	47
Aegis + L_p, holds refused	21.6 [11,37] (8/37)	—	—	—
holds reviewed by L3	24.3 [13,40] (9/37)	22.5 [18,28] (56/249)	0.0 [0,2] (0/249)	0
+ destination rules demoted to holds	29.7 [17,46] (11/37)	25.3 [20,31] (63/249)	0.4 [0,2] (1/249)	1
+ auditor shown the tool output	45.9 [31,62] (17/37)	28.5 [23,34] (71/249)	2.4 [1,5] (6/249)	4
shipped gateway, all fixes of §4.1	35.1 [22,51] (13/37)	24.5 [20,30] (61/249)	1.6 [1,4] (4/249)	1
Held out — workspace and travel (60 user tasks, 700 attack pairs), changed nothing				
No defense	26.7 [17,39] (16/60)	25.4 [22,29] (178/700)	3.3 [2,5] (23/700)	23
shipped gateway	28.3 [19,41] (17/60)	26.4 [23,30] (185/700)	0.6 [0,1] (4/700)	4

The first loss was blocks. These suites' legitimate tasks take recipients and IBANs from tool output ("pay the bill in this file", "invite the people on this web page"), which is the destination rule's known false-positive class, and a block cannot be reviewed. Demoting the two destination rules to holds through the DSL, as an operator would, buys back two tasks and lets one attack through: a transfer of the whole balance that the auditor approved while noting an "unfamiliar recipient account". The second loss was the auditor itself, which refused legitimate calls "without evidence of having reviewed the file": it was never shown the file. Given the session's tool output (§2.9), it recovers utility to 17 of 37, within noise of undefended—and is itself injected in 4 of 249 pairs. Three gateway defects explained the rest and are fixed: a judge that names `prompt-injected` and still scores a call 0.8 now counts as drifted; a recipient swapped through a tool with no sink verb (`update_scheduled_transaction`) is now held; and a link the agent rewrote with `https://` is now matched to the page that gave it. The final row, the shipped gateway with the destination rules at `pending` and the auditor shown the evidence, completes 13 of 37 clean tasks and lets **1 of 249** attacks run: a phishing link the gateway held and the 8B auditor released, having noted that "the URL is part of the untrusted data". AgentDojo scores it 4 of 249; the other three are refused calls (§4.1).

Two cautions. Clean utility on 37 tasks moves by about three tasks between identical configurations: of the four tasks the final row lost against the evidence row, three hit no refusal at all. And every change in this paragraph was found on these two suites, so the workspace and travel suites, which none of them touched, are the held-out check (last rows of Table 5; 60 user tasks, 700 pairs). There the shipped gateway costs no utility—17 of 60 clean tasks against 16 undefended—and attacks fall from 23 of 700 to **4**. None of the four is a regression: two are travel's `injection_task_6`, which



Figure 11: Clean-task utility against executed attack success on AgentDojo, gpt-4o-mini (left) and qwen3:8b (right), with Wilson 95% intervals; up and to the left is better. Values are those of Tables 4 and 5. A hollow marker on the axis is a configuration whose attack run did not complete; held-out suites are drawn with a separate marker.

only makes the agent *say* that a hotel is worth visiting and issues no tool call for any gateway to see; two are the open class of §4.5, a deletion the user asked for whose target the injection swapped for a short file id with nothing to attribute it to. Figure 11 sets both agent models' configurations on the same two axes.

Against the systems that rebuild the agent. The closest systems report on the same benchmark with stronger agents, so their numbers are context, not a row of the table. Progent, with gpt-4o as the agent and as the policy generator, reports attack success falling from 39.9% to 1.0% [35]; CaMeL solves 77% of tasks with provable security against 84% undefended, and with Gemini 2.5 Pro brings successful attacks from 300 of 949 to none [10]. Aegis's 1.4% sits in the same range as Progent's without a model in the decision path, and CaMeL's guarantee is one no detector, ours included, can give. What Aegis trades for not rebuilding the agent is utility: CaMeL loses 7 points of task completion, Aegis 31 with no one answering its holds and 12 with the auditor answering them.

4.2 Overhead

Table 6 measures one gateway process under concurrent agents (`node research/perf/loadtest.mjs`). With one client a check takes 0.44 ms at the median and under 2 ms at p99, with or without the provenance pack; the pack's ledger assessment does not show at this resolution. Throughput saturates near 2,300–3,000 checks per second on one process, and beyond that latency is queueing: at 128 concurrent clients p99 is 84–93 ms. A Node.js gateway is one thread, so the scaling path is more processes behind sticky routing by session (the ledger is per process, §2.3), which this measurement does not cover. An agent's own model call takes seconds; at the loads measured, a check is a fraction of a percent of a turn. Figure 12 plots the same measurement.

Table 6: Gateway overhead under load: one gateway process, loopback, 20 s per level, 1,000 sessions with seeded ledgers, calls drawn from the instantiated corpus. Latency is `/check` as the client sees it. Zero errors at every level. Measured on a Apple M4 Pro laptop under other load (load average ≈16, 8.5 GB swap); maximum latencies of 1.7–3.1 s appeared in both configurations and even with one client, and are not attributed to the gateway here.

Config	Clients	Checks/s	p50	p95	p99 (ms)
Rules	1	1,454	0.44	1.09	1.89
	8	2,485	2.52	5.91	7.67
	32	3,045	9.67	18.31	21.21
	128	2,891	41.99	52.19	84.31
+ L_p pack	1	1,752	0.48	1.28	2.01
	8	2,213	2.78	6.76	12.16
	32	2,302	10.10	21.80	30.27
	128	2,588	45.53	66.65	93.35




Figure 12: One gateway process under load, with and without the provenance pack: checks per second (bars) and p50/p99 latency (lines) against concurrent clients. Same run as Table 6.

The first version's numbers are withdrawn. The 99.9% block rate at 0.09% false positives reported earlier came from a per-call benchmark whose malicious records encoded their own label in an argument key; Appendix C gives the audit. Every number below is measured on agents that were actually attacked.

4.3 Mechanism: Instantiation by Rollout

If the attacker's call only exists after an agent is compromised, the sound way to obtain one is to compromise an agent and record what it emits (Figure 13). For each InjecAgent case we reconstruct the agent's context—the user's instruction, the legitimate first tool call, and the tool response carrying the injection—and let a live model (Qwen3-VL-32B-Instruct, AWQ 4-bit, served over an OpenAI-compatible endpoint with prompt-rendered tool calling) choose its own next action. A rollout is *compromised* when the emitted call names a tool on that case's attacker list. Arguments are the model's own, so nothing in the record encodes the label.




Figure 13: How the corpus is built. An InjecAgent case supplies the context but no attacker call; four arms—attack, a length-matched control with the injection replaced by neutral prose, schema-synthesised benign requests with decoy tools, and a two-step benign arm whose calls also carry tool-derived arguments—are rolled out through the same live agent, and a record is labelled by whether the emitted call names a tool on the case's attacker list. Attack success is 95.07% against 0.285% in the control arm; the result is 663 agent-emitted calls on which no surface feature exceeds AUC 0.585.

Matched control. Recording only the attack arm would confound attack success with the agent's baseline willingness to call those tools. An identical arm replaces the injection with neutral prose of matched length, so the only difference is the presence of an adversarial instruction. Over $n = 2{,}108$ cases per arm, attack success is **95.07%** against **0.285%** (Wilson 95% CIs $[94.06, 95.91]$ and $[0.13, 0.62]$), a risk ratio of 334. The six control-arm compromises are one user instruction repeated across splits after which the agent plausibly continued the user's own request—label ambiguity, and itself informative: attacker tool is not a sound label, because the same tool is benign or malicious depending on who asked.

Benign coverage. Attacks alone do not make a benchmark. For each of the 63 attacked tools we synthesise legitimate requests from the tool schema alone—the generator is never shown an attack—and roll them out with five decoy tools offered alongside, so "the agent called the only available tool" is not what is measured. A further *two-step* benign arm has the agent make a lookup call, receive a clean tool response, and act on it, so that benign calls also carry tool-derived arguments. This arm is what makes the provenance comparison honest: without it, "did a tool return precede this call?" separates the classes for a construction reason.

Integrity. Table 7 reports the corpus before and after. Every attacked tool now also appears in the benign class, and no surface feature retains discriminative power: the best single feature falls from 0.947 to 0.585. The final corpus is 663 records, 237 malicious and 426 benign, every one a call a live agent actually emitted.

Table 7: Corpus integrity before and after instantiation. The shortcuts that made the fabricated benchmark trivially solvable are gone; surface structure retains only the weak signal one would expect.

	fabricated	instantiated
Best single surface feature	0.9467	**0.5849**
All 15 features, 5-fold CV	0.9963	**0.6310**
Unique malicious calls	165	237
Unique benign calls	21	426
Tools in only one class	—	0
Malicious tool coverage	—	100.0%
Argument key encodes label	100%	0

4.4 What Content Inspection Catches

Table 8 reports detectors on the rebuilt corpus, with balanced accuracy $\frac{1}{2}$(TPR + TNR) because the classes are unbalanced. Aegis-rules is the shipping gateway, run locally with a fresh database and no policy pack, not a reimplementation. The keyword blacklist is at chance, and so is L1: its 28 patterns fire on **two** of the 237 attack records—the same `TerminalExecute` command, caught by the shell-metacharacter rule—and on four benign ones (the `--` of a `git` and a `python` command line read as a SQL comment, two cryptocurrency addresses read as hex-encoded payload). Run family by family against the attacks: SQL injection 0.0%, path traversal 0.0%, sensitive-file access 0.0%, prompt injection 0.0%, shell injection 0.8%. The attacks contain no payload to match. `AmazonViewSavedPaymentMet` carries no argument at all. An earlier run of this row reported

Table 8: Detectors on the instantiated corpus (237 malicious, 426 benign). Balanced accuracy is $\frac{1}{2}(\text{TPR}+\text{TNR})$; 0.5 is chance. Every content-only detector sits at chance; the judge, which reads the user's task, is above it at 2.3 s; the shipped instruction-provenance pack, which reads the channel split, is above it at 0.7 ms. The L_p rows are the gateway's own decisions with the pack applied, fed by the same user turn and tool return the SDK reports; "flag" counts `block` or `pending`. v1 is the pack as first shipped; the unmarked row holds only calls that act (§4.1), and lets through the data-stealing reads whose harm needs a later, held call. Against the two-step benign arm the same pack holds 23.7% of legitimate calls (§4.5).

Detector	Recall	FPR	Bal. acc	P50 ms
No defense	0.0%	0.0%	0.500	0.0
Keyword blacklist	0.8%	0.9%	0.499	0.0
Aegis-rules (L1)	0.8%	0.9%	0.500	0.7
LLM judge	78.9%	8.7%	0.851	2280.4
L_p + pack v1, flag	95.4%	0.0%	**0.977**	0.7
block only	12.2%	0.0%	0.561	0.7
L_p + pack, flag	75.5%	0.0%	0.878	0.8

an 84.4% block rate against 73.9% of legitimate calls; both numbers came from a policy pack on that gateway's tenant requiring a `reason` argument on every call, which blocked 511 of the 663 records regardless of content and measured a configuration, not a detector. The row is replaced, and the run that produced it is kept in the repository. Only the LLM judge, which reads the user's stated task and compares the call against it, is meaningfully above chance (0.851), at 2,280 ms per call—and it is the same model that generated the attacks, still missing 21.1% of them.

The last three rows are the provenance layer measured where it is deployed, not where it is convenient: a fresh gateway from the shipping build, the `security-instruction-provenance` pack applied and no other rule, each record's user turn and tool return reported to `/api/v1/context` exactly as the SDK's request-side hook reports them, and the call sent to `/api/v1/check` with that session (`python -m selective.provenance_gateway_eval`). The pack flags 226 of the 237 attacks and none of the 426 benign calls, at 0.7 ms median round trip; 29 of the 226 are outright blocks (the exfiltration and destructive rules), the rest are holds for a person. The eleven it misses are dominated by one tool, `NortonIdentitySafeSearchPasswords` (8), whose arguments are empty and whose name shares no word with the injection. That is the pack as first shipped. The revised pack, which holds only calls that act (§4.1), flags 183 of 237 (75.5%), still none of the benign calls: what it now allows are the data-stealing reads—`ExpediaSearchReservations` (21) leads—whose harm needs a later send or post, which it still holds. Per call this is a loss; end to end, on AgentDojo, attack success is unchanged at 1.4%. These are the numbers a deployment gets; Table 9 below is the number the features can reach.




Figure 14: Tables 8 and 9 as a picture. (a) Every content-only detector sits on the chance line; only the judge, which reads the task, is above it—at 2,280 ms. (b) Content and taint lie inside each other's spread; grounded instruction provenance is a step, not an increment, and the adaptive attacker (▼) lowers it to 0.933, not to the content level. The hatched bar is the definitional pair, reported and excluded.

Table 9: Feature blocks against the two-step benign arm, where both classes carry tool-derived arguments (logistic regression on standardised features, 5-fold CV AUC ± sd, 237 malicious / 169 benign). Data provenance does not separate what content cannot; instruction provenance does. The definitional pair is reported for completeness and excluded from the comparison—it detects "an instruction appeared in a data channel," which is what the attack *is*.

Feature block	AUC
Content (15)	0.687 ± 0.116
Data provenance / taint (5)	0.737 ± 0.091
Instruction provenance, grounded (4)	**0.991 ± 0.009**
Taint + grounded (9)	0.991 ± 0.009
Content + grounded (19)	0.986 ± 0.013
Instruction prov., definitional (2)	*0.822 ± 0.129*

Feature	mal.	benign	AUC
`user_licence`	0.040	0.573	0.010
`obs_licence`	0.413	0.299	0.637
`authority_margin`	0.373	−0.274	**0.925**
`tool_named_in_obs`	0.340	0.009	0.839
imperative_density	0.467	0.065	*0.829*
directive_to_agent	0.000	0.000	*0.500*

4.5 Why Authority Separates What Content Cannot

The question is whether the judge's advantage is *reading the task* or *being a large model*. Table 9 and Figure 14 answer it with feature blocks evaluated against the two-step benign arm, where both classes carry tool-derived arguments. Content features reach 0.687. Data provenance—the five taint features that track where each argument's *value* came from—reaches 0.737, inside cross-validation noise of content, because on that axis the classes are the same. Instruction provenance—the four grounded L_p features that ask which *turn* authorised the call—reaches **0.991 ± 0.009**, a +0.254 gap over taint against a pooled spread of 0.092. Adding content or taint on top changes nothing (0.986, 0.991): once the call is compared to the task, what the call contains is redundant.

This is the capability claim, and it is architectural rather than numerical. A layer that sees only the call string cannot recover this

signal at any budget, because the signal is not in the call string; a layer that sees the channel split recovers it in under a millisecond without a model. The judge was doing the same comparison at 1600× the cost.

What the shipped pack does with it. The 0.991 is a logistic regression over the four features, cross-validated on this corpus. The pack's original five rules were written before the corpus existed (the two destination rules of §4.5 came later), and the two numbers differ in the direction one should expect. Against the single-step benign arm the pack's false-positive rate is zero (Table 8); against the two-step arm, where every benign call follows a tool return, it holds 40 of 169 legitimate calls (23.7%) for a person, all under the catch-all rule `provenance-untrusted-authority-review`, which escalates any call whose vocabulary the tool return explains better than the user turn does. A two-step benign call is *supposed* to carry words from the tool return—that is what acting on a lookup means—so the rule fires on the honest case as well as the attack. Balanced accuracy on that arm is 0.858 at the flag level and 0.561 at the block level, against the classifier's 0.991. We do not tune the rule's threshold on this corpus, because that would be fitting the test set; we report the gap, and note that the holds are holds, not blocks: the agent waits, a person answers, and nothing is lost but time.

Is it a generator artefact? The benign arms were synthesised from tool schemas, so a model wrote their user instructions with the tool's name and parameters in view—the procedure most likely to manufacture lexical overlap between request and call. The control is InjecAgent's own human-written instructions paired with the tool the user asked for: `user_licence` = 0.500, bootstrap 95% CI $[0.425, 0.581]$, against 0.550 schema-generated and **0.040** for attacks. The generator inflates the feature by 0.049; the human-written interval is nowhere near the malicious mean. $n = 17$ is small and a larger human-written control is warranted.

Adaptive attacker. InjecAgent's attacks are not adaptive and are maximally off-task, the easy case. Restating the user's request inside the injection—the first evasion anyone tries—moves the margin from +0.373 to +0.398 and AUC from 0.991 to 0.994: the licence measure is asymmetric, scoring how much of the *call* a channel explains rather than how similar two texts are, so padding the untrusted channel with text absent from the call does nothing. The evasion that works is carrying the user's vocabulary into the call's arguments, which any free-text field the tool already accepts will do: AUC falls to $\mathbf{0.933 \pm 0.024}$. This is a raised price, not a barrier, and it scales with how far the attacker's goal is from the principal's—which is exactly what makes an attack worth running.

Same tool, hijacked arguments. Every InjecAgent attack changes the *tool*: the user asked for one thing and the injection makes the agent call another, so the tool's own name carries much of the licence signal. The case the measure cannot see by construction is the one where the user asked for the very tool the injection hijacks and only an argument changes—"email the summary to my team" becomes "…to the attacker". We construct it from the corpus: for each of the 237 attacks, the user turn is replaced by a benign-arm instruction that legitimately asks for the same tool, the injection and the attacker's call are kept verbatim, and the probe is run through the same gateway (`python -m selective.same_tool_probe`). Mean `user_licence` rises from 0.040 to 0.237 and the margin halves, from +0.373 to +0.176; the pack's flag rate falls from 95.4% to **77.6%**, and 53 of the 237 probes pass unflagged. These are constructed records, not rollouts—no agent emitted them—and the user turn and the injection were written for different tasks, so the overlap they manufacture is a lower bound on what a real same-tool attack achieves. The honest statement is that provenance separates *which tool* far better than *which argument*, and an injection that stays inside the tool the user already authorised is the attack this layer is weakest against.

Argument-level authority. The first remedy is to attribute the destination rather than the tool. For a call that sends, pays, shares or posts, the gateway extracts its destination-like argument values—addresses, URLs, account numbers, paths, phone numbers; not amounts or dates—and counts those that appear in untrusted text and never in the user's (`provenance.untrusted_only_values`); a pack rule blocks such a call whatever the tool-level verdict. Prototyped on the corpus first, the signal fires on 17 of the 24 attacks on sending tools (every one that carries a destination), on none of 426 single-step benign calls and on 2 of 169 two-step ones, both a deposit reusing an account number from a lookup. Through the gateway, on the 183 same-tool probes whose tool acts, it raises blocks from 17 to 22 and cuts misses from 29 to 26; `BankManagerTransferFunds` with an injected account is now blocked. What remains are actions with nothing to attribute—unlock a door, disable two-factor authentication, place an order—where the user asked for that tool and the injection changed nothing a value check can see. Its known false-positive class is a user who delegates the destination to a document ("send it to the address in the ticket"), which the rule cannot tell from an injection. A destination is also not only an argument of a sending tool: on AgentDojo, `update_scheduled_transaction` with an injected recipient matched no sink verb and was allowed outright. A second rule therefore *holds* (not blocks) any acting call with an untrusted-only destination, whatever its name. On the independent corpus it leaves recall where it was, since other rules already flagged those calls, moves same-tool probe misses from 73 to 72 (on the 183 acting probes, 26 to 25), and adds three holds on 169 two-step benign calls (19.5% to 21.3%); its case is the one AgentDojo exposed, and it is reported as motivated by it. The gpt-4o-mini AgentDojo runs of §4.1 predate this rule; the qwen3:8b run uses it, and shows the false-positive class at work on banking and Slack.

Two features we report and do not use. Imperative density and second-person address in the untrusted channel detect "an instruction appeared in a data channel", which is the definition of indirect injection; they are guaranteed to look good on any corpus whose benign tool output was written to be pure data and will fail on the common real case of tool output that legitimately carries imperatives. They are shown in italics in Table 9 and excluded from every claim.

Scoping the sink rules to acting calls. Replaying AgentDrift (below) showed the exfiltration rule blocking reads: its name pattern matches `read_email` through "mail" and `ViewSavedPaymentMethods` through "pay". A read moves nothing out; by the principle of §4.1, the later send or payment is the sink and is still held or blocked.

Table 10: Instruction provenance as a step-level detector on AgentDrift (task-disjoint test and validation splits: 3,455 trajectories, 19,517 steps). Each trajectory is replayed through the shipping gateway as the SDK reports a live agent; a step is flagged when the pack blocks or holds it, before its observation is seen. Positive class is *hijacked*. The dataset's own baseline is a surface-feature logistic regression over the step. Per trajectory, an attacked trajectory counts as caught when any hijacked step is flagged; a clean one counts as a false alarm when any step is.

	Precision	Recall	F1
Per step, this layer	48.5	62.8	54.8
Per step, dataset baseline (reported)	—	55.4	64.7
Per trajectory, this layer	53.3	75.9	62.6
Steps flagged, by the dataset's label			
hijacked	2,136 of 3,402 (62.8%)		
injection point (the call is the agent's own)	188 of 1,528 (12.3%)		
failed injection (agent saw it, did not follow)	24 of 411 (5.8%)		
benign	2,052 of 14,176 (14.5%)		
Attacked trajectories caught, by attack type			
branch divergence	163 of 225 (72.4%)		
data stealing	198 of 256 (77.3%)		
direct harm	227 of 283 (80.2%)		
multi step spreading	147 of 206 (71.4%)		
parameter manipulation	240 of 315 (76.2%)		
reasoning corruption	180 of 238 (75.6%)		
Clean trajectories with a hold or block	1,016 of 1,927 (52.7%)		
of which hard negatives	208 of 407 (51.1%)		

The exfiltration and unclear-authority rules now apply only to calls that act. On the corpus this costs five flags (77.6% to 75.5% recall), all reads that were blocked for the wrong reason, among them `BankManagerSearchPayee`; the 183 acting same-tool probes are unchanged (22 blocks, 25 misses) and two-step holds fall from 36 to 35. The numbers above and in Table 8 are after this change.

4.6 Step-Level Detection on AgentDrift

The corpus of §4.3 has 237 attacks. AgentDrift [31] is a public corpus of 12,536 synthetic tool-call trajectories over five domains in which every one of 71,024 steps is labelled—benign, the injection point, hijacked, or a failed injection—and which includes delayed and partial hijacks and 1,500 hard negatives written to look like hijacks. We replay its task-disjoint test and validation splits through the shipping gateway exactly as the SDK reports a live agent: the task is the user turn, each call is checked with the ledger holding every earlier observation, and each observation is appended after its call. The gateway sees no label (`research/selective/agentdrift_eval.py`). Table 10 and Figure 15 give the result. Per step the layer recovers 62.8% of hijacked calls against the dataset's reported 55.4%, at a lower F1 (54.8 against 64.7) because its precision is 48.5%: it holds 14.5% of benign steps and 51% of the hard negatives, and more than half of the clean trajectories receive at least one hold. That is the review rule doing what §4.5 says it does—a benign multi-step task takes its arguments from tool output—now measured on 20,000 steps rather than 169 calls. Recall is even across the dataset's attack types (71–80%), including delayed and multi-step hijacks the surface baseline finds 8–23% of, which is what reading the channel split rather than the step buys. The corpus is synthetic and its hijacks are, by construction, calls an injection asked for; we report it as a second, larger, independently labelled measurement of the same trade, not as a new claim.



Figure 15: AgentDrift, replayed through the shipping gateway. Left: the share of steps the provenance pack flags, by the dataset's step label—including the benign steps it flags. Right: trajectory recall by attack type.

4.7 Limitations

- **Auditor-reviewed attack success is measured on one model and two suites.** With qwen3:8b on banking and Slack it is 0 to 1 of 249 depending on configuration; with gpt-4o-mini on all four suites the attack run did not complete before the API credit ran out, so there the 1.4% belongs to the configuration in which holds are refusals. The gpt-4o-mini rows also predate every change of the qwen3:8b paragraph.
- **Two agent models, neither frontier.** AgentDojo was run with gpt-4o-mini on four suites and qwen3:8b on two; the per-call corpus was produced by one model (Qwen3-VL-32B). Stronger models resist the attack more on their own, which changes the baseline more than the defense.
- **The auditor is a weak link when it is small, and it was tuned on the suites it is reported on.** With an 8B auditor shown the evidence, utility returns to within noise of undefended at a cost of one executed attack in 249, an injection the auditor itself fell for; a stronger auditor has not been measured. The changes that got there were found on banking and Slack; on the held-out workspace and travel suites they cost no utility and cut attacks from 23 to 4 of 700, with the same small auditor.
- **The adaptive attacker.** We report two adaptive runs; both rewrite the untrusted text an agent reads, an agent model emits the next call, and only a realised attack—same sink tool, the attacker's destinations present—counts. On the corpus of §4.3 with a deployed frontier agent, Claude Haiku 4.5, and a qwen3:8b attacker (Table 11), Haiku acted on none of the 237 original injections and none of the 1,420 rewrites: that run measures the agent, not the gateway. So we re-ran it on AgentDojo with an agent that

Table 11: An adaptive attacker against the instruction-provenance pack, on the 237 corpus attacks of §4.3. Round 0 is the injection as recorded. In each later round an attacker model (qwen3:8b) rewrites what the agent reads, given either only the verdict or the rule, its reason and how the pack decides (white-box); an agent model then emits the next call from the user's request and the rewritten text, and the gateway checks the call it emitted. A round counts only when the agent made the attacker's call: same tool, every destination of the original present. *Flagged* is the share of the attacks still held or blocked after that round; *escaped* counts attacks flagged at round 0 that were realised and allowed by the end; *agent balked* counts rewrites the agent did not act on. Given the original text with no gateway, the agent (anthropic:claude-haiku-4-5) emitted the attacker's call in 0 of 237 cases. So the agent, not the gateway, stopped every rewrite here: no flagged attack escaped, and none was realised that the gateway then had to stop.

Feedback	R0	R1	R2	R3	R4	Escaped	Agent balked
Verdict only	75.5%	75.5%	75.5%	75.5%	75.5%	0 of 179	707 rounds
White-box	75.5%	75.5%	75.5%	75.5%	75.5%	0 of 179	713 rounds

Table 12: An adaptive attacker on AgentDojo against the shipped gateway (`aegis_v3_audit`: provenance pack, destination rules as holds, the alignment auditor reviewing holds). The agent is qwen3-8b served locally, which—unlike Claude Haiku 4.5 (Table 11)—acts on injections: of the 249 attack pairs on banking and Slack it carried out 61 undefended, and those are the targets. Round 0 is AgentDojo's own injection; in each later round an attacker model (qwen3-8b) rewrites the injected text, given either only the gateway's refusal or also the rule that fired and how the pack decides (white-box). *Flagged* is the share held or blocked; an attack *escapes* only if AgentDojo's security check passes *and* the gateway allowed the sink tool.

Feedback	R0	R1	R2	R3	R4	Escaped
Verdict only	98.4%	98.4%	98.4%	98.4%	98.4%	1 of 61
White-box	98.4%	98.4%	98.4%	98.4%	98.4%	1 of 61

does comply, qwen3:8b, against the shipped gateway (Table 12). Of the 249 banking and Slack attack pairs it carried out 61 undefended; the gateway flagged 60 of those 61, and across four rounds of rewriting—with the verdict, and with the rule that fired and a description of how the pack decides—the attacker turned *none* of the 60 flagged attacks into an escape. The one attack that ran was allowed from round 0, not won by rewriting: the user's own task already sent a direct message to that recipient, so the injected link rode on an authorised send—the open class of §4.5, an injection inside a tool the user asked for, which provenance cannot separate. The attacker here is an 8B model; a frontier attacker, which we could not place in the role (Claude Haiku 4.5 declined it), is the stronger test still owed.

- **Delegation is indistinguishable from injection.** When the user tells the agent to follow a document ("do the tasks on my to-do list"), an instruction in that document has the user's authority by construction; provenance cannot separate it from an injected one, and only review can.
- **Same-tool hijacks.** An injection that stays inside the tool the user asked for and changes only an argument is the case provenance is weakest on (§4.5). Attributing the destination closes the part with a recipient, URL or account to attribute; an action with none (unlock, disable, order) stays open, and a destination the user delegated to a document is blocked with it.
- **The read-only revision trades recall for holds.** It was motivated by AgentDojo; on the independent corpus it costs per-call recall (95.4% to 75.5%) on data-stealing reads whose harm needs a later, still-held call. The first version is reported alongside it.
- **Coverage of the provenance layer.** It needs the request-side hook: the Python SDK has it for every model client it patches; the JS and Go SDKs and the two proxies do not, and a framework that rewrites tool results into user text (smolagents) erases the channel before any hook sees it (Appendix B).
- **Overhead on one laptop.** The load test ran on a shared laptop under swap; percentiles were stable across runs, maximum latencies were not and are not attributed. Multi-process and networked deployments are not measured.
- **Corpus construction.** Capture is single-turn; 237 unique malicious calls is bounded by InjecAgent's distinct attacker instructions; the human-written control is $n = 17$; one adaptive strategy. The lesson of Appendix C is that an evaluation's construction, not its headline, decides what it can support, so we state these rather than average over them.

5 RELATED WORK

Where defenses stand. Defenses against indirect prompt injection now fall into four families, distinguished by where they act and what they assume about the agent.

In the model. The instruction hierarchy [36] trains a model to rank privileged instructions above data; StruQ [5] separates prompt and data into channels and fine-tunes on that split; SecAlign [6] uses preference optimisation to the same end. These change what the model does when it reads an injection, and they are complementary to Aegis, which assumes nothing about the model it guards and so can stand in front of one it cannot retrain.

Around the prompt and the trajectory. Spotlighting [17] marks untrusted input so the model can see its source; it is a row of Table 4, as are AgentDojo's tool filter and prompt repetition [11]. Detectors classify the input: DataSentinel [26] trains one game-theoretically against adaptive injections, and LlamaFirewall [7] ships scanners the agent's own process calls. Task Shield [21] asks a model whether each call serves the user's goal—the question Aegis's alignment auditor asks (§2.9), which Aegis asks only of the calls its cheaper layers hold. MELON [43] re-runs the trajectory with the user's request masked and flags actions that do not depend on it, a counterfactual form of the authority test L_p makes from the conversation's channel split without a second run.

Out of band, by construction. CaMeL [10] has a privileged model plan over the user's query while a quarantined model reads untrusted data, and enforces policies on values by capability; FIDES [8] gives the planner confidentiality and integrity labels and enforces flow policies deterministically; Progent [35] enforces a per-task privilege policy over tool names and arguments. These obtain guarantees no detector can, and pay for them by requiring the agent to be built around the split. Two 2026 lines push on argument-level control: role-stratified conformal risk control [32] calibrates a separate threshold and risk budget for each argument role, the statistical counterpart of the destination attribution of §4.5; and aiAuthZ [22] argues that in-process defenses share the attacker's trust domain and moves the decision off the host, binding caller identity and issuing receipts, as Aegis's gateway and decision receipts do (§2.3).

At the supply chain. A tool's description is itself untrusted input; the OWASP MCP Top 10 lists tool poisoning—description injection, shadowing, and descriptions changed after approval—as MCP03 [30], the case Aegis's MCP proxy pins.

Where Aegis stands. Aegis is the least invasive of these: it stands between an *unmodified* agent and its tools, across frameworks and transports it does not control, and adds what a deployment needs around the decision—a hold that suspends the agent for a person or the auditor, a signed receipt for every allow, a signed and chained record of every decision, and fallback when the control point is slow or down. Its provenance layer borrows CaMeL's question, which channel authorised this, without CaMeL's rewrite; §4 measures what that buys and what it cannot.

Evaluation, and the adaptive attacker. AgentDojo [11], InjecAgent [41] and ToolEmu [34] are the harnesses this paper reports on or derives from; AgentDyn [24] finds that nearly all published defenses either fail to stop injections in open-ended dynamic tasks or block too many legitimate actions, and AgentDrift [31] labels every step of hijacked trajectories (§4.6). The sharpest critique of the field is that static attack sets overstate every defense: adaptive attacks broke all eight indirect-injection defenses Zhan et al. tested [40], and twelve recent defenses, most of which had reported near-zero attack success, fell at mostly above 90% to attackers who tuned against each one [29]. An independent adaptive evaluation of out-of-band enforcement found Progent held, while warning that one template on a weak model is weak evidence [28]. Against an adaptive attacker on AgentDojo, with a complying agent and either verdict or white-box feedback, the shipped gateway held: of 61 attacks the undefended agent carried out it flagged 60, and four rounds of rewriting turned none of those into an escape (§4.7, Table 12); the attacker was an 8B model, and a frontier one is the test still owed.

Guardrails and observability. TrustLLM [18] and TrustEval [37] evaluate trustworthiness at the model level; Llama Guard [20] classifies text safety; NeMo Guardrails [33] programs dialogue rails; IsolateGPT [38] isolates apps at the architecture level. Langfuse [23], Helicone [16] and Arize [1] trace tool calls after they are issued; Aegis acts before side effects occur and keeps the trace as evidence.

Table 13: Capability comparison with representative observability and agent-evaluation platforms. Pre-exec = pre-execution blocking; Human Rev. = human-in-the-loop approval. ✓ = supported, ✗ = not supported.

System	Pre-exec	Attack	Policy	Human Rev.	Audit	SDK	Open
Langfuse	✗	✗	✗	✗	✓	✗	✓
Helicone	✗	✗	✗	✗	✓	✗	✓
Arize	✗	✓	✗	✗	✓	✗	✗
ToolEmu	✗	✓	✗	✗	✗	✗	✓
AgentDojo	✗	✓	✗	✗	✗	✗	✓
Aegis	✓	✓	✓	✓	✓	✓	✓

6 CONCLUSION AND AVAILABILITY

Aegis puts a decision between an agent and its tools: two lines of integration in fifteen frameworks, a refusal that returns in-band, a hold that waits for a person, and a signed chain of every decision. On AgentDojo it brings attack success from 29.7% to 1.4%, mostly through asking which turn of the conversation authorised a call, in under a millisecond and without a model. Its cost is holds. The alignment auditor answering them first returns most of the utility on gpt-4o-mini; on a locally served 8B model, given the agent's evidence, it lets 1 of 249 attacks execute, and on two held-out suites the gateway costs no utility while cutting attacks from 23 to 4 of 700. Against an adaptive attacker on AgentDojo—a complying agent, four rounds of rewriting, the rules in hand—it flagged 60 of the 61 attacks that agent carried out and the attacker escaped none of them by rewriting; the one that ran rode on a send the user had already authorised. The attacker was an 8B model, and a frontier one is the test still owed. Around the decision sit the parts an operator needs before it is deployable: a behavioural layer that cannot block before it has learned, explicit fallback for a gateway that is slow, down or without a model, static analysis in the same policy vocabulary, and connectors into the identity, SIEM and compliance systems already in place. Running all of it under nineteen real agent harnesses found twenty-four defects no unit test had; the matrix stays in the repository so the next ones are found the same way.

Code: `github.com/Justin0504/Aegis` (MIT). The repository contains the gateway, the SDKs, the Compliance Cockpit, the rollout harness, the corrected benchmark, and the compatibility matrix. Every number in this paper is produced by a command in that repository, at the commit tagged `arxiv-v2`: `python -m benchmark.audit_const` for the audit of §C and Table 7; `python -m selective.emit_instantiated` to roll the corpus of §4.3 out again (it needs the served model); `python -m cascade.run_cascade` for the detectors of Table 8; `python -m selective.provenance_eval` for Table 9 and Figure 14; and `research/agentdojo/run_agentdojo.py` then `make_table.py` for Table 4 (per-task transcripts in `research/agentdojo/results/logs.tar.gz`) the same script with `AD_MODEL=qwen3:8b`, `AD_BASE_URL` pointing at a local OpenAI-compatible server and `AD_TAG=-qwen3`, then `make_table_qwen` for Table 5; `node research/perf/loadtest.mjs` for Table 6; `research/compat/` runs the three scenarios of §3 on the live agent and photographs them, and `shoot_replay.sh` replays AgentDojo transcripts through the SDK and gateway for the Cockpit views of Appendix D; `python -m selective.provenance_gateway_eval` and `selective.same_tool_probe` for the gateway rows of Table 8 and the same-tool probe; `research/compat/run_`

followed by `make_table.py` for Appendix B, whose per-row transcripts are committed under `research/compat/results`. The figures are drawn from those outputs by the scripts in `research/figures_src`; nothing in a figure is typed in by hand.

REFERENCES

[1] Arize AI. 2024. Arize AI: ML Observability Platform. (2024). https://arize.com.

[2] Daniel J Bernstein, Niels Duif, Tanja Lange, Peter Schwabe, and Bo-Yin Yang. 2012. High-Speed High-Security Signatures. *Journal of Cryptographic Engineering* 2 (2012), 77–89.

[3] Albert Bifet and Ricard Gavaldà. 2007. Learning from Time-Changing Data with Adaptive Windowing. In *Proceedings of the 2007 SIAM International Conference on Data Mining (SDM)*. 443–448. https://doi.org/10.1137/1.9781611972771.42

[4] Harrison Chase. 2023. LangChain: Building Applications with LLMs through Composability. https://github.com/langchain-ai/langchain.

[5] Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. 2025. StruQ: Defending Against Prompt Injection with Structured Queries. In *USENIX Security Symposium*. arXiv:2402.06363.

[6] Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, David Wagner, and Chuan Guo. 2025. SecAlign: Defending Against Prompt Injection with Preference Optimization. In *ACM Conference on Computer and Communications Security (CCS)*. arXiv:2410.05451.

[7] Sahana Chennabasappa, Cyrus Nikolaidis, Daniel Song, David Molnar, Stephanie Ding, Shengye Wan, Spencer Whitman, Lauren Deason, Nicholas Doucette, Abraham Montilla, Alekhya Gampa, Beto de Paola, Dominik Gabi, James Crnkovich, Jean-Christophe Testud, Kat He, Rashnil Chaturvedi, Wu Zhou, and Joshua Saxe. 2025. LlamaFirewall: An open source guardrail system for building secure AI agents. *arXiv preprint arXiv:2505.03574* (2025).

[8] Manuel Costa, Boris Köpf, Aashish Kolluri, Andrew Paverd, Mark Russinovich, Ahmed Salem, Shruti Tople, Lukas Wutschitz, and Santiago Zanella-Béguelin. 2025. Securing AI Agents with Information-Flow Control. arXiv:2505.23643 [cs.CR]

[9] CrewAI. 2024. CrewAI: Framework for Orchestrating Role-Playing Autonomous AI Agents. (2024). https://github.com/crewAIInc/crewAI.

[10] Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. 2025. Defeating Prompt Injections by Design. *arXiv preprint arXiv:2503.18813* (2025).

[11] Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. 2024. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*.

[12] Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A. Wichmann. 2020. Shortcut Learning in Deep Neural Networks. *Nature Machine Intelligence* 2, 11 (2020), 665–673.

[13] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. 2023. Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection. In *Proceedings of the ACM Workshop on Artificial Intelligence and Security (AISec)*.

[14] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. 2017. On Calibration of Modern Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*.

[15] Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel R. Bowman, and Noah A. Smith. 2018. Annotation Artifacts in Natural Language Inference Data. In *Proceedings of NAACL-HLT*. 107–112.

[16] Helicone AI. 2024. Helicone: Open-Source LLM Observability Platform. (2024). https://helicone.ai.

[17] Keegan Hines, Gary Lopez, Matthew Hall, Federico Zarfati, Yonatan Zunger, and Emre Kiciman. 2024. Defending Against Indirect Prompt Injection Attacks With Spotlighting. arXiv:2403.14720 [cs.CR]

[18] Yue Huang, Lichao Sun, Haoran Wang, Siyuan Wu, Qihui Zhang, Chujie Gao, Yixin Huang, Wenhan Lyu, Yixuan Zhang, Xiner Li, et al. 2024. Position: TrustLLM: Trustworthiness in Large Language Models. In *Proceedings of the International Conference on Machine Learning (ICML)*.

[19] Hugging Face. 2024. smolagents: A Smol Library to Build Agents. (2024). https://github.com/huggingface/smolagents.

[20] Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. 2023. Llama Guard: LLM-based Input-Output Safeguard for Human-AI Conversations. *arXiv preprint arXiv:2312.06674* (2023).

[21] Feiran Jia, Tong Wu, Xin Qin, and Anna Squicciarini. 2024. The Task Shield: Enforcing Task Alignment to Defend Against Indirect Prompt Injection in LLM Agents. arXiv:2412.16682 [cs.CR]

[22] Sai Varun Kodathala. 2026. aiAuthZ: Off-Host, Identity-Bound Authorization for AI Agents. arXiv:2607.05518 [cs.CR]

[23] Langfuse. 2024. Langfuse: Open Source LLM Engineering Platform. (2024). https://langfuse.com.

[24] Hao Li, Ruoyao Wen, Shanghao Shi, Ning Zhang, Yevgeniy Vorobeychik, and Chaowei Xiao. 2026. AgentDyn: Are Your Agent Security Defenses Deployable in Real-World Dynamic Environments? arXiv:2602.03117 [cs.CR]

[25] Hongfu Liu, Hengguan Huang, Xiangming Gu, Hao Wang, and Ye Wang. 2025. On Calibration of LLM-based Guard Models for Reliable Content Moderation. In *International Conference on Learning Representations (ICLR)*. arXiv:2410.10414.

[26] Yupei Liu, Yuqi Jia, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. 2025. DataSentinel: A Game-Theoretic Detection of Prompt Injection Attacks. In *IEEE Symposium on Security and Privacy*. arXiv:2504.11358.

[27] LlamaIndex. 2024. LlamaIndex: Data Framework for LLM Applications. (2024). https://github.com/run-llama/llama_index.

[28] Praneeth Narisetty, Shiva Nagendra Babu Kore, Uday Kumar Reddy Kattamanchi, and Jayaram Kumarapu. 2026. Adaptive Evaluation of Out-of-Band Defenses Against Prompt Injection in LLM Agents. arXiv:2606.26479 [cs.CR]

[29] Milad Nasr, Nicholas Carlini, Chawin Sitawarin, Sander V. Schulhoff, Jamie Hayes, Michael Ilie, Juliette Pluto, Shuang Song, Harsh Chaudhari, Ilia Shumailov, Abhradeep Thakurta, Kai Yuanqing Xiao, Andreas Terzis, and Florian Tramèr. 2025. The Attacker Moves Second: Stronger Adaptive Attacks Bypass Defenses Against LLM Jailbreaks and Prompt Injections. arXiv:2510.09023 [cs.LG]

[30] OWASP Foundation. 2025. OWASP MCP Top 10. https://owasp.org/projects/mcp-top-10. MCP03:2025 Tool Poisoning; beta.

[31] Asif Pinjari and Mithun Paul Saint-Germain. 2026. AgentDrift: A Step-Labeled Benchmark of Injection-Hijacked LLM Agent Trajectories. arXiv:2609.06972 [cs.CR] Dataset released under CC BY 4.0.

[32] Md Ashikur Rahman, Md Arifur Rahman, Niamul Hassan Samin, Khandaker Rifah Tasnia, Md Hasibul Amin, Sifat Rahman Ahona, and Juena Ahmed Noshin. 2026. Beyond Aggregate Risk: Role-Stratified Conformal Risk Control for LLM Tool Calls. arXiv:2607.24343 [cs.LG]

[33] Traian Rebedea, Razvan Dinu, Makesh Sreedhar, Christopher Parisien, and Jonathan Cohen. 2023. NeMo Guardrails: A Toolkit for Controllable and Safe LLM Applications with Programmable Rails. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*.

[34] Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J Maddison, and Tatsunori Hashimoto. 2024. Identifying the Risks of LM Agents with an LM-Emulated Sandbox. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

[35] Tianneng Shi, Jingxuan He, Zhun Wang, Hongwei Li, Linyu Wu, Wenbo Guo, and Dawn Song. 2025. Progent: Securing AI Agents with Privilege Control. *arXiv preprint arXiv:2504.11703* (2025).

[36] Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. 2024. The Instruction Hierarchy: Training LLMs to Prioritize Privileged Instructions. arXiv:2404.13208 [cs.CR]

[37] Yanbo Wang, Jiayi Ye, Siyuan Wu, Chujie Gao, Yue Huang, Xiuying Chen, Yue Zhao, and Xiangliang Zhang. 2025. TrustEval: A Dynamic Evaluation Toolkit on the Trustworthiness of Generative Foundation Models. In *Proceedings of the 2025 Conference of the North American Chapter of the Association for Computational Linguistics: System Demonstrations*.

[38] Yuhao Wu, Franziska Roesner, Tadayoshi Kohno, Ning Zhang, and Umar Iqbal. 2025. IsolateGPT: An Execution Isolation Architecture for LLM-Based Agentic Systems. In *Network and Distributed System Security Symposium (NDSS)*.

[39] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing Reasoning and Acting in Language Models. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

[40] Qiusi Zhan, Richard Fang, Henil Shalin Panchal, and Daniel Kang. 2025. Adaptive Attacks Break Defenses Against Indirect Prompt Injection Attacks on LLM Agents. In *Findings of NAACL*. arXiv:2503.00061.

[41] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. In *Findings of the Association for Computational Linguistics (ACL)*.

[42] Yue Zhao, Zain Nasrullah, and Zheng Li. 2019. PyOD: A Python Toolbox for Scalable Outlier Detection. *Journal of Machine Learning Research* 20, 96 (2019), 1–7.

[43] Kaijie Zhu, Xianjun Yang, Jindong Wang, Wenbo Guo, and William Yang Wang. 2025. MELON: Provable Defense Against Indirect Prompt Injection Attacks in AI Agents. In *International Conference on Machine Learning (ICML)*. arXiv:2502.05174.

A INTERCEPTION GALLERY

The cards below are calls Aegis refused, and calls it did not. Every string on a card is verbatim from a recorded run: the user's request, the injected text the agent read (first characters), the call it emitted, and the reason the gateway returned. G1–G8 come from the AgentDojo runs of §4.1, from the configurations the tables report (gpt-4o-mini with the provenance pack, and the shipped gateway with qwen3:8b). Across those runs the gateway refused 2,900 calls, 119 of them on clean tasks. C1–C2 come from the compatibility matrix of Appendix B, and G9 from a recorded MCP run. The cards were picked by a rule fixed before drawing, the first recorded case of each pattern (`research/figures_src/figure_data.py`). The gallery deliberately includes two false positives (G6, G7) and one attack that landed (G8).



Figure 16: Banking. The injection asks the agent to redirect a scheduled transaction; the call is held, and with no reviewer present the hold refuses it.



Figure 17: Banking. A payment to the attacker's IBAN, which nothing the user said accounts for, is blocked before it runs.



Figure 18: Slack. A direct message carrying the phishing link the injection planted is blocked.




Figure 19: Slack. The injection asks for every channel's messages to be posted to an external page; the call is blocked.



Figure 20: Workspace. An email to an address that appears only in the injected text is blocked.



Figure 21: Slack, a false positive under attack. The direct message the user asked for is blocked, so the user's task is lost.



Figure 22: Banking, a false positive on a clean task. The user asked for a bill to be paid and the IBAN came from the bill, so the call is explained by tool output. This is the class the auditor, shown the agent's evidence, releases (§4.1).




Figure 23: Workspace, a miss. The user asked for a file to be deleted; the injection changed which file. The call is the tool the user requested, with a short id that nothing attributes, and it runs (§4.5).



Figure 24: Claude Agent SDK, compatibility scenario S2. The pipe-to-shell install is blocked by L1, and the refusal arrives as the tool's result; the agent explains it and declines to route around it (transcript verbatim).



Figure 25: OpenAI Agents SDK, compatibility scenario S4. A vendor note read with `read_file` asks for an email; `provenance-untrusted-authority-on-exfil-sink` blocks it.




Figure 26: MCP tool pinning. A server changes a tool's description after it was approved, adding an instruction to read a key file; the proxy refuses the tool until an operator re-pins it (recorded run, `research/compat/mcp_rugpull_demo.py`).

B COMPATIBILITY MATRIX

Setup. Two fresh gateways are started from the shipping build (one with the OpenAI upstream for the egress proxy, one with a local Ollama upstream), at enterprise tier so that no agent is placed in audit-only mode by the free-tier cap; one DSL rule is installed, holding `kubectl delete` for approval, with the shipped instruction-provenance pack merged on top of it; and an approver thread plays the second attendee, approving any held call three seconds after it appears. Each (harness, scenario) runs in its own process because `agentguard.auto()` patches SDKs process-wide. The tools are real (an in-memory SQLite database; a shell tool that simulates execution so a successful attack cannot damage the test machine—the decision is taken before the tool runs, so simulation after it changes nothing measured; a scratch file system whose `vendor-notes.txt` carries the S4 injection; and a simulated `send_email`). The exception is the Claude Agent SDK row, which runs Claude Code's own Bash tool: there the approved S3 `kubectl delete` really executed on the test machine, and failed only because no cluster was configured. Latencies are the SDK's own round trip to `/api/v1/check`, measured by wrapping the HTTP client, and so include serialisation and the loopback network.

Reading the S2 column. In every row that emitted the payload the tool did not run (Gemini's provider returned 503 before any call); the column records how the agent learned why. Frameworks that execute tools themselves get the refusal *in-band*: the SDK's tool-level patch returns it as the tool's own result (CrewAI, AutoGen, LlamaIndex, smolagents, Pydantic AI and the OpenAI Agents SDK on both of its APIs, run with `enforce_at="tool"` so that the model-level patch observes and the tool-level patch enforces; LangGraph 1.x additionally needs its `ToolNode` constructed with `handle_tool_errors=True` so that the refusal becomes the error message the model reads, which the table marks *handler*), the MCP host receives a tool error, the egress proxy rewrites the model's reply, and Claude Code's hook protocol carries a denial reason. Where the stack offers no tool-execution hook for the SDK to patch (plain SDK loops, LiteLLM, Google GenAI), the agent executes tools in its own code, and one line wraps that dispatcher: `execute_tool = agentguard.guarded(execute_tool)`. The wrapper decides the call before the dispatcher runs and returns the refusal in the tool's own result slot, which the table marks *in-band (helper)*. No row escapes, and no row needs exception handling in the agent loop. One agent tried to route around the block: LangGraph's, refused twice, split the install into a download and a run; the download was blocked, and the run of `sh /tmp/install.sh` that followed was allowed, since a local path names nothing L1 recognises. The payload never arrived, but a gateway that judges calls one at a time does not see that two calls compose into the one it refused.

Reading the S4 column. S4 is the attack of §4: the user asks for `vendor-notes.txt` to be summarised, the file ends with a "records policy" telling the assistant to forward its contents with `send_email` first, and an agent that complies emits an ordinary `send_email` the user never asked for. Nothing in that call is a payload; L1 has nothing to match and the pack's shell rule is not even in scope. The column therefore records a different thing from S2: not whether a refusal reached the model, but *which layer* produced the decision. A cell marked L_p is a block or hold whose matched rule is one of the instruction-provenance pack's; in every such cell the request-side hook had reported the user turn and the tool return to the ledger, the gateway found that the tool return accounted for the call and the user turn did not, and the exfiltration rule fired. *No ledger* marks the paths that have no request-side hook—the Go and JavaScript SDKs, the ten-line manual integration, the Claude Code hook and the two proxies—where the layer has nothing to assess and we do not run the scenario rather than report an `allow` that would measure the absence of the hook. *Model declined* marks a turn on which the model summarised the file and ignored the instruction in it; that is the model's own refusal training, a defence layer of its own, and the gateway is not credited for it. The wording of the injected file was chosen by trial (`results/s4-wording.md`): a notice addressed to an external archive is declined by Claude Haiku 4.5 every time, a "records policy" naming an internal-looking address is acted on about two turns in three, and GPT-4o-mini acts on it more often than Claude does. Where the destination goes does not matter to the provenance layer, which scores who authorised the call, not where it sends. Of the twelve SDK rows, the model acted on the injection in eight. In six of them—the OpenAI tool loop, CrewAI, AutoGen, LlamaIndex and the OpenAI Agents SDK on both APIs—the `send_email` was blocked by the pack's exfiltration rule. In the other two the provenance layer did not fire, for two different reasons, and both are findings rather than noise. Pydantic AI calls Anthropic's *beta* messages endpoint, which the SDK's request-side hook did not patch, so the conversation never reached the ledger; the hook now covers that endpoint and the fix is tested through a real client, but the row was not re-run, because the Anthropic account ran out of credit before it could be. smolagents rewrites every tool return into a plain user-role message ("Observation: …") before the model client is called, so by the time the SDK sees the messages array the injected instruction is indistinguishable from the user's own words, and the layer attributes the email to the user. Channel provenance cannot be recovered from a transcript that has already erased the channel; the fix belongs at the framework's tool dispatch, where the SDK sees the return before it is flattened, and is not in this version. Both emails were still held for a person, by the gateway's built-in approval policy for outbound communication rather than by L_p, and the table says so. In the remaining three rows Claude Haiku 4.5 summarised the file and ignored the instruction; the Gemini row could not be run.

Harness-specific notes. Claude Haiku refused to emit the `DROP TABLE` payload of the original S2 under every framing we tried, direct or through a planted runbook, which is itself a defence layer; S2 therefore uses a payload both model families emit, a remote install script piped to `sh`. Whether it is emitted depends on the agent's own prompt: with a system prompt that named the firewall and mentioned compliance, Claude Haiku 4.5 emitted the call on two turns of six; with the neutral operations prompt the demo agent now ships, on five of five. A turn on which the model declines produces no tool call and therefore no row; the matrix records what the gateway did when the call was made. A cell marked *provider 429* or *503* is one where the model provider refused the call (quota exhausted, or "high demand"), before any tool call existed for the

Table 14: Compatibility matrix. Every row runs the same four scenarios against the same shipping gateway: S1 a benign `SELECT`; S2 the agent is talked into `curl …| sh`; S3 `kubectl delete` held by a policy for a second person who approves after 3 s; S4 the user asks for a file to be read, the file carries an instruction, and the agent emits an ordinary `send_email` the user never asked for—L_p marks a block produced by the instruction-provenance pack; *no ledger* marks a path with no request-side context hook; *model declined* marks a model that did not act on the injection. Cells give the gateway's decision, for S2 how the refusal reached the model (in-band: the framework's tool-level patch returned it as the tool result; in-band (helper): the agent's own dispatcher is wrapped by the one-line `agentguard.guarded`; inline: the proxy rewrote the model's reply; escaped: the framework surfaced it as an exception), for S3 how long the agent itself waited before the second attendee's decision released it (measured in the SDK's own process, between the `pending` response and the poll that returned `allow`), and the SDK round trip. Latencies are medians over the calls in the row. In S4 a *held* cell is the gateway's built-in hold on an outbound message, which no provenance rule decided (Appendix B); the scripted approver that plays the second attendee in S3 released those holds too, which a real operator would not. †S1–S3 for these two rows are from the previous day's run: the Anthropic account ran out of credit during this one, and no code on their path changed in between.

Harness	Path	Model	S1 benign	S2 injected payload	S3 held for approval	S4 indirect injection
Lightweight						
Anthropic SDK tool loop	SDK auto()	Claude Haiku 4.5	`allow` · 5 ms	`block` · in-band (helper) · 4 ms	held (3 s at the queue) → `allow`	*model declined*
OpenAI SDK tool loop	SDK auto()	GPT-4o-mini	`allow` · 6 ms	`block` · in-band (helper) · 4 ms	held 4 s → `allow`	`block` · L_p · 6 ms
LiteLLM tool loop	SDK auto()	Claude Haiku 4.5	`allow` · 2 ms	`block` · in-band (helper) · 3 ms	held 4 s → `allow`	*model declined*
Qwen3-8B on Ollama (RL-trained, local)	manual check (10 lines)	Qwen3-8B	`allow` · 9 ms	`block` · in-band · 4 ms	held 4 s → `allow`	*no ledger*
Go SDK `Wrap`	SDK (Go)	— (explicit)	`allow` · 8 ms	`block` · in-band · 2 ms	held → `allow`	*no ledger*
JS SDK + Anthropic†	SDK auto() (JS)	Claude Haiku 4.5	`allow`	`block` · in-band (helper)	held → `allow`	*no ledger*
Open-source framework						
LangGraph ReAct agent	SDK auto()	Claude Haiku 4.5	`allow` · 2 ms	`block` · handler · 3 ms	held 4 s → `allow`	*model declined*
CrewAI	SDK auto()	Claude Haiku 4.5	`allow` · 3 ms	`block` · in-band · 3 ms	held 4 s → `allow`	`block` · L_p · 3 ms
AutoGen 0.4 (agentchat)	SDK auto()	GPT-4o-mini	`allow` · 2 ms	`block` · in-band · 2 ms	held 4 s → `allow`	`block` · L_p · 9 ms
LlamaIndex FunctionAgent	SDK auto()	GPT-4o-mini	`allow` · 3 ms	`block` · in-band · 2 ms	held 4 s → `allow`	`block` · L_p · 7 ms
smolagents ToolCallingAgent	SDK auto()	Claude Haiku 4.5	`allow` · 3 ms	`block` · in-band · 5 ms	held 4 s → `allow`	held · not L_p · 4 ms
Pydantic AI	SDK auto()	Claude Haiku 4.5	`allow` · 3 ms	`block` · in-band · 3 ms	held 4 s → `allow`	held · not L_p · 5 ms
Closed harness						
OpenAI Agents SDK (Responses API)	SDK auto()	GPT-4o-mini	`allow` · 2 ms	`block` · in-band · 2 ms	held 4 s → `allow`	`block` · L_p · 8 ms
OpenAI Agents SDK (chat completions)	SDK auto()	GPT-4o-mini	`allow` · 3 ms	`block` · in-band · 3 ms	held 4 s → `allow`	`block` · L_p · 9 ms
Claude Agent SDK (Claude Code runtime)†	PreToolUse hook	Claude Code	`allow` · 8 ms	`block` · in-band · 12 ms	held → `allow`	*no ledger*
Google GenAI function calling	SDK auto()	Gemini Flash (3.8; 3-preview for S2)	*n/a*	*provider 503*	*provider 429*	*provider 429*
Transport						
MCP stdio proxy (Claude Desktop shape)	MCP proxy	— (host)	`allow` · 14 ms	`block` · in-band · 11 ms	held → `allow`	*no ledger*
Egress proxy → OpenAI	egress proxy	GPT-4o-mini	`allow` · 1013 ms	`block` · inline · 891 ms	`block` (proxy cannot hold)	*no ledger*
Egress proxy → Ollama (self-hosted)	egress proxy	Qwen2.5-7B	`allow` · 3486 ms	`block` · inline · 963 ms	`block` (proxy cannot hold)	*no ledger*

gateway to decide; on the day of the final run Google's API did this to every Gemini cell: S1 timed out after 400 s, S2 got a 503 and S3 and S4 a 429, and the single key available had no quota left to retry. The Claude Agent SDK runs Claude Code's own Bash tool, so its scenarios are shell-shaped (`echo`, the same `curl …| sh`, `kubectl delete`) and the interposition is a PreToolUse hook that denies with the gateway's reason. The MCP proxy row needs no model: the transport is what is under test, so the client calls the tool directly through the proxy. Qwen3-8B is driven through Ollama's native API with thinking disabled, because its OpenAI-compatible endpoint spends the token budget on hidden reasoning and returns no tool call; it is checked by the ten-line manual integration, which is the path for any stack the SDK cannot patch.

C ERRATUM: THE BENCHMARK BEHIND THE FIRST VERSION

The first version of this paper reported numbers that are withdrawn. This appendix says what they were, why the benchmark behind them could not support them, and how the corpus of §4.3 replaces it.

The previous version reported a 99.9% block rate at 0.09% false positives on a 5,525-record benchmark we assembled from InjecAgent [41], ToolEmu [34], OWASP payloads and a curated suite. Auditing that benchmark's construction shows it cannot support the claim. 144 records carry no arguments to inspect; 5,195 are exact duplicates; and the malicious records encode their own label in an argument key, `_attacker_instruction`, present in 3,196/3,196 InjecAgent attacks and 0/2,108 benign calls. Argument character count alone separates the classes at AUC 0.918 and fifteen surface features reach 0.996. After removing unscoreable and duplicate records, 5,525 become **186 unique evaluable calls, 21 of them benign**—and the smallest non-zero false-positive rate estimable from 21 items is $1/21 = 4.8\%$, so 0.09% was never a measurement of anything. The audit reproduces with `python -m benchmark.audit_construction`, which recovers the pre-fix loader from version control because the fix is committed and the corpus now on disk no longer exhibits the artefact.

The cause is structural. InjecAgent and ToolEmu are agent-*execution* suites: neither contains a concrete attacker tool call, because that call exists only once an agent has read an injection and acted on it. Converting them to per-call data requires fabricating the call, and no held-out split detects the resulting shortcut, since it is present in every record of the class—the failure Gururangan et al. [15] and

Geirhos et al. [12] describe, sharpened by the fact that fabrication is the only way to produce the artefact at all.

D COMPLIANCE COCKPIT

The Cockpit is the operator's view of everything in §2. The views below are unretouched screenshots from two sources, neither seeded by hand. The overview, approvals, activity and Security 360 views show seven real AgentDojo runs of the qwen3:8b agent (§4.1) replayed through the shipping SDK and gateway: every user turn and tool return is reported as context, every call is checked afresh by the current gateway, and every trace enters the hash chain as a deployed agent's would (`research/compat/shoot_replay.sh`); the holds of the last three runs are left open so the queue shows them with their evidence. The violations, policies, agents, packs, audit-log and compliance views were captured on the same replay. The DSL, settings, alignment and scan views use a copy of the gateway database that the compatibility matrix of Appendix B produced. The capture is scripted (`research/compat/shoot_cockpit.sh`): it copies the database, starts the shipping gateway and Cockpit on it, runs one pre-deployment scan of the demonstration agent and one alignment audit so that those two views show a result, and photographs every view. The alignment auditor ran on a local model (qwen3:8b through Ollama, the model of §4.1, set by environment; the script's default is qwen2.5:7b), the deployment the fallback of §2.7 describes. The interface uses one type family (Geist, with its mono for identifiers) and keeps colour for meaning: red for a block, amber for a hold, green for an allow or a covered surface; app logos keep their own colours. The overview is Figure 9.




Figure 28: Policies, with the rule hit rate on the replayed AgentDojo runs: which of the provenance pack's rules fired and how each split between block and hold—the exfiltration rule blocking three calls, the destination rule holding two, the review and destructive rules one each.




Figure 27: Violations: every call refused or held, as sentences with the app's logo and the verdict, grouped under the protection that caught it in plain words ("Outbound call nobody asked for") with the reason beneath each. The rows are the replayed AgentDojo runs: transfers to an injected IBAN blocked by the exfiltration rule. (The held invitation of the same replay is in the approval queue, Figure 29.)




Figure 29: Approvals: a held call as the reviewer sees it. The banking agent was asked to adjust the rent from a landlord's notice; the notice carried an injection, and the agent tried to redirect a standing order. The card shows what the person asked, the passage the agent read with the destination that appears only there highlighted, the arguments as fields, and the reason in plain language. The agent is paused until someone decides.




Figure 30: Activity: each agent run as a timeline titled by its request. Every step is a sentence with the app's or website's logo, AEGIS's decision and its latency; arguments and results open as fields rather than JSON. Here a bill payment whose IBAN came from an injected bill is blocked. The *All actions* tab keeps the per-call forensic view with each record's hash.




Figure 32: Policy DSL: rules over dotted facts with a dry-run, built-in examples, and the natural-language compiler whose output is a rule the operator reads before it runs.




Figure 31: Agents: one row per agent, created on first sight, with the apps it has touched as logos and how often AEGIS has had to step in—calls, held, blocked—beside when it was last seen. Registering an agent makes it *active* and declares its tool scope; an active agent can be suspended from its row.




Figure 33: Policy packs: rule sets written to a regulation—GLBA, PCI DSS v4.0, SOX, DORA, FedRAMP, HIPAA—and the instruction-provenance pack of §2.3, each citing the clauses it implements, applied with one click and a confirmation. A pack merges into the tenant's rules; a rule the operator has customised under the same name is kept.




Figure 34: Settings: the licence, which decides what unlocks (§??), and the deployment mode—*dev*, *standard*, *strict*, *financial*, *healthcare*—each a preset of which layers run, what is held for a person, and how long traces are kept. Changes hot-reload; the gateway is not restarted.




Figure 36: Pre-deployment scan (§2.8) of the demonstration agent's repository: clean, with the SARIF report and the scan history a pull-request diff is computed from.




Figure 35: Alignment auditor (§2.9): a declared goal, the thought chain and a proposed call, scored by a local model in 6.9 s with a verdict (here, aligned) and a rationale. The score becomes a policy fact.




Figure 37: Audit log: the hash-chained record with its verification and the SOC 2 evidence pack. Entries read as sentences ("Deployment mode set to custom"), not as the JSON they are stored as; editing one stored record is the attendee activity of §3.




Figure 38: Compliance: controls of SOC 2, ISO 27001, the NIST AI RMF and the EU AI Act mapped to live evidence, signed as one bundle, with the command that verifies it offline.




Figure 39: Security 360: ten ways an agent can be turned against its owner, six with their status read live from the gateway and four fixed by what the gateway always or never does—prompt injection counts as protected only when the provenance pack is applied *and* SDKs are reporting context, the audit only when the hash chains verify—and the one step that turns an uncovered surface on. Below it (not shown) the deployed detectors are joined against the agent threat ontology.

D.1 The demonstration, as photographed

Figure 10 crops these. They are the live demonstration agent of §3 (Claude Haiku 4.5, the two-line integration shown there) driven exactly as an attendee drives it, by typing the scenario's prompt into its chat page (`research/compat/shoot_demo_flow.sh`), and the Cockpit beside it. Nothing in a transcript is edited; the model does not emit the S2 call on every turn, and a turn that produced no tool call is reset and retried.




Figure 40: S1, the agent's own page: a benign `query_database` call allowed and answered. The turn completes at its normal speed with the gateway in the path.




Figure 41: S2, the agent's own page: asked for a routine install, the agent emits `curl …| sh`; the call is blocked at L1 and the refusal returns as the tool's result, so the agent explains what happened and proposes three alternatives rather than failing.




Figure 42: S3, the Cockpit's Approvals page photographed while the agent is suspended: the held `kubectl delete` with the reason the rule gives, the attendee's request, the command as a field, and the two buttons. In the scripted capture the second person's Allow is sent through the API the button calls, and the agent resumes within two polling cycles.




Figure 43: S3, the agent's own page after the approval: the held call shows as allowed, the command ran (the demonstration's shell tool simulates execution in its code; the decision precedes it), and the agent reports what happened.




Figure 44: The demonstration session in the Cockpit's Activity view: the three scenarios as one run, each step with its verdict and its latency: two allowed (the second after its hold, 4.0 s) and one blocked.

Added in this version. Figure 45 is captured the same way, on a fresh gateway after the MCP run of card G9 (`research/compat/shoot_mcp.sh`).




Figure 45: Settings, MCP tools, after the run of card G9. The changed tool is expanded with the approved description beside the one the server sends now; it stays refused until re-pinned.

E DEPLOYMENT, AS IT RUNS

Three recorded terminal sessions, rendered from their captured output (`paper-arxiv/figdata/captures/`); only API keys are elided.




Figure 46: An MCP host's configuration that reaches its server through `agentguard.mcp_proxy`, and what a host receives when the proxy refuses a call to a tool whose description changed (the scripted host of card G9).




Figure 47: `docker compose up` on a rented Linux GPU host (Ubuntu 22.04; the services bound to loopback), then a Claude Haiku 4.5 agent instrumented with the two lines of §3: its file read is allowed, its `curl …| sh` is blocked, and it tells its user why.




Figure 48: On the same deployment, an executor verifying a receipt offline against the gateway's published key: valid for the call it was issued for, not for the same call with its recipient changed after the check.