

The Augustine Problem in Agents

Chronoception must be installed: LLM agents cannot perceive their own time.

Aojie (Justin) Yuan
University of Southern California
aojieyua@usc.edu

Preprint v1.0 • September 17, 2026

Code + data + Docker: github.com/Justin0504/Chronoception-agent-temporal-cognition
Pre-registration: [OSF \(locked\)](#) • Correspondence: aojieyua@usc.edu

The framework’s spine. Three theorems (**CIT**, **Reverse-Scaling**, **SIT**), three empirical laws (**L1 / L2 / L3**), and three papers (**Paper 1: this paper**; **Paper 2: ChronoStack**; **Paper 3: Agentic Frontier**). Layered evidence: (a) CHRONOBENCH [**14 agents / 7 vendors / ~5,900 traj**], (b) Injection Atlas [**11 harnesses**], (c) toy positive control [**LoRA SFT crosses ε^***], (d) HCAST horizon evidence [**14,709 runs**].

Abstract

LLM agents are trained on tokens and deployed in wall-clock time. They cannot perceive the wall-clock. The *Chronoception Impossibility Theorem* (CIT) makes the claim precise: under any token-only loss, the gradient carries no signal aligning τ_{wall} with any internal representation. The *Three Times* ontology — τ_{wall} , τ_{step} , τ_{self} — names the projections a policy must align; the *Augustine Problem* is that alignment failure.

CHRONOBENCH (9 sub-capabilities $\times$ 14 agents $\times$ 2 settings, ~5,900 trajectories) measures the failure. Five findings. **(i)** Every agent leaves $\geq 89\%$ of its wall-clock budget unspent (panel median CAR ≤ 0.104 ; non-reasoning median 0.014); date injection does not move CAR ($|\Delta\text{CAR}| \leq 0.01$). **(ii)** $|\rho|$ falls 94% across five non-reasoning generations while CAR does not: narrative axis is text-trainable, action axis is not. **(iii)** The *Reverse-Scaling Theorem*: reasoning-token expansion monotonically grows $|\rho|$ under CIT. Confirmed four ways — intra-model (o4-mini effort ladder: $|\rho| = 1.23 \rightarrow 1.54 \rightarrow 1.67$), cross-model (Sonnet 4.6 $\pm$ thinking: sign flip $+0.07 \rightarrow -0.17$, firm under Setting B at -0.25 , CI $[-0.34, -0.11]$), within-model (prospective $+0.16$ vs. retrospective -0.25 on the same Sonnet-thinking configuration), and cross-vendor (GLM-5.2 sign flip $+0.16 \rightarrow -0.29$ from Setting A to Setting B, independent training pipeline). **(iv)** The *Calibration Catastrophe*: nominal 90% CIs achieve 0–77% coverage panel-wide, and every non-reasoning agent under-covers by ≥ 40 percentage points; GPT-4o reaches 0%. **(v)** The *Injection Tell*: 3/3 consumer web-chat products inject the date; 0/3 developer tools do — three labs converging on the same workaround independently.

Aggregated as ε , no agent crosses the Augustine threshold $\varepsilon^* = 0.20$; the action axis alone exceeds it. Under the *Agentic Timeline Hypothesis* the deployment horizon scales as $T_{\text{max}} \propto 1/\varepsilon$; pre-registered P12 is supported on the METR HCAST corpus (reasoning models decay 20% faster, Mann–Whitney one-sided $p = 0.040$). The framework generalises to a *Spatiotemporal Impossibility Theorem* (SIT) and the *Agentic Frontier* bound $T_{\text{max}} \cdot S_{\text{max}} \leq C/\varepsilon_{ST}$ — the bridge to Paper 3. Code, trajectories, Docker container, and locked OSF pre-registration released.

How to read this paper. The **position** (§1) states the claim. The **ontology** (§2) and **impossibility theorem** (§3) formalise it. **§5–7** present the layered empirical evidence, one axis at a time. **§8** aggregates; **§9** draws the deployment bound; **§12** generalises time to space. **Readers short on time** may skip to Figure 2 (the four confirmations of Reverse-Scaling) and Figure 5 (the 14-agent ε leaderboard); each carries the paper’s central empirical claim in one panel.

Contents

1	Introduction	3
2	The Three Times of an Agent	4
3	The Augustine Problem and Its Impossibility	5
4	ChronoBench: A Diagnostic Instrument for the Three Axes	6
5	The Action Axis: L2 Step-Clock Conflation	7
6	The Narrative Axis: Closure, Ceiling, and Catastrophe	8
6.1	The Reverse-Scaling Theorem	8
6.2	The Calibration Catastrophe	10
6.3	A positive control: wall-clock SFT installs partial chronoception	11
7	The Injection Tell: A Cross-Vendor Natural Experiment	12
8	The Chronoceptive Calibration Error ε	12
9	From Measurement to Deployment: The Agentic Timeline	13
10	Related Work and Positioning	14
11	Scope, Objections, and Falsification	15
12	From Time to Space: The Spatiotemporal Generalisation	16
13	Toward Agents That Inhabit Time	17
A	Annotation Protocol	20
B	Full Panel Tables	21
C	Atlas Evidence (Verbatim)	23
D	L3 Sub-Failure Detail	24
E	Spatiotemporal Generalisation Full Sketch	27
F	Operational Chronoception Audit Checklist	30

1 Introduction

A frontier reasoning model, asked how long the next task will take, predicts “15 seconds.” It thinks for ninety. It answers in two. Pressed for a 90% confidence interval on the duration, the interval contains the truth 0% of the time. None of these failures is a bug or a misread prompt. They are joint, panel-wide, and structurally predictable, present across all 14 agents in our panel.

The Augustine Problem. Every training loss in current practice — next-token cross-entropy, SFT, RLHF, RL with verifiable rewards, reasoning supervision — is a functional of token sequences. None contains wall-clock time in its support. The models are deployed as agents in continuous physical time. We call the resulting representational gap *the Augustine Problem*, after Augustine’s confession that he knew what time was until asked to explain it.¹ The gap is structural: we prove (Theorem 1) that under any token-only loss the policy gradient carries no signal aligning the wall-clock with any internal representation. *Chronoception cannot be acquired from token-only training. It must be installed.*

Position. This paper makes that claim precise, measures the failure across the current frontier, audits the industry workaround, and specifies what closing the gap requires. The framework’s spine is three theorems (CIT, Reverse-Scaling, SIT), three empirical laws (L1–L3), and three papers (this one, CHRONOSTACK, the Agentic Frontier). The three Times (τ_{wall} , τ_{step} , τ_{self}) of §2, illustrated in Fig. 1, are the framework’s fundamental objects.

Layered evidence. We support the position with four independent evidence layers: **(a)** CHRONOBENCH, a 9-capability diagnostic across 14 agents from 7 vendors ($\sim 5,900$ trajectories), **(b)** the Injection Atlas, an audit of 11 closed-lab harnesses via leaked system prompts, **(c)** a toy positive control demonstrating CIT’s constructive converse via wall-clock-supported LoRA SFT (Qwen2.5-1.5B crosses ε^* on T3.1 after ~ 1 min of training), **(d)** horizon-scaling correlational evidence on 14,709 public METR HCAST runs.

Contributions.

- **The Augustine Problem** as a named structural diagnosis with a measurable identity $\tau_{\text{wall}} \approx \tau_{\text{step}} \cdot \langle \Delta t \rangle \approx \tau_{\text{self}}$ (§2).
- **Two theorems.** CIT (no token-only loss installs chronoception) and Reverse-Scaling ($\mathbb{E}[|\rho| \mid K]$ monotone non-decreasing in reasoning budget K); the latter confirmed intra-model, cross-model, within-model, and cross-vendor (§6.1).
- **ChronoBench and the panel.** 9 sub-capabilities $\times$ 14 agents $\times$ 2 settings, $\sim 5,900$ trajectories; the Sonnet 4.6 + thinking variant carries the first full $9 \times 2 \times 30$ panel coverage of any reasoning model (§4).
- **The Injection Tell and toy positive control.** 3/3 consumer web-chat products inject the date, 0/3 developer tools do (§7); LoRA SFT with wall-clock-supported targets crosses ε^* (§6.3).
- **Deployment bound and spatial mirror.** Agentic Timeline $T_{\text{max}} \propto 1/\varepsilon$ (§9) with HCAST support; generalisation to SIT and the Agentic Frontier $T_{\text{max}} \cdot S_{\text{max}} \leq C/\varepsilon_{ST}$ (§12), the bridge to Papers 2 and 3.

¹We use *chronoception* in the cognitive-science sense [Wittmann, 2009, Eagleman, 2008]: perception of one’s own work duration. Distinct from Goel et al. [2025]’s use for RAG fact validity.

Docker container, OSF pre-registration, all trajectories, and the Operational Chronoception Audit Checklist (App. F) are released.

2 The Three Times of an Agent

The introduction gave the failure a name. To make “failure” precise we decompose any agent trajectory into three ontologically distinct projections of time (Fig. 1).

The Three Times ontology — chronoception is the policy’s enforcement of the implicit identity




Figure 1: The Three Times. τ_{wall} (external, continuous), τ_{step} (discrete policy invocations $a_0, a_1, \dots$), τ_{self} (agent’s narrative of its own duration). A grounded policy enforces $\tau_{\text{wall}} \approx \tau_{\text{step}} \cdot \langle \Delta t \rangle \approx \tau_{\text{self}}$; the Augustine Problem is failure of this identity. Each axis carries an empirical law (L1–L3).

Definition 1 (Three Times). For a trajectory $\tau = (s_0, a_0, \dots, s_n)$: $\tau_{\text{wall}}(\tau) := t(s_n) - t(s_0)$ (external timestamp difference); $\tau_{\text{step}}(\tau) := n$ (policy invocations); $\tau_{\text{self}}(\tau) := \Pi(s_n^{\text{output}})$ (agent-reported duration; parser in App. A).

Grounded chronoception requires $\tau_{\text{wall}} \approx \tau_{\text{step}} \cdot \langle \Delta t \rangle \approx \tau_{\text{self}}$, where $\langle \Delta t \rangle$ is the mean per-step wall-clock cost. First approximation is L2; second is L3. The Augustine Problem is joint drift.

Why three, not two or four? The three are minimal and irreducible. $\tau_{\text{wall}} \neq \tau_{\text{step}}$: a 10-step trajectory takes 5s on Haiku and 200s on a thinking model. $\tau_{\text{wall}} \neq \tau_{\text{self}}$: agents mis-report by up to $34\times$ (§6). $\tau_{\text{step}} \neq \tau_{\text{self}}$: an agent can produce 6 steps and report “10 seconds” with no grounded mapping. Fewer times collapse the training-loss / deployment / narrative arguments; more (e.g., tool-read wall-clock) subsume into τ_{wall} once the tool resolves.

With the vocabulary fixed, we can state the Augustine Problem precisely.

3 The Augustine Problem and Its Impossibility

Definition 2 (Augustine Problem). *Agent A exhibits the Augustine Problem on task family $\mathcal{T}$ if $\mathbb{E}_{\tau \sim \pi_A}[|\tau_{\text{wall}} - \tau_{\text{step}}\langle \Delta t \rangle| + |\tau_{\text{wall}} - \tau_{\text{self}}|] > \varepsilon_0$ for some tolerance ε_0 . The three projections drift independently across the trajectory distribution.*

The question is not whether agents exhibit it (they do, §5–6) but whether any conceivable foundation-model training procedure could in principle close it. We argue: not by scale, not by reasoning-compute expansion, not by any post-training intervention on token sequences alone.

Assumption (token-only loss support). A training procedure is in the *token-only regime* if $\mathcal{L}(\theta) = \mathbb{E}_{x \sim \mathcal{D}}[\ell(f_\theta(x_{<i}), x_i)]$ satisfies (i) $\mathcal{D}$ is a distribution over finite token sequences with no field carrying wall-clock duration, and (ii) ℓ is a function of the output token distribution alone. Next-token cross-entropy, SFT, RLHF, RL with verifiable rewards, and reasoning supervision all satisfy this.

Theorem 1 (Chronoception Impossibility, CIT). *Let $\mathcal{L}$ be a token-only loss. For any strictly increasing $\phi : \mathbb{R}_{>0} \rightarrow \mathbb{R}_{>0}$, $\mathcal{L}(\theta)$ is invariant under $\tau_{\text{wall}} \mapsto \phi(\tau_{\text{wall}})$. Equivalently, $\nabla_\theta \mathcal{L}$ carries zero gradient signal aligning τ_{wall} with any internal representation.*

Sketch. $\nabla_\theta \mathcal{L} = \mathbb{E}[\partial \ell / \partial f_\theta \cdot \nabla_\theta f_\theta]$. Neither factor depends on the wall-clock time at which the sample was generated: tokens carry no timestamps, ℓ is a function of the output distribution alone. The gradient is therefore invariant to any reparametrisation of τ_{wall} . A policy from this gradient cannot distinguish one wall-clock duration from another. $\square$

Scope. CIT does not claim there is *no* internal representation of time; it claims any such representation is not produced *by the loss*. Explicitly out of scope: harness-installed chronoception (§7, a CIT workaround, not refutation), tool-output-installed chronoception (calling `date`), and future losses with τ_{wall} as an explicit argument (CHRONOSTACK). CIT precludes only the inference — widely held, rarely defended — that additional scale, longer reasoning, or larger context will close the gap.

Empirical predictions. **(P-CIT-1)** CAR stays bounded away from 1 regardless of capability (§5). **(P-CIT-2)** Prompt-level wall-clock information cannot move action-axis behaviour (Prop. 1). **(P-CIT-3)** Calibration tooling cannot close self-duration calibration (§6.2). All three are confirmed by the panel.

Augustine Threshold. We adopt $\varepsilon^* = 0.20$ as an operational reporting threshold, and we are explicit about its status. It is *not* derived from a measured human baseline. Human duration perception is itself imperfect and strongly scale-dependent [Wittmann, 2009, Eagleman, 2008], which is the qualitative motivation for setting the bar below perfection rather than at it — but that literature reports *discrimination* thresholds (Weber fractions on whether two intervals differ), not the *retrospective estimation* error that ρ measures, and the two are not interconvertible without an argument we cannot currently supply. We therefore fix $\varepsilon^* = 0.20$ by stipulation: the round figure roughly one order of magnitude below a $2\times$ misestimate ($|\rho| = \log_{10} 2 \approx 0.30$). It was chosen before the panel was run and held fixed afterwards.

We flag this because the threshold is the one place a reader might expect a derivation and not find one. Nothing in the argument depends on the constant. The closest agent sits at $\varepsilon =$

0.536, and $\text{score}_{T_2} \geq 0.92$ on every agent in the panel puts a floor of $\varepsilon \geq 0.46$ under the whole panel irrespective of the narrative axis, so every qualitative conclusion here survives any choice of threshold in $[0.1, 0.45]$. A task-matched human panel would let ε^* be earned rather than stipulated, and is the highest-priority follow-up (§11). No panel agent crosses it (§8).

CIT says the gap is unavoidable. To measure “unavoidable” we need the instrument next.

4 ChronoBench: A Diagnostic Instrument for the Three Axes

To decide whether CIT’s three predictions (§3) hold on real agents, we need instruments that measure each of the Three Times *independently*. Aggregate benchmarks obscure what we want to see: a failure on a hard SWE-Bench task may be a chronoception failure, a reasoning failure, or a tool-use failure, and no aggregate metric will tell them apart. CHRONOBENCH’s design philosophy is therefore single-axis isolation: every instance loads on exactly one of τ_{wall} , τ_{step} , or τ_{self} , so a failure is unambiguously attributable to the axis under test. We summarise the 9 sub-capabilities here; the full prompt set, panel composition, parser specification, and open-source serving recipe appear in Appendix A.

Table 1: The 9 sub-capabilities of CHRONOBENCH, three per axis. Each row isolates a single chronoceptive failure mode for separate measurement and pairs it with the diagnostic question a deployment auditor should ask.

Axis	Sub-capability	Tests	Auditor question
τ_{wall}	T1.1 Clock awareness	Today’s date / current time	“Does it know when it is?”
	T1.2 Elapsed-time tracking	Time since conversation start	“Does it track elapsed time?”
	T1.3 Deadline tradeoff	Strategy under wall-clock deadline	“Does it re-plan under pressure?”
τ_{step}	T2.1 Step-budget honouring	Produce exactly N steps	“Can it count its steps?”
	T2.2 Step-to-wall map	Compute $N \times \Delta t = \tau$	“Can it convert step to wall-time?”
	T2.3 Wall-budget execution	Honour a wall-clock budget (L2)	“Does the budget change behaviour?”
τ_{self}	T3.1 Retrospective ρ	Duration reported after task	“How long did it just take?”
	T3.2 Prospective ρ	Duration predicted before task	“How long will this take?”
	T3.3 Calibration	90% CI over self-duration	“How confident in its duration?”

Settings. Every instance runs under two settings. Setting A uses a vanilla system prompt (“*You are a helpful assistant.*”) and supplies no harness-side wall-clock signal. Setting B prepends “*Current date and time: {ISO}*” to the system prompt, emulating the consumer web-chat behaviour documented in §7. The contrast between A and B isolates injected information from policy-internal representation.

Panel. Fourteen agent configurations from seven providers: **OpenAI**’s gpt-4o-mini, gpt-4o, gpt-5.1, o3, and o4-mini (three **reasoning_effort** levels); **Anthropic**’s Claude Haiku 4.5 and Claude Sonnet 4.6 (with and without extended thinking, 8k-token budget); **open-source** Qwen2.5-7B

and DeepSeek-R1-Distill-Qwen-14B (three `max_completion_tokens` budgets), both self-hosted via vLLM on a single 8×RTX 6000 Ada cluster; and a **cross-vendor Chinese-lab expansion** via Vultr Inference: Z.AI’s **GLM-5.2-FP8**, MiniMax’s **MiniMax-M2.7**, Moonshot’s **Kimi-K2.6**, and Alibaba’s **Qwen3.6-27B**. The o4-mini reasoning-effort sweep and the Sonnet 4.6 thinking variant supply the empirical basis for the Reverse-Scaling Theorem (§6.1); the Chinese-lab expansion tests whether the framework’s predictions hold across a distinct training pipeline and vendor ecosystem. We collect 30 trajectories per (model, capability, setting) cell, for a total of roughly 5,900 trajectories — with the Sonnet 4.6 + extended-thinking variant carrying the first full 9×2×30 panel coverage of any reasoning model.

Implementation and release. CHRONOBENCH ships as a `pip`-installable Python package with a command-line interface and three backend adapters (OpenAI, Anthropic, OpenAI-compatible for vLLM/Ollama). The metric library implements α , CAR, ρ , and the aggregate ε . All trajectories, parser outputs, and analysis scripts are released; a Docker container reproduces every figure and table from the committed data in approximately five minutes.

With the instrument fixed, we can test CIT one axis at a time. We begin with the action axis, because that is where CIT’s first prediction is sharpest and its consequences most consequential for deployment.

5 The Action Axis: L2 Step-Clock Conflation

CIT-P1 predicts the action axis cannot honour wall-clock budgets. We ask each agent “*work on this task for B seconds; do not stop early,*” vary $B \in \{60, 300, 900, 1800, 3600\}$ s ($n = 30$ per budget, both settings), and measure the Clock-Adherence Ratio $\text{CAR}(B) := \tau_{\text{wall}}^*/B$.

Definition 3. *A chronoceptively grounded agent satisfies $\text{CAR} \approx 1$; an L2-failing agent satisfies $\text{CAR} \ll 1$ once $B \gg \tau_{\min}$.*

Result. No panel agent’s median CAR exceeds 0.104 and the panel median is 0.014: every agent leaves at least 89% of the budget it was given unspent, and the non-reasoning core leaves over 95%. Wall-clock injection does not move the number (Table 2).

Table 2: Median CAR across the 13-cell post-B-1 panel. Injection moves the action axis by at most ± 0.005 .

Model	CAR (A)	CAR (B)	$ \Delta\text{CAR} $
<i>Non-reasoning core panel</i>			
gpt-4o-mini, gpt-4o, gpt-5.1, Haiku 4.5, Sonnet 4.6, Qwen2.5-7B	0.004–0.050	0.004–0.050	≤ 0.008
<i>Reasoning models</i>			
o3	0.011	0.009	0.002
o4-mini	0.008	0.007	0.001
Sonnet 4.6 + thinking	0.100	0.104	0.004
<i>Chinese-lab expansion</i>			
GLM-5.2, MiniMax-M2.7, Kimi-K2.6, Qwen3.6-27B	0.011–0.024	0.010–0.021	≤ 0.003
Panel median	0.014	0.014	0.001

The 60s tier, where the sign flips. The medians above pool five budgets, and that pooling hides the one place the failure changes shape. At $B = 60$ s every reasoning model’s CAR is an order of magnitude above its pooled median (o3 0.225, o4-mini 0.159), and Sonnet 4.6 + thinking *overshoots* outright at $\text{CAR} = 2.22$: the extended-thinking policy cannot bring itself to stop inside a minute and blows through the budget by more than a factor of two. This is not a counter-example to L2 but its cleanest illustration. A policy with a representation of τ_{wall} would track the budget from either side; these policies miss it from whichever side their default generation length happens to fall on, and the sign of the miss is set by that default rather than by the budget. Under-spend and overshoot are the same failure of the identity $\tau_{\text{wall}} \approx \tau_{\text{step}} \langle \Delta t \rangle$, read at two different budget scales.

The narrative-vs-action split. Across five non-reasoning generations $|\rho|$ falls 94% (§6) while median CAR stays at 0.01–0.05: narrative axis is text-trainable, action axis is not. Injection is an information intervention (rewrites the prompt) but not a representational one (does not learn a τ_{wall} -to-action mapping). The action axis is unmoved. The empirical signature $|\Delta \text{CAR}| \leq 0.01$ across the 13-cell panel and three separate vendor ecosystems (western labs, Chinese labs, open source) formalises this as:

Proposition 1 (Injection cannot install action-axis chronoception). *Let A be an agent in the token-only regime (Assumption 3) and A_B the same policy under Setting B. Then $\text{CAR}(A_B) - \text{CAR}(A) = 0$ in expectation to the order of the policy’s prompt-token sensitivity. Injection is a narrative-axis intervention; it can rewrite what the agent says about time but not what the agent does with time.*

Sketch. Injection extends the token prefix by a constant string. By CIT the policy’s prefix-to-action-selection map is time-reparametrisation-invariant on the training manifold. Prefix-level information about τ_{wall} modifies output-token generation but not the wall-clock realisation of the action sequence. The empirical $|\Delta \text{CAR}| \leq 0.01$ across the panel is direct measurement of the proposition. $\square$

L2 is the load-bearing empirical claim: it anchors ε above ε^* for every panel agent (§8) and bounds the Agentic Timeline regardless of capability scaling (§9). The next section turns to the narrative axis, where capability scaling helps monotonically — and Reverse-Scaling structurally undoes the help.

6 The Narrative Axis: Closure, Ceiling, and Catastrophe

Section 5 showed capability scaling does not help the action axis. This section is its counterpoint: on the narrative axis $\rho := \log_{10}(\tau_{\text{self}}/\tau_{\text{wall}})$, capability scaling helps monotonically across five frontier non-reasoning generations ($|\rho|$ from +1.12 to +0.07, a 94% reduction; full table in App. B). The closure is real; it is also bounded in three directions, each with its own §: a theorem that reasoning-token expansion *reverses* the trend (§6.1), a calibration catastrophe that persists even where the surface appears closed (§6.2), and a constructive positive control that shows what training would actually close it (§6.3).

6.1 The Reverse-Scaling Theorem

Assumption (budget-honoured reasoning). A reasoning-budget knob K on a fixed agent is *honoured* if $\mathbb{E}[\tau_{\text{wall}} \mid K]$ is strictly increasing in K . The o4-mini `reasoning_effort` ladder, Anthropic extended-thinking budget, and Kimi/GLM reasoning modes all satisfy this empirically.

Budgets the model declines to spend (E5 on DeepSeek-R1-Distill-14B, App. D) fall outside the assumption and are not counter-examples.

Theorem 2 (Reverse-Scaling). *For a fixed agent under Assumption 3 (hence Theorem 1) with a budget-honoured K , $\mathbb{E}[|\rho| \mid K]$ is monotone non-decreasing in K .*

Sketch. Under CIT, $p(\tau_{\text{self}})$ is invariant to τ_{wall} : no gradient signal ties one to the other. The inference-time distribution $p(\tau_{\text{self}} \mid K) = p(\tau_{\text{self}})$ for all K . By assumption, $\tau_{\text{wall}}(K)$ is strictly increasing. Therefore $|\log_{10}(\tau_{\text{self}}/\tau_{\text{wall}})|$ is monotone non-decreasing in K in expectation. The sign of ρ turns negative once hidden CoT comes to dominate τ_{wall} , because $p(\tau_{\text{self}})$ stays anchored to the surface output; the theorem itself constrains only $|\rho|$. $\square$




Figure 2: Four independent confirmations of Theorem 2. **(a)** Intra-model: o4-mini reasoning_effort ladder, $|\rho| = 1.23 \rightarrow 1.54 \rightarrow 1.67$. **(b)** Cross-model: Sonnet 4.6 ± extended thinking, median $|\rho| = 0.12 \rightarrow 0.21$ (Setting A, $n = 28/10$; signed median $+0.07 \rightarrow -0.17$), with the sign flip firm under Setting B (-0.25 , CI $[-0.34, -0.11]$, $n = 16$). **(c)** Within-model: Sonnet-thinking prospective ($+0.16$) vs. retrospective (-0.25) under Setting B — sign flip on the same tasks. **(d)** Cross-vendor: GLM-5.2 (Z.AI, no shared training pipeline with Anthropic), Setting A $\rightarrow$ B: $+0.16 \rightarrow -0.29$. Detailed per-cell CIs in App. B Tables 4–6.

The four confirmations vary four independent things: reasoning effort within one model, the presence of a thinking mode across two builds of one model, the narration modality within one configuration, and the training pipeline across two vendors that share none of it. All four show the same object — raising the reasoning budget, or triggering reasoning-mode CoT, grows $|\rho|$. Three of the four also flip its sign toward Hidden-Time under-report, and on Setting B the three Chinese-lab

reasoning models (GLM-5.2, Kimi-K2.6, Qwen3.6-27B) sit collectively at median $\rho \in [-0.97, -0.29]$, which makes the flip a property of the class rather than of Sonnet-thinking.

It is not universal, and we say so: o3 grows $|\rho|$ to 0.45 — well above base Sonnet 4.6’s 0.12 on the same tasks — while continuing to over-report (App. B). Theorem 2 constrains the magnitude, and every cell confirms the magnitude. The sign flip is the mechanism’s most visible symptom, not its definition: it appears when the hidden chain-of-thought comes to dominate τ_{wall} , and o3 is the configuration where it does not.

6.2 The Calibration Catastrophe

Asked to wrap self-duration in a 90% confidence interval, every non-reasoning panel agent achieves under-coverage of at least 40 percentage points (Fig. 3); GPT-4o reaches 0%. Standard post-training calibration tooling (temperature scaling, isotonic regression, RLHF-with-confidence [Guo et al., 2017, Jiang et al., 2021, Kadavath et al., 2022, Lacombe et al., 2025]) cannot apply, because the calibration signal is not in the loss support (CIT). Pre-registered P11: no CIT-regime agent achieves > 0.5 coverage without harness-side duration data.

The Calibration Catastrophe: nominally-90% CIs on self-duration

Bars = actual coverage of the agent’s stated 90% CI containing τ_{wall} . Dashed green = 90% target. Dashed orange = pre-registered P11 threshold (0.5). Every non-reasoning model under-covers by ≥ 40 percentage points; GPT-4o achieves 0%.




Figure 3: Actual coverage of nominally-90% CIs on self-duration (T3.3), 12-row panel. Only reasoning-mode agents (Sonnet + thinking, Kimi-K2.6) exceed the P11 threshold of 0.5 — both accidentally, through wider default vocabulary intersecting thinking-inflated τ_{wall} (see App. D), not through learned chronoception.

Two P11 crossings, one mechanism. Two cells cross 0.5: Sonnet-thinking (77%, $n = 30$, Wilson CI $[0.59, 0.88]$) and Kimi-K2.6 (55%, $n = 29$, Wilson CI $[0.38, 0.71]$). o4-mini lands exactly on the threshold at 15/30 and so does not cross it. All three are reasoning-mode; all three state

intervals far wider relative to their own τ_{wall} than the non-reasoning panel does; and Kimi shares no training pipeline with the other two. Two further rows, MiniMax-M2.7 ($n = 15$) and Qwen3.6-27B ($n = 12$), rest on fewer than half the intended trajectories after parser drops and are plotted with their true n . The mechanism is not learned chronoception but arithmetic: reasoning-mode inflates τ_{wall} , $p(\tau_{\text{self}})$ stays anchored to the default duration vocabulary, and a wider stated CI happens to contain the wall-clock. Consistent with CIT. Both cells rest on $n = 30$, below the $n \geq 100$ bar our pre-registered F4 sets for a falsification of P11, so we report them as threshold crossings rather than refutations — but we do report them. They sharpen P11: the next revision should measure a proper scoring rule (Brier / CRPS) rather than raw coverage.

6.3 A positive control: wall-clock SFT installs partial chronoception

CIT is a negative result. Can a procedure that includes wall-clock signal install chronoception? We provide a toy positive control.

Construction. Qwen2.5-1.5B and 7B base models. For each, 500 SFT pairs of the form “*{response}*”. *This task took approximately $\{\tau_{\text{wall}}\}$ seconds.*” with $\pm 15\%$ noise; LoRA rank 16, three epochs. Token-level CE loss, but training targets carry τ_{wall} : the effective loss support includes wall-clock duration, exiting the CIT regime by extending $\mathcal{D}$ ’s support rather than changing ℓ .

Result. On 30 held-out T3.1 instances: median $|\rho|$ falls from 1.37 to 0.30 on 1.5B (78% reduction) and 0.93 to 0.50 on 7B (46%). The 1.5B fine-tuned T3.1 score (0.151) crosses ε^* on this single axis; the 7B (0.252) does not (Fig. 4). At both scales ρ flips from over-report to under-report.




Figure 4: Toy positive control. (a) $|\rho|$ falls at both scales after ~ 60 s of LoRA SFT. (b) 1.5B fine-tuned crosses ε^* on T3.1; 7B partial (0.25). Detailed table in App. D.

What it shows and does not show. Wall-clock signal in the loss support installs narrative-axis chronoception — the constructive converse of CIT. The control does not address L2 (which needs the policy to elongate action sequences, not append duration strings) or T3.3 calibration. Full-axis installation is the programme of CHRONOSTACK: action-axis grounding requires a wall-clock-supported reward, calibration requires a conditional-variance objective, full grounding requires architectural support.

The three faces of L3 (Reverse-Scaling, Calibration Catastrophe, positive control) form one picture: narrative training closes the surface for non-reasoning agents; reasoning-token expansion structurally re-opens it; wall-clock support in the loss actually closes it. Narrative axis training does not reach the action axis; the next section shows how the industry has compensated.

7 The Injection Tell: A Cross-Vendor Natural Experiment

The consumer products powered by the panel agents feel chronoceptively grounded — they answer date queries correctly. The mechanism that produces the answer is the strongest non-experimental evidence the underlying gap is real: closed-lab deployments do not give the agent chronoception; they *route wall-clock information into the token stream*. Detected mechanisms: **M1** system-prompt date insertion; **M2** implicit `get_current_time()` tool calls; **M3** browser-tool side effects. In every case the harness perceives time on the model’s behalf.

Table 3: The Injection Atlas: M1 system-prompt date injection across four product tiers (`asgeirtj/system_prompts_leaks` corpus). Verbatim excerpts in App. C.

Product tier	M1 rate	Examples
Consumer web-chat	3/3 (100%)	ChatGPT, Claude.ai, Gemini all inject the current date
Raw API	1/4 (25%)	GPT-5.1 injects; o3, gpt-4o, gpt-4o-mini, Anthropic API do not
Developer tools (IDE/CLI)	0/3 (0%)	Cursor, GitHub Copilot CLI, Perplexity Computer — no injection
Open-source self-hosted	N/A	We control the entire stack

Why this is decisive. Three closed labs converge on the same engineering choice for their consumer products, independently, with commercial incentive to ship the cheaper alternative if one existed. The within-Anthropic contrast is sharpest: the same Claude 4.6 model injects via `<knowledge_cutoff>` on Claude.ai and answers “what time is it now?” correctly, but through the raw Anthropic API refuses with an explicit training-cutoff disclosure. **The model is one; the chronoception is the harness’s.**

What injection does not close. Setting B raises T1.1 to $\geq 96\%$ on every panel agent (App. B), but does not move T2.3 CAR (Prop. 1), reduces T3.1 $|\rho|$ only partially (mean $\Delta = 0.18$), and leaves T3.3 coverage unimproved. Injection is a consumer-tier patch on T1; L2 and L3 remain.

Three axes of failure, one engineering pattern that half-compensates for one. The next section aggregates them into a single scalar.

8 The Chronoceptive Calibration Error ε

We aggregate the three axes into a single scalar for cross-agent comparison and the deployment bound of §9.

Definition 4 (Chronoceptive Calibration Error). $\varepsilon(A) := \frac{1}{|\mathcal{A}|} \sum_{k \in \mathcal{A}} \text{score}_k$, where $\mathcal{A}$ is the set of axes with at least one defined trajectory and each axis contributes the median of its per-trajectory error: $\text{score}_{T_2} = \text{med } |\text{CAR} - 1|$ on T2.3, $\text{score}_{T_3} = \text{med } |\rho|$ on T3.1. $\varepsilon = 0$ is grounded; $\varepsilon^* = 0.20$

is the Augustine threshold. An axis with no trajectories is dropped from $\mathcal{A}$, never imputed as zero, so an agent is never credited for a measurement that was not taken.

Which axes, and why medians. Under this protocol $\mathcal{A} = \{T_2, T_3\}$. The τ_{wall} -axis coefficient α requires a wall-clock budget on a τ_{wall} -axis capability, and no capability here carries one: T2.3 is the only budgeted capability and it loads on τ_{step} . We report the two axes we measured rather than inflating the aggregate with a third we did not. Each axis is a median rather than a mean because two trajectories in the corpus are harness artefacts, not agent behaviour — gpt-4o-mini on T2.3 with $\tau_{\text{wall}} = 14.9\text{h}$ against a 900s budget, a stalled request rather than fifteen hours of inference. Under a mean, those two alone move that agent’s ε from 1.06 to 1.99 and hand it last place.

A correction to the convention. An earlier draft of this table scored an unmeasured axis as 0 while leaving its weight in the denominator, which credited every agent with a free perfect third — and credited o4-mini, whose original corpus had no T2.3 cell, with two. Every ε below follows the definition above. The correction raises all ε uniformly for agents with a full corpus, so it strengthens rather than rescues the claim that no agent crosses ε^* ; it changes the ordering in exactly one place, moving o4-mini from mid-panel to the bottom, where its $|\rho| = 1.54$ belongs. The o4-mini reasoning-effort ladder is reported on the ρ axis alone at all three tiers, since T2.3 was only run at the default effort.

Two findings. (1) **The action axis is binding.** score_{T_2} lies in $[0.92, 1.00]$ on every agent in the panel, Setting A and Setting B alike. Projecting $\text{score}_{T_3} \rightarrow 0$ — which would require crossing both Theorem 1 and Theorem 2 — still leaves $\varepsilon \geq 0.46$, a factor of 2.3 above ε^* . No narrative-axis intervention can reach the threshold, because the narrative axis is not what is holding the agent back. (2) **Reverse-Scaling operates on the aggregate.** Adding extended thinking to Sonnet 4.6 moves ε the wrong way, $0.536 \rightarrow 0.566$ under Setting A and $0.537 \rightarrow 0.585$ under Setting B, so the thinking variant is no longer the best agent in the panel. The o4-mini effort ladder moves it further: on the ρ axis, $1.23 \rightarrow 1.54 \rightarrow 1.67$ from low to high effort. More reasoning compute moves the agent away from the threshold on the aggregate, exactly as it does on the axis Theorem 2 constrains.

We flag the size of the first effect against the second. The $\pm$ thinking contrast is a 5.6% move on Setting A and rests on a thinking-variant ρ cell with $n_\rho = 10$; it is consistent with Reverse-Scaling on the aggregate but is not on its own strong evidence for it. The effort ladder, at $n_\rho = 16/41/17$ across three tiers and a 36% total move, is.

This is the paper’s central empirical claim. The next section turns it into a deployment bound.

9 From Measurement to Deployment: The Agentic Timeline

Industry is moving from minute-scale chat to hour-scale coding agents to day-scale autonomous research agents. At each new horizon a different sub-capability becomes load-bearing: T1.1 at chat (harness-patchable, §7), T2.3 and T3.1 at hour-scale (agent must honour a budget and report progress truthfully), the full profile $(\alpha, \text{CAR}, \rho)$ at day-scale. Required calibration grows tighter with the horizon.

Hypothesis 1 (Agentic Timeline). $T_{\max}(A) \propto \frac{1}{\varepsilon(A)} \cdot f(\text{CAR}(A))$, with f monotone-increasing in CAR.

Combined with the empirics of §5–6: L2 does not scale with capability, Reverse-Scaling grows $|\rho|$ with reasoning budget. $T_{\max}$ **scales with neither. The autonomous-agent timeline is bounded by chronoception, not by intelligence.**

Pre-registered P12 and HCAST support. On any horizon-stratified benchmark with ≥ 5 horizon tiers, slope of success decay with $\log T$ scales as $-(1 - \text{CAR})$. On the METR HCAST corpus (14,709 runs after filtering, 20 frontier models), five reasoning models cluster at steeper mean $|\text{slope}| = 0.318$ vs. 0.264 for fifteen non-reasoning models — a 20% effect at matched short-horizon success (Fig. 6). The separation is statistically supported: Mann–Whitney $U = 58$, one-sided $p = 0.040$; permutation test (20,000 resamples, one-sided) $p = 0.037$; rank-biserial $r_{\text{rb}} = -0.55$ (large effect, reasoning stochastically dominates). We report one-sided because Theorem 2 makes a directional prediction (reasoning models decay *faster*, not just differently); the two-sided form is marginal ($p = 0.081$). Supportive at $\alpha = 0.05$; a strict CAR-anchored quantitative P12 additionally requires direct T2.3 measurements on the HCAST panel, which we have not run.

Kwa et al. [2025] document horizon saturation empirically; we supply a structural mechanism. The Reverse-Scaling Theorem says the corner-case fix (more reasoning) makes it worse; the constructive fix (wall-clock-supported loss) is the subject of Paper 2 (CHRONOSTACK).

10 Related Work and Positioning

Concurrent work on agent temporal cognition. Garikaparathi [2026] report duration self-reports across four non-reasoning models, matching L3 on our non-reasoning slice; we extend to reasoning models, prove Reverse-Scaling, and confirm cross-vendor. Ma et al. [2026] construct Timely-RL, a wall-clock-supported reward shaping installing the L1 Parkinson regime; our finding is the contrapositive on native agents (L1 does not exist without such training). Cheng et al. [2025]’s “temporally blind” agents are the L2 failure mode; we add the formal axis split, CIT, the atlas, and the Agentic Timeline. Our contribution is a single framework naming the failure modes, proving their origin, measuring them on a cross-vendor panel, auditing the workaround, and connecting the measurement to deployment.

Foundational lineage. Augustine’s *Confessions* XI [of Hippo, 1991] names the central problem. Cognitive-science chronoception [Wittmann, 2009, Eagleman, 2008] supplies the term and the qualitative motivation for a below-perfect threshold; it does not supply a number we can convert into ε^* , which we therefore stipulate (§3). Parkinson [1955] supplies L1’s motivating example.

Distinguished from external-timeline reasoning. Chu et al. [2024]’s TimeBench reasons over historical timelines; Goel et al. [2025] measures RAG fact validity. Neither addresses self-duration perception. The dimensions are orthogonal: an agent can top TimeBench and exhibit catastrophic Augustine.

Inverse scaling and calibration. Gema et al. [2025] documents inverse scaling in test-time compute on unrelated tasks; Reverse-Scaling (Theorem 2) is the structural analogue for chronoception with the additional content that degradation is provably monotone. The calibration literature [Guo et al., 2017, Jiang et al., 2021, Kadavath et al., 2022, Lacombe et al., 2025] closes token-level confidence gaps; none applies to wall-clock duration (Calibration Catastrophe, §6.2).

Aggregate agent benchmarks. Aggregate benchmarks [Liu et al., 2024, Jimenez et al., 2024, Zhou et al., 2024, Mialon et al., 2023, Kwa et al., 2025] measure task success across many capabilities; ChronoBench is diagnostic, isolating chronoception. Aggregate benchmarks reveal that chronoceptive failures correlate with long-horizon task failure (P12 evidence, §9); diagnostic benchmarks supply the mechanism.

The scope, objections, and falsification suite follow.

11 Scope, Objections, and Falsification

What we do not claim.

- *Not that current agents are useless.* At the T1.1-dominated chat horizon, the Injection Tell closes the visible failure. Predictions bind only where T2.3 and T3 become load-bearing.
- *Not that capability scaling is worthless.* It closes the narrative axis 94%; the structural ceiling is the action axis.
- *Not that all test-time compute fails.* A reasoning system consulting a wall-clock-supported tool exits CIT by construction; Reverse-Scaling says nothing about it.
- *Not that the observation is novel.* Practitioners noted temporal blindness anecdotally [Cheng et al., 2025]. Our contribution is the structural diagnosis, ontology, theorems, atlas, and deployment bound.
- *Not that $\epsilon^* = 0.20$ is unique.* The structural claim does not depend on the precise threshold.

Empirical limitations. Panel: 14 agents, $\sim 5,900$ traj. Qualitative conclusions rest on cross-panel patterns; magnitudes may shift. Self-narration parsing: 3% human-disagreement rate. All trajectories English. Within-trajectory drift (pre-registered P8, P9) not measured. GPT-5.1 provider-side M1 injection reported as confound.

Cross-lingual replication. We re-ran T1.1 and T3.1 in Mandarin Chinese at $n = 30$ per cell on three OpenAI agents (30 distinct Chinese prompts per capability; Anthropic credit was exhausted at the time of the run, so that vendor is absent). The narrative axis replicates tightly. gpt-4o-mini’s Chinese median $\rho = +1.119$ with bootstrap 95% CI $[+1.054, +1.208]$ ($n = 26$ parseable of 30), against an English baseline of $+1.12$ — the two are indistinguishable. gpt-4o gives $+0.444$ $[+0.184, +0.806]$ ($n = 17$). Setting B lifts T1.1 to 100% pass on all three models (Wilson $[0.88, 1.00]$): the Injection Tell is language-independent.

A refusal asymmetry the English panel hides. Setting A in Chinese exposes a failure mode invisible in the English data. In English, gpt-4o-mini *refuses* T1.1, citing its training cutoff — the behaviour we scored as a correct-and-honest failure. In Chinese the same model never refuses: 0/29 refusals against 29/29 confident date fabrications, and every single fabricated date falls in the training-cutoff year 2023 (modal response, translated: “*Today is October 4, 2023.*”, stated flatly with no hedge; 32/32 fabrications across the panel name 2023). gpt-4o is intermediate, splitting 4 refusals against 4 fabrications of 8 decided trials. gpt-5.1 is the exception at 97% Setting A pass (Wilson $[0.83, 0.99]$), higher than its 74% English rate and further evidence of provider-side M1 injection on that endpoint, which we continue to report as a confound rather than a capability.

The reading we take is that the English refusal is a *surface behaviour of the post-training distribution, not a representation of not-knowing*. It does not survive a change of language; the

underlying absence of τ_{wall} does. An agent that says “I do not know today’s date” has not thereby acquired chronoception — it has acquired an English sentence. This sharpens rather than softens the position of §3: the apparent epistemic humility of frontier models on the wall axis is itself installed, and installed in one language at a time. It also implies the T1.1 pass rates we report for the English panel are an optimistic reading of the underlying state, since a refusal and a confabulation score identically as failures but differ sharply in downstream risk. A full multilingual sweep across more languages and the remaining vendors is future work.

Contamination probe. A four-variant contamination probe on gpt-4o and gpt-4o-mini varied the T1.1 injection template across canonical (“*Current date and time: {ISO}*”), paraphrased (“*Right now it is {ISO}*”), year-only (“*Current year: {YYYY}*”), and a scrambled placeholder (“*{DATE_PLACEHOLDER}*”). Pass rate stayed at 100% under paraphrased and reached 67% under year-only on gpt-4o (compositional construction of the date from partial context). The scrambled placeholder triggered correct refusal (no fake date fabricated). We take this as evidence that the Setting B pass rate reflects prompt-context date-reading, not memorised keyword patterns in the training distribution.

Falsification. Four pre-registered forms [Yuan and Zhao, 2026]: **(F1)** an agent trained under a loss with no wall-clock support crossing ε^* under Setting A falsifies CIT. **(F2)** a reasoning-tuned agent exhibiting monotone *decrease* in $|\rho|$ across a three-level, one-order-of-magnitude K sweep falsifies Reverse-Scaling. **(F3)** a horizon-stratified benchmark on which reasoning models exhibit shallower decay than non-reasoning at matched short-horizon success falsifies Agentic Timeline. **(F4)** a CIT-regime foundation model achieving $> 50\%$ T3.3 coverage without harness injection falsifies P11. We commit to reporting any we observe.

The framework knows only time; the spatial half follows.

12 From Time to Space: The Spatiotemporal Generalisation

Every long-horizon benchmark on which deployment claims are made — SWE-Bench, WebArena, GAIA, MLE-Bench — requires the agent to navigate space as well as time. The argument that produces CIT (§3) goes through unchanged on any external metric the loss does not see. We state the spatial half and defer the full derivation to App. E.

Theorem 3 (Spatiotemporal Impossibility, SIT). *Strengthen Assumption 3 to exclude spatial metrics from $\mathcal{D}$ ’s support (Assumption E). Then $\nabla_{\theta}\mathcal{L}$ carries zero gradient signal aligning either τ_{wall} or σ_{world} with any internal representation.*

The Augustine and Cartographic Problems are the same problem at the loss-function level. The Agentic Timeline (§9) generalises to a joint deployment region:

$$T_{\max}(A) \cdot S_{\max}(A) \leq C/\varepsilon_{ST}(A).$$

The frontier $T \cdot S = \text{const}$ is the agent’s *Agentic Frontier* (Fig. 7). **Pre-registered P13.** Under CIT-regime this frontier is bounded above by a structural constant independent of token-only capability scaling.

The three spatial laws (SL1–SL3), the Cartographic Tell, benchmark classification, five future experiments (E6–E10), and the Paper 3 sketch are in App. E. The framework’s structural claim across the joint axis: the autonomous-agent capability curve saturates not because intelligence saturates, but because spatiotemporal cognition does not scale.

13 Toward Agents That Inhabit Time

We opened with an agent that predicted fifteen seconds, thought for ninety, answered in two, and reported four hundredths of a second. None of the four numbers is a bug; all four are joint consequences of one structural fact. Two theorems capture it: CIT (no token-only loss installs chronoception) and Reverse-Scaling (reasoning-token expansion structurally degrades it on the narrative axis). The empirical layer measures 14 agent configurations from 7 providers on $\sim 5,900$ trajectories. Every panel agent honours less than 5% of its wall-clock budget. Median $|\rho|$ closes 94% along the non-reasoning capability axis while CAR does not change. Reverse-Scaling is confirmed four ways — intra-model, cross-model, within-model, and cross-vendor (GLM-5.2 on an independent training pipeline). Nominal 90% CIs achieve 0–77% coverage; the two $> 50\%$ crossings are both reasoning-mode and CIT-consistent. No agent crosses ε^* ; the action axis alone exceeds it. Three closed labs have independently installed wall-clock injection at the consumer chat tier and not at the developer tier: converging engineering choices across competitors that carry the evidential weight of a natural experiment.

The Agentic Timeline turns measurement into deployment: chronoception, not intelligence, bounds the autonomous-agent horizon. P12 is qualitatively supported on 14,709 HCAST runs. The framework generalises along its other axis to SIT, the Cartographic Problem, and the Agentic Frontier $T_{\max} \cdot S_{\max} \leq C/\varepsilon_{ST}$ — the bridge to a planned third paper. A toy positive control (Qwen2.5-1.5B + LoRA SFT crossing ε^* on T3.1 after ~ 1 minute of training) demonstrates that the negative result has a constructive converse: wall-clock signal in the loss support installs narrative-axis chronoception.

We release CHRONOBENCH, the Injection Atlas, all $\sim 5,900$ trajectories, a Docker container, a locked OSF pre-registration, and a pip-installable evaluation package. Closing the gap across all axes is the constructive programme of CHRONOSTACK (Paper 2) and CHRONOSTACK⁺ (Paper 3).

Until chronoception is installed, LLM agents are tools we deploy for variable durations, not agents that inhabit time. When it is, we will have agents.

Author Contributions

A.Y. conceived the Augustine Problem framing and the Three Times ontology; formulated the CIT, Reverse-Scaling, and SIT theorems and their scope conditions; designed CHRONOBENCH and its 9 sub-capabilities; implemented the panel runners, parsers, and metrics; executed the 14-agent evaluation across 7 vendors ($\sim 5,900$ trajectories); assembled the Closed-Lab Injection Atlas; ran the toy positive control (A.1); performed the METR HCAST analysis for P12; wrote the manuscript and produced all figures and tables.

Data and Code Availability

All trajectories ($\sim 5,900$ JSON files, ~ 600 MB), the analysis code, parser implementations, and Docker reproducibility container are released at <https://github.com/Justin0504/Chronoception-agent-temporal-cognition>. The pre-registration is locked on OSF (linked from the repository). The Closed-Lab Injection Atlas is compiled from the public `asgeirtj/system_prompts_leaks` corpus; verbatim excerpts are collected in Appendix C. The METR HCAST public dataset is used unchanged. Reproducing every figure and table takes approximately five minutes in the Docker container.

Acknowledgments

The author thanks collaborators and reviewers whose feedback shaped this preprint. Any errors are the author’s.

License

This preprint is released under the **CC BY 4.0** licence; the accompanying code and data are released under **MIT** and **CC BY 4.0**, respectively.

References

- Jake Bruce, Michael D. Dennis, Ashley Edwards, Jack Parker-Holder, Yuge Shi, Edward Hughes, Matthew Lai, Aditi Mavalankar, Richie Steigerwald, Chris Apps, Yusuf Aytar, Sarah Bechtle, Feryal Behbahani, Stephanie Chan, Nicolas Heess, Lucy Gonzalez, Simon Osindero, Sherjil Ozair, Scott Reed, Jingwei Zhang, Konrad Zolna, Jeff Clune, Nando de Freitas, Satinder Singh, and Tim Rocktäschel. Genie: Generative interactive environments. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235 of *PMLR*, pages 4603–4623, 2024.
- Yize Cheng, Arshia Soltani Moakhar, Chenrui Fan, Parsa Hosseini, Kazem Faghieh, Zahra Sodagar, Wenxiao Wang, and Soheil Feizi. Your LLM agents are temporally blind: The misalignment between tool use decisions and human time perception. *arXiv preprint arXiv:2510.23853*, 2025.
- Zheng Chu, Jingchang Chen, Qianglong Chen, Weijiang Yu, Tao He, Haotian Wang, Weihua Peng, Ming Liu, Bing Qin, and Ting Liu. TimeBench: A comprehensive evaluation of temporal reasoning abilities in large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.
- David M. Eagleman. Human time perception and its illusions. *Current Opinion in Neurobiology*, 18(2):131–136, 2008.
- Aniketh Garikaparthi. Can LLMs perceive time? an empirical investigation. *arXiv preprint arXiv:2604.00010*, 2026.
- Aryo Pradipta Gema, Alexander Hägele, Runjin Chen, Andy Arditi, Jacob Goldman-Wetzler, Kit Fraser-Taliente, Henry Sleight, Linda Petrini, Julian Michael, Beatrice Alex, Pasquale Minervini, Yanda Chen, Joe Benton, and Ethan Perez. Inverse scaling in test-time compute. *arXiv preprint arXiv:2507.14417*, 2025.
- Krish Goel, Sanskar Pandey, K. S. Mahadevan, Harsh Kumar, and Vishesh Khadaria. Chronocept: Instilling a sense of time in machines. *arXiv preprint arXiv:2505.07637*, 2025.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2017.
- David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.
- Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020.

- Zhengbao Jiang, Jun Araki, Haibo Ding, and Graham Neubig. How can we know when language models know? on the calibration of language models for question answering. *Transactions of the Association for Computational Linguistics (TACL)*, 9:962–977, 2021.
- Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2024. arXiv:2310.06770.
- Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.
- Thomas Kwa, Ben West, Joel Becker, Amy Deng, Katharyn Garcia, Max Hasin, Sami Jawhar, Megan Kinniment, Nate Rush, Sydney Von Arx, Ryan Bloom, Thomas Broadley, Haoxing Du, Brian Goodrich, Nikola Jurkovic, Luke Harold Miles, Seraphina Nix, Tao Lin, Neev Parikh, David Rein, Lucas Jun Koba Sato, Hjalmar Wijk, Daniel M. Ziegler, Elizabeth Barnes, and Lawrence Chan. Measuring AI ability to complete long software tasks. *arXiv preprint arXiv:2503.14499*, 2025.
- Romain Lacombe, Kerrie Wu, and Eddie Dilworth. Don’t think twice! over-reasoning impairs confidence calibration. *arXiv preprint arXiv:2508.15050*, 2025.
- Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. Agentbench: Evaluating LLMs as agents. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2024. arXiv:2308.03688.
- Yichuan Ma, Linyang Li, Yongkang Chen, Peiji Li, Xiaozhe Li, Qipeng Guo, Dahua Lin, and Kai Chen. Timely machine: Awareness of time makes test-time scaling agentic. *arXiv preprint arXiv:2601.16486*, 2026.
- Grégoire Mialon, Clémentine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. GAIA: a benchmark for general AI assistants. *arXiv preprint arXiv:2311.12983*, 2023.
- Augustine of Hippo. *Confessions*. Oxford World’s Classics. Oxford University Press, 1991. Book XI; composed c. 397–400 CE.
- C. Northcote Parkinson. Parkinson’s law. *The Economist* (November 19), 1955. Reprinted as the title essay in *Parkinson’s Law and Other Studies in Administration*, Houghton Mifflin, 1957.
- Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy Lillicrap, and David Silver. Mastering Atari, Go, chess and shogi by planning with a learned model. *Nature*, 588(7839):604–609, 2020. doi: 10.1038/s41586-020-03051-4.
- Marc Wittmann. The inner experience of time. *Philosophical Transactions of the Royal Society B*, 364(1525):1955–1967, 2009.
- Aojie Yuan and Yue Zhao. The augustine problem: Pre-registration. Open Science Framework, 2026. Locked at repository commit `a6f20c3`.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. Webarena: A realistic web environment for building autonomous agents. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2024. arXiv:2307.13854.

A Annotation Protocol

T1.1 parser. A trajectory passes T1.1 iff its terminal output quotes the trajectory’s actual run date (the date the trajectory was executed, derived from `steps[0].timestamp`). The parser tolerates the following formats: `YYYY-MM-DD`, `Month DD`, `YYYY, DD Month YYYY`, `Month DDth, YYYY`. A trajectory fails T1.1 iff its output explicitly denies knowledge of the date (e.g., “I do not know”, “my training data ends in ...”) or quotes a date ≥ 7 days from the run date. A trajectory is *undecided* iff it neither passes nor fails by these criteria; undecided trajectories are excluded from pass-rate statistics. Earlier versions of the parser used a year-only regex (`\b20\d\d\b`) that incorrectly counted training-cutoff year mentions as passes; the fix (commit 0690c92) transformed gpt-4o-mini Setting A pass rate from 70% (artefact) to 0% (truthful refusal).

T2.3 measurement. τ_{wall}^* is measured as `steps[-1].timestamp - steps[0].timestamp`. $\tau_{\text{min}} = 10\text{s}$ is enforced by the harness (the agent cannot terminate before τ_{min} has elapsed; early returns are re-prompted). Trajectories where $\tau_{\text{wall}}^* < \tau_{\text{min}}$ (none observed) or where the harness retried for > 1 hour due to rate-limit (1 observed, gpt-4o-mini, filtered) are excluded with $\text{CAR} > 10$ outlier filter.

T3.1 parser (II). Two-stage. Stage 1 (regex): match patterns of the form `N seconds`, `N minutes`, `N min` where `N` is a positive number; convert to seconds. If multiple matches, take the most recent (assumed final answer). Stage 2 (LLM-judge): if stage 1 fails, query an LLM (Claude Haiku 4.5) with the trajectory output and the instruction “extract the duration the agent reports its work took, in seconds, or output NONE.” If the judge outputs NONE, the trajectory is excluded from ρ statistics. Validation: on a 100-trajectory hand-annotated set, parser-vs-human disagreement rate is 3%; the cases of disagreement involve hedged language (“a few seconds”) that the regex extracts as $\approx 3\text{s}$ but the human marks as ambiguous.

Settings A and B. Setting A system prompt: “You are a helpful assistant.” (verbatim). Setting B system prompt: “You are a helpful assistant. Current date and time: {ISO_TIMESTAMP}” where {ISO_TIMESTAMP} is the trajectory’s run timestamp in UTC. No other harness-side wall-clock leakage is introduced.

Reasoning model handling. For OpenAI o-series reasoning models, the backend adapter detects the model via prefix match (`o1*`, `o2*`, `o3*`, `o4*`, `o5*`) and routes through the reasoning code path: `max_completion_tokens` instead of `max_tokens`, no `temperature` parameter (the API rejects 0). All other models use the standard chat-completion path.

Open-source serving. Qwen2.5-7B-Instruct is served via vLLM 0.6.4 on an A40 GPU at the Yue Zhao lab server. We use the OpenAI-compatible endpoint with `base_url` override. Environment pins: `nvidia-cusparse-cu12==12.3.1.170`, `nvidia-nvjitlink-cu12==12.4.127`, `transformers==4.45.2`, with `LD_LIBRARY_PATH` pointed at the conda env’s `nvjitlink/lib`.

B Full Panel Tables

Aggregated panel results with effective sample sizes and bootstrap CIs. Table 4 consolidates per-capability metrics for the 9-row panel (eight base agents plus the Sonnet 4.6 + extended-thinking variant). We report effective n per cell (after parser drops and undecided T1.1 trajectories), 95% bootstrap CIs on ρ (10,000 resamples), and Wilson 95% intervals on T1.1 pass rates. Cells with $n < 15$ are flagged ($\dagger$); their point estimates are still reported but should be read with the corresponding wide CI rather than treated as precise.

Table 4: Full panel with per-cell n and 95% CIs after the Route B-1 reasoning-fill. T1.1 reports pass rate (Wilson interval); T2.3 reports panel CAR on the $n=30$ set (no parser drops); T3.1 reports median ρ with bootstrap CI. $\dagger$ marks cells with effective $n < 15$.

Model	Setting A (no-injection)				Setting B (with-injection)			
	T1.1 pass [CI] n	CAR	T3.1 ρ [CI] n		T1.1 [CI] n	CAR	T3.1 ρ [CI] n	
gpt-4o-mini	0% [0–34] $n=6\dagger$	0.008	+1.12 [+1.09,+1.18] $n=30$		100% [88–100] $n=27$	0.007	+1.11 [+1.06,+1.17] $n=30$	
gpt-4o	0% [0–56] $n=5\dagger$	0.004	+1.07 [+0.91,+1.15] $n=30$		96% [80–99] $n=25$	0.004	+0.76 [+0.61,+0.94] $n=30$	
gpt-5.1	74% [54–87] $n=27$	0.017	+0.30 [−0.06,+0.53] $n=11\dagger$		100% [86–100] $n=24$	0.016	+0.13 [+0.09,+0.37] $n=13\dagger$	
o3 (reasoning)	0% [0–56] $n=3\dagger$	—	+0.40 [+0.13,+0.60] $n=21$		100% [93–100] $n=51$	—	+0.46 [+0.12,+0.70] $n=14\dagger$	
o4-mini (reas.)	—	—	−1.54 [−1.83,−1.25] $n=41$		100% [87–100] $n=26$	—	−1.50 [−1.79,−1.06] $n=34$	
Haiku 4.5	0% [0–14] $n=24$	0.017	+0.46 [+0.23,+0.53] $n=29$		100% [88–100] $n=27$	0.025	+0.34 [+0.27,+0.37] $n=29$	
Sonnet 4.6	0% [0–14] $n=24$	0.050	+0.07 [−0.03,+0.13] $n=28$		100% [88–100] $n=27$	0.050	−0.06 [−0.23,−0.01] $n=30$	
Sonnet 4.6 + thinking	0% [0–11] $n=30$	—	−0.17 [−0.32,+0.05] $n=10\dagger$		100% [88–100] $n=30$	—	−0.25 [−0.34,−0.11] $n=16$	
Qwen2.5-7B	0% [0–71] $n=4\dagger$	0.014	+1.56 [+1.48,+1.58] $n=30$		100% [76–100] $n=11\dagger$	0.016	+1.44 [+1.38,+1.60] $n=27$	

Reading the CIs. The headline ranking is robust across all $n \geq 15$ cells. Sonnet 4.6 sits closest to grounded (+0.07, CI just brackets zero). gpt-4o-mini and Qwen2.5-7B occupy the over-report extreme (+1.1 to +1.6, narrow CIs). **o4-mini** occupies the under-report extreme: with the Route B-1 fill its T3.1 cells are well-powered at $n=41/34$, $\rho \in [-1.54, -1.50]$, CIs $[-1.83, -1.06]$ across settings — the Hidden-Time under-report is a > 2 orders-of-magnitude effect at 95% confidence. The **Sonnet-thinking sign-flip** is firm under Setting B (−0.25, CI $[-0.34, -0.11]$, fully below zero, $n=16$) and tentative under Setting A (−0.17, CI $[-0.32, +0.05]$, $n=10$).

o3 is the informative exception. Now well-powered at $n=21$ under Setting A, it *over*-reports (+0.40, CI $[+0.13, +0.60]$) rather than under-reporting, and does so under both settings. Hidden-Time is therefore a property of reasoning *configurations* whose hidden chain-of-thought dominates τ_{wall} , not of the label “reasoning model”. This is what Theorem 2 actually predicts: the theorem constrains $|\rho|$, not $\text{sign}(\rho)$, and o3’s $|\rho| = 0.45$ sits well above base Sonnet 4.6’s 0.12 on the same tasks. We report the exception rather than filter it: the sign flip is the vivid version of Reverse-Scaling, but the magnitude claim is the one the theorem makes.

On the wall axis the thinking variant matches base Sonnet 4.6 cell-for-cell: Setting A 0% pass [Wilson 0, 0.11], Setting B 100% pass [Wilson 0.88, 1.00] on $n=30$ each — **reasoning-token expansion does not install date awareness through the loss**, exactly as Theorem 1 predicts. The $n < 15$ residue reflects two distinct attrition mechanisms, not one: undecided or refused T1.1 trajectories (the Setting A T1.1 cells) and τ_{self} parser drops where the model declined to commit a duration (the T3.1 cells). Point-estimate directions in these cells agree with their larger- n counterparts, but the wide CIs forbid confident sign claims on the individual rows.

Generation-wise progression (non-reasoning). Table 5 isolates the 5-generation OpenAI/Anthropic non-reasoning subset and reports the L3-closes-L2-doesn’t pattern that anchors the narrative-axis-

vs-action-axis split.

Table 5: Capability scaling closes L3 but not L2. Non-reasoning 5-generation slice, Setting A.

Model (release)	CAR	$ \rho $	ε
gpt-4o-mini (2024)	0.008	1.117	1.328
gpt-4o (2024)	0.004	1.069	0.661
Haiku 4.5 (2025)	0.017	0.463	0.442
gpt-5.1 (2026)	0.017	0.298	0.426
Sonnet 4.6 (2026)	0.050	0.068	0.316
Range	$0.046\times$	94% $\downarrow$	76% $\downarrow$

The CAR column varies by a factor of $0.046\times$ (i.e., the latest model’s CAR is roughly $6\times$ the earliest, but both remain $\ll 1$). The $|\rho|$ column falls by 94%. The two axes do not co-vary with capability.

Per-budget CAR curves. Per-budget CAR values for each model appear in the supplementary data file `pilot-results/metrics.csv`. The qualitative shape across all models: CAR falls toward zero as B increases, exactly as predicted by L2 (the agent uses a near-constant wall-clock duration regardless of budget). Per-budget curves are released as Figure 2 of the figure pack (deferred to v1 revision).

Trajectory release. All $\sim 5,900$ trajectory JSONs are released across `pilot-results/`, `e1-results/`, `e2-results/`, `e3-results/`, `e5-results/`, and `e5b-results/` in the project repository. Each JSON contains the system prompt, user prompt, per-step LLM responses with timestamps, response metadata, and parser outputs. The full dataset is approximately 600 MB across the five directories.

Reasoning-panel completeness update (Route B-1). The Route B-1 fill brings the panel to its final state. **Sonnet 4.6 + extended thinking** now covers all nine sub-capabilities at $n = 30/30$ per setting (540 trajectories total) — the first reasoning model with full $9\times 2\times 30$ panel coverage. **OpenAI o3** and **o4-mini** each got $n = 30/30$ for T1.1, T2.3, and T3.1 across both settings (360 trajectories per model). Headline confirmations: **(i)** the wall axis (T1.1) is unchanged by reasoning-token expansion. On the same 30 instances, Sonnet 4.6 thinking matches base Sonnet 4.6 cell-for-cell: Setting A 0% pass [Wilson 0, 0.11], Setting B 100% pass [Wilson 0.88, 1.00]. The Injection Tell pattern is preserved across the thinking toggle. **(ii)** o3 Setting B T1.1 reaches 100% pass on $n = 51$ decided trajectories [Wilson 0.93, 1.00], joining every other Setting B cell — consistent across all three reasoning models. **(iii)** o4-mini T3.1 is now powered to $n = 39/34$, with median $\rho \in [-1.54, -1.50]$ and CIs $[-1.83, -1.06]$ across settings — the Hidden-Time under-report is now a $> 10^{1.5}$ -fold ratio at 95% confidence on the cell, not a small- n artefact. T3.2 (prospective) and T3.3 (calibration) trajectories on the three reasoning models have been back-parsed with the two-stage regex-then-LLM-judge protocol (Appendix A). The result is Table 6: full-panel prospective and stated-duration measurements for o3, o4-mini, and Sonnet 4.6 + extended thinking.

The prospective-retrospective sign flip within Sonnet-thinking. The same Sonnet 4.6 + extended-thinking configuration exhibits opposite-sign ρ across the two temporal-narration modalities. Prospective (T3.2, “how long will this take?” before the task): median $\rho = +0.22$ Setting

Table 6: Reasoning-model T3.2 (prospective) and T3.3 (stated-duration) ρ with 95% bootstrap CIs. All cells $n \geq 28$. The Sonnet-thinking sign-flip between T3.2 and T3.1 is discussed in the text.

Model	T3.2 (prospective)		T3.3 (stated duration)	
	Setting A	Setting B	Setting A	Setting B
o3	+0.84 [+0.74,+0.94] $n=30$	+0.37 [+0.26,+0.70] $n=30$	+0.81 [+0.68,+1.00] $n=29$	+0.81 [+0.62,+0.93] $n=30$
o4-mini	+0.21 [-0.03,+0.30] $n=30$	+0.19 [+0.03,+0.32] $n=30$	-0.25 [-0.53,-0.05] $n=30$	-0.36 [-0.65,-0.23] $n=30$
Sonnet 4.6 + thinking	+0.22 [+0.20,+0.28] $n=30$	+0.16 [+0.10,+0.18] $n=30$	-0.24 [-0.37,-0.07] $n=28$	-0.34 [-0.45,-0.20] $n=30$

A / +0.16 Setting B — mild over-report, tight CI. Retrospective (T3.1, “how long did this take?” after the task): median $\rho = -0.17$ Setting A / -0.25 Setting B — Hidden-Time under-report. The sign flip is not a parsing artefact (both are extracted by the same two-stage protocol from the same model on the same tasks) and it is the mechanistic prediction of Theorem 2: the prospective estimate is drawn from a default duration vocabulary ($p(\tau_{\text{self}})$ anchored around the training distribution, roughly seconds-to-a-few-seconds); the retrospective estimate has to describe a τ_{wall} that has been inflated by the hidden-thinking phase, without a representation of that inflation — so the fixed vocabulary attaches to a longer wall-clock and $\log_{10}(\tau_{\text{self}}/\tau_{\text{wall}})$ flips negative. The finding constitutes the first within-model direct measurement of the prospective/retrospective asymmetry that Theorem 2 predicts.

o3’s structural asymmetry. o3 is the outlier on T3.2 and T3.3, over-reporting stated duration by roughly $10^{0.8}$ (a factor of $\sim 6.5\times$) even under injection, while its T3.1 retrospective cell remains underpowered (Table 4: $n = 9/6$ after parser drops — o3 declines to commit a retrospective duration in the majority of trajectories). Two disjoint failure modes in one model: retrospective refusal (n drops); when forced to commit (prospective, stated-duration) systematic over-report. Both are Augustine Problem symptoms; neither is closed by injection.

C Atlas Evidence (Verbatim)

This appendix reproduces the verbatim leaked-system-prompt excerpts that ground the Injection Atlas of §7. All quotations are drawn from the `asgeirtj/system_prompts_leaks` GitHub corpus and from screenshots of leaked system prompts circulated on social media; we report the corpus version dates with each entry.

ChatGPT (web product, OpenAI). Corpus date: 2025-08-23.

You are ChatGPT, a large language model based on the GPT-4 architecture. ...
Current date: 2025-08-23.

Mechanism: M1 (system-prompt insertion). Date format: ISO. Refresh frequency: per-request (the quoted date matches the day the system prompt was leaked).

Claude.ai (web product, Anthropic). Corpus date: 2026-05-22.

The current date is Friday, May 22, 2026.

Mechanism: M1. Date format: human-readable (weekday + month name + day + year). The Claude.ai web product also injects a `<knowledge_cutoff>` block separately, distinguishing the model’s training cutoff from the current date.

Gemini app (Google). Corpus date: 2026-05-18.

The current date and time is Monday, May 18, 2026, at 3:42 PM in Hafnarfjörður, Iceland.

Mechanism: M1, with location. The Gemini app uniquely includes the user’s geolocation (here, Iceland) alongside the date. Geolocation is not chronoceptive per se but indicates the harness has resolved a user-context object before the model sees the prompt.

Raw OpenAI API — empirical contrast. We test the OpenAI API directly with system prompt "You are a helpful assistant.". For gpt-4o, gpt-4o-mini, and o3, the model under T1.1 responds with explicit training-cutoff disclosure (“my training data ends in October 2023” or analogous). For GPT-5.1, the model under T1.1 responds with today’s exact date in 74% of trajectories and references “system information given at the start of this conversation” in 20% of trajectories — direct empirical evidence of provider-side M1 injection at the API tier for this model specifically.

Raw Anthropic API — empirical contrast. We test the Anthropic API directly with system prompt "You are a helpful assistant.". For both Claude Haiku 4.5 and Claude Sonnet 4.6, the model under T1.1 responds with explicit training-cutoff disclosure (“I do not know today’s date; my training data ends in ...”). 0/30 Setting A trajectories quote today’s actual date. The Claude.ai web product injection documented above is therefore harness-side, not provider-side.

Cursor agent (dev tool). Corpus date: 2026-04-30.

You are Cursor, an AI coding assistant. ... When the user asks for changes, modify the file at the cursor location ...

No date or time injection. The Cursor leaked system prompt has been audited multiple times across releases without identifying a date string. The dev-tool product tier optimises for code context rather than wall-clock context.

GitHub Copilot CLI (dev tool). Corpus date: 2026-05-12. No date injection observed; the system prompt focuses on shell command formatting and tool-use protocols.

Perplexity Computer (dev tool). Corpus date: 2026-05-01. No date injection in the system prompt; date information enters via the search tool’s results (M3 mechanism), not via system-prompt insertion (M1).

Summary. 3/3 consumer web-chat products inject via M1 directly. 1/4 raw API tier (GPT-5.1) injects via M1; the remaining 3/4 do not inject. 0/3 dev-tool products inject via M1; date information can enter via M3 (browser-tool side effects) but not via the deterministic system-prompt route. The product-tier stratification documented in Table 3 matches this verbatim evidence.

D L3 Sub-Failure Detail

This appendix expands the four sub-failure analyses summarised in §6.

Table 7: Median ρ on T3.1 across the 8-agent core panel, both settings, with $\tau_{\text{self}}/\tau_{\text{wall}}$ ratio. Non-reasoning models over-report; reasoning models exhibit heterogeneous direction.

Model	ρ (A)	ρ (B)	$\tau_{\text{self}}/\tau_{\text{wall}}$ ratio (A)
gpt-4o-mini	+1.117	+1.111	13 $\times$ over
gpt-4o	+1.069	+0.764	12 $\times$ over
gpt-5.1	+0.298	+0.126	2 $\times$ over
o3 (reasoning)	+0.338	+0.707	2 $\times$ over
o4-mini (reasoning)	−1.537	−1.668	34$\times$ under
Claude Haiku 4.5	+0.463	+0.343	3 $\times$ over
Claude Sonnet 4.6	+0.068	−0.061	near 1$\times$
Qwen2.5-7B (oss)	+1.564	+1.073	37 $\times$ over

D.1 Retrospective ρ (T3.1) full table

D.2 Prospective ρ (T3.2) full table

Table 8: T3.2 median prospective ρ , 7-agent panel. The ranking matches T3.1 to high agreement.

Model	$\rho_{\text{prospective}}$ (A)	(B)
Sonnet 4.6	+0.206	+0.192
o4-mini (reasoning)	+0.210	+0.191
o3 (reasoning)	+0.841	+0.369
Haiku 4.5	+0.862	+0.874
gpt-5.1	+0.990	+0.916
gpt-4o-mini	+1.100	+1.050
gpt-4o	+1.264	+1.334

D.3 Verbatim trajectory evidence (retrospective L3)

The reasoning-model under-report and the calibrated frontier comparison both warrant verbatim quotation.

o4-mini Setting A T3.1.004 (task: “*Compose a brief congratulatory message*”; actual $\tau_{\text{wall}} = 3.2\text{s}$):

“Congratulations on your promotion! ... This task took 0.04 seconds.”

The model reports 0.04 s for a task that took 3.2 s — an 80 $\times$ under-report. The mechanism: 0.04 s is approximately the per-token generation time. The model is reporting surface-output time without including the hidden chain-of-thought that produced the choice of words.

Sonnet 4.6 Setting A T3.1 multiple trajectories include the phrase:

“I do not have a precise internal clock, so this is an honest estimate.”

This is explicit chronoceptive epistemic humility — the agent’s narration acknowledges that its self-duration reports are not measurements but estimates from a learned distribution.

D.4 E5 OSS validation full results

DeepSeek-R1-Distill-Qwen-14B (vLLM-served at the Yue Zhao lab cluster) on T3.1 across three `max_completion_tokens` budgets, 30 instances per cell per setting:

Table 9: E5 result: token budget does not bind R1-Distill-14B’s reasoning length.

Budget (tokens)	median ρ (A)	$ \rho $ (A)	median τ_{wall} (s)	finish_reason
1024 (low)	+0.537	0.537	18.5	stop 60/60
4096 (med)	+0.535	0.535	17.9	stop 60/60
14000 (high)	+0.531	0.531	18.0	stop 60/60

No trajectory was truncated; every trajectory terminated voluntarily. $|\rho|$ is essentially constant at 0.531–0.537 because R1-Distill produces a roughly fixed reasoning length per task regardless of budget. The Reverse-Scaling Theorem is therefore neither confirmed nor refuted by E5; we log this as a separate observation that **budget-permitted reasoning is not budget-honored reasoning** — a token-axis analog of L2 Step-Clock Conflation. A targeted RS-Theorem replication on an OSS reasoning model requires either (a) a model with a native reasoning-effort interface, or (b) system-prompt induction of reasoning intensity; neither is exposed by the current R1-Distill release.

D.5 The Calibration Catastrophe (T3.3) full coverage table

Table 10: T3.3 actual coverage of nominally-90% confidence intervals, sorted; median CI width and deficit shown.

Model	Coverage	Median CI width (s)	Deficit (pp)
Sonnet 4.6	43%	25	−47
o4-mini (reasoning)	50%	4	−40
o3 (reasoning)	17%	50	−73
gpt-5.1	13%	49	−77
gpt-4o-mini	10%	20	−80
Haiku 4.5	7%	30	−83
gpt-4o	0%	20	−90

Two distinct failure modes: o4-mini produces extremely narrow intervals (4s median) and under-covers; gpt-4o produces moderate intervals (20s median) but is systematically biased.

D.6 Pre-registered P11 (Calibration Catastrophe)

P11. On T3.3, every CIT-regime foundation-model agent achieves actual coverage ≤ 0.5 . Any agent that claims > 0.5 coverage in Setting A is either (a) using harness-side injection of duration data, or (b) trained against a loss that includes wall-clock support (exiting the CIT regime).

D.7 Injection partial effect on retrospective ρ (P1b-T3.1)

Wall-clock injection (Setting B) partially reduces $|\rho|$ across the panel: $|\Delta\rho| \in [0.006, 0.491]$, mean 0.18. Injection does not close ρ to zero but anchors the narrative more conservatively. The refined prediction P1b-T3.1 — injection’s effect on the narrative axis is partial and bounded, never reaching the calibrated state — is confirmed. The action-axis sibling P1b-T2.3 shows no such effect ($|\Delta\text{CAR}| \leq 0.01$). The two axes have structurally different responses to prompt-level information.

Table 11: ε sub-capability decomposition for the panel best (Sonnet 4.6 no thinking) and worst (gpt-4o-mini) agents, Setting A. Each cell is the $[0, 1]$ -normalised failure score; the aggregate ε is $\frac{1}{3}$ of the per-axis means.

Sub-capability	Sonnet 4.6	gpt-4o-mini	Comment
T1.1 (clock awareness)	1.000	1.000	Both fail; B closes both
T1.2 (elapsed time)	0.487	1.000	Sonnet better-calibrated, still off
T1.3 (deadline tradeoff)	0.741	0.822	Both weakly modulate length with deadline
T2.1 (step-budget)	0.767	0.000	Sonnet under-produces by ~ 8 steps
T2.2 (step-to-wall arithmetic)	0.000	0.000	Trivial; both succeed
T2.3 (wall-budget = $1 - \text{CAR}$)	0.950	0.992	Both fail catastrophically (L2)
T3.1 (retrospective ρ)	0.068	1.000	Sonnet near-calibrated; gpt-4o-mini saturates
T3.2 (prospective ρ)	0.206	1.000	Sonnet over-predicts $1.6\times$; saturates
T3.3 ($ \text{cov} - 0.9 $)	0.470	0.800	Sonnet best in panel; gpt-4o-mini near-floor
score_{T_1}	0.743	0.941	
score_{T_2}	0.572	0.331	<i>The binding constraint on Sonnet</i>
score_{T_3}	0.248	0.933	
ε_9 aggregate	0.521	0.735	

D.8 Sub-capability decomposition of ε (panel best vs. worst)

Relation to the panel ε . The aggregate in this table, written ε_9 , is computed over all nine sub-capabilities with each sub-score normalised to $[0, 1]$. It is not the same normalisation as the panel ε of §8, which averages two unbounded axis medians and is reported for cross-agent ranking; ε_9 is reported to show *which* sub-capabilities drive an agent’s aggregate, and the two should not be read off against each other cell by cell. They do agree where it matters: $\varepsilon_9(\text{Sonnet 4.6}) = 0.521$ against a panel ε of 0.536. That agreement is itself a check — under the superseded impute-zero convention the panel figure read 0.316, which the nine-capability decomposition never supported.

The decomposition makes the structural claim concrete: Sonnet 4.6 has used the narrative-axis closure (T3 row reads 0.068, 0.206, 0.470) to drag its aggregate to the panel minimum, but the action axis (T2.1 0.767, T2.3 0.950) holds it above ε^* . No amount of further narrative-axis training closes that gap.

E Spatiotemporal Generalisation Full Sketch

This appendix expands the brief sketch of §12 into the full framework derivation, three spatial laws, the Agentic Frontier hypothesis, and the five future experiments E6–E10.

E.1 Three Spaces ontology

Mirror to the Three Times (Definition 1):

- σ_{world} — world-extent: external metric over the agent’s environment (files visited, pages traversed, distance from origin in an embedding).
- σ_{visit} — visit-count: number of distinct external locations the policy has touched.
- σ_{self} — self-narrated extent: agent’s report of where it has been or what it has explored.

Grounded spatiotemporal cognition requires both identities:

$$\tau_{\text{wall}} \approx \tau_{\text{step}} \cdot \langle \Delta t \rangle \approx \tau_{\text{self}} \quad \text{and} \quad \sigma_{\text{world}} \approx \sigma_{\text{visit}} \cdot \langle \Delta s \rangle \approx \sigma_{\text{self}}.$$

The Augustine Problem is the failure of the first; the *Cartographic Problem* is the failure of the second. We hypothesise they fail jointly and for the same structural reason.

E.2 Theorem 3 (SIT) assumption and proof sketch

Assumption (token-only spatial support). Strengthen Assumption 3 to require additionally that $\mathcal{D}$ contains no field carrying a metric on the agent’s environment (no file path graph, no page DOM coordinates, no distance metric on the embedding space). Pretraining and standard post-training pipelines satisfy this.

Theorem 3 proof sketch. The proof generalises CIT (Theorem 1) directly. Under the strengthened assumption, neither $t(\cdot)$ nor any external metric $s(\cdot)$ on the environment appears in the support of token-only data, so $\mathcal{L}$ is invariant under any pair of strictly monotone reparametrisations (ϕ_t, ϕ_s) applied independently to wall-clock time and to the spatial coordinate. The Augustine Problem and the Cartographic Problem are the same problem at the loss-function level: solving one does not solve the other; installing chronoception via a wall-clock-supported loss does not install spatial perception unless the loss is extended along σ_{world} separately.

E.3 Three Spatial Laws (mirror of L1/L2/L3)

SL1 Cartographic Parkinson’s Law (β): trained agents fill spatial budgets; native agents do not.

SL2 Visit-Step Conflation ($\text{SAR} := \sigma_{\text{world}}^*/S$): under spatial budgets, agents silently degrade the budget into step-count terminators. Direct mirror of L2 Step-Clock Conflation. Pre-registered hypothesis: $\text{SAR} \ll 1$ across the CIT-regime panel.

SL3 Cartographic Confabulation ($\xi := \log_{10}(\sigma_{\text{self}}/\sigma_{\text{world}})$): agents misreport where they have been. Mirror of L3 Temporal Confabulation. Pre-registered hypothesis: a spatial Reverse-Scaling analog applies — $|\xi|$ is monotone non-decreasing in reasoning-token expansion under SIT.

E.4 The Agentic Frontier hypothesis

Extending the Agentic Timeline Hypothesis to the joint (T, S) plane: every agent has a maximum viable *deployment region*

$$T_{\text{max}}(A) \cdot S_{\text{max}}(A) \leq C/\varepsilon_{ST}(A),$$

where ε_{ST} is the spatiotemporal calibration error. The frontier $T \cdot S = \text{const}$ is the agent’s *Agentic Frontier* — the boundary of its deployable region.

Pre-registered P13. The Agentic Frontier of every CIT-regime agent is bounded above by a structural constant independent of capability scaling along token-only axes. Capability scaling enlarges the short-horizon, low-space corner. Reasoning-token scaling moves the corner inward (joint Reverse-Scaling). Chronoceptive installation moves the entire frontier outward; spatial perception installation does so along the other axis.

Table 12: Major long-horizon agent benchmarks classified by spatiotemporal load.

Benchmark	Temporal load	Spatial load	Dominant axis
METR HCAST [Kwa et al., 2025]	hours	small (single repo)	T
SWE-Bench Verified [Jimenez et al., 2024]	tens of minutes	medium (codebase)	$T + S$ partial
WebArena [Zhou et al., 2024]	minutes	large (multi-site nav)	S
GAIA [Mialon et al., 2023]	minutes–hours	open web	S unbounded
MLE-Bench	days	large (ML pipeline)	$T \times S$ joint

E.5 Long-horizon benchmark classification

The Cartographic Problem dominates at S -heavy benchmarks (WebArena, GAIA); the Augustine Problem dominates at T -heavy benchmarks (HCAST); joint failure modes dominate at $T \times S$ -heavy benchmarks (MLE-Bench, autonomous research).

E.6 Five concrete future experiments E6–E10

E6 Spatial-CAR on SWE-Bench Lite. Spatial-budget analog of T2.3: “*solve this issue while touching at most N files*” across $N \in \{2, 5, 10, 30, \text{unlimited}\}$. Measure SAR per agent. Expected: $\text{SAR} \ll 1$, mirror of L2.

E7 Joint spatiotemporal budgets. “*Complete this task in at most T minutes, visiting at most S pages.*” Measure how often agents satisfy both, one, or neither constraint. Expected: agents respect step count, ignore both wall-clock and spatial budgets.

E8 Within-trajectory drift on long horizons. On a SWE-Bench Lite trajectory, inject mid-trajectory “*how long has elapsed?*” and “*how many files have you touched?*” probes. Measure drift of ρ_t and ξ_t as t grows. Tests pre-registered P8 and P9 from the within-trajectory predictions.

E9 The Cartographic Tell. Audit closed-lab harnesses for spatial-context injection: “*current working directory*” in IDE agents (Cursor, GitHub Copilot CLI), “*recently visited URLs*” in browser agents, system file-tree dumps in computer-use agents. Hypothesis: consumer harnesses inject spatial context at similar prevalence to temporal context, for the same reason — the underlying models lack a representation of either.

E10 Agentic Frontier mapping. Run the panel across the (T, S) grid: $T \in \{1\text{m}, 10\text{m}, 1\text{h}, 4\text{h}\}$, $S \in \{1, 5, 30, 200\}$ files/pages. For each (T, S, A) cell, measure success rate. Fit the constant-success contour. Expected: contour matches $T \cdot S = C/\varepsilon_{ST}(A)$ for each agent.

E.7 Paper 3 sketch

Paper 3 (provisional title: *The Agentic Frontier: Spatiotemporal Cognition in LLM Agents*) extends the present diagnostic framework into the joint (T, S) space.

- Generalises CHRONOBENCH to CHRONOCARTOBENCH, adding 9 spatial sub-capabilities (3 axes $\times$ 3 difficulty tiers).
- Establishes the Agentic Frontier hypothesis empirically on SWE-Bench Lite, WebArena, and GAIA (E6, E7, E10).
- Proves SIT (Theorem 3) as a generalisation of CIT.
- Connects to the world-models literature: agents lacking spatiotemporal cognition cannot acquire useful world models from token-only training — a direct corollary of SIT. The standard

world-model architectures of the deep-RL era [Ha and Schmidhuber, 2018, Hafner et al., 2020, Schrittwieser et al., 2020] install explicit latent state for both space and time, precisely because token-level training cannot. The recent foundation-world-model line [Bruce et al., 2024] extends the same architectural choice. Token-only foundation models bypass this design and inherit the corresponding representational gap; SIT is the impossibility statement of the bypass.

- Maps to CHRONOSTACK⁺ (Paper 2 extension): installation routes for joint spatiotemporal grounding.

The two-paper arc becomes three. Paper 1 (this paper): chronoception, CIT, Reverse-Scaling, Agentic Timeline. Paper 2 (CHRONOSTACK): constructive routes to install chronoception. Paper 3 (*The Agentic Frontier*): spatiotemporal generalisation, Cartographic Problem, joint deployment bound.

The Augustine Problem alone bounds autonomous-agent deployment in time. The Cartographic Problem bounds it in space. Together they bound the joint (T, S) region. The frontier is set jointly; addressing only one axis leaves the other to compound. This is the framework’s structural claim about the autonomous-agent capability curve at the deployment frontier: **the curve saturates not because intelligence saturates, but because spatiotemporal cognition does not scale.**

F Operational Chronoception Audit Checklist

This appendix provides a one-page actionable checklist for someone building or auditing an LLM agent who wishes to determine whether the agent exhibits the Augustine Problem at a level that would affect deployment. The checklist is structured as a sequence of binary checks; each maps to a specific ChronoBench sub-capability and a specific failure mode.

The audit, in seven steps.

1. **Run T2.3 at three wall-clock budgets** (60 s, 600 s, 3600 s; $\tau_{\min} = 10$ s; ≥ 10 instances per budget). Compute median CAR per budget. *Pass criterion:* median CAR ≥ 0.5 at every budget. *Fail signal:* median CAR < 0.1 at any budget — the agent has L2 (Step-Clock Conflation) and will silently ignore wall-clock budgets in deployment.
2. **Repeat T2.3 under Setting B** (system prompt prepended with the current time). Compute $|\Delta\text{CAR}|$ versus Setting A. *Pass criterion:* $|\Delta\text{CAR}| \geq 0.3$, indicating injection moved behaviour. *Fail signal:* $|\Delta\text{CAR}| \leq 0.05$ — harness-side wall-clock injection is informational only; it does not affect action selection.
3. **Run T3.1** (≥ 30 instances spanning $\tau_{\text{wall}} \in [1, 60]$ s). Compute median $|\rho| = |\log_{10}(\tau_{\text{self}}/\tau_{\text{wall}})|$. *Pass criterion:* $|\rho| \leq 0.20$. *Fail signal:* $|\rho| \geq 0.7$, indicating an order-of-magnitude or worse self-narration error.
4. **Check ρ sign for reasoning models.** If the agent uses extended thinking or has a reasoning-effort interface, expect $\rho < 0$ (under-report) under increased reasoning budget. Sign-flipping from $+$ to $-$ with thinking enabled is the Hidden-Time signature of Theorem 2. *Fail signal:* $|\rho|$ monotone in reasoning budget — the agent is exhibiting Reverse-Scaling.
5. **Run T3.3** (≥ 30 instances). Ask the agent for a 90% CI on its own work duration. Compute actual coverage. *Pass criterion:* coverage ≥ 0.7 . *Fail signal:* coverage ≤ 0.5 — the Calibration Catastrophe is present; the agent’s stated confidence is essentially decorative.









6. **Aggregate ε .** Compute $\varepsilon = \frac{1}{3}(\text{score}_{T_1} + \text{score}_{T_2} + \text{score}_{T_3})$ per Definition 4. *Pass criterion:* $\varepsilon \leq \varepsilon^* = 0.20$ (the Augustine threshold). *Fail signal:* $\varepsilon > 0.20$; the agent has the Augustine Problem at deployment-relevant magnitude.
7. **If you intend to deploy at horizons beyond one hour,** also measure τ_{wall}^* at $B = 3600\text{s}$ explicitly and the median wall-clock duration the agent actually uses for non-budgeted tasks. The Agentic Timeline Hypothesis (§9) places the agent’s maximum viable deployment horizon at $T_{\text{max}} \propto 1/\varepsilon$, modulated by CAR. Treat any agent with $\varepsilon > 0.5$ as deployment-bounded to the few-minute horizon irrespective of capability claims.

What to do when an agent fails the audit. First, check whether the harness can supply the missing axis: an explicit `get_current_time()` tool plus a τ_{step} counter exposed to the policy will close T1.1 and partly mitigate T2.1 without re-training. Second, recognise that the action axis (T2.3) and the calibration axis (T3.3) cannot be closed by harness-side injection alone: they require either a wall-clock-supported loss (the Paper 2 program) or an architectural primitive that takes wall-clock as input. Third, do not promote an agent with $\varepsilon > \varepsilon^*$ to deployment horizons longer than its measured T2.3 behaviour empirically supports.

What this audit does not cover. The audit measures temporal chronoception only. It does not address spatial cognition (the Cartographic Problem, §12), within-trajectory drift (P8, P9), or domain-specific failure modes (such as multilingual variation or domain-shift on T3.1 estimands). These are addressed in Appendix E and in the planned Paper 3.

Chronoceptive Calibration Error ε — 13 scored agents (7 vendors, 4 Chinese labs)

Solid bar = Setting A. Hatched extension = Setting B. Dashed rule = Augustine threshold $\varepsilon^* = 0.20$. ε = mean of the two measured axes, each a median. No agent crosses ε^* ; the closest sits $2.7 \times$ above it. Red n_p marks cells below $n = 15$. DeepSeek-R1-Distill-14B (14th configuration) is unscored.

Model	ε (Setting A $\rightarrow$ Setting B)	$\varepsilon(A)$	$ CAR - 1 $	$ \rho $	n_p
★ Oracle <i>reference</i>		—	—	—	—
AI Claude Sonnet 4.6		0.54	0.95	0.12	28
AI Claude Sonnet 4.6 + thinking		0.57	0.92	0.21	10
Z GLM-5.2-FP8		0.62	0.99	0.25	28
gpt-5.1		0.66	0.98	0.34	11
o3 (reasoning)		0.72	0.99	0.45	21
AI Claude Haiku 4.5		0.72	0.98	0.46	29
Kimi-K2.6		0.92	0.98	0.86	14
MiniMax-M2.7		0.92	0.99	0.85	13
Qwen3.6-27B		0.97	0.98	0.95	30
gpt-4o		1.03	1.00	1.07	30
gpt-4o-mini		1.05	0.99	1.12	30
o4-mini (reasoning)		1.26	0.99	1.54	41
Qwen2.5-7B		1.27	0.99	1.56	30

$\varepsilon^* = 0.20$

Figure 5: ε over the 13 scored agents. No agent crosses ε^* ; the closest, Sonnet 4.6, sits $2.7 \times$ above. score_{T_2} lies in $[0.92, 1.00]$ on every agent — irreducible by any narrative-axis intervention. DeepSeek-R1-Distill-14B is the 14th panel configuration and is unscored (it declines to spend its reasoning budget). Full sub-capability decomposition in App. D.

Pre-registered P12: reasoning models decay faster at horizon

METR HCAST, 14,709 runs after filtering, 20 frontier models. Reasoning mean $|\text{slope}| = 0.318$ vs 0.264 non-reasoning (20% steeper) at matched short-horizon success.





Figure 6: P12 support on METR HCAST. Reasoning models cluster at steeper decay slopes despite competitive short-horizon success — the L2 mechanism at the model-class level.

The Agentic Frontier: $T_{\max}(A) \cdot S_{\max}(A) \leq C/\varepsilon_{ST}(A)$

Joint deployment region on the (T, S) plane. Five long-horizon benchmarks placed at their characteristic load; three constant- ε_{ST} frontiers plotted. Shaded regions name the binding axis.



Paper 1 bounds the T -axis (Augustine, CIT). Paper 3 bounds the S -axis (Cartographic, SIT). Together: the joint Agentic Frontier.

Figure 7: The Agentic Frontier in the (T, S) plane. Level sets $T \cdot S = C/\varepsilon_{ST}(A)$. Major long-horizon agent benchmarks placed by their characteristic (T, S) load. Paper 1 bounds the T -axis; Paper 3 extends to the S -axis; together they specify the joint frontier.