

INTRODUCTORY APPLIED MACHINE LEARNING

Yan-Fu Kuo

Dept. of Bio-industrial Mechatronics Engineering

National Taiwan University

Today:

- Nearest-neighbor classifiers
- Bayesian classifiers
- Logistic regression
- Ensemble methods

Outline


- Goal of the lecture
- K-nearest neighbor
- Naïve Bayesian classification
- Logistic regression
- Bagging
- Boosting

Goals


- After this, you should be able to:
 - Build k-nearest neighbor and naïve Bayesian classifiers
 - Build logistic regression models
 - Get basic ideas of ensemble methods
 - Understand the advantages and disadvantages of k-nearest neighbor, naïve Bayesian, logistic regression, and ensemble methods

k -Nearest Neighbor (kNN) Classifier

- An instance-based classifier
- Basic idea: if an animal walks like a duck, quacks like a duck, then it's probably a duck



Requirements of kNN



- Uses k “closest” points (nearest neighbors) for performing classification
- Requirements:
 1. The set of stored records
 2. **Distance metric** to compute distance between records
 3. **The value of “ k ”,** the number of nearest neighbors to retrieve

kNN Classification Procedure

1. Compute the distance $d \in \Re$ between the unknown sample point and neighbor points

(Typically the Euclidean (L_2) norm is used)


2. Identify k nearest neighbors

3. Take the majority vote of class labels among the k -nearest neighbors

(Typically the weight factor $w = \frac{1}{d^2} \in \Re$ is used)


Choice of the k Value

- If k is too small, sensitive to noise points
- If k is too large, neighborhood may include points from other classes




The Value of “ k ”


- k -nearest neighbors of a record x are data points that have the k smallest distance to x



(a) 1-nearest neighbor



(b) 2-nearest neighbor




(c) 3-nearest neighbor

Special Case: 1-nearest Neighbor

- Voronoi Diagram:

decomposition
of a space
determined by
distances to
objects



Attribute Normalization

- Attributes may have to be scaled to prevent distance measures from being dominated by one of the attributes
- Example:
 - Height of a person may vary from 1.5m to 1.8m
 - Weight of a person may vary from 90lb to 300lb
 - Income of a person may vary from \$10K to \$1M

kNN Summary


- kNN classifiers do not build models explicitly
- Classifying unknown records are relatively time consuming and computationally intensive
- Highly effective inductive inference method for noisy training data and complex target functions
- Nonparametric architecture

Bayes Theorem

- A probabilistic framework for solving classification problems
- Conditional probability:

$$P(C|A) = \frac{P(A \cap C)}{P(A)}$$

$$P(A|C) = \frac{P(A \cap C)}{P(C)}$$



- Bayes theorem:

$$\text{posterior} \rightarrow P(C|A) = \frac{\overset{\text{likelihood}}{P(A|C)} \overset{\text{prior}}{P(C)}}{\underset{\text{evidence}}{P(A)}}$$

Example of Bayes Theorem

- Given:
 - A doctor knows that meningitis (M) causes stiff neck (S) 50% of the time
 - Prior probability of any patient having meningitis is $1/50,000$
 - Prior probability of any patient having stiff neck is $1/20$
- If a patient has stiff neck, what's the probability he/she has meningitis?

$$P(M|S) = \frac{P(S|M)P(M)}{P(S)} = \frac{0.5 \times 1/50000}{1/20} = 0.0002$$

Towards Naïve Bayesian Classification

- Given a training set of attributes $\mathbf{x} = (x_1, x_2, \dots, x_K)$ and class $y_j, j = 1 \dots m$
- Consider each attribute and class label as a random variable
- Goal is to predict the class y_j for given (x_1, x_2, \dots, x_K)
- This is equivalent to find the value of y_j that maximizes the posteriori $P(y_j|\mathbf{x}) = P(y_j|x_1, x_2, \dots, x_K)$

Classification Using Naïve Bayes

<i>Tid</i>	Refund	Marital Status	Taxable Income	Evade
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

- Question: find the evade $y_j = \text{Yes or No}$, given the evidence $x = (\text{No refund, Married, Inc} = 120K)$
- This is equivalent to find y that maximizes $P(y_j|x) = P(y_j|\text{No refund, Married, Inc} = 120K)$

Derivation of Naïve Bayes Classifier

- From Bayes theorem:

$$P(y_j|\mathbf{x}) = \frac{P(\mathbf{x}|y_j)P(y_j)}{P(\mathbf{x})}$$

$$\Rightarrow P(y_j|x_1, x_2, \dots, x_K) = \frac{P(x_1, x_2, \dots, x_K|y_j)P(y_j)}{P(x_1, x_2, \dots, x_K)} \quad \dots(a)$$

- Note that $P(\mathbf{x}) = P(x_1, x_2, \dots, x_K)$ is constant for all classes
- Choosing the value of y_j that maximizes $P(y_j|\mathbf{x})$ is equivalent to choosing the value of y_j that maximizes $P(\mathbf{x}|y_j)P(y_j)$

Derivation of Naïve Bayes Classifier (Cont'd)

- Assume independence among attributes x_i , i.e.,

$$P(x_1, x_2, \dots, x_K | y_j) = P(x_1 | y_j) \cdot P(x_2 | y_j) \cdots P(x_K | y_j)$$

- Equation (a)

$$\Rightarrow P(y_j | \mathbf{x}) = \frac{P(x_1 | y_j) \cdot P(x_2 | y_j) \cdots P(x_K | y_j) \cdot P(y_j)}{P(x_1, x_2, \dots, x_n)}$$

- The objective is to find the y_j that maximizes

$$P(y_j) \prod_{i=1}^K P(x_i | y_j), \text{ i.e.,}$$

$$y = \arg \max_y \left[\left(\prod_{i=1}^K P(x_i | y_j = y) \right) P(y_j = y) \right]$$

Estimate Probabilities for Discrete Attributes

- Find y_j given $x = (No\ ref, M)$

<i>Tid</i>	Refund	Marital Status		Evade
1	Yes	Single		No
2	No	Married		No
3	No	Single		No
4	Yes	Married		No
5	No	Divorced		Yes
6	No	Married		No
7	Yes	Divorced		No
8	No	Single		Yes
9	No	Married		No
10	No	Single		Yes

Estimate Probabilities for Continuous Attributes

- Two Common methods:
 1. Two-way split: $(x < v)$ or $(x > v)$, and choose only one of the two splits as the new attribute
 2. Probability density estimation:
 - Assume attribute follows a normal distribution
 - Use data to estimate parameters of distribution, e.g., mean and standard deviation
 - Once probability distribution is known, it can be used to estimate the conditional probability $P(x_i|y_j)$

Estimate Probabilities for Continuous Attributes

Tid	Refund	Marital Status	Taxable Income	Evade
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

- Normal distribution:

$$P(x_i|y_j) = \frac{1}{\sqrt{2\pi\sigma_{ij}^2}} e^{-\frac{(x_i - \mu_{ij})^2}{2\sigma_{ij}^2}}$$

for each (x_i, y_j) pair

- Example:

Let $x_i = \text{Income}$, and $y_j = \text{No}$

$\Rightarrow \mu_{ij} = 110$, and $\sigma_{ij}^2 = 2975$

$$P(\text{Income} = 120|\text{No}) = \frac{1}{\sqrt{2\pi(54.54)}} e^{-\frac{(120-110)^2}{2(2975)}} = 0.0072$$

Example

- Given that $\mathbf{x} = (\text{No refund}, \text{Married}, \text{Inc} = 120K)$, find the evade $y_j = \text{Yes}$ or No
- Calculate the probability:
 - $P(\text{Refund} = \text{Yes}|\text{No}) = 3/7$
 - $P(\text{Refund} = \text{No}|\text{No}) = 4/7$
 - $P(\text{Refund} = \text{Yes}|\text{Yes}) = 0$
 - $P(\text{Refund} = \text{No}|\text{Yes}) = 1$
 - $P(\text{Marital Status} = \text{Single}|\text{No}) = 2/7$
 - $P(\text{Marital Status} = \text{Divorced}|\text{No}) = 1/7$
 - $P(\text{Marital Status} = \text{Married}|\text{No}) = 4/7$
 - $P(\text{Marital Status} = \text{Single}|\text{Yes}) = 2/3$
 - $P(\text{Marital Status} = \text{Divorced}|\text{Yes}) = 1/3$
 - $P(\text{Marital Status} = \text{Married}|\text{Yes}) = 0$
- Conduct Bayes' classifier:
 - $$\begin{aligned} P(\mathbf{x}|\text{No}) &= P(\text{No refund}|\text{No}) \\ &\quad \times P(\text{Married}|\text{No}) \\ &\quad \times P(\text{Inc} = 120K|\text{No}) \\ &= 4/7 \times 4/7 \times 0.0072 = 0.0024 \end{aligned}$$
 - $$\begin{aligned} P(\mathbf{x}|\text{Yes}) &= P(\text{No Refund}|\text{Yes}) \\ &\quad \times P(\text{Married}|\text{Yes}) \\ &\quad \times P(\text{Inc} = 120K|\text{Yes}) \\ &= 1 \times 0 \times 1.2 \times 10^{-9} = 0 \end{aligned}$$
 - $P(\mathbf{x}|\text{No})P(\text{No}) > P(\mathbf{x}|\text{Yes})P(\text{Yes})$
 $\Rightarrow \mathbf{evade} = \text{No}$

Another Example

Name	Give Birth	Can Fly	Live in Water	Have Legs	Class
human	yes	no	no	yes	mammals
python	no	no	no	no	non-mammals
salmon	no	no	yes	no	non-mammals
whale	yes	no	yes	no	mammals
frog	no	no	sometimes	yes	non-mammals
komodo	no	no	no	yes	non-mammals
bat	yes	yes	no	yes	mammals
pigeon	no	yes	no	yes	non-mammals
cat	yes	no	no	yes	mammals
leopard shark	yes	no	yes	no	non-mammals
turtle	no	no	sometimes	yes	non-mammals
penguin	no	no	sometimes	yes	non-mammals
porcupine	yes	no	no	yes	mammals
eel	no	no	yes	no	non-mammals
salamander	no	no	sometimes	yes	non-mammals
gila monster	no	no	no	yes	non-mammals
platypus	no	no	no	yes	mammals
owl	no	yes	no	yes	non-mammals
dolphin	yes	no	yes	no	mammals
eagle	no	yes	no	yes	non-mammals

M: mammals; N: non-mammals

Give Birth	Can Fly	Live in Water	Have Legs	Class
yes	no	yes	no	?

- Conditional probability:

$$P(x|M) = \frac{6}{7} \times \frac{6}{7} \times \frac{2}{7} \times \frac{2}{7} = 0.06$$

$$P(x|N) = \frac{1}{13} \times \frac{10}{13} \times \frac{3}{13} \times \frac{4}{13} = 0.0042$$

$$P(x|M)P(M) = 0.06 \times \frac{7}{20} = 0.021$$

$$P(x|N)P(N) = 0.004 \times \frac{13}{20} = 0.0027$$

$$P(x|M)P(M) > P(x|N)P(N) \\ \Rightarrow \text{Mammals}$$

Avoiding the Zero-probability Problem

- Naïve Bayesian prediction requires each conditional probability be non-zero; otherwise, the predicted probability will be zero

$$P(\mathbf{x}|y_j) = \prod_{i=1}^K P(x_i|y_j)$$

- Corrected probability are used


$$\text{Laplace: } P(x_i|y_j) = \frac{N_{ij}+1}{N_j+|y|}$$

$$\text{m-estimate: } P(x_i|y_j) = \frac{N_{ij}+mp}{N_j+m}$$

where $|y|$ is number of classes, p is a predetermined parameter, and m is the equivalent sample size

Geometric Interpretation of Naïve Bayes

- Consider boolean y_j , x_i normally distributed, and $P(y_j = 1) = 0.5$
- Naïve Bayes: $y = \arg \max_y P(y_j = y) \prod_{i=1}^K P(x_i | y_j = y)$




- Note that $P(\mathbf{x} | y_j) = \prod_{i=1}^K P(x_i | y_j)$
- Assume $P(x_i | y_j) \sim N(\mu_{ij}, \sigma)$

The Minimum Possible Error

- Conditional independence assumption is satisfied
- Assume that we know $P(x_i|y_j)$, and $P(y_j = 1) = 0.5$

$$\begin{aligned} P(err) &= P(\text{pred } y_j = 1 \text{ but } y_j = 0) + P(\text{pred } y_j = 0 \text{ but } y_j = 1) \\ &= \int_{-\infty}^t P(x_1 | y_j = 1) P(y_j = 1) + \int_t^{\infty} P(x_1 | y_j = 0) P(y_j = 0) \end{aligned}$$



Naïve Bayes Summary

- Assumption of independently continuous distribution may not hold for some attributes
- Easy to implement
- Robust to isolated noise points
- Can handle missing values by ignoring the instance during probability estimate calculations
- Robust to irrelevant attributes

Logistic Regression Problem Definition

- Objective: estimate $P(y_j|\mathbf{x}) = f(\mathbf{x})$ for given $\mathbf{x} \in \mathbb{R}^K$
- Strategy: follow naïve Bayes rule
- Assumptions:
 - ◆ y is Boolean (i.e., $y = 1$ or 0)
 - ◆ $P(y = 1) = \gamma$ and $P(y = 0) = 1 - \gamma$
 - ◆ All x_i are conditionally independent for given y
 - ◆ $P(x_i|y_j) \sim N(\mu_{ij}, \sigma_i)$, i.e., Gaussian distributed

Logistic Regression Derivation

- Bayes rule indicates that

$$\begin{aligned}
 \boxed{P(y = 1|\mathbf{x})} &= \frac{P(\mathbf{x}|y = 1)P(y = 1)}{P(\mathbf{x}|y = 1)P(y = 1) + P(\mathbf{x}|y = 0)P(y = 0)} \\
 &= \frac{1}{1 + \frac{P(\mathbf{x}|y = 0)P(y = 0)}{P(\mathbf{x}|y = 1)P(y = 1)}} = \frac{1}{1 + \exp(\ln \left(\frac{P(\mathbf{x}|y = 0)P(y = 0)}{P(\mathbf{x}|y = 1)P(y = 1)} \right))} \\
 &= \frac{1}{1 + \exp(\ln \left(\frac{P(y = 0)}{P(y = 1)} \right) + \ln \left(\prod_i \frac{P(x_i|y = 0)}{P(x_i|y = 1)} \right))} \\
 &= \frac{1}{1 + \exp(\ln \left(\frac{1 - \gamma}{\gamma} \right) + \boxed{\sum_i \ln \left(\frac{P(x_i|y = 0)}{P(x_i|y = 1)} \right)}}
 \end{aligned}$$

Logistic Regression Derivation (Cont'd)

$$\begin{aligned}\sum_i \ln \left(\frac{P(x_i|y=0)}{P(x_i|y=1)} \right) &= \sum_i \ln \left(\frac{\frac{1}{\sqrt{2\pi\sigma_i^2}} \exp\left(\frac{-(x_i - \mu_{i0})^2}{2\sigma_i^2}\right)}{\frac{1}{\sqrt{2\pi\sigma_i^2}} \exp\left(\frac{-(x_i - \mu_{i1})^2}{2\sigma_i^2}\right)} \right) \\&= \sum_i \ln \left(\exp \left(\frac{(x_i - \mu_{i1})^2 - (x_i - \mu_{i0})^2}{2\sigma_i^2} \right) \right) \\&= \sum_i \frac{(x_i^2 - 2x_i\mu_{i1} + \mu_{i1}^2) - (x_i^2 - 2x_i\mu_{i0} + \mu_{i0}^2)}{2\sigma_i^2} \\&= \sum_i \left(\frac{\mu_{i0} - \mu_{i1}}{\sigma_i^2} x_i + \frac{\mu_{i1}^2 - \mu_{i0}^2}{2\sigma_i^2} \right)\end{aligned}$$

Logistic Regression Derivation (Cont'd)

$$P(y = 1|\mathbf{x}) = \frac{1}{1 + \exp\left(\ln\left(\frac{1-\gamma}{\gamma}\right) + \sum_i \left(\frac{\mu_{i0} - \mu_{i1}}{\sigma_i^2} x_i + \frac{\mu_{i1}^2 - \mu_{i0}^2}{2\sigma_i^2} \right)\right)}$$


$$= \frac{1}{1 + \exp(w_0 + \sum_{i=1}^K w_i x_i)} \quad \Leftarrow \text{A sigmoid equation!}$$

where $w_0 = \ln\left(\frac{1-\gamma}{\gamma}\right) + \sum_i \left(\frac{\mu_{i1}^2 - \mu_{i0}^2}{2\sigma_i^2} \right), \quad w_i = \frac{\mu_{i0} - \mu_{i1}}{\sigma_i^2}$

$$\Rightarrow \underline{P(y = 0|\mathbf{x})} = 1 - P(y = 1|\mathbf{x}) = \frac{\exp(w_0 + \sum_{i=1}^K w_i x_i)}{1 + \exp(w_0 + \sum_{i=1}^K w_i x_i)}$$

Logistic Function

$$P(y = 1|\mathbf{x}) = \frac{1}{1 + \exp(\sum_{i=1}^K w_i x_i)}$$



Logistic Regression Derivation (Cont'd)

- This indicates:


$$\frac{P(y = \textcolor{red}{0}|\mathbf{x})}{P(y = \textcolor{red}{1}|\mathbf{x})} = \exp(w_0 + \sum_{i=1}^K w_i x_i)$$

which implies

$$\ln \left(\frac{P(y = \textcolor{red}{0}|\mathbf{x})}{P(y = \textcolor{red}{1}|\mathbf{x})} \right) = w_0 + \sum_{i=1}^K w_i x_i$$

Ensemble Methods

- General idea: combine multiple classifiers



Why Does It Work?

- Suppose there are 25 “base” classifiers
- Each classifier has an error rate $\varepsilon = 0.35$
- Assume classifiers are independent
- Probability that the ensemble classifier makes a wrong prediction:

$$\sum_{i=13}^{25} \binom{25}{i} \varepsilon^i (1 - \varepsilon)^{25-i} = 0.06$$

- The ensemble makes a wrong prediction only if more than half of the base classifiers predict incorrectly

Typical Ensemble Methods

- Bagging (by Leo Breiman):
Resampling, i.e., generating new training samples from the original sample set, based on uniform distribution
- Boosting:
Adaptively changes the weights of samples in resampling to tackle those “hard to classify” samples



Bagging

- Sample with replacement from the original data set according to a uniform probability distribution
- Examples chosen during each bagging:

Original Data	1	2	3	4	5	6	7	8	9	10
Bagging (Round 1)	7	8	10	8	2	5	10	10	5	9
Bagging (Round 2)	1	4	9	1	2	3	2	7	3	2
Bagging (Round 3)	1	8	5	10	5	5	9	6	3	7

- Build classifier on each bagging sample set
- A particular training data has a probability of $1 - 1/N$ of not being picked, where N is number of samples
- A sample has probability $1 - (1 - 1/N)^N$ of being selected
- The probability is equal to 0.632 if $N \rightarrow \infty$, so this method is also called 0.632 bootstrap

Boosting


- Sample with replacement from the original data set
- Iteratively change distribution of training data by focusing more on previously misclassified records
- Initially, all n records are assigned equal weights
- Records that are wrongly classified will have their weights increased in the future iteration

Original Data	1	2	3	4	5	6	7	8	9	10
Boosting (Round 1)	7	3	2	8	7	9	4	10	6	3
Boosting (Round 2)	5	4	9	4	2	5	1	7	4	2
Boosting (Round 3)	4	4	8	10	4	5	4	6	3	4

Example 4 is hard to classify

Adaptive Boosting (AdaBoost) Classifier

- Suppose there exists T “basis” classifiers C_t , $t = 1 \dots T$
- Each classifier is associated with a weight α_t
- For a query input x , the output y is determined by weighted majority voting:



AdaBoost Classifier


- Output is determined by weighted majority voting:

$$C^*(\mathbf{x}) = \arg \max_y \sum_{t=1}^T \alpha_t I(C_t(\mathbf{x}) = y)$$

$$\text{where } \begin{cases} I(p) = 1 & \text{when } p \text{ is true} \\ I(p) = 0 & \text{otherwise} \end{cases}$$


Basis Classifier Training

- Let $\{(\mathbf{x}_i, y_i) | i = 1 \dots N\}$ denote a set of samples, $y_i = \{+1, -1\}$
- Objective: generate basis classifiers $C_t, t = 1 \dots T$
- The basis classifiers are developed iteratively
- In each iteration, data points are sampled with replacement using weight $w_t(i)$
- The initial sample weights $w_1(i) = \frac{1}{N}, i = 1 \dots N$



Basis Classifier Training Steps

- Determine the follows in each iteration
 1. The error rate ε_t for the basis classifier C_t
 2. The weights α_t for the basis classifier C_t
 3. The resampling weights w_{t+1} for the next iteration



Basis Classifier Error Rate ε_t

- The (misclassification) error rate of a basis classifier C_t is:

$$\varepsilon_t = \frac{1}{N} \sum_{i=1}^N w_t(i) I(C_t(\mathbf{x}_i) \neq y_i)$$

where $w_t(i) \in \mathbb{R}$ is the weight assigned to sample (\mathbf{x}_i, y_i) , and

$$\begin{cases} I(p) = 1 & \text{when } p \text{ is true} \\ I(p) = 0 & \text{otherwise} \end{cases},$$


- Note that $0 \leq \varepsilon_t \leq 1$

Basis Classifier Weight α_t

- The weight $\alpha_t \in \mathbb{R}$ of a basis classifier C_t is defined as

$$\alpha_t = \frac{1}{2} \ln \left(\frac{1 - \varepsilon_t}{\varepsilon_t} \right)$$

- The lower a base classifier's error rate ε_t , the higher its weight α_t for voting



Resampling Sample Weights $w_{t+1}(i)$



- The weights of sample (\mathbf{x}_i, y_i) for next iteration is

$$w_{t+1}(i) = \frac{w_t(i)}{z_t} \begin{cases} e^{-\alpha_t} & \text{if } C_t(\mathbf{x}_i) = y_i \\ e^{\alpha_t} & \text{if } C_t(\mathbf{x}_i) \neq y_i \end{cases}$$


where z_t is a normalization factor that ensures

$$\sum_i w_{t+1}(i) = 1$$


- The weights of incorrectly classified samples is increased



Illustrating AdaBoost



Illustrating AdaBoost



Ensemble Method Summary

- Ensemble methods use multiple models to obtain better predictive performance
- Bagging increases prediction accuracy because it reduces the variance of the individual classifier

Acknowledgement

- Especially thank Dr. Tom Mitchell for sharing his valuable teaching material in this course

References

- P. Tan, M. Steinbach, and V. Kumar, *Introduction to Data Mining*