Segmentation Groups for the Synthetic Users

Quick glossary

Term	Meaning
Service tier	A client's service level, based on total assets. Higher tiers get more services. Standard, Voyager, Voyager Select, Flagship, and Flagship Select are real public Vanguard tier names.
Rollover	Moving retirement savings from an old employer plan (401(k)) into an IRA. People 55+ who still hold a 401(k) are a common rollover audience.
529	A tax-advantaged account for education costs. Holding one marks a client as saving for education.
Self-directed / digitally advised / human-advised	The client manages their own investments / an algorithm manages them (Digital Advisor) / a human advisor manages them (Personal Advisor).

Part 1 — Segment families

Family	Exclusive?	Key field(s)
`SERVICE_TIER`	Yes: exactly one segment, or `OTHER`	Qualifying account balances
`LIFE_STAGE`	Yes: exactly one segment, or `OTHER`	`dateOfBirth`
`ADVICE`	Yes: exactly one segment, or `OTHER`	`adviceService`
`ENGAGEMENT`	Yes: at most one segment, `OTHER`, or none (see below)	`lastLoginDate`
`OPPORTUNITY`	No: zero or more segments	Combined

`OTHER` rule: each family returns `OTHER` plus a reason code when its key data is missing or unmapped. The client still gets segments from every other family.

Key-field rule: each family looks at its key field only. If another field disagrees (for example, age 29 but `employmentStatus = RETIRED`), ignore it for segmentation and return a `dataQuality` warning.

SERVICE_TIER

Qualifying balance = the sum of `balance` over accounts where:

- `status = OPEN` (CLOSED accounts never count), and
- the client is `ownerClientIds[0]`, the primary owner. A joint account counts in full for the primary owner and $0 for the secondary owner.
- Null or negative balances are excluded, with a `dataQuality` warning.
- Use decimal math, not floats.

All account types count for now. This is an interim rule: Potentially, a formula replaces it, and that would be a config change, not a code change.

Segment	Qualifying balance
`STANDARD`	< $50,000
`VOYAGER`	≥ $50,000
`VOYAGER_SELECT`	≥ $500,000
`FLAGSHIP`	≥ $1,000,000
`FLAGSHIP_SELECT`	≥ $5,000,000

The highest threshold the client meets wins.

`OTHER` reason	When
`NO_ACCOUNTS`	The client has no account records.
`NO_OPEN_ACCOUNTS`	The client has accounts, but every one is CLOSED.

LIFE_STAGE

Age is whole years at 2026-10-01. A client whose birthday falls on 2026-10-01 has already had it.

Segment	Age
`EARLY_CAREER`	22–34
`MID_CAREER`	35–54
`PRE_RETIREE`	55–64
`RETIREE`	65+

`OTHER` reason	When
`MISSING_DOB`	`dateOfBirth` is null.

A DOB that makes the client under 22, or that isn't a valid date, is **rejected at ingestion** as a data-quality error. It never reaches the rules.

ADVICE

Upstream `adviceService`	Segment
`NONE`	`SELF_DIRECTED`
`DIGITAL_ADVISOR`	`DIGITALLY_ADVISED`
`PERSONAL_ADVISOR`	`HUMAN_ADVISED`

Upstream `adviceService`	Segment
`PERSONAL_ADVISOR_SELECT`	`HUMAN_ADVISED`
`PERSONAL_ADVISOR_WEALTH_MGMT`	`HUMAN_ADVISED`

`OTHER` reason	When
`MISSING_ADVICE_RECORD`	The client has no advice record.
`UNMAPPED_ADVICE_VALUE`	`adviceService` holds a value that isn't in the table above.

`advisorId` is not a key field. `NONE` with an `advisorId` set is `SELF_DIRECTED` plus a `dataQuality` warning.

ENGAGEMENT

Segment	Days since `lastLoginDate`
`DIGITALLY_ACTIVE`	≤ 30
`DORMANT`	≥ 180
(no segment)	31–179

`OTHER` reason	When
`MISSING_ENGAGEMENT_RECORD`	The client has no engagement record.

The 31–179-day range is deliberately left without a segment. It isn't an error, so it isn't `OTHER`. Still return `daysSinceLogin` in the response, because the intent and personalization layer should use it as a signal.

OPPORTUNITY

Segment	Rule
`ROLLOVER_CANDIDATE`	Age ≥ 55 **and** holds an OPEN `401K`
`EDUCATION_SAVER`	Holds an OPEN `529`
`ADVICE_PROSPECT`	Qualifying balance ≥ $500,000 **and** ADVICE = `SELF_DIRECTED`

- "Holds" means appears anywhere in `ownerClientIds`. A secondary joint owner still holds the account for these rules.
- If a rule's input is missing (no DOB, no advice record), that opportunity is **not assigned**. Return a `dataQuality` note saying it couldn't be evaluated.