

Activity No. 5.2 Files	
Course Code: CPE 103	Program: Computer Engineering
Course Title: Object Oriented Programming	Date Performed: April 12, 2025
Section: 1--A	Date Submitted: April 12, 2025
Name: Villacin, Justine R.	Instructor:
1. Objective(s)	
This activity aims to demonstrate of creating a file, executing the file, updating the file, and deleting the file using python.	
2. Intended Learning Outcomes (ILOs)	
After this module, the students should: <ul style="list-style-type: none"> Demonstrate using files for different operations in python. 	
3. Discussion	
<p>Persistence</p> <p>So far, we have learned how to write programs and communicate our intentions to the <i>Central Processing Unit</i> using conditional execution, functions, and iterations. We have learned how to create and use data structures in the <i>Main Memory</i>. The CPU and memory are where our software works and runs. It is where all of the “thinking” happens.</p> <p>But if you recall from our hardware architecture discussions, once the power is turned off, anything stored in either the CPU or main memory is erased. So up to now, our programs have just been transient fun exercises to learn Python.</p> <p>Secondary Memory</p> <p>In this chapter, we start to work with <i>Secondary Memory</i> (or files). Secondary memory is not erased when the power is turned off. Or in the case of a USB flash drive, the data we write from our programs can be removed from the system and transported to another system.</p> <p>We will primarily focus on reading and writing text files such as those we create in a text editor. Later we will see how to work with database files which are binary files, specifically designed to be read and written through database software.</p> <p>Opening files</p> <p>When we want to read or write a file (say on your hard drive), we first must <i>open</i> the file. Opening the file communicates with your operating system, which knows where the data for each file is stored. When you open a file, you are asking the operating system to find the file by name and make sure the file exists. In this example, we open the file <i>mbox.txt</i>, which should be stored in the same folder that you are in when you start Python.</p> <pre>>>> fhand = open('mbox.txt') >>> print(fhand) <_io.TextIOWrapper name='mbox.txt' mode='r' encoding='cp1252'></pre> <p>If the open is successful, the operating system returns us a <i>file handle</i>. The file handle is not the actual data contained in the file, but instead it is a “handle” that we can use to read the data. You are given a handle if the requested file exists and you have the proper permissions to read the file.</p> <p>A File Handle</p>	

If the file does not exist, open will fail with a traceback and you will not get a handle to access the contents of the file:

```
>>> fhand = open('stuff.txt')
```

Traceback (most recent call last):

File "<stdin>", line 1, in <module>

FileNotFoundError: [Errno 2] No such file or directory: 'stuff.txt'

Later we will use try and except to deal more gracefully with the situation where we attempt to open a file that does not exist.

Text files and lines

A text file can be thought of as a sequence of lines, much like a Python string can be thought of as a sequence of characters. For example, this is a sample of a text file which records mail activity from various individuals in an open source project development team:

From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008

Return-Path: <postmaster@collab.sakaiproject.org>

Date: Sat, 5 Jan 2008 09:12:18 -0500

To: source@collab.sakaiproject.org

From: stephen.marquard@uct.ac.za

Subject: [sakai] svn commit: r39772 - content/branches/

Details: <http://source.sakaiproject.org/viewsvn/?view=rev&rev=39772>

These files are in a standard format for a file containing multiple mail messages. The lines which start with "From" separate the messages and the lines which start with "From:" are part of the messages.

To break the file into lines, there is a special character that represents the "end of the line" called the *newline* character.

In Python, we represent the *newline* character as a backslash-n in string constants. Even though this looks like two characters, it is actually a single character. When we look at the variable by entering "stuff" in the interpreter, it shows us the \n in the string, but when we use print to show the string, we see the string broken into two lines by the newline character.

```
>>> stuff = 'Hello\nWorld!'
```

```
>>> stuff
```

```
'Hello\nWorld!'
```

```
>>> print(stuff)
```

```
Hello
```

```
World!
```

```
>>> stuff = 'X\nY'
```

```
>>> print(stuff)
```

```
X
```

```
Y
```

```
>>> len(stuff)
```

```
3
```

You can also see that the length of the string X\nY is *three* characters because the newline character is a single character.

So when we look at the lines in a file, we need to *imagine* that there is a special invisible character called the newline at the end of each line that marks the end of the line.

So the newline character separates the characters in the file into lines.

Reading files

While the *file handle* does not contain the data for the file, it is quite easy to construct a for loop to read through and count each of the lines in a file:

```
fhand = open('mbox-short.txt')
count = 0
for line in fhand:
    count = count + 1
print('Line Count:', count)
```

Code: <https://www.py4e.com/code3/open.py>

We can use the file handle as the sequence in our for loop. Our for loop simply counts the number of lines in the file and prints them out. The rough translation of the for loop into English is, “for each line in the file represented by the file handle, add one to the count variable.”

The reason that the open function does not read the entire file is that the file might be quite large with many gigabytes of data. The open statement takes the same amount of time regardless of the size of the file. The for loop actually causes the data to be read from the file.

When the file is read using a for loop in this manner, Python takes care of splitting the data in the file into separate lines using the newline character. Python reads each line through the newline and includes the newline as the last character in the line variable for each iteration of the for loop.

Because the for loop reads the data one line at a time, it can efficiently read and count the lines in very large files without running out of main memory to store the data. The above program can count the lines in any size file using very little memory since each line is read, counted, and then discarded.

If you know the file is relatively small compared to the size of your main memory, you can read the whole file into one string using the read method on the file handle.

```
>>> fhand = open('mbox-short.txt')
>>> inp = fhand.read()
>>> print(len(inp))
94626
>>> print(inp[:20])
```

From stephen.marquar

In this example, the entire contents (all 94,626 characters) of the file *mbox-short.txt* are read directly into the variable *inp*. We use string slicing to print out the first 20 characters of the string data stored in *inp*.

When the file is read in this manner, all the characters including all of the lines and newline characters are one big string in the variable *inp*. It is a good idea to store the output of read as a variable because each call to read exhausts the resource:

```
>>> fhand = open('mbox-short.txt')
>>> print(len(fhand.read()))
94626
>>> print(len(fhand.read()))
0
```

Remember that this form of the open function should only be used if the file data will fit comfortably in the main memory of your computer. If the file is too large to fit in main memory, you should write your program to read the file in chunks using a for or while loop.

Searching through a file

When you are searching through data in a file, it is a very common pattern to read through a file, ignoring most of the lines and only processing lines which meet a particular condition. We can combine the pattern for reading a file with string methods to build simple search mechanisms.

For example, if we wanted to read a file and only print out lines which started with the prefix “From:”, we could use the string method *startswith* to select only those lines with the desired prefix:

```
fhand = open('mbox-short.txt')
for line in fhand:
    if line.startswith('From:'):
        print(line)
```

Code: <https://www.py4e.com/code3/search1.py>

When this program runs, we get the following output:

From: stephen.marquard@uct.ac.za

From: louis@media.berkeley.edu

From: zqian@umich.edu

From: rjlowe@iupui.edu

...

The output looks great since the only lines we are seeing are those which start with “From:”, but why are we seeing the extra blank lines? This is due to that invisible *newline* character. Each of the lines ends with a newline, so the print statement prints the string in the variable *line* which includes a newline and then print adds *another* newline, resulting in the double spacing effect we see.

We could use line slicing to print all but the last character, but a simpler approach is to use the *rstrip* method which strips whitespaces from the right side of a string as follows:

```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if line.startswith('From:'):
        print(line)
```

Code: <https://www.py4e.com/code3/search2.py>

When this program runs, we get the following output:

From: stephen.marquard@uct.ac.za

From: louis@media.berkeley.edu

From: zqian@umich.edu

From: rjlowe@iupui.edu

From: zqian@umich.edu

From: rjlowe@iupui.edu

From: cwen@iupui.edu

...

As your file processing programs get more complicated, you may want to structure your search loops using *continue*. The basic idea of the search loop is that you are looking for “interesting” lines and effectively skipping “uninteresting” lines. And then when we find an interesting line, we do something with that line.

We can structure the loop to follow the pattern of skipping uninteresting lines as follows:

```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    # Skip 'uninteresting lines'
    if not line.startswith('From:'):
        continue
    # Process our 'interesting' line
    print(line)
```

Code: <https://www.py4e.com/code3/search3.py>

The output of the program is the same. In English, the uninteresting lines are those which do not start with “From:”, which we skip using continue. For the “interesting” lines (i.e., those that start with “From:”) we perform the processing.

We can use the find string method to simulate a text editor search that finds lines where the search string is anywhere in the line. Since find looks for an occurrence of a string within another string and either returns the position of the string or -1 if the string was not found, we can write the following loop to show lines which contain the string “@uct.ac.za” (i.e., they come from the University of Cape Town in South Africa):

```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if line.find('@uct.ac.za') == -1: continue
    print(line)
```

Code: <https://www.py4e.com/code3/search4.py>

Which produces the following output:

```
From stephen.marquard@uct.ac.za Sat Jan  5 09:14:16 2008
X-Authentication-Warning: set sender to stephen.marquard@uct.ac.za using -f
From: stephen.marquard@uct.ac.za
Author: stephen.marquard@uct.ac.za
From david.horwitz@uct.ac.za Fri Jan  4 07:02:32 2008
X-Authentication-Warning: set sender to david.horwitz@uct.ac.za using -f
From: david.horwitz@uct.ac.za
Author: david.horwitz@uct.ac.za
...
```

Here we also use the contracted form of the if statement where we put the continue on the same line as the if. This contracted form of the if functions the same as if the continue were on the next line and indented.

Letting the user choose the file name

We really do not want to have to edit our Python code every time we want to process a different file. It would be more usable to ask the user to enter the file name string each time the program runs so they can use our program on different files without changing the Python code.

This is quite simple to do by reading the file name from the user using input as follows:

```
fname = input('Enter the file name: ')
```

```
fhand = open(fname)
count = 0
for line in fhand:
    if line.startswith('Subject:'):
        count = count + 1
print('There were', count, 'subject lines in', fname)
```

Code: <https://www.py4e.com/code3/search6.py>

We read the file name from the user and place it in a variable named `fname` and open that file. Now we can run the program repeatedly on different files.

```
python search6.py
```

Enter the file name: mbox.txt

There were 1797 subject lines in mbox.txt

```
python search6.py
```

Enter the file name: mbox-short.txt

There were 27 subject lines in mbox-short.txt

Before peeking at the next section, take a look at the above program and ask yourself, “What could go possibly wrong here?” or “What might our friendly user do that would cause our nice little program to ungracefully exit with a traceback, making us look not-so-cool in the eyes of our users?”

Using try, except, and open

I told you not to peek. This is your last chance.

What if our user types something that is not a file name?

```
python search6.py
```

Enter the file name: missing.txt

Traceback (most recent call last):

File "search6.py", line 2, in <module>

fhand = open(fname)

FileNotFoundError: [Errno 2] No such file or directory: 'missing.txt'

```
python search6.py
```

Enter the file name: na na boo boo

Traceback (most recent call last):

File "search6.py", line 2, in <module>

fhand = open(fname)

FileNotFoundError: [Errno 2] No such file or directory: 'na na boo boo'

Do not laugh. Users will eventually do every possible thing they can do to break your programs, either mistakenly or with malicious intent. As a matter of fact, an important part of any software development team is a person or group called *Quality Assurance* (or QA for short) whose very job it is to do the craziest things possible in an attempt to break the software that the programmer has created.

The QA team is responsible for finding the flaws in programs before we have delivered the program to the end users who may be purchasing the software or paying our salary to write the software. So the QA team is the programmer's best friend.

So now that we see the flaw in the program, we can elegantly fix it using the try/except structure. We need to assume that the open call might fail and add recovery code when the open fails as follows:

```

fname = input('Enter the file name: ')
try:
    fhand = open(fname)
except:
    print('File cannot be opened:', fname)
    exit()
count = 0
for line in fhand:
    if line.startswith('Subject:'):
        count = count + 1
print('There were', count, 'subject lines in', fname)

```

Code: <https://www.py4e.com/code3/search7.py>

The exit function terminates the program. It is a function that we call that never returns. Now when our user (or QA team) types in silliness or bad file names, we “catch” them and recover gracefully:

```
python search7.py
```

```
Enter the file name: mbox.txt
```

```
There were 1797 subject lines in mbox.txt
```

```
python search7.py
```

```
Enter the file name: na na boo boo
```

```
File cannot be opened: na na boo boo
```

Protecting the open call is a good example of the proper use of try and except in a Python program. We use the term “Pythonic” when we are doing something the “Python way”. We might say that the above example is the Pythonic way to open a file.

Once you become more skilled in Python, you can engage in repartee with other Python programmers to decide which of two equivalent solutions to a problem is “more Pythonic”. The goal to be “more Pythonic” captures the notion that programming is part engineering and part art. We are not always interested in just making something work, we also want our solution to be elegant and to be appreciated as elegant by our peers.

Writing files

To write a file, you have to open it with mode “w” as a second parameter:

```
>>> fout = open('output.txt', 'w')
```

```
>>> print(fout)
```

```
<_io.TextIOWrapper name='output.txt' mode='w' encoding='cp1252'>
```

If the file already exists, opening it in write mode clears out the old data and starts fresh, so be careful! If the file doesn’t exist, a new one is created.

The write method of the file handle object puts data into the file, returning the number of characters written. The default write mode is text for writing (and reading) strings.

```
>>> line1 = "This here's the wattle,\n"
```

```
>>> fout.write(line1)
```

```
24
```

Again, the file object keeps track of where it is, so if you call write again, it adds the new data to the end.

We must make sure to manage the ends of lines as we write to the file by explicitly inserting the newline character when we want to end a line. The print statement automatically appends a newline, but the write method does not add the newline automatically.

```
>>> line2 = 'the emblem of our land.\n'
```

```
>>> fout.write(line2)
```

```
24
```

When you are done writing, you have to close the file to make sure that the last bit of data is physically written to the disk so it will not be lost if the power goes off.

```
>>> fout.close()
```

We could close the files which we open for read as well, but we can be a little sloppy if we are only opening a few files since Python makes sure that all open files are closed when the program ends. When we are writing files, we want to explicitly close the files so as to leave nothing to chance.

Reference:

PY4E - Python for everybody. (n.d.). <https://www.py4e.com/html3/07-files>

4. Materials and Equipment

To properly perform this activity, the student must have:

- Python
- Spyder IDE
- Jupyter Notebook

5. Procedure

1. Open the Anaconda.
2. Use the jupyter notebook and follow the instructions below.
3. Provide a screenshot for every test case in each code and insert in the Output section with a corresponding description and observation.

Opening files

```
[ ] fhand = open('mbox.txt')  
    print(fhand)
```

```
[ ] fhand = open('stuff.txt')
```


Text files and lines

```
[ ] stuff = 'Hello\nWorld!'
    stuff
```

```
[ ] print(stuff)
```

```
[ ] stuff = 'X\nY'
    print(stuff)
```

```
[ ] len(stuff)
```

Reading files

```
[ ] fhand = open('mbox-short.txt')
    count = 0
    for line in fhand:
        count = count + 1
    print('Line Count:', count)
```

```
[ ] fhand = open('mbox-short.txt')
    inp = fhand.read()
    print(len(inp))
```

```
[ ] print(inp[:20])
```

```
[ ] fhand = open('mbox-short.txt')
    print(len(fhand.read()))
```

```
[ ] print(len(fhand.read()))
```

Searching through a file

```
[ ] fhand = open('mbox-short.txt')
    for line in fhand:
        if line.startswith('From:'):
            print(line)
```

```
[ ] fhand = open('mbox-short.txt')
    for line in fhand:
        line = line.rstrip()
        if line.startswith('From:'):
            print(line)
```

```
[ ] fhand = open('mbox-short.txt')
    for line in fhand:
        line = line.rstrip()
        # Skip 'uninteresting lines'
        if not line.startswith('From:'):
            continue
        # Process our 'interesting' line
        print(line)
```

```
[ ] fhand = open('mbox-short.txt')
    for line in fhand:
        line = line.rstrip()
        if line.find('@uct.ac.za') == -1: continue
        print(line)
```

Letting the user choose the file name

```
[ ] fname = input('Enter the file name: ')
    fhand = open(fname)
    count = 0
    for line in fhand:
        if line.startswith('Subject:'):
            count = count + 1
    print('There were', count, 'subject lines in', fname)
```

Using try, except, and open

```
[ ] fname = input('Enter the file name: ')
try:
    fhand = open(fname)
except:
    print('File cannot be opened:', fname)
    exit()
count = 0
for line in fhand:
    if line.startswith('Subject:'):
        count = count + 1
print('There were', count, 'subject lines in', fname)
```

Writing files

```
[ ] fout = open('output.txt', 'w')
    print(fout)
```

```
[ ] line1 = "This here's the wattle,\n"
    fout.write(line1)
```

```
[ ] line2 = 'the emblem of our land.\n'
    fout.write(line2)
```

```
[ ] fout.close()
```

6. Output

Provide an output of your work here. (include an analyzation for every screenshot or output)

1. Text files and lines

```
[1] stuff = 'hello\nworld!'
stuff
'hello\nworld!'

[2] print(stuff)
hello
world!

[3] stuff = 'x\ny'
print(stuff)
x
y

[4] len(stuff)
3
```

- *I understand that they store data as a series of lines, each ending with a newline character, which makes it easier for me to read and process the file line by line.*

2. Reading files

```
fhand = open('mbox-short.txt')
count = 0
for line in fhand:
    count = count + 1
    print('Line Count:', count)
Line Count: 1

[14] fhand = open('mbox-short.txt')
inp = fhand.read()
print(len(inp))
14

[15] print(inp[:20])
Laboratory 5.2

[16] fhand = open('mbox-short.txt')
print(len(fhand.read()))
14

[17] print(len(fhand.read()))
0
```

- *I open it using the `open()` function and then use methods like `.read()` or `.readlines()` to access its contents.*

3. Searching through a file

```
[20] fhand = open('mbox-short.txt')
for line in fhand:
    if line.startswith('From:'):
        print(line)

[21] fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if line.startswith('From:'):
        print(line)

[22] fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    # skip 'uninteresting lines'
    if not line.startswith('From:'):
        continue
    # Process our 'interesting' line
    print(line)

[23] fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if line.find('@uct.ac.za') == -1: continue
    print(line)
```

- *I can search through a file by looping through each line and applying conditions to find specific text or patterns I'm interested in.*

4. Letting the user choose the file name

```
16s [✓] ▶ fname = input('Enter the file name:')
      fhand = open(fname)
      count = 0
      for line in fhand:
          if line.startswith('Subject:'):
              count = count + 1
      print('There were', count, 'subject lines in', fname)

Enter the file name:mbox-short.txt
There were 0 subject lines in mbox-short.txt
```

- *Instead of hardcoding the file name, I allow the user to enter it themselves, which gives my program the flexibility to work with different files.*

5. Using try, except, and open

```
7s [✓] ▶ fname = input('Enter the file name:')
      try:
          fhand = open(fname)
      except :
          print('File cannot be opened:', fname)
          exit()
      count = 0
      for line in fhand:
          if line.startswith('Subject:'):
              count = count + 1
      print('There were', count, 'subject lines in', fname)

Enter the file name:mbox-short.txt
There were 0 subject lines in mbox-short.txt
```

- *I use try and except blocks when opening files to handle errors—such as when the file doesn't exist—so my program doesn't crash unexpectedly.*

6. Writing files

```
[32] fout = open('output.txt', 'w')
      print(fout)
      <_io.TextIOWrapper name='output.txt' mode='w' encoding='utf-8'>

line1 = "This here's the wattle, \n"
      fout.write(line1)

25

line2 = 'the emblem of our land. \n'
      fout.write(line2)

25

[35] fout.close()
```


- *When I need to save data, I open a file in write or append mode and use the .write() method to add content to it.*

7. Supplementary Activity

Solve the following problems:

1. Create a SURNAME.txt to file write your analysis in the text file. Write a program to read through a file and print the contents of the file (line by line).

*Insert the code and the output here with the corresponding analyzation.




```
[57]: supple = open('VILLACIN.txt')
obs = supple.read()
print(obs)
```

VILLACIN

- *In this task, I created a VILLACIN.txt file, and I used notepad to create the filename txt, this exercise helped me understand the fundamental concepts of file handling in Python, such as creating, writing to, and reading from files, which are essential skills for working with data storage and manipulation in programming.*

2. Write a python program that demonstrate the CRUD (Create, Read, Update and Delete). The txt file name SURNAME.txt.

*Insert the code and the output here with the corresponding analyzation.



```
[50]: #create
supple = open('VILLACIN.txt')

#read
obs = supple.read()
print(obs)

#update
supple = open('VILLACIN.txt', 'u')
line1 = "Basic operations you can perform on data, especially in the context of databases or persistent storage systems."
supple.write(line1)
supple.close()

#read
supple = open('VILLACIN.txt')
obs = supple.read()
print(obs)

#delete
!unlink VILLACIN.txt
```

Basic operations you can perform on data, especially in the context of databases or persistent storage systems.

- *This task helped me understand how to perform basic CRUD operations—creating, reading, updating, and deleting—on a text file in Python, which is essential for managing and modifying data.*

8. Conclusions/Observations

- ***In conclusion, using files in Python is essential for handling data storage and retrieval. By performing various operations such as reading, writing, and appending, Python enables efficient file management, making it a powerful tool for building data-driven applications.***

9. Assessment Rubric

