

ITEMS	INFORMATION
<b>Unit Dimension</b>	
Width (mm)	120
Lenght (mm)	200
Height (mm)	60
<b>Package Dimension</b>	
Width (mm)	180
Lenght (mm)	270
Height (mm)	64
<b>Weight</b>	
Gross Weight (g) [Solus / LINK Gateway]	752 / 792
Net Weight (g) [Solus / LINK Gateway]	640 / 680
<b>Power</b>	
Operation Voltage (DC Volt)	9 – 36
Maximum Power Consumption (W)	3
Maximun Current (mA) @24 VDC	125
Average Current (mA) @24 VDC	96
<b>Operating Environments</b>	
Operating Temperature Range	-20°C to 60°C
Operating Relative Humidity Range	RH < 99%
Enclosure IP Rating	IP66
<b>User Interface</b>	
Keypad	5 Buttons
Display	Monochrome Graphic LCD 128 x 64
<b>Sensor Input</b>	
Sensor input type	Pressure level Sensor 4-20 mA
Number of Analog Input channel	4 Channels
Accuracy	+/- 0.5% (of total capacity)
<b>Communication Port</b>	
Ethernet Port	1 Port
RS485 Port	3 Ports
CAN Bus	2 Ports
Internet Connection (Modem)	1 Port
<b>Communication Protocol</b>	
Compatible Protocol	Modbus RTU, TCP/IP, CAN 2.0B

