EXPERIMENT – 5



	F	G	H	I	J
A	0.620576	0.140053	1.352728	NaN	0.808078
B	NaN	0.526829	NaN	NaN	0.170902
C	NaN	0.458827	1.406713	0.071119	NaN
D	NaN	2.307197	NaN	NaN	NaN
E	0.203402	0.259913	NaN	0.505811	1.516755

```
Cust_No                int64
Cust_Name             object
Product_id             int64
Product_cost         float64
Purchase_Date    datetime64[ns]
dtype: object
```

NAME : JVN GANESH

Roll No : 21BDS0085



Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
> # Load necessary libraries
> library(dlookr)
> library(dplyr)
> library(ggplot2)
> library(mice)
> # Load default dataset - for example, airquality
> data("airquality")
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
> # 1. View basic summary
> print("Basic Summary of airquality dataset:")
[1] "Basic Summary of airquality dataset:"
> summary(airquality)
     Ozone           Solar.R          Wind             Temp           Month            Day
 Min.   :  1.00   Min.   :  7.0   Min.   : 1.700   Min.   :56.00   Min.   :5.000   Min.   : 1.0
 1st Qu.: 18.00   1st Qu.:115.8   1st Qu.: 7.400   1st Qu.:72.00   1st Qu.:6.000   1st Qu.: 8.0
 Median : 31.50   Median :205.0   Median : 9.700   Median :79.00   Median :7.000   Median :16.0
 Mean   : 42.13   Mean   :185.9   Mean   : 9.958   Mean   :77.88   Mean   :6.993   Mean   :15.8
 3rd Qu.: 63.25   3rd Qu.:258.8   3rd Qu.:11.500   3rd Qu.:85.00   3rd Qu.:8.000   3rd Qu.:23.0
 Max.   :168.00   Max.   :334.0   Max.   :20.700   Max.   :97.00   Max.   :9.000   Max.   :31.0
 NA's   :37       NA's   :7
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
> # 2. Data Transformation (Standardization and Log Transformation)
> # Standardize the Ozone column in airquality dataset
> airquality$Ozone_scaled <- scale(airquality$Ozone, center = TRUE, scale = TRUE)
> print("Standardized Ozone column:")
[1] "Standardized Ozone column:"
> print(head(airquality$Ozone_scaled, 10))
             [,1]
 [1,] -0.03423409
 [2,] -0.18580489
 [3,] -0.91334473
 [4,] -0.73145977
 [5,]          NA
 [6,] -0.42831817
 [7,] -0.57988897
 [8,] -0.70114561
 [9,] -1.03460136
[10,]          NA
> # Log transformation of Wind (adding 1 to avoid log(0))
> airquality$Log_Wind <- log(airquality$Wind + 1)
> print("Log transformed Wind column:")
[1] "Log transformed Wind column:"
> print(head(airquality$Log_Wind, 10))
 [1] 2.128232 2.197225 2.610070 2.525729 2.727853 2.766319 2.261763 2.694627 3.049273 2.261763
>
```


RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Go to file/function
Addins
Source
Console
Terminal
Background Jobs
R 4.4.1 · ~/
> install.packages("naniar")
Error in install.packages : Updating loaded packages
> library(naniar)
>
Restarting R session...
> install.packages("naniar")
WARNING: Rtools is required to build R packages but is not currently installed. Please download and install
the appropriate version of Rtools before proceeding:
https://cran.rstudio.com/bin/windows/Rtools/
Installing package into 'C:/Users/lenovo/AppData/Local/R/win-library/4.4'
(as 'lib' is unspecified)
trying URL 'https://cran.rstudio.com/bin/windows/contrib/4.4/naniar_1.1.0.zip'
Content type 'application/zip' length 2766333 bytes (2.6 MB)
downloaded 2.6 MB
package 'naniar' successfully unpacked and MD5 sums checked
The downloaded binary packages are in
C:\Users\lenovo\AppData\Local\Temp\RtmpiSdJTM\downloaded_packages
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
> # Load necessary libraries
> library(dlookr)
Registered S3 methods overwritten by 'dlookr':
method from
plot.transform scales
print.transform scales
Because it is an offline environment, only offline fonts are imported.
Attaching package: 'dlookr'
The following object is masked from 'package:base':
transform
Warning message:
In file.rename(tmp, destfile) :
cannot rename file 'C:\Users\lenovo\AppData\Local\Temp\RtmpiSdJTM\PbykFmXiEBPT4ITbgNA5Cgm2OHTs4JMMuA.otf.c
urltmp' to 'C:\Users\lenovo\AppData\Local\Temp\RtmpiSdJTM\PbykFmXiEBPT4ITbgNA5Cgm2OHTs4JMMuA.otf', reason 'C
annot create a file when that file already exists'
> library(dplyr)
Attaching package: 'dplyr'
The following objects are masked from 'package:stats':
filter, lag
The following objects are masked from 'package:base':
intersect, setdiff, setequal, union
27°C
Mostly cloudy
Search


RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Go to file/function
Addins
Source
Console
Terminal
Background Jobs
R 4.4.1 · ~/
> library(naniar) # For visualizing missing data
> library(Hmisc)   # For single variable imputation
Attaching package: 'Hmisc'
The following objects are masked from 'package:dplyr':
src, summarize
The following object is masked from 'package:dlookr':
describe
The following objects are masked from 'package:base':
format.pval, units
> library(VIM)   # For missing data visualization
Error in library(VIM) : there is no package called 'VIM'
> Install necessary libraries (uncomment if not already installed)
Error: unexpected symbol in "Install necessary"
> #Install necessary libraries (uncomment if not already installed)
> install.packages("Hmisc")   # For single variable imputation
Error in install.packages : Updating loaded packages
> install.packages("mice")   # For multiple imputation methods
Error in install.packages : Updating loaded packages
> install.packages("VIM")   # For visualizing missing data
Error in install.packages : Updating loaded packages
> install.packages("dplyr")   # For data manipulation
Error in install.packages : Updating loaded packages
Restarting R session...
> install.packages("Hmisc")
WARNING: Rtools is required to build R packages but is not currently installed. Please download and install
the appropriate version of Rtools before proceeding:
https://cran.rstudio.com/bin/windows/Rtools/
Installing package into 'C:/Users/lenovo/AppData/Local/R/win-library/4.4'
(as 'lib' is unspecified)
trying URL 'https://cran.rstudio.com/bin/windows/contrib/4.4/Hmisc_5.1-3.zip'
Content type 'application/zip' length 3606271 bytes (3.4 MB)
downloaded 3.4 MB
package 'Hmisc' successfully unpacked and MD5 sums checked
The downloaded binary packages are in
C:\Users\lenovo\AppData\Local\Temp\RtmpaOWN9Z\downloaded_packages
Restarting R session...
> install.packages("mice")

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
> # Load default dataset - airquality
> data("airquality")
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
>
> # 1. View basic summary
> print("Basic Summary of airquality dataset:")
[1] "Basic Summary of airquality dataset:"
> summary(airquality)
     Ozone           Solar.R          Wind             Temp           Month            Day
 Min.   :  1.00   Min.   :  7.0   Min.   : 1.700   Min.   :56.00   Min.   :5.000   Min.   : 1.0
 1st Qu.: 18.00   1st Qu.:115.8   1st Qu.: 7.400   1st Qu.:72.00   1st Qu.:6.000   1st Qu.: 8.0
 Median : 31.50   Median :205.0   Median : 9.700   Median :79.00   Median :7.000   Median :16.0
 Mean   : 42.13   Mean   :185.9   Mean   : 9.958   Mean   :77.88   Mean   :6.993   Mean   :15.8
 3rd Qu.: 63.25   3rd Qu.:258.8   3rd Qu.:11.500   3rd Qu.:85.00   3rd Qu.:8.000   3rd Qu.:23.0
 Max.   :168.00   Max.   :334.0   Max.   :20.700   Max.   :97.00   Max.   :9.000   Max.   :31.0
 NA's   :37       NA's   :7
>
> # 2. Data Transformation (Standardization and Log Transformation)
> airquality$Ozone_scaled <- as.numeric(scale(airquality$Ozone, center = TRUE, scale = TRUE))
> print("Standardized Ozone column:")
[1] "Standardized Ozone column:"
> print(head(airquality$Ozone_scaled, 10))
 [1] -0.03423409 -0.18580489 -0.91334473 -0.73145977          NA -0.42831817 -0.57988897 -0.70114561
 [9] -1.03460136          NA
> airquality$Log_Wind <- log(airquality$Wind + 1)
> print("Log transformed Wind column:")
[1] "Log transformed Wind column:"
> print(head(airquality$Log_Wind, 10))
 [1] 2.128232 2.197225 2.610070 2.525729 2.727853 2.766319 2.261763 2.694627 3.049273 2.261763
> # 3. Imputation of Missing Values
> airquality$Ozone[is.na(airquality$Ozone)] <- mean(airquality$Ozone, na.rm = TRUE)
> airquality$Solar.R[is.na(airquality$Solar.R)] <- median(airquality$Solar.R, na.rm = TRUE)
>
> airquality <- airquality %>%
+   group_by(Month) %>%
+   mutate(Ozone = ifelse(is.na(Ozone), median(Ozone, na.rm = TRUE), Ozone))
> # 4. Multiple Imputation Using MICE
> set.seed(123)  # Initialize random seed
> airquality_for_imputation <- airquality %>% select(-Ozone_scaled)
> airquality_imputed <- mice(airquality_for_imputation, method = 'pmm', m = 5)

 iter imp variable
  1   1
  1   2
  1   3
  1   4
  1   5
  2   1
  2   2
  2   3
  2   4
  2   5
```

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
[1] "Log transformed Wind column:"
> print(head(airquality$Log_Wind, 10))
 [1] 2.128232 2.197225 2.610070 2.525729 2.727853 2.766319 2.261763 2.694627 3.049273 2.261763
> # 3. Imputation of Missing Values
> airquality$Ozone[is.na(airquality$Ozone)] <- mean(airquality$Ozone, na.rm = TRUE)
> airquality$Solar.R[is.na(airquality$Solar.R)] <- median(airquality$Solar.R, na.rm = TRUE)
>
> airquality <- airquality %>%
+   group_by(Month) %>%
+   mutate(Ozone = ifelse(is.na(Ozone), median(Ozone, na.rm = TRUE), Ozone))
> # 4. Multiple Imputation Using MICE
> set.seed(123)  # Initialize random seed
> airquality_for_imputation <- airquality %>% select(-Ozone_scaled)
> airquality_imputed <- mice(airquality_for_imputation, method = 'pmm', m = 5)

 iter imp variable
  1   1
  1   2
  1   3
  1   4
  1   5
  2   1
  2   2
  2   3
  2   4
  2   5
  3   1
  3   2
  3   3
  3   4
  3   5
  4   1
  4   2
  4   3
  4   4
  4   5
  5   1
  5   2
  5   3
  5   4
  5   5
> completed_airquality <- complete(airquality_imputed)
> print("Completed airquality dataset after multiple imputation:")
[1] "Completed airquality dataset after multiple imputation:"
> print(completed_airquality)
        Ozone Solar.R Wind Temp Month Day  Log_Wind
1    41.00000     190  7.4   67     5   1 2.1282317
2    36.00000     118  8.0   72     5   2 2.1972246
3    12.00000     149 12.6   74     5   3 2.6100698
4    18.00000     313 11.5   62     5   4 2.5257286
5    42.12931     205 14.3   56     5   5 2.7278528
6    28.00000     205 14.9   66     5   6 2.7663191
7    23.00000     299  8.6   65     5   7 2.2617631
8    19.00000      99 13.8   59     5   8 2.6946272
```

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
> completed_airquality <- complete(airquality_imputed)
> print("Completed airquality dataset after multiple imputation:")
[1] "Completed airquality dataset after multiple imputation:"
> print(completed_airquality)
```

	Ozone	Solar.R	Wind	Temp	Month	Day	Log_Wind
1	41.00000	190	7.4	67	5	1	2.1282317
2	36.00000	118	8.0	72	5	2	2.1972246
3	12.00000	149	12.6	74	5	3	2.6100698
4	18.00000	313	11.5	62	5	4	2.5257286
5	42.12931	205	14.3	56	5	5	2.7278528
6	28.00000	205	14.9	66	5	6	2.7663191
7	23.00000	299	8.6	65	5	7	2.2617631
8	19.00000	99	13.8	59	5	8	2.6946272
9	8.00000	19	20.1	61	5	9	3.0492730
10	42.12931	194	8.6	69	5	10	2.2617631
11	7.00000	205	6.9	74	5	11	2.0668628
12	16.00000	256	9.7	69	5	12	2.3702437
13	11.00000	290	9.2	66	5	13	2.3223877
14	14.00000	274	10.9	68	5	14	2.4765384
15	18.00000	65	13.2	58	5	15	2.6532420
16	14.00000	334	11.5	64	5	16	2.5257286
17	34.00000	307	12.0	66	5	17	2.5649494
18	6.00000	78	18.4	57	5	18	2.9652731
19	30.00000	322	11.5	68	5	19	2.5257286
20	11.00000	44	9.7	62	5	20	2.3702437
21	1.00000	8	9.7	59	5	21	2.3702437
22	11.00000	320	16.6	73	5	22	2.8678989
23	4.00000	25	9.7	61	5	23	2.3702437
24	32.00000	92	12.0	61	5	24	2.5649494
25	42.12931	66	16.6	57	5	25	2.8678989
26	42.12931	266	14.9	58	5	26	2.7663191
27	42.12931	205	8.0	57	5	27	2.1972246
28	23.00000	13	12.0	67	5	28	2.5649494
29	45.00000	252	14.9	81	5	29	2.7663191
30	115.00000	223	5.7	79	5	30	1.9021075
31	37.00000	279	7.4	76	5	31	2.1282317
32	42.12931	286	8.6	78	6	1	2.2617631
33	42.12931	287	9.7	74	6	2	2.3702437
34	42.12931	242	16.1	67	6	3	2.8390785
35	42.12931	186	9.2	84	6	4	2.3223877
36	42.12931	220	8.6	85	6	5	2.2617631
37	42.12931	264	14.3	79	6	6	2.7278528
38	29.00000	127	9.7	82	6	7	2.3702437
39	42.12931	273	6.9	87	6	8	2.0668628
40	71.00000	291	13.8	90	6	9	2.6946272
41	39.00000	323	11.5	87	6	10	2.5257286
42	42.12931	259	10.9	93	6	11	2.4765384
43	42.12931	250	9.2	92	6	12	2.3223877
44	23.00000	148	8.0	82	6	13	2.1972246
45	42.12931	332	13.8	80	6	14	2.6946272
46	42.12931	322	11.5	79	6	15	2.5257286
47	21.00000	191	14.9	77	6	16	2.7663191
48	37.00000	284	20.7	72	6	17	3.0773123
49	20.00000	37	9.2	65	6	18	2.3223877

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
> # Log transformation of Wind (adding 1 to avoid log(0))
> airquality$Log_Wind <- log(airquality$Wind + 1)
> print("Log transformed Wind column:")
[1] "Log transformed Wind column:"
> print(head(airquality$Log_Wind, 10))
 [1] 2.128232 2.197225 2.610070 2.525729 2.727853 2.766319 2.261763 2.694627 3.049273 2.261763
>
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
> # 3. Imputation of Missing Values
> # Mean Imputation for Ozone
> airquality$Ozone[is.na(airquality$Ozone)] <- mean(airquality$Ozone, na.rm = TRUE)
> print("After Mean Imputation of Ozone column:")
[1] "After Mean Imputation of Ozone column:"
> print(summary(airquality$Ozone))
   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
   1.00   21.00   42.13   42.13   46.00  168.00
>
> # Median Imputation for Solar.R
> airquality$Solar.R[is.na(airquality$Solar.R)] <- median(airquality$Solar.R, na.rm = TRUE)
> print("After Median Imputation of Solar.R column:")
[1] "After Median Imputation of Solar.R column:"
> print(summary(airquality$Solar.R))
   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
    7.0   120.0   205.0   186.8   256.0   334.0
>
> # Class-based Imputation (Imputation by median within groups)
> airquality <- airquality %>%
+   group_by(Month) %>%
+   mutate(Ozone = ifelse(is.na(Ozone), median(Ozone, na.rm = TRUE), Ozone))
> print("Class-based imputation of Ozone column by Month:")
[1] "Class-based imputation of Ozone column by Month:"
> print(airquality)
# A tibble: 153 × 8
# Groups:   Month [5]
   Ozone Solar.R  Wind  Temp Month   Day Ozone_scaled Log_Wind
   <dbl>   <dbl> <dbl> <int> <int> <int>        <dbl>    <dbl>
 1  41       190   7.4    67     5     1      -0.0342     2.13
 2  36       118   8      72     5     2      -0.186      2.20
 3  12       149  12.6    74     5     3      -0.913      2.61
 4  18       313  11.5    62     5     4      -0.731      2.53
 5  42.1     205  14.3    56     5     5      NA          2.73
 6  28       205  14.9    66     5     6      -0.428      2.77
 7  23       299   8.6    65     5     7      -0.580      2.26
 8  19        99  13.8    59     5     8      -0.701      2.69
 9   8        19  20.1    61     5     9      -1.03       3.05
10  42.1     194   8.6    69     5    10      NA          2.26
# ℹ 143 more rows
# ℹ Use `print(n = ...)` to see more rows
>
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
>
```

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function Addins

Source

Console Terminal Background Jobs

R 4.4.1 · ~/

76	7.00000	48	14.3	80	7	15	2.7278528
77	48.00000	260	6.9	81	7	16	2.0668628
78	35.00000	274	10.3	82	7	17	2.4248027
79	61.00000	285	6.3	84	7	18	1.9878743
80	79.00000	187	5.1	87	7	19	1.8082888
81	63.00000	220	11.5	85	7	20	2.5257286
82	16.00000	7	6.9	74	7	21	2.0668628
83	42.12931	258	9.7	81	7	22	2.3702437
84	42.12931	295	11.5	82	7	23	2.5257286
85	80.00000	294	8.6	86	7	24	2.2617631
86	108.00000	223	8.0	85	7	25	2.1972246
87	20.00000	81	8.6	82	7	26	2.2617631
88	52.00000	82	12.0	86	7	27	2.5649494
89	82.00000	213	7.4	88	7	28	2.1282317
90	50.00000	275	7.4	86	7	29	2.1282317
91	64.00000	253	7.4	83	7	30	2.1282317
92	59.00000	254	9.2	81	7	31	2.3223877
93	39.00000	83	6.9	81	8	1	2.0668628
94	9.00000	24	13.8	81	8	2	2.6946272
95	16.00000	77	7.4	82	8	3	2.1282317
96	78.00000	205	6.9	86	8	4	2.0668628
97	35.00000	205	7.4	85	8	5	2.1282317
98	66.00000	205	4.6	87	8	6	1.7227666
99	122.00000	255	4.0	89	8	7	1.6094379
100	89.00000	229	10.3	90	8	8	2.4248027
101	110.00000	207	8.0	90	8	9	2.1972246
102	42.12931	222	8.6	92	8	10	2.2617631
103	42.12931	137	11.5	86	8	11	2.5257286
104	44.00000	192	11.5	86	8	12	2.5257286
105	28.00000	273	11.5	82	8	13	2.5257286
106	65.00000	157	9.7	80	8	14	2.3702437
107	42.12931	64	11.5	79	8	15	2.5257286
108	22.00000	71	10.3	77	8	16	2.4248027
109	59.00000	51	6.3	79	8	17	1.9878743
110	23.00000	115	7.4	76	8	18	2.1282317
111	31.00000	244	10.9	78	8	19	2.4765384
112	44.00000	190	10.3	78	8	20	2.4248027
113	21.00000	259	15.5	77	8	21	2.8033604
114	9.00000	36	14.3	72	8	22	2.7278528
115	42.12931	255	12.6	75	8	23	2.6100698
116	45.00000	212	9.7	79	8	24	2.3702437
117	168.00000	238	3.4	81	8	25	1.4816045
118	73.00000	215	8.0	86	8	26	2.1972246
119	42.12931	153	5.7	88	8	27	1.9021075
120	76.00000	203	9.7	97	8	28	2.3702437
121	118.00000	225	2.3	94	8	29	1.1939225
122	84.00000	237	6.3	96	8	30	1.9878743
123	85.00000	188	6.3	94	8	31	1.9878743
124	96.00000	167	6.9	91	9	1	2.0668628
125	78.00000	197	5.1	92	9	2	1.8082888
126	73.00000	183	2.8	93	9	3	1.3350011
127	91.00000	189	4.6	93	9	4	1.7227666
128	47.00000	95	7.4	87	9	5	2.1282317

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
116  45.00000     212  9.7   79     8  24 2.3702437
117 168.00000     238  3.4   81     8  25 1.4816045
118  73.00000     215  8.0   86     8  26 2.1972246
119  42.12931     153  5.7   88     8  27 1.9021075
120  76.00000     203  9.7   97     8  28 2.3702437
121 118.00000     225  2.3   94     8  29 1.1939225
122  84.00000     237  6.3   96     8  30 1.9878743
123  85.00000     188  6.3   94     8  31 1.9878743
124  96.00000     167  6.9   91     9   1 2.0668628
125  78.00000     197  5.1   92     9   2 1.8082888
126  73.00000     183  2.8   93     9   3 1.3350011
127  91.00000     189  4.6   93     9   4 1.7227666
128  47.00000      95  7.4   87     9   5 2.1282317
129  32.00000      92 15.5   84     9   6 2.8033604
130  20.00000     252 10.9   80     9   7 2.4765384
131  23.00000     220 10.3   78     9   8 2.4248027
132  21.00000     230 10.9   75     9   9 2.4765384
133  24.00000     259  9.7   73     9  10 2.3702437
134  44.00000     236 14.9   81     9  11 2.7663191
135  21.00000     259 15.5   76     9  12 2.8033604
136  28.00000     238  6.3   77     9  13 1.9878743
137   9.00000      24 10.9   71     9  14 2.4765384
138  13.00000     112 11.5   71     9  15 2.5257286
139  46.00000     237  6.9   78     9  16 2.0668628
140  18.00000     224 13.8   67     9  17 2.6946272
141  13.00000      27 10.3   76     9  18 2.4248027
142  24.00000     238 10.3   68     9  19 2.4248027
 [ reached 'max' / getOption("max.print") -- omitted 11 rows ]
> # 5. Exploratory Data Analysis (EDA)
> summary(airquality)
     Ozone           Solar.R          Wind             Temp           Month            Day
 Min.   :  1.00   Min.   :  7.0   Min.   : 1.700   Min.   :56.00   Min.   :5.000   Min.   : 1.0
 1st Qu.: 21.00   1st Qu.:120.0   1st Qu.: 7.400   1st Qu.:72.00   1st Qu.:6.000   1st Qu.: 8.0
 Median : 42.13   Median :205.0   Median : 9.700   Median :79.00   Median :7.000   Median :16.0
 Mean   : 42.13   Mean   :186.8   Mean   : 9.958   Mean   :77.88   Mean   :6.993   Mean   :15.8
 3rd Qu.: 46.00   3rd Qu.:256.0   3rd Qu.:11.500   3rd Qu.:85.00   3rd Qu.:8.000   3rd Qu.:23.0
 Max.   :168.00   Max.   :334.0   Max.   :20.700   Max.   :97.00   Max.   :9.000   Max.   :31.0

  Ozone_scaled        Log_Wind
 Min.   :-1.2468   Min.   :0.9933
 1st Qu.:-0.7315   1st Qu.:2.1282
 Median :-0.3222   Median :2.3702
 Mean   : 0.0000   Mean   :2.3376
 3rd Qu.: 0.6403   3rd Qu.:2.5257
 Max.   : 3.8157   Max.   :3.0773
 NA's   :37
>
> ggplot(airquality, aes(x = Wind, y = Ozone)) +
+   geom_point() +
+   geom_smooth(method = 'lm') +
+   labs(title = 'Scatter Plot of Wind vs Ozone')
`geom_smooth()` using formula = 'y ~ x'
>
```


Scatter Plot of Wind vs Ozone
Ozone
Wind
150
100
50
0
5
10
15
20


RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
set.seed(123) # Initialize random seed
airquality_for_imputation <- airquality %>% select(-Ozone_scaled)
airquality_imputed <- mice(airquality_for_imputation, method = 'pmm', m = 5)
completed_airquality <- complete(airquality_imputed)
print("Completed airquality dataset after multiple imputation:")
print(completed_airquality)
# 5. Exploratory Data Analysis (EDA)
summary(airquality)
ggplot(airquality, aes(x = Wind, y = Ozone)) +
geom_point() +
geom_smooth(method = 'lm') +
labs(title = 'Scatter Plot of Wind vs Ozone')
# 6. Data Cleaning and Outlier Detection
Q1 <- quantile(airquality$Ozone, 0.25, na.rm = TRUE)
Q3 <- quantile(airquality$Ozone, 0.75, na.rm = TRUE)
IQR <- Q3 - Q1
outliers <- which(airquality$Ozone < (Q1 - 1.5 * IQR) | airquality$Ozone > (Q3 + 1.5 * IQR))
print("Detected Outliers:")
print(airquality[outliers,])
# 7. Diagnose Missing Values using dlookr
airquality %>% diagnose() %>% print()
# Visualize missing data using naniar
gg_miss_var(airquality)
Environment History Connections Tutorial
Data
airquality 153 obs. of 8 variables
airquality_for_imputati… 153 obs. of 7 variables
airquality_imputed List of 22
completed_airquality 153 obs. of 7 variables
Values
IQR Named num 25
outliers int [1:15] 30 62 69 70 71 86 99 100 101 117 ...
Q1 Named num 21
Q3 Named num 46
Console Terminal Background Jobs
Min. : 1.00 Min. : 7.0 Min. : 1.700 Min. :56.00 Min. :5.000 Min. : 1.0
1st Qu.: 21.00 1st Qu.:120.0 1st Qu.: 7.400 1st Qu.:72.00 1st Qu.:6.000 1st Qu.: 8.0
Median : 42.13 Median :205.0 Median : 9.700 Median :79.00 Median :7.000 Median :16.0
Mean : 42.13 Mean :186.8 Mean : 9.958 Mean :77.88 Mean :6.993 Mean :15.8
3rd Qu.: 46.00 3rd Qu.:256.0 3rd Qu.:11.500 3rd Qu.:85.00 3rd Qu.:8.000 3rd Qu.:23.0
Max. :168.00 Max. :334.0 Max. :20.700 Max. :97.00 Max. :9.000 Max. :31.0
Ozone_scaled Log_Wind
Min. :-1.2468 Min. :0.9933
1st Qu.:-0.7315 1st Qu.:2.1282
Median :-0.3222 Median :2.3702
Mean : 0.0000 Mean :2.3376
3rd Qu.: 0.6403 3rd Qu.:2.5257
Max. : 3.8157 Max. :3.0773
NA's :37
> ggplot(airquality, aes(x = Wind, y = Ozone)) +
+ geom_point() +
+ geom_smooth(method = 'lm') +
+ labs(title = 'Scatter Plot of Wind vs Ozone')
`geom_smooth()` using formula = 'y ~ x'
Files Plots Packages Help Viewer Presentation
Scatter Plot of Wind vs Ozone
Ozone
Wind

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins

Untitled3* | Untitled4* | Untitled5* | Pranay.R | Untitled2* | Untitled6* | Untitled7*

Source on Save | Run | Source

```
59
60  # 6. Data Cleaning and Outlier Detection
61
```

66:30 (Top Level) R Scri

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
1st Qu.: 21.00   1st Qu.:120.0   1st Qu.: 7.400   1st Qu.:72.00   1st Qu.:6.000   1st Qu.: 8.0
Median : 42.13   Median :205.0   Median : 9.700   Median :79.00   Median :7.000   Median :16.0
Mean   : 42.13   Mean   :186.8   Mean   : 9.958   Mean   :77.88   Mean   :6.993   Mean   :15.8
3rd Qu.: 46.00   3rd Qu.:256.0   3rd Qu.:11.500   3rd Qu.:85.00   3rd Qu.:8.000   3rd Qu.:23.0
Max.   :168.00   Max.   :334.0   Max.   :20.700   Max.   :97.00   Max.   :9.000   Max.   :31.0

 Ozone_scaled        Log_Wind
Min.   :-1.2468   Min.   :0.9933
1st Qu.:-0.7315   1st Qu.:2.1282
Median :-0.3222   Median :2.3702
Mean   : 0.0000   Mean   :2.3376
3rd Qu.: 0.6403   3rd Qu.:2.5257
Max.   : 3.8157   Max.   :3.0773
NA's   :37
>
> ggplot(airquality, aes(x = Wind, y = Ozone)) +
+   geom_point() +
+   geom_smooth(method = 'lm') +
+   labs(title = 'Scatter Plot of Wind vs Ozone')
`geom_smooth()` using formula = 'y ~ x'
> # 6. Data Cleaning and Outlier Detection
> Q1 <- quantile(airquality$Ozone, 0.25, na.rm = TRUE)
> Q3 <- quantile(airquality$Ozone, 0.75, na.rm = TRUE)
> IQR <- Q3 - Q1
> outliers <- which(airquality$Ozone < (Q1 - 1.5 * IQR) | airquality$Ozone > (Q3 + 1.5 * IQR))
> print("Detected Outliers:")
[1] "Detected Outliers:"
> print(airquality[outliers, ])
# A tibble: 15 x 8
# Groups:   Month [4]
   Ozone Solar.R  Wind  Temp Month   Day Ozone_scaled Log_Wind
   <dbl>   <dbl> <dbl> <int> <int> <int>        <dbl>    <dbl>
 1   115     223   5.7    79     5    30         2.21     1.90
 2   135     269   4.1    84     7     1         2.82     1.63
 3    97     267   6.3    92     7     8         1.66     1.99
 4    97     272   5.7    92     7     9         1.66     1.90
 5    85     175   7.4    89     7    10         1.30     2.13
 6   108     223   8      85     7    25         2.00     2.20
 7   122     255   4      89     8     7         2.42     1.61
 8    89     229  10.3    90     8     8         1.42     2.42
 9   110     207   8      90     8     9         2.06     2.20
10   168     238   3.4    81     8    25         3.82     1.48
11   118     225   2.3    94     8    29         2.30     1.19
12    84     237   6.3    96     8    30         1.27     1.99
13    85     188   6.3    94     8    31         1.30     1.99
14    96     167   6.9    91     9     1         1.63     2.07
15    91     189   4.6    93     9     4         1.48     1.72
>
```


Ozone_scaled
Wind
Temp
Solar.R
Ozone
Log_Wind
Day
Variables
0
5
10
15
20
Missing

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
> # 8. Regression-based Imputation
> ozone_model <- lm(Ozone ~ Wind + Temp, data = airquality)
> airquality$Ozone[is.na(airquality$Ozone)] <- predict(ozone_model, newdata = airquality[is.na(airquality$Ozone), ])
> print("After regression-based imputation of Ozone column:")
[1] "After regression-based imputation of Ozone column:"
> print(head(airquality$Ozone, 10))
 [1] 41.00000 36.00000 12.00000 18.00000 42.12931 28.00000 23.00000 19.00000  8.00000 42.12931
> # 9. Data Visualization after Imputation
> ggplot(airquality, aes(x = Ozone)) +
+   geom_histogram(bins = 30, fill = "blue", alpha = 0.7) +
+   labs(title = "Distribution of Ozone after Imputation")
>
> # Step 10: Additional Imputation Techniques
>
> # Imputation with Constant Value (Wind column)
> airquality$Wind <- impute(airquality$Wind, 5)
>
> # Visualize Missing Data Patterns using VIM
> aggr_plot <- aggr(airquality, col = c('navyblue', 'yellow'), numbers = TRUE, sortVars = TRUE, labels = names(airquality), cex.axis = .7, ga
p = 3, ylab = c("Missing data", "Pattern"))

 Variables sorted by number of missings:
    Variable     Count
 Ozone_scaled 0.2418301
       Ozone 0.0000000
     Solar.R 0.0000000
        Wind 0.0000000
        Temp 0.0000000
       Month 0.0000000
         Day 0.0000000
    Log_Wind 0.0000000
>
> # Imputation for Entire Dataset using Median
> all_column_median <- apply(airquality, 2, median, na.rm = TRUE)
> for (i in colnames(airquality)) {
+   airquality[, i][is.na(airquality[, i])] <- all_column_median[i]
+ }
>
> # View the dataset after global median imputation
> print("Dataset after Global Median Imputation:")
[1] "Dataset after Global Median Imputation:"
> head(airquality)
# A tibble: 6 x 8
# Groups:   Month [1]
  Ozone Solar.R  Wind  Temp Month   Day Ozone_scaled Log_Wind
  <dbl>   <dbl> <dbl> <int> <int> <int>        <dbl>    <dbl>
1  41       190   7.4    67     5     1      -0.0342     2.13
2  36       118   8      72     5     2      -0.186      2.20
3  12       149  12.6    74     5     3      -0.913      2.61
4  18       313  11.5    62     5     4      -0.731      2.53
5  42.1     205  14.3    56     5     5      -0.322      2.73
6  28       205  14.9    66     5     6      -0.428      2.77
>
```

RStudio

File Edit Code View Plots Session Build Debug Profile Tools Help

Go to file/function | Addins | Project: (None)

Source

Console | Terminal | Background Jobs

R 4.4.1 · ~/

```
> # 8. Regression-based Imputation
> ozone_model <- lm(Ozone ~ Wind + Temp, data = airquality)
> airquality$Ozone[is.na(airquality$Ozone)] <- predict(ozone_model, newdata = airquality[is.na(airquality$Ozone), ])
> print("After regression-based imputation of Ozone column:")
[1] "After regression-based imputation of Ozone column:"
> print(head(airquality$Ozone, 10))
 [1] 41.00000 36.00000 12.00000 18.00000 42.12931 28.00000 23.00000 19.00000  8.00000 42.12931
> # 9. Data Visualization after Imputation
> ggplot(airquality, aes(x = Ozone)) +
+   geom_histogram(bins = 30, fill = "blue", alpha = 0.7) +
+   labs(title = "Distribution of Ozone after Imputation")
>
> # Step 10: Additional Imputation Techniques
>
> # Imputation with Constant Value (Wind column)
> airquality$Wind <- impute(airquality$Wind, 5)
>
> # Visualize Missing Data Patterns using VIM
> aggr_plot <- aggr(airquality, col = c('navyblue', 'yellow'), numbers = TRUE, sortVars = TRUE, labels = names(airquality), cex.axis = .7, ga
p = 3, ylab = c("Missing data", "Pattern"))

 Variables sorted by number of missings:
    Variable     Count
 Ozone_scaled 0.2418301
       Ozone 0.0000000
     Solar.R 0.0000000
        Wind 0.0000000
        Temp 0.0000000
       Month 0.0000000
         Day 0.0000000
    Log_Wind 0.0000000
>
> # Imputation for Entire Dataset using Median
> all_column_median <- apply(airquality, 2, median, na.rm = TRUE)
> for (i in colnames(airquality)) {
+   airquality[, i][is.na(airquality[, i])] <- all_column_median[i]
+ }
>
> # View the dataset after global median imputation
> print("Dataset after Global Median Imputation:")
[1] "Dataset after Global Median Imputation:"
> head(airquality)
# A tibble: 6 x 8
# Groups:   Month [1]
  Ozone Solar.R  Wind  Temp Month   Day Ozone_scaled Log_Wind
  <dbl>   <dbl> <dbl> <int> <int> <int>       <dbl>    <dbl>
1  41       190   7.4    67     5     1     -0.0342     2.13
2  36       118   8      72     5     2     -0.186      2.20
3  12       149  12.6    74     5     3     -0.913      2.61
4  18       313  11.5    62     5     4     -0.731      2.53
5  42.1     205  14.3    56     5     5     -0.322      2.73
6  28       205  14.9    66     5     6     -0.428      2.77
>
```

Environment | History | Connections | Tutorial

Import Dataset | 510 MiB | List

R | Global Environment

Data

aggr_plot	List of 7
airquality	153 obs. of 8 variables
airquality_for…	153 obs. of 7 variables
airquality_imp…	List of 22
completed_airq…	153 obs. of 7 variables
ozone_model	List of 12

Values

all_column_med…	Named num [1:8] 42.1 205 9.7 79 7 ...
i	"Log_Wind"
IQR	Named num 25
outliers	int [1:15] 30 62 69 70 71 86 99 100 101 1…
Q1	Named num 21
Q3	Named num 46

Files | Plots | Packages | Help | Viewer | Presentation

Zoom | Export | Publish




Missing data
0.00
0.05
0.10
0.15
0.20
Ozone_scaled
Ozone
Solar.R
Wind
Temp
Month
Day
Log_Wind


Pattern
Ozone_scaled
Ozone
Solar.R
Wind
Temp
Month
Day
Log_Wind
0.76
0.24

CODE :

```
print("21BDS0085 JVNGANESH")
#
# #Install necessary libraries (uncomment if not already installed)
# install.packages("Hmisc")    # For single variable imputation
# install.packages("mice")     # For multiple imputation methods
# install.packages("VIM")      # For visualizing missing data
# install.packages("dplyr")    # For data manipulation



# Load necessary libraries
library(dlookr)
library(dplyr)
library(ggplot2)
library(mice)
library(naniar)  # For visualizing missing data
library(Hmisc)   # For single variable imputation
library(VIM)    # For missing data visualization

# Load default dataset - airquality
data("airquality")
print("21BDS0085 JVNGANESH")

# 1. View basic summary
print("Basic Summary of airquality dataset:")
summary(airquality)
```

```
# 2. Data Transformation (Standardization and Log Transformation)
airquality$Ozone_scaled <- as.numeric(scale(airquality$Ozone, center = TRUE, scale = TRUE))
print("Standardized Ozone column:")
print(head(airquality$Ozone_scaled, 10))

airquality$Log_Wind <- log(airquality$Wind + 1)
print("Log transformed Wind column:")
print(head(airquality$Log_Wind, 10))

# 3. Imputation of Missing Values
airquality$Ozone[is.na(airquality$Ozone)] <- mean(airquality$Ozone, na.rm = TRUE)
airquality$Solar.R[is.na(airquality$Solar.R)] <- median(airquality$Solar.R, na.rm = TRUE)

airquality <- airquality %>%
 group_by(Month) %>%
 mutate(Ozone = ifelse(is.na(Ozone), median(Ozone, na.rm = TRUE), Ozone))

# 4. Multiple Imputation Using MICE
set.seed(123)  # Initialize random seed
airquality_for_imputation <- airquality %>% select(-Ozone_scaled)
airquality_imputed <- mice(airquality_for_imputation, method = 'pmm', m = 5)
completed_airquality <- complete(airquality_imputed)
print("Completed airquality dataset after multiple imputation:")
print(completed_airquality)
```

```
# 5. Exploratory Data Analysis (EDA)
summary(airquality)

ggplot(airquality, aes(x = Wind, y = Ozone)) +
 geom_point() +
 geom_smooth(method = 'lm') +
 labs(title = 'Scatter Plot of Wind vs Ozone')

# 6. Data Cleaning and Outlier Detection
Q1 <- quantile(airquality$Ozone, 0.25, na.rm = TRUE)
Q3 <- quantile(airquality$Ozone, 0.75, na.rm = TRUE)
IQR <- Q3 - Q1
outliers <- which(airquality$Ozone < (Q1 - 1.5 * IQR) | airquality$Ozone > (Q3 + 1.5 * IQR))
print("Detected Outliers:")
print(airquality[outliers, ])

# 7. Diagnose Missing Values using dlookr
airquality %>% diagnose() %>% print()

# Visualize missing data using naniar
gg_miss_var(airquality)

# 8. Regression-based Imputation
ozone_model <- lm(Ozone ~ Wind + Temp, data = airquality)
```

```
airquality$Ozone[is.na(airquality$Ozone)] <- predict(ozone_model, newdata =
airquality[is.na(airquality$Ozone), ])

print("After regression-based imputation of Ozone column:")

print(head(airquality$Ozone, 10))


# 9. Data Visualization after Imputation

ggplot(airquality, aes(x = Ozone)) +

 geom_histogram(bins = 30, fill = "blue", alpha = 0.7) +

 labs(title = "Distribution of Ozone after Imputation")


# Step 10: Additional Imputation Techniques


# Imputation with Constant Value (Wind column)

airquality$Wind <- impute(airquality$Wind, 5)


# Visualize Missing Data Patterns using VIM

aggr_plot <- aggr(airquality, col = c('navyblue', 'yellow'), numbers = TRUE, sortVars = TRUE,
labels = names(airquality), cex.axis = .7, gap = 3, ylab = c("Missing data", "Pattern"))


# Imputation for Entire Dataset using Median

all_column_median <- apply(airquality, 2, median, na.rm = TRUE)

for (i in colnames(airquality)) {

 airquality[, i][is.na(airquality[, i])] <- all_column_median[i]

}


# View the dataset after global median imputation

print("Dataset after Global Median Imputation:")
```

head(airquality)

OUTPUTS:

> install.packages("naniar")

Error in install.packages : Updating loaded packages

> library(naniar)

>

Restarting R session...

> install.packages("naniar")

WARNING: Rtools is required to build R packages but is not currently installed. Please download and inst

https://cran.rstudio.com/bin/windows/Rtools/

Installing package into ‘C:/Users/lenovo/AppData/Local/R/win-library/4.4’

(as ‘lib’ is unspecified)

trying URL 'https://cran.rstudio.com/bin/windows/contrib/4.4/naniar_1.1.0.zip'

Content type 'application/zip' length 2766333 bytes (2.6 MB)

downloaded 2.6 MB

package ‘naniar’ successfully unpacked and MD5 sums checked

The downloaded binary packages are in

C:\Users\lenovo\AppData\Local\Temp\RtmpiSdJTM\downloaded_packages

> print("21BDS0085 JVNGANESH")

[1] "21BDS0085 JVNGANESH"

```
> # Load necessary libraries
> library(dlookr)
Registered S3 methods overwritten by 'dlookr':
  method        from
  plot.transform  scales
  print.transform scales
Because it is an offline environment, only offline fonts are imported.


Attaching package: ‘dlookr’


The following object is masked from ‘package:base’:


    transform


Warning message:
In file.rename(tmp, destfile) :
  cannot rename file 'C:\Users\lenovo\AppData\Local\Temp\RtmpiSdJTM\PbykFmXiEBPT4ITbgNA5Cgm20
'C:\Users\lenovo\AppData\Local\Temp\RtmpiSdJTM\PbykFmXiEBPT4ITbgNA5Cgm20HTs4JMMuA.otf', rea
> library(dplyr)


Attaching package: ‘dplyr’


The following objects are masked from ‘package:stats’:


    filter, lag
```

```
The following objects are masked from ‘package:base’:

    intersect, setdiff, setequal, union

> library(ggplot2)
> library(mice)

Attaching package: ‘mice’

The following object is masked from ‘package:stats’:

    filter

The following objects are masked from ‘package:base’:

    cbind, rbind

> library(naniar)  # For visualizing missing data
> library(Hmisc)   # For single variable imputation

Attaching package: ‘Hmisc’

The following objects are masked from ‘package:dplyr’:

    src, summarize
```

The following object is masked from ‘package:dlookr’:

describe

The following objects are masked from ‘package:base’:

format.pval, units

```
> library(VIM)    # For missing data visualization
Error in library(VIM) : there is no package called ‘VIM’
> Install necessary libraries (uncomment if not already installed)
Error: unexpected symbol in "Install necessary"
> #Install necessary libraries (uncomment if not already installed)
> install.packages("Hmisc")    # For single variable imputation
Error in install.packages : Updating loaded packages
> install.packages("mice")     # For multiple imputation methods
Error in install.packages : Updating loaded packages
> install.packages("VIM")      # For visualizing missing data
Error in install.packages : Updating loaded packages
> install.packages("dplyr")    # For data manipulation
Error in install.packages : Updating loaded packages
```

Restarting R session...

```
> install.packages("Hmisc")
WARNING: Rtools is required to build R packages but is not currently installed. Please download and inst

https://cran.rstudio.com/bin/windows/Rtools/
Installing package into ‘C:/Users/lenovo/AppData/Local/R/win-library/4.4’
(as ‘lib’ is unspecified)
trying URL 'https://cran.rstudio.com/bin/windows/contrib/4.4/Hmisc_5.1-3.zip'
Content type 'application/zip' length 3606271 bytes (3.4 MB)
downloaded 3.4 MB

package ‘Hmisc’ successfully unpacked and MD5 sums checked

The downloaded binary packages are in
        C:\Users\lenovo\AppData\Local\Temp\RtmpaOWN9Z\downloaded_packages

Restarting R session...

> install.packages("mice")
WARNING: Rtools is required to build R packages but is not currently installed. Please download and inst

https://cran.rstudio.com/bin/windows/Rtools/
Installing package into ‘C:/Users/lenovo/AppData/Local/R/win-library/4.4’
(as ‘lib’ is unspecified)
trying URL 'https://cran.rstudio.com/bin/windows/contrib/4.4/mice_3.16.0.zip'
Content type 'application/zip' length 1882211 bytes (1.8 MB)
```

```
downloaded 1.8 MB

package ‘mice’ successfully unpacked and MD5 sums checked

The downloaded binary packages are in
        C:\Users\lenovo\AppData\Local\Temp\Rtmpob3omE\downloaded_packages
> library(dlookr)
Registered S3 methods overwritten by 'dlookr':
  method        from
  plot.transform  scales
  print.transform scales

Attaching package: ‘dlookr’

The following object is masked from ‘package:base’:

    transform

> library(dplyr)

Attaching package: ‘dplyr’

The following objects are masked from ‘package:stats’:

    filter, lag
```

```
The following objects are masked from ‘package:base’:

    intersect, setdiff, setequal, union

> library(ggplot2)
> library(mice)

Attaching package: ‘mice’

The following object is masked from ‘package:stats’:

    filter

The following objects are masked from ‘package:base’:

    cbind, rbind

> library(naniar)  # For visualizing missing data
> library(Hmisc)   # For single variable imputation

Attaching package: ‘Hmisc’

The following objects are masked from ‘package:dplyr’:
```

```
    src, summarize

The following object is masked from 'package:dlookr':

    describe

The following objects are masked from 'package:base':

    format.pval, units

> library(VIM)    # For missing data visualization
Loading required package: colorspace
Loading required package: grid
VIM is ready to use.

Suggestions and bug-reports can be submitted at: https://github.com/statistikat/VIM/issues

Attaching package: 'VIM'

The following object is masked from 'package:datasets':

    sleep

>
> # Load default dataset - airquality
```

```
> data("airquality")
> print("21BDS0085 JVNGANESH")
[1] "21BDS0085 JVNGANESH"
>
> # 1. View basic summary
> print("Basic Summary of airquality dataset:")
[1] "Basic Summary of airquality dataset:"
> summary(airquality)
     Ozone           Solar.R          Wind             Temp           Month            Day
 Min.   :  1.00   Min.   :  7.0   Min.   : 1.700   Min.   :56.00   Min.   :5.000   Min.   : 1.0
 1st Qu.: 18.00   1st Qu.:115.8   1st Qu.: 7.400   1st Qu.:72.00   1st Qu.:6.000   1st Qu.: 8.0
 Median : 31.50   Median :205.0   Median : 9.700   Median :79.00   Median :7.000   Median :16.0
 Mean   : 42.13   Mean   :185.9   Mean   : 9.958   Mean   :77.88   Mean   :6.993   Mean   :15.8
 3rd Qu.: 63.25   3rd Qu.:258.8   3rd Qu.:11.500   3rd Qu.:85.00   3rd Qu.:8.000   3rd Qu.:23.0
 Max.   :168.00   Max.   :334.0   Max.   :20.700   Max.   :97.00   Max.   :9.000   Max.   :31.0
 NA's   :37       NA's   :7
>
> # 2. Data Transformation (Standardization and Log Transformation)
> airquality$Ozone_scaled <- as.numeric(scale(airquality$Ozone, center = TRUE, scale = TRUE))
> print("Standardized Ozone column:")
[1] "Standardized Ozone column:"
> print(head(airquality$Ozone_scaled, 10))
 [1] -0.03423409 -0.18580489 -0.91334473 -0.73145977         NA -0.42831817 -0.57988897 -0.70114561
 [9] -1.03460136         NA
> airquality$Log_Wind <- log(airquality$Wind + 1)
```

```
> print("Log transformed Wind column:")
[1] "Log transformed Wind column:"
> print(head(airquality$Log_Wind, 10))
 [1] 2.128232 2.197225 2.610070 2.525729 2.727853 2.766319 2.261763 2.694627 3.049273 2.261763
> # 3. Imputation of Missing Values
> airquality$Ozone[is.na(airquality$Ozone)] <- mean(airquality$Ozone, na.rm = TRUE)
> airquality$Solar.R[is.na(airquality$Solar.R)] <- median(airquality$Solar.R, na.rm = TRUE)
>
> airquality <- airquality %>%
+   group_by(Month) %>%
+   mutate(Ozone = ifelse(is.na(Ozone), median(Ozone, na.rm = TRUE), Ozone))
> # 4. Multiple Imputation Using MICE
> set.seed(123)  # Initialize random seed
> airquality_for_imputation <- airquality %>% select(-Ozone_scaled)
> airquality_imputed <- mice(airquality_for_imputation, method = 'pmm', m = 5)

 iter imp variable
  1   1
  1   2
  1   3
  1   4
  1   5
  2   1
  2   2
  2   3
```

```
 2  4
 2  5
 3  1
 3  2
 3  3
 3  4
 3  5
 4  1
 4  2
 4  3
 4  4
 4  5
 5  1
 5  2
 5  3
 5  4
 5  5
> completed_airquality <- complete(airquality_imputed)
> print("Completed airquality dataset after multiple imputation:")
[1] "Completed airquality dataset after multiple imputation:"
> print(completed_airquality)
      Ozone Solar.R Wind Temp Month Day  Log_Wind
1   41.00000    190  7.4   67     5   1 2.1282317
2   36.00000    118  8.0   72     5   2 2.1972246
3   12.00000    149 12.6   74     5   3 2.6100698
```

4	18.00000	313	11.5	62	5	4	2.5257286
5	42.12931	205	14.3	56	5	5	2.7278528
6	28.00000	205	14.9	66	5	6	2.7663191
7	23.00000	299	8.6	65	5	7	2.2617631
8	19.00000	99	13.8	59	5	8	2.6946272
9	8.00000	19	20.1	61	5	9	3.0492730
10	42.12931	194	8.6	69	5	10	2.2617631
11	7.00000	205	6.9	74	5	11	2.0668628
12	16.00000	256	9.7	69	5	12	2.3702437
13	11.00000	290	9.2	66	5	13	2.3223877
14	14.00000	274	10.9	68	5	14	2.4765384
15	18.00000	65	13.2	58	5	15	2.6532420
16	14.00000	334	11.5	64	5	16	2.5257286
17	34.00000	307	12.0	66	5	17	2.5649494
18	6.00000	78	18.4	57	5	18	2.9652731
19	30.00000	322	11.5	68	5	19	2.5257286
20	11.00000	44	9.7	62	5	20	2.3702437
21	1.00000	8	9.7	59	5	21	2.3702437
22	11.00000	320	16.6	73	5	22	2.8678989
23	4.00000	25	9.7	61	5	23	2.3702437
24	32.00000	92	12.0	61	5	24	2.5649494
25	42.12931	66	16.6	57	5	25	2.8678989
26	42.12931	266	14.9	58	5	26	2.7663191
27	42.12931	205	8.0	57	5	27	2.1972246
28	23.00000	13	12.0	67	5	28	2.5649494

29	45.00000	252	14.9	81	5	29	2.7663191
30	115.00000	223	5.7	79	5	30	1.9021075
31	37.00000	279	7.4	76	5	31	2.1282317
32	42.12931	286	8.6	78	6	1	2.2617631
33	42.12931	287	9.7	74	6	2	2.3702437
34	42.12931	242	16.1	67	6	3	2.8390785
35	42.12931	186	9.2	84	6	4	2.3223877
36	42.12931	220	8.6	85	6	5	2.2617631
37	42.12931	264	14.3	79	6	6	2.7278528
38	29.00000	127	9.7	82	6	7	2.3702437
39	42.12931	273	6.9	87	6	8	2.0668628
40	71.00000	291	13.8	90	6	9	2.6946272
41	39.00000	323	11.5	87	6	10	2.5257286
42	42.12931	259	10.9	93	6	11	2.4765384
43	42.12931	250	9.2	92	6	12	2.3223877
44	23.00000	148	8.0	82	6	13	2.1972246
45	42.12931	332	13.8	80	6	14	2.6946272
46	42.12931	322	11.5	79	6	15	2.5257286
47	21.00000	191	14.9	77	6	16	2.7663191
48	37.00000	284	20.7	72	6	17	3.0773123
49	20.00000	37	9.2	65	6	18	2.3223877
50	12.00000	120	11.5	73	6	19	2.5257286
51	13.00000	137	10.3	76	6	20	2.4248027
52	42.12931	150	6.3	77	6	21	1.9878743
53	42.12931	59	1.7	76	6	22	0.9932518

54	42.12931	91	4.6	76	6	23	1.7227666
55	42.12931	250	6.3	76	6	24	1.9878743
56	42.12931	135	8.0	75	6	25	2.1972246
57	42.12931	127	8.0	78	6	26	2.1972246
58	42.12931	47	10.3	73	6	27	2.4248027
59	42.12931	98	11.5	80	6	28	2.5257286
60	42.12931	31	14.9	77	6	29	2.7663191
61	42.12931	138	8.0	83	6	30	2.1972246
62	135.00000	269	4.1	84	7	1	1.6292405
63	49.00000	248	9.2	85	7	2	2.3223877
64	32.00000	236	9.2	81	7	3	2.3223877
65	42.12931	101	10.9	84	7	4	2.4765384
66	64.00000	175	4.6	83	7	5	1.7227666
67	40.00000	314	10.9	83	7	6	2.4765384
68	77.00000	276	5.1	88	7	7	1.8082888
69	97.00000	267	6.3	92	7	8	1.9878743
70	97.00000	272	5.7	92	7	9	1.9021075
71	85.00000	175	7.4	89	7	10	2.1282317
72	42.12931	139	8.6	82	7	11	2.2617631
73	10.00000	264	14.3	73	7	12	2.7278528
74	27.00000	175	14.9	81	7	13	2.7663191
75	42.12931	291	14.9	91	7	14	2.7663191
76	7.00000	48	14.3	80	7	15	2.7278528
77	48.00000	260	6.9	81	7	16	2.0668628
78	35.00000	274	10.3	82	7	17	2.4248027

79	61.00000	285	6.3	84	7	18	1.9878743
80	79.00000	187	5.1	87	7	19	1.8082888
81	63.00000	220	11.5	85	7	20	2.5257286
82	16.00000	7	6.9	74	7	21	2.0668628
83	42.12931	258	9.7	81	7	22	2.3702437
84	42.12931	295	11.5	82	7	23	2.5257286
85	80.00000	294	8.6	86	7	24	2.2617631
86	108.00000	223	8.0	85	7	25	2.1972246
87	20.00000	81	8.6	82	7	26	2.2617631
88	52.00000	82	12.0	86	7	27	2.5649494
89	82.00000	213	7.4	88	7	28	2.1282317
90	50.00000	275	7.4	86	7	29	2.1282317
91	64.00000	253	7.4	83	7	30	2.1282317
92	59.00000	254	9.2	81	7	31	2.3223877
93	39.00000	83	6.9	81	8	1	2.0668628
94	9.00000	24	13.8	81	8	2	2.6946272
95	16.00000	77	7.4	82	8	3	2.1282317
96	78.00000	205	6.9	86	8	4	2.0668628
97	35.00000	205	7.4	85	8	5	2.1282317
98	66.00000	205	4.6	87	8	6	1.7227666
99	122.00000	255	4.0	89	8	7	1.6094379
100	89.00000	229	10.3	90	8	8	2.4248027
101	110.00000	207	8.0	90	8	9	2.1972246
102	42.12931	222	8.6	92	8	10	2.2617631
103	42.12931	137	11.5	86	8	11	2.5257286

104	44.00000	192	11.5	86	8	12	2.5257286
105	28.00000	273	11.5	82	8	13	2.5257286
106	65.00000	157	9.7	80	8	14	2.3702437
107	42.12931	64	11.5	79	8	15	2.5257286
108	22.00000	71	10.3	77	8	16	2.4248027
109	59.00000	51	6.3	79	8	17	1.9878743
110	23.00000	115	7.4	76	8	18	2.1282317
111	31.00000	244	10.9	78	8	19	2.4765384
112	44.00000	190	10.3	78	8	20	2.4248027
113	21.00000	259	15.5	77	8	21	2.8033604
114	9.00000	36	14.3	72	8	22	2.7278528
115	42.12931	255	12.6	75	8	23	2.6100698
116	45.00000	212	9.7	79	8	24	2.3702437
117	168.00000	238	3.4	81	8	25	1.4816045
118	73.00000	215	8.0	86	8	26	2.1972246
119	42.12931	153	5.7	88	8	27	1.9021075
120	76.00000	203	9.7	97	8	28	2.3702437
121	118.00000	225	2.3	94	8	29	1.1939225
122	84.00000	237	6.3	96	8	30	1.9878743
123	85.00000	188	6.3	94	8	31	1.9878743
124	96.00000	167	6.9	91	9	1	2.0668628
125	78.00000	197	5.1	92	9	2	1.8082888
126	73.00000	183	2.8	93	9	3	1.3350011
127	91.00000	189	4.6	93	9	4	1.7227666
128	47.00000	95	7.4	87	9	5	2.1282317

```
129  32.00000     92 15.5   84    9   6 2.8033604
130  20.00000    252 10.9   80    9   7 2.4765384
131  23.00000    220 10.3   78    9   8 2.4248027
132  21.00000    230 10.9   75    9   9 2.4765384
133  24.00000    259  9.7   73    9  10 2.3702437
134  44.00000    236 14.9   81    9  11 2.7663191
135  21.00000    259 15.5   76    9  12 2.8033604
136  28.00000    238  6.3   77    9  13 1.9878743
137   9.00000     24 10.9   71    9  14 2.4765384
138  13.00000    112 11.5   71    9  15 2.5257286
139  46.00000    237  6.9   78    9  16 2.0668628
140  18.00000    224 13.8   67    9  17 2.6946272
141  13.00000     27 10.3   76    9  18 2.4248027
142  24.00000    238 10.3   68    9  19 2.4248027
 [ reached 'max' / getOption("max.print") -- omitted 11 rows ]
> # 5. Exploratory Data Analysis (EDA)
> summary(airquality)
    Ozone          Solar.R         Wind           Temp          Month            Day
 Min.   :  1.00   Min.   :  7.0   Min.   : 1.700   Min.   :56.00   Min.   :5.000   Min.   : 1.0
 1st Qu.: 21.00   1st Qu.:120.0   1st Qu.: 7.400   1st Qu.:72.00   1st Qu.:6.000   1st Qu.: 8.0
 Median : 42.13   Median :205.0   Median : 9.700   Median :79.00   Median :7.000   Median :16.0
 Mean   : 42.13   Mean   :186.8   Mean   : 9.958   Mean   :77.88   Mean   :6.993   Mean   :15.8
 3rd Qu.: 46.00   3rd Qu.:256.0   3rd Qu.:11.500   3rd Qu.:85.00   3rd Qu.:8.000   3rd Qu.:23.0
 Max.   :168.00   Max.   :334.0   Max.   :20.700   Max.   :97.00   Max.   :9.000   Max.   :31.0
```

```
 Ozone_scaled       Log_Wind
Min.   :-1.2468   Min.   :0.9933
1st Qu.:-0.7315   1st Qu.:2.1282
Median :-0.3222   Median :2.3702
Mean   : 0.0000   Mean   :2.3376
3rd Qu.: 0.6403   3rd Qu.:2.5257
Max.   : 3.8157   Max.   :3.0773
NA's   :37
>
> ggplot(airquality, aes(x = Wind, y = Ozone)) +
+   geom_point() +
+   geom_smooth(method = 'lm') +
+   labs(title = 'Scatter Plot of Wind vs Ozone')
`geom_smooth()` using formula = 'y ~ x'
> # 6. Data Cleaning and Outlier Detection
> Q1 <- quantile(airquality$Ozone, 0.25, na.rm = TRUE)
> Q3 <- quantile(airquality$Ozone, 0.75, na.rm = TRUE)
> IQR <- Q3 - Q1
> outliers <- which(airquality$Ozone < (Q1 - 1.5 * IQR) | airquality$Ozone > (Q3 + 1.5 * IQR))
> print("Detected Outliers:")
[1] "Detected Outliers:"
> print(airquality[outliers, ])
# A tibble: 15 × 8
# Groups:   Month [4]
   Ozone Solar.R  Wind  Temp Month   Day Ozone_scaled Log_Wind
```

```
  <dbl>   <dbl> <dbl> <int> <int> <int>      <dbl>    <dbl>
1  115    223  5.7    79    5   30       2.21    1.90
2  135    269  4.1    84    7    1       2.82    1.63
3   97    267  6.3    92    7    8       1.66    1.99
4   97    272  5.7    92    7    9       1.66    1.90
5   85    175  7.4    89    7   10       1.30    2.13
6  108    223  8      85    7   25       2.00    2.20
7  122    255  4      89    8    7       2.42    1.61
8   89    229 10.3    90    8    8       1.42    2.42
9  110    207  8      90    8    9       2.06    2.20
10  168    238  3.4    81    8   25       3.82    1.48
11  118    225  2.3    94    8   29       2.30    1.19
12   84    237  6.3    96    8   30       1.27    1.99
13   85    188  6.3    94    8   31       1.30    1.99
14   96    167  6.9    91    9    1       1.63    2.07
15   91    189  4.6    93    9    4       1.48    1.72
>  7. Diagnose Missing Values using dlookr
Error: unexpected symbol in " 7. Diagnose"
> # 7. Diagnose Missing Values using dlookr
> airquality %>% diagnose() %>% print()
# A tibble: 40 × 8
  variables types   Month data_count missing_count missing_percent unique_count unique_rate
  <chr>     <chr>  <int>      <int>         <dbl>           <dbl>        <int>       <dbl>
1 Ozone     numeric    5         31             0               0           22       0.710
2 Ozone     numeric    6         30             0               0           10       0.333
```

```
 3 Ozone    numeric    7       31          0          0        25      0.806
 4 Ozone    numeric    8       31          0          0        25      0.806
 5 Ozone    numeric    9       30          0          0        22      0.733
 6 Solar.R  numeric    5       31          0          0        28      0.903
 7 Solar.R  numeric    6       30          0          0        28      0.933
 8 Solar.R  numeric    7       31          0          0        29      0.935
 9 Solar.R  numeric    8       31          0          0        28      0.903
10 Solar.R  numeric    9       30          0          0        27      0.9
# ℹ 30 more rows
# ℹ Use `print(n = ...)` to see more rows
>
> # Visualize missing data using naniar
> gg_miss_var(airquality)
> # 8. Regression-based Imputation
> ozone_model <- lm(Ozone ~ Wind + Temp, data = airquality)
> airquality$Ozone[is.na(airquality$Ozone)] <- predict(ozone_model, newdata = airquality[is.na(airquality
> print("After regression-based imputation of Ozone column:")
[1] "After regression-based imputation of Ozone column:"
> print(head(airquality$Ozone, 10))
 [1] 41.00000 36.00000 12.00000 18.00000 42.12931 28.00000 23.00000 19.00000  8.00000 42.12931
> # 9. Data Visualization after Imputation
> ggplot(airquality, aes(x = Ozone)) +
+   geom_histogram(bins = 30, fill = "blue", alpha = 0.7) +
+   labs(title = "Distribution of Ozone after Imputation")
>
```

```
> # Step 10: Additional Imputation Techniques
>
> # Imputation with Constant Value (Wind column)
> airquality$Wind <- impute(airquality$Wind, 5)
>
> # Visualize Missing Data Patterns using VIM
> aggr_plot <- aggr(airquality, col = c('navyblue', 'yellow'), numbers = TRUE, sortVars = TRUE, labels = nam
"Pattern"))


 Variables sorted by number of missings:
    Variable     Count
 Ozone_scaled 0.2418301
       Ozone 0.0000000
     Solar.R 0.0000000
        Wind 0.0000000
        Temp 0.0000000
       Month 0.0000000
         Day 0.0000000
    Log_Wind 0.0000000
>
> # Imputation for Entire Dataset using Median
> all_column_median <- apply(airquality, 2, median, na.rm = TRUE)
> for (i in colnames(airquality)) {
+   airquality[, i][is.na(airquality[, i])] <- all_column_median[i]
+ }
>
```

```
> # View the dataset after global median imputation
> print("Dataset after Global Median Imputation:")
[1] "Dataset after Global Median Imputation:"
> head(airquality)
# A tibble: 6 × 8
# Groups:   Month [1]
  Ozone Solar.R  Wind  Temp Month   Day Ozone_scaled Log_Wind
  <dbl>   <dbl> <dbl> <int> <int> <int>       <dbl>    <dbl>
1  41     190   7.4    67    5    1     -0.0342     2.13
2  36     118   8      72    5    2     -0.186      2.20
3  12     149  12.6    74    5    3     -0.913      2.61
4  18     313  11.5    62    5    4     -0.731      2.53
5  42.1    205  14.3    56    5    5     -0.322      2.73
6  28     205  14.9    66    5    6     -0.428      2.77
```