

Computational methods and applications (AMS 147)

Homework 1 - Due Wednesday, Feb 25, 11:59 pm

Please submit to CANVAS a .zip file that includes the following Matlab functions:

```
compute_factorial.m  
compute_Euclidean_norm.m  
matrix_times_vector.m  
pi_series.m
```

Exercise 1 The factorial of a natural number is defined as

$$n! = n(n-1)(n-2) \cdots 1, \quad 0! = 1. \quad (1)$$

Write a Matlab function `compute_factorial.m` that takes an integer number as input and returns (1). The function should be in the following form

```
function [b] = compute_factorial(n)
```

Input:

n: natural number (possibly including 0)

Output:

b: factorial of **n**

Exercise 2 The Euclidean norm of an n -dimensional vector is defined as

$$\|\mathbf{x}\| = \sqrt{\sum_{k=1}^n x_k^2}. \quad (2)$$

Write a Matlab function `compute_Euclidean_norm.m` that computes the norm (2), for an arbitrary input vector \mathbf{x} . The function should be in the following form

```
function [z] = compute_Euclidean_norm(x)
```

Input:

x: n -dimensional vector (either column or row vector)

Output:

z: norm of the vector

Hint: You can use the **for** loop. The number of components of the input vector can be determined by using the Matlab command **length(x)** (see the Matlab documentation). You can compare the output of your function with the Matlab command **norm(x)**.

Exercise 3 Write a Matlab program **matrix.times.vector.m** that computes the product between an n -dimensional square matrix **A** and an n -dimensional (column) vector **x**. The components of the (column) vector **y** = **Ax** are defined

$$y_i = \sum_{j=1}^n A_{ij}x_j \quad i = 1, \dots, n. \quad (3)$$

The Matlab function should be in the following form

```
function [y] = matrix.times_vector(A,x)
```

Input:

A: $n \times n$ matrix

x: $n \times 1$ vector

Output:

y: $n \times 1$ vector

You are not allowed to use the Matlab expression **A*x** within your function.

Hints: You can use two nested **for** loops to compute the vector **y** (one loop computes the sum (3) while the other one controls the index i in (3)). The size of the matrix **A** can be determined by using the Matlab command **size(A)** (see the Matlab documentation). You can debug your function by comparing the output with the Matlab expression **A*x**, for simple matrices **A** and vectors **x**.

Exercise 4 The number π can be defined as a limit of various converging series of numbers. Among them

$$\pi = \lim_{n \rightarrow \infty} \sum_{k=0}^n \frac{1}{16^k} \left(\frac{4}{8k+1} - \frac{2}{8k+4} - \frac{1}{8k+5} - \frac{1}{8k+6} \right) \quad \text{Simon Plouffe (1995),} \quad (4)$$

$$\pi = \sqrt{6} \sqrt{\lim_{n \rightarrow \infty} \sum_{k=1}^n \frac{1}{k^2}} \quad \text{Euler (1735).} \quad (5)$$

Write a Matlab function `pi_series.m` that plots in the same figure the first 10 partial sums of the series (4)-(5), that is the vectors `P(1:10)` and `E(1:10)` with components

$$P_{n+1} = \sum_{k=0}^n \frac{1}{16^k} \left(\frac{4}{8k+1} - \frac{2}{8k+4} - \frac{1}{8k+5} - \frac{1}{8k+6} \right) \quad n = 0, 1, 2, \dots \quad (6)$$

$$E_n = \sqrt{6} \sqrt{\sum_{k=1}^n \frac{1}{k^2}} \quad n = 1, 2, \dots \quad (7)$$

The function should be in the following form

```
function pi_series()
```

Output:

One figure that includes the plots of `P(1:10)` and `E(1:10)`

Hints: Once you have constructed the vectors `P` and `E` with as many components as you like, you can plot them in the same figure by using the sequence of Matlab commands `figure(1)`, `clf`, `plot(P(1:10), 'r.')` (plots (6) with red dots), `hold`, `plot(E(1:10), 'b.')` (plots (7) with blue dots) (see the Matlab documentation for further details). Which sequence between (6) and (7) converges faster to π ?

Extra Credit: At the end of the Matlab function `pi_series.m`, write a code that returns in the command window the smallest integer numbers n_1 and n_2 such that

$$|P_{n_1+1} - \pi| < 10^{-5} \quad |E_{n_2} - \pi| < 10^{-5}. \quad (8)$$

To determine n_1 and n_2 , you can use a `for` loop combined with an `if` statement or, equivalently, a `while` loop.