

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

Filter objects

SCHEMAS

classicmodels

Tables

customers

employees

Columns

employeeNumber

lastName

firstName

extension

email

officeCode

reportsTo

jobTitle

Indexes

Foreign Keys

Triggers

offices

Columns

officeCode

city

phone

addressLine1

addressLine2

state

country

postalCode

territory

Indexes

Foreign Keys

Triggers

orderdetails

orders

payments

productlines

products

Views

Stored Procedures

Administration Schemas

Information

Column: officeCode

Collation: latin1_swedish_ci

Definition: officeCode varchar(10)

Object Info Session

Query 1 SQL File 3* SQL File 6* SQL File 9* x offices employees

Limit to 1000 rows

```
1 /*Write query to update (must use 'sub query') Territory to the value 'West' for list of employees who are not Sales reps
2 and have offices in USA.
3 */
4
5 • set sql_safe_updates = 0;
6 • update offices
7   set territory = 'West'
8   where country = 'USA' and
9   officeCode in (select officeCode from employees where jobTitle != 'Sales Rep');
10 • set sql_safe_updates = 1;
11
12
13
```

Result Grid

jobTitle	officeCountry	territory
President	USA	West
VP Sales	USA	West
VP Marketing	USA	West
Sales Manager (NA)	USA	West

Result 11 x

Output

Action Output

#	Time	Action	Message	Duration / Fetch
1	20:58:07	set sql_safe_updates = 0	0 row(s) affected	0.000 sec
2	20:58:07	update offices set territory = 'West' where country = 'USA' and officeCode in (...)	1 row(s) affected Rows matched: 1 Changed: 1 Warnings: 0	0.000 sec
3	20:58:07	set sql_safe_updates = 1	0 row(s) affected	0.000 sec
4	20:58:10	select e.jobTitle, o.country as officeCountry, o.territory from employees e join off...	4 row(s) returned	0.000 sec / 0.000 sec
5	20:58:34	SELECT * FROM classicmodels.offices LIMIT 0, 1000	7 row(s) returned	0.000 sec / 0.000 sec