


1 (https://www.interviewcake.com/question/javascript/rectangular-love)

A crack team of love scientists from OkEros (a hot new dating site) have devised a way to represent dating profiles as rectangles on a two-dimensional plane.

They need help writing an algorithm to find the intersection of two users' love rectangles. They suspect finding that intersection is the key to a matching algorithm so *powerful* it will cause an immediate acquisition by Google or Facebook or Obama or something.



Write a function to find the rectangular intersection of two given love rectangles.

As with the example above, love rectangles are always "straight" and never "diagonal." More rigorously: each side is parallel with either the x-axis or the y-axis.

They are defined as objects like this:

```
var myRectangle = {  
  
  // coordinates of bottom-left corner  
  leftX: 1,  
  bottomY: 5,  
  
  // width and height  
  width: 10,  
  height: 4,  
  
};
```

▼ JavaScript

Your output rectangle should use this format as well.

Gotchas

What if there is *no* intersection? Does your function do something reasonable in that case?

What if one rectangle is entirely contained in the other? Does your function do something reasonable in that case?

What if the rectangles don't really intersect but share an edge? Does your function do something reasonable in that case?

Do some parts of your function seem very similar? Can they be refactored so you repeat yourself less?

Breakdown

Let's break this problem into subproblems. How can we divide this problem into smaller parts?

We could look at the two rectangles' "horizontal overlap" or "x overlap" separately from their "vertical overlap" or "y overlap."

Lets start with a helper function `findXOverlap()`.

Need help finding the x overlap?

Since we're only working with the x dimension, we can treat the two rectangles' widths as ranges on a 1-dimensional number line.

What are the possible cases for how these ranges might overlap or not overlap? Draw out some examples!

There are four relevant cases:

1) The ranges partially overlap:



2) One range is completely contained in the other:



3) The ranges don't overlap:



4) The ranges "touch" at a single point:



Let's start with the first 2 cases. **How do we compute the overlapping range?**

One of our ranges starts "further to the right" than the other. We don't know ahead of time which one it is, but we can check the starting points of each range to see which one has the `highestStartPoint`. **That `highestStartPoint` is always the left-hand side of the overlap**, if there is one.

Not convinced? Draw some examples!

Similarly, **the right-hand side of our overlap is always the `lowestEndPoint`**. That may or may not be the end point of the same input range that had the `highestStartPoint`—compare cases (1) and (2).

This gives us our x overlap! So we can handle cases (1) and (2). **How do we know when there is *no* overlap?**

If `highestStartPoint > lowestEndPoint`, the two rectangles do not overlap.

But be careful—is it just *greater than* or is it *greater than or equal to*?

It depends how we want to handle case (4) above.

If we use *greater than*, we treat case (4) as an overlap. This means we could end up returning a rectangle with *zero width*, which ... may or may not be what we're looking for. You could make an argument either way.

Let's say a rectangle with zero width (or zero height) isn't a rectangle at all, so we should treat that case as "no intersection."

Can you finish findXOverlap()?

Here's one way to do it:

```
function findXOverlap(x1, width1, x2, width2) {  
  
    // find the highest ("rightmost") start point and lowest ("leftmost") end point  
    var highestStartPoint = Math.max(x1, x2);  
    var lowestEndPoint = Math.min(x1 + width1, x2 + width2);  
  
    // return null overlap if there is no overlap  
    if (highestStartPoint >= lowestEndPoint) {  
        return {startPoint: null, width: null};  
    }  
  
    // compute the overlap width  
    var overlapWidth = lowestEndPoint - highestStartPoint;  
  
    return {startPoint: highestStartPoint, width: overlapWidth};  
}
```

How can we adapt this for the rectangles' ys and heights?

Can we just make one findRangeOverlap() function that can handle x overlap and y overlap?

Yes! We simply use more general parameter names:

```
function findRangeOverlap(point1, length1, point2, length2) {  
  
    // find the highest start point and lowest end point.  
    // the highest ("rightmost" or "upmost") start point is  
    // the start point of the overlap.  
    // the lowest end point is the end point of the overlap.  
    var highestStartPoint = Math.max(point1, point2);  
    var lowestEndPoint = Math.min(point1 + length1, point2 + length2);  
  
    // return null overlap if there is no overlap  
    if (highestStartPoint >= lowestEndPoint) {  
        return {startPoint: null, overlapLength: null};  
    }  
  
    // compute the overlap length  
    var overlapLength = lowestEndPoint - highestStartPoint;  
  
    return {startPoint: highestStartPoint, overlapLength: overlapLength};  
}
```

We've solved our subproblem of finding the x and y overlaps! **Now we just need to put the results together.**

Solution

We divide the problem into two halves:

1. The intersection along the x-axis
2. The intersection along the y-axis

Both problems are basically the same as finding the intersection of two "ranges" on a 1-dimensional number line.

So we write a helper function `findRangeOverlap()` that can be used to find both the x overlap and the y overlap, and we use it to build the rectangular overlap:

```
function findRangeOverlap(point1, length1, point2, length2) {
    // find the highest start point and lowest end point.
    // the highest ("rightmost" or "upmost") start point is
    // the start point of the overlap.
    // the lowest end point is the end point of the overlap.
    var highestStartPoint = Math.max(point1, point2);
    var lowestEndPoint = Math.min(point1 + length1, point2 + length2);

    // return null overlap if there is no overlap
    if (highestStartPoint >= lowestEndPoint) {
        return {startPoint: null, overlapLength: null};
    }

    // compute the overlap length
    var overlapLength = lowestEndPoint - highestStartPoint;

    return {startPoint: highestStartPoint, overlapLength: overlapLength};
}

function findRectangularOverlap(rect1, rect2) {
    // get the x and y overlap points and lengths
    var xOverlap = findRangeOverlap(rect1.leftX, rect1.width, rect2.leftX, rect2.width);
    var yOverlap = findRangeOverlap(rect1.bottomY, rect1.height, rect2.bottomY, rect2.height);

    // return null rectangle if there is no overlap
    if (!xOverlap.overlapLength || !yOverlap.overlapLength) {
        return {
            leftX: null,
            bottomY: null,
            width: null,
            height: null,
        };
    }

    return {
        leftX: xOverlap.startPoint,
        bottomY: yOverlap.startPoint,
        width: xOverlap.overlapLength,
        height: yOverlap.overlapLength,
    };
}
```



Type code!

Complexity

$O(1)$ time and $O(1)$ space.

Bonus

What if we had an array of rectangles and wanted to find *all* the rectangular overlaps between all possible pairs of two rectangles within the array? Note that we'd be returning *an array of rectangles*.

What if we had an array of rectangles and wanted to find the overlap between *all* of them, if there was one? Note that we'd be returning *a single rectangle*.

Did you get it right?



Yes, I'm expert on this



Not quite, review later

Like this problem? Pass it on!



Share



Tweet

(https://www.facebook.com/interviewcake/?u=https://www.interviewcake.com/question/javascript/rectangular-love)

(https://www.facebook.com/interviewcake/?u=https://www.interviewcake.com/question/javascript/rectangular-love)

Yo, follow along!



(https://www.facebook.com/interviewcake)

Subscribe to our weekly question email list » (/free-weekly-coding-interview-problem-newsletter)

Programming interview questions by company:

- Google interview questions (/google-interview-questions)
- Facebook interview questions (/facebook-interview-questions)
- Amazon interview questions (/amazon-interview-questions)

Programming interview questions by language:

- Java interview questions (/java-interview-questions)
- Python interview questions (/python-interview-questions)
- Ruby interview questions (/ruby-interview-questions)
- JavaScript interview questions (/javascript-interview-questions)
- **NEW:** Testing and QA interview questions (/testing-and-qa-interview-questions)
- **NEW:** SQL interview questions (/sql-interview-questions)

Copyright © 2016 Cake Labs, Inc. All rights reserved.
228 Park Ave S #82632, New York, NY US 10003 (804) 876-2253
Privacy (/privacy-policy) | Terms (/terms-and-conditions)