

## Your company built an in-house calendar tool called HiCal. You want to add a feature to see the times in a day when *everyone* is available.

To do this, you'll need to know when *any* team is having a meeting. In HiCal, a meeting is stored as `objects` with attributes `startTime` and `endTime`. These integers represent the number of 30-minute blocks past 9:00am.

For example:

```
{startTime: 2, endTime: 3} // meeting from 10:00 - 10:30 am
{startTime: 6, endTime: 9} // meeting from 12:00 - 1:30 pm
```

▼ JavaScript

Write a function `condenseMeetingTimes()` that takes an array of meeting time ranges and returns an array of condensed ranges.

For example, given:

```
[
  {startTime: 0, endTime: 1},
  {startTime: 3, endTime: 5},
  {startTime: 4, endTime: 8},
  {startTime: 10, endTime: 12},
  {startTime: 9, endTime: 10},
]
```

▼ JavaScript

your function would return:

```
[
  {startTime: 0, endTime: 1},
  {startTime: 3, endTime: 8},
  {startTime: 9, endTime: 12},
]
```

▼ JavaScript

**Do not assume the meetings are in order.** The meeting times are coming from multiple teams.

**Write a solution that's efficient even when we can't put a nice upper bound on the numbers representing our time ranges.** Here we've simplified our times down to the number of 30-minute slots past 9:00 am. But we want the function to work even for very large numbers, like Unix timestamps. In any case, the spirit of the challenge is to merge meetings where `startTime` and `endTime` don't have an upper bound.

## Gotchas

Look at this case:

```
 [{startTime: 1, endTime: 2}, {startTime: 2, endTime: 3}]
```

▼ JavaScript

These meetings should probably be merged, although they don't exactly "overlap"—they just

"touch". Does your function do this?

```
var meetings = [[0,1
```

Look at this case:

```
[{startTime: 1, endTime: 5}, {startTime: 2, endTime: 3}]
```

▼ JavaScript

Notice that although the second meeting starts later, it ends before the first meeting ends. Does your function correctly handle the case where a later meeting is "subsumed by" an earlier meeting?

Look at this case:

```
[
  {startTime: 1, endTime: 10},
  {startTime: 2, endTime: 6},
  {startTime: 3, endTime: 5},
  {startTime: 7, endTime: 9},
]
```

▼ JavaScript

Here *all* of our meetings should be merged together into just `{startTime: 1, endTime: 10}`. We need keep in mind that after we've merged the first two we're not done with the result—the result of that merge *may itself need to be merged into other meetings as well*.

Make sure that your function won't "leave out" the *last* meeting.

We can do this in  $O(n \lg n)$  time.

## Breakdown

What if we only had two ranges? Let's take:

```
[{startTime: 1, endTime: 3}, {startTime: 2, endTime: 4}]
```

▼ JavaScript

These meetings clearly overlap, so we should merge them to give:

```
[{startTime: 1, endTime: 4}]
```

▼ JavaScript

But how did we know that these meetings overlap?

We could tell the meetings overlapped because the *end time* of the first one was after the *start time* of the second one! But our ideas of "first" and "second" are important here—this only works after we ensure that we treat the meeting that *starts earlier* as the "first" one.

How would we formalize this as an algorithm? **Be sure to consider these edge cases:**

1. The end time of the first meeting and the start time of the second meeting are equal. For example: `[{startTime: 1, endTime: 2}, {startTime: 2, endTime: 3}]`
2. The second meeting ends before the first meeting ends. For example: `[{startTime: 1, endTime: 5}, {startTime: 2, endTime: 3}]`

Here's a formal algorithm:

1. We treat the meeting with earlier start time as "first," and the other as "second."
2. If the end time of the first meeting is *equal to or greater than* the start time of the second meeting, we merge the two meetings into one time range. The resulting time range's start time is the first meeting's start, and its end time is *the later of* the two meetings' end times.
3. Else, we leave them separate.

So, we could compare *every* meeting to *every other* meeting in this way, merging them or leaving them separate.

Comparing *all pairs* of meetings would take  $O(n^2)$  time. We can do better!

If we're going to beat  $O(n^2)$  time, maybe we're going to get  $O(n)$  time? Is there a way to do this in one pass?

It'd be great if, for each meeting, we could just try to merge it with the *next* meeting. But that's definitely not sufficient, because the ordering of our meetings is random. There might be a non-next meeting that the current meeting could be merged with.

What if we sorted our array of meetings by start time?

Then any meetings that could be merged would always be adjacent!

So we could sort our meetings, then walk through the sorted array and see if each meeting can be merged with the one after it.

Sorting takes  $O(n \lg n)$  time in the worst case. If we can then do the merging in one pass, that's another  $O(n)$  time, for  $O(n \lg n)$  overall. That's not as good as  $O(n)$ , but it's better than  $O(n^2)$ !

## Solution

First, we sort our input array of meetings by start time so any meetings that might need to be merged are now next to each other.

Then we walk through our sorted meetings from left to right. At each step, either:

1. We *can* merge the current meeting with the previous one, so we do.
2. We *can't* merge the current meeting with the previous one, so we know the previous meeting can't be merged with any future meetings and we throw the current meeting into `mergedMeetings`.

```
function mergeRanges(meetings) {  
  
    // sort by start times  
    var sortedMeetings = meetings.slice().sort(function(a, b) {  
        return a.startTime > b.startTime ? 1 : -1;  
    });  
  
    // initialize mergedMeetings with the earliest meeting  
    var mergedMeetings = [sortedMeetings[0]];  
  
    for (var i = 1; i < sortedMeetings.length; i++) {  
  
        var currentMeeting = sortedMeetings[i];  
        var lastMergedMeeting = mergedMeetings[mergedMeetings.length - 1];  
  
        // if the current and last meetings overlap, use the latest end time  
        if (currentMeeting.startTime <= lastMergedMeeting.endTime) {  
            lastMergedMeeting.endTime = Math.max(lastMergedMeeting.endTime, currentMeeting.endTime);  
  
            // add the current meeting since it doesn't overlap  
        } else {  
            mergedMeetings.push(currentMeeting);  
        }  
    }  
  
    return mergedMeetings;  
}
```

## Complexity

$O(n \lg n)$  time and  $O(n)$  space.

Even though we only walk through our array of meetings once to merge them, we *sort* all the meetings first, giving us a runtime of  $O(n \lg n)$ . It's worth noting that *if* our input were sorted, we could skip the sort and do this in  $O(n)$  time!

We create a new array of merged meeting times. In the worst case, none of the meetings overlap, giving us an array identical to the input array. Thus we have a worst-case space cost of  $O(n)$ .

## Bonus

1. What if we *did* have an upper bound on the input values? Could we improve our runtime? Would it cost us memory?
2. Could we do this "in-place" on the input array and save some space? What are the pros and cons of doing this in-place?

Did you get it right?



Yes, I'm expert on this



Not quite, review later

**Like this problem? Pass it on!**



Share



Tweet

(https://www.facebook.com/sharer/sharer.php?u=https://www.interviewcake.com/question/javascript/merging-ranges)

(https://www.facebook.com/sharer/sharer.php?u=https://www.interviewcake.com/question/javascript/merging-ranges)

---

**Yo, follow along!**

(http://www.facebook.com/interviewcake)

Subscribe to our weekly question email list » (/free-weekly-coding-interview-problem-newsletter)

**Programming interview questions by company:**

- Google interview questions (/google-interview-questions)
- Facebook interview questions (/facebook-interview-questions)
- Amazon interview questions (/amazon-interview-questions)

**Programming interview questions by language:**

- Java interview questions (/java-interview-questions)
- Python interview questions (/python-interview-questions)
- Ruby interview questions (/ruby-interview-questions)
- JavaScript interview questions (/javascript-interview-questions)
- **NEW:** Testing and QA interview questions (/testing-and-qa-interview-questions)
- **NEW:** SQL interview questions (/sql-interview-questions)

Copyright © 2016 Cake Labs, Inc. All rights reserved.  
228 Park Ave S #82632, New York, NY US 10003 (804) 876-2253  
[Privacy \(/privacy-policy\)](#) | [Terms \(/terms-and-conditions\)](#)