

1 (https://www.interviewcake.com/question/javascript/highest-product-of-3)

## Given an arrayOfInts, find the highestProduct you can get from three of the integers.

The input arrayOfInts will always have at least three integers.

### Gotchas

Does your function work with negative numbers? If arrayOfInts is  $[-10, -10, 1, 3, 2]$  we should return 300 (which we get by taking  $-10 * -10 * 3$ ).

We can do this in  $O(n)$  time and  $O(1)$  space.

### Breakdown

To brute force an answer we could iterate through arrayOfInts and multiply each integer by each other integer, and then multiply that product by each other other integer. This would probably involve nesting 3 loops. But that would be an  $O(n^3)$  runtime! We can *definitely* do better than that.

Because any integer in the array could potentially be part of the greatest product of three integers, we must at least look at *each integer*. So we're doomed to spend at least  $O(n)$  time.

Sorting the array would let us grab the highest numbers quickly, so it might be a good first step. Sorting takes  $O(n \lg n)$  time. That's better than the  $O(n^3)$  time our brute force approach required, but we can still do better.

Since we know we must spend at *least*  $O(n)$  time, let's see if we can solve it in *exactly*  $O(n)$  time.

A great way to get  $O(n)$  runtime is to use a greedy approach. **How can we keep track of the highestProductOfThree "so far" as we do one walk through the array?**

Put differently, for each new current number during our iteration, how do we know if it gives us a new highestProductOfThree?

We have a new highestProductOfThree if the current number times two other numbers gives a product that's higher than our current highestProductOfThree. **What must we keep track of at each step so that we know if the current number times two other numbers gives us a new highestProductOfThree?**

Our first guess might be:

1. our current highestProductOfThree
2. the threeNumbersWhichGiveHighestProduct

But consider this example:

```
var arrayOfInts = [1, 10, -5, 1, -100];
```

▼ JavaScript

Right before we hit  $-100$  (so, in our second-to-last iteration), our highestProductOfThree was 10, and the threeNumbersWhichGiveHighestProduct were  $[10, 1, 1]$ . But once we hit  $-100$ , suddenly we can take  $-100 * -5 * 10$  to get 5000. So we should have "held on to" that  $-5$ , even though it wasn't one of the threeNumbersWhichGiveHighestProduct.

We need something a little smarter than `threeNumbersWhichGiveHighestProduct`. **What should we keep track of to make sure we can handle a case like this?**

There are at least two great answers:

1. **Keep track of the highest2 and lowest2 (most negative) numbers.** If the current number times *some combination of those* is higher than the current `highestProductOfThree`, we have a new `highestProductOfThree`! Which combinations of `highest2`, `lowest2`, and current must we test? We'll leave that as an exercise.
2. **Keep track of the highestProductOf2 and lowestProductOf2** (could be a low negative number). If the current number times one of those is higher than the current `highestProductOfThree`, we have a new `highestProductOfThree`!

We'll go with (2). It ends up being *slightly* cleaner than (1), though they both work just fine.

**How do we keep track of the highestProductOf2 and lowestProductOf2 at each iteration?**

(Hint: we may need to also keep track of *something else*.)

We also keep track of the lowest number and highest number. If the current number times the current highest—or *the current lowest*, if current is negative—is greater than the current `highestProductOf2`, we have a new `highestProductOf2`. Same for `lowestProductOf2`.

So at each iteration we're keeping track of and updating:

- `highestProductOfThree`
- `highestProductOf2`
- `highest`
- `lowestProductOf2`
- `lowest`

Can you implement this in code? **Careful—make sure you update each of these variables in the right order**, otherwise you might end up e.g. multiplying the current number by itself to get a new `highestProductOf2`.

## Solution

We use a greedy approach to solve the problem in one pass. At each iteration we keep track of:

- `highestProductOfThree`
- `highestProductOf2`
- `highest`
- `lowestProductOf2`
- `lowest`

When we reach the end, the `highestProductOfThree` is our answer. We maintain the others because they're necessary for keeping the `highestProductOfThree` up to date as we walk through the array. At each iteration, the `highestProductOfThree` is the highest of:

1. the current `highestProductOfThree`
2. `current * highestProductOf2`
3. `current * lowestProductOf2` (if current and `lowestProductOf2` are both low negative numbers, this product is a high positive number).

```
function highestProductOf3(arrayOfInts) {
  if (arrayOfInts.length < 3) {
    throw new Error('Less than 3 items!');
  }

  // We're going to start at the 3rd item (at index 2)
  // so pre-populate highests and lowests based on the first 2 items.
  // we could also start these as null and check below if they're set
  // but this is arguably cleaner
  var highest = Math.max(arrayOfInts[0], arrayOfInts[1]);
  var lowest = Math.min(arrayOfInts[0], arrayOfInts[1]);

  var highestProductOf2 = arrayOfInts[0] * arrayOfInts[1];
  var lowestProductOf2 = arrayOfInts[0] * arrayOfInts[1];

  // except this one--we pre-populate it for the first /3/ items.
  // this means in our first pass it'll check against itself, which is fine.
  var highestProductOf3 = arrayOfInts[0] * arrayOfInts[1] * arrayOfInts[2];

  // walk through items, starting at index 2
  for (var i = 2; i < arrayOfInts.length; i++) {
    var current = arrayOfInts[i];

    // do we have a new highest product of 3?
    // it's either the current highest,
    // or the current times the highest product of two
    // or the current times the lowest product of two
    highestProductOf3 = Math.max(
      highestProductOf3,
      current * highestProductOf2,
      current * lowestProductOf2
    );

    // do we have a new highest product of two?
    highestProductOf2 = Math.max(
      highestProductOf2,
      current * highest,
      current * lowest
    );

    // do we have a new lowest product of two?
    lowestProductOf2 = Math.min(
      lowestProductOf2,
      current * highest,
      current * lowest
    );

    // do we have a new highest?
    highest = Math.max(highest, current);

    // do we have a new lowest?
    lowest = Math.min(lowest, current);
  }

  return highestProductOf3;
}
```

## Complexity

$O(n)$  time and  $O(1)$  additional space.

## Bonus

1. What if we wanted the highest product of 4 items?
2. What if we wanted the highest product of  $k$  items?
3. If our highest product is really big, it could overflow<sup>1</sup>. How should we protect against this?

Did you get it right?



Yes, I'm expert on this



Not quite, review later

## Like this problem? Pass it on!



Share



Tweet

(https://www.facebook.com/interviewcake/?u=https://www.interviewcake.com/question/javascript/highest-product-of-3)

product-of-3) product-of-3)

Yo, follow along!



(https://www.facebook.com/interviewcake)

Subscribe to our weekly question email list » (/free-weekly-coding-interview-problem-newsletter)

### Programming interview questions by company:

- Google interview questions (/google-interview-questions)
- Facebook interview questions (/facebook-interview-questions)
- Amazon interview questions (/amazon-interview-questions)

### Programming interview questions by language:

- Java interview questions (/java-interview-questions)
- Python interview questions (/python-interview-questions)
- Ruby interview questions (/ruby-interview-questions)
- JavaScript interview questions (/javascript-interview-questions)
- **NEW:** Testing and QA interview questions (/testing-and-qa-interview-questions)
- **NEW:** SQL interview questions (/sql-interview-questions)

Copyright © 2016 Cake Labs, Inc. All rights reserved.  
228 Park Ave S #82632, New York, NY US 10003 (804) 876-2253  
Privacy (/privacy-policy) | Terms (/terms-and-conditions)